

2016



# MEASURING INSTRUMENTS

CATALOGUE NO. 202



# QUALITY | INNOVATION | SERVICE | VALUE



Our aims:

- Quality products made to international standards with full guarantee
- Innovation by continually striving to improve and develop new products
- Service and support to ensure you have trouble-free use of our products
- High performance products at a good price

**←INSIZE→** is our standard quality and made in Asia

**←INSIZE→  
PLUS** is our premium quality and mainly made in Germany, UK and Italy

We reserve the right to change or modify the design and specification of products in this catalogue without prior notice.

Copyright © INSIZE CO., LTD. All Rights Reserved.  
INSIZE is the registered trademark of INSIZE CO., LTD.



# 1

## DATA OUTPUT AND SOFTWARE PAGE 1-5



MEASURING DATA MANAGEMENT SOFTWARE



WIRELESS DATA TRANSFER SYSTEM



DATA OUTPUT CABLE

# 2

## CALIPER PAGE 6-40



DIGITAL CALIPER



DIAL CALIPER



VERNIER CALIPER



LARGE RANGE CALIPER



SPECIAL PURPOSE CALIPER

# 3

## DEPTH MEASUREMENT PAGE 41-52



DEPTH GAGE



DIAL DEPTH GAGE



DEPTH MICROMETER

# 4

## HEIGHT MEASUREMENT PAGE 53-56



DIGITAL HEIGHT GAGE



VERNIER HEIGHT GAGE

# 5

## MICROMETER PAGE 57-96



DIGITAL OUTSIDE MICROMETER



OUTSIDE MICROMETER



LARGE RANGE MICROMETER



INDICATING MICROMETER



MICROMETER WITH DIAL INDICATOR



3-WIRES



SPECIAL PURPOSE MICROMETER



MICROMETER MEASURING FORCE DETECTOR



OPTICAL PARALLEL



MICROMETER STAND



MICROMETER HEAD

# 6

## INTERNAL AND EXTERNAL DIAMETER MEASUREMENT PAGE 97-118



INSIDE MICROMETER



THREE POINTS INTERNAL MICROMETER



TUBULAR INSIDE MICROMETER



BORE GAGE



BORE GAGE SETTER



SETTING RING



TELESCOPING GAGE SET



DIGITAL RADIUS GAGE



CIRCUMFERENCE TAPE

# 7

## INDICATOR PAGE 119-151



DIGITAL INDICATOR



DIAL INDICATOR



POINTS



DIAL TEST INDICATOR



DIAL TEST INDICATOR HOLDER



MAGNETIC STAND



DIAL INDICATOR STAND



TRANSFER STAND



CONCENTRICITY GAGE



BENCH CENTER



SINE BENCH CENTER

# 9


## PAGE 168-194



GAGE BLOCKS



GAGE BLOCK ACCESSORY



CYLINDER GAGE BLOCK



CHECK MASTER



ANGLE GAGE BLOCK



PIN GAGE



PIN GAGE HANDLE



PLAIN PLUG GAGE



THREAD PLUG GAGE



THREAD RING GAGE

# 8

## PAGE 152-167



INTERNAL/EXTERNAL CALIPER GAGE



DIGITAL THICKNESS GAGE



THICKNESS GAGE



DIAL SNAP GAGE



DIAL SNAP GAGE



ADJUSTABLE SNAP GAGE



DIGITAL SNAP GAGE



STEP AND GAP GAGE



CRANKSHAFT TESTER

# 10

## PAGE 195-212



DIGITAL PROTRACTOR



PROTRACTOR



PROTRACTOR



UNIVERSAL PROTRACTOR



DIGITAL PROTRACTOR



COMBINATION SQUARE SET



GRANITE SQUARE



CYLINDER SQUARE



PERPENDICULARITY TESTER



SQUARE



45° SQUARE



STRAIGHT EDGE



GRANITE STRAIGHT EDGE



PRECISION STRAIGHT EDGE




FEELER GAGE



FEELER GAGE TAPE



PITCH GAGE




CENTER GAGE



ANGLE GAGE



RADIUS GAGE



CHAMFER GAGE



TAPER GAGE



WELDING GAGE



WELDING GAGE



PIPE WELDING GAGE



DRILL POINT GAGE




DRILL ANGLE GAGE



INSIDE/OUTSIDE CALIPER



DIVIDER



STEEL RULE



MARKING GAGE



CENTER MARKING GAGE



SCRIBING CALIPER



HEIGHT SCRIBER



SCRIBER



GRANITE SURFACE PLATE



STAND FOR GRANITE SURFACE PLATE



JACK SET FOR GRANITE SURFACE PLATE



MAGNETIC RECTANGULAR BLOCKS




V-BLOCK SET



ROLLER BEARING V-BLOCK SET




GRANITE V-BLOCK SET



MAGNETIC V-BLOCK



PARALLEL SET



ANGLE PLATE SET



ADJUSTABLE ANGLE BLOCK



RIGHT ANGLE PLATE



SINE TABLE



PRECISION SINE VISE



PRECISION UNIVERSAL VISE



PRECISION VISE



CENTERING INDICATOR



3D TESTER




EDGE FINDER



ZERO SETTER



MEASURING TOOL SET



DIGITAL SCALE



LINEAR SCALE



COUNTER

# 15

LINEAR GAGE PAGE 274-276



LINEAR GAGE AND DISPLAY UNIT



HIGH PRECISION LINEAR GAGE AND DISPLAY UNIT

# 16

EXTERNAL THREAD MEASURING DEVICE PAGE 277-278



EXTERNAL THREAD MEASURING DEVICE

# 17

PROFILE PROJECTOR PAGE 279-286



PROFILE PROJECTOR



HORIZONTAL PROFILE PROJECTOR

# 18

VISION MEASURING SYSTEM PAGE 287-290



VISION MEASURING SYSTEM



VISION MEASURING SYSTEM

# 20

BORESCOPE PAGE 304-317



VIDEOSCOPE



PIPE VIDEOSCOPE



RIGID BORESCOPE

# 19

MICROSCOPE PAGE 291-303



DIGITAL MEASURING MICROSCOPE



ZOOM STEREO MICROSCOPE



METALLURGICAL MICROSCOPE



DIGITAL CAMERA



PORTABLE MEASURING MICROSCOPE

# 21

PAGE 318-324



COATING THICKNESS GAGE



ULTRASONIC THICKNESS GAGE



DIGITAL LED TACHOMETER/STROBOSCOPE



LASER DISTANCE METER

# 22

ROUGHNESS TESTER PAGE 325-340



ROUGHNESS TESTER



ROUGHNESS TESTER



SURFACE ROUGHNESS SPECIMEN

# 23

LEVEL PAGE 341-345



DIGITAL LEVEL



DIGITAL LEVEL AND PROTRACTOR



DIGITAL LEVEL AND PROTRACTOR



FRAME LEVEL



BLOCK LEVEL



DIGITAL LEVEL



ALUMINUM ALLOY LEVEL

# 25

FORCE GAGE PAGE 378-380



DIGITAL FORCE GAGE



TEST STAND

# 26

TORQUE TESTER TORQUE WRENCH PAGE 381-391



DIGITAL TORQUE TESTER



TORQUE WRENCH TEST STAND



DIGITAL BOTTLE CAP TORQUE TESTER



DIGITAL TORQUE SCREWDRIVER



DIGITAL TORQUE WRENCH



TORQUE WRENCH

# 24

HARDNESS TESTER PAGE 346-377



ROCKWELL HARDNESS TESTER



BRINELL/ROCKWELL/VICKERS HARDNESS TESTER



BRINELL HARDNESS TESTER



MICRO-VICKERS HARDNESS TESTER



VICKERS HARDNESS TESTER



BRINELL INDENTATION MEASURING SYSTEM



VICKERS HARDNESS MEASURING SYSTEM



PORTABLE LEEB HARDNESS TESTER



ULTRASONIC HARDNESS TESTER



PORTABLE ROCKWELL HARDNESS TESTER



MAGNETIC ROCKWELL HARDNESS TESTER



HYDRAULIC BRINELL HARDNESS TESTER



PIN BRINELL HARDNESS TESTER



WEBSTER HARDNESS TESTER



BARCOL HARDNESS TESTER



SHORE DUROMETER

# 27

PAGE 392-394



PRECISION CUTTING MACHINE




GRINDER AND POLISHER



MOUNTING PRESS

# MEASURING DATA MANAGEMENT SOFTWARE



## SOFTWARE FOR DATABASE COMPUTER CODE 7311-1

**make measurement program**

**Production Configuration**

Product: FAKT 1

Require Lot Number  Require Serial Number

Part No: SPI-ISP-23015-A1

Part Name: HANDWHEEL

Customer: IMSIZE

Comment: All dimensions should be in tolerance.

NO	POINT	PARAMETER	INSTRUMENT TYPE	INSTRUMENT NAME	ID	SPEC TYPE	DATA TYPE	SPEC
1	A	DEPTH	USB	DEPTH CALIPER		Center (+/-)	Decimal	2.5 0.1
2	B	WIDTH	USB	DEPTH CALIPER		Lower/Upper	Decimal	1.9
3	C	DIAMETER	USB	CALIPER		Base/Lower/Upper	Decimal	10 0.1
4	D	DIAMETER	USB	CALIPER		Center (+/-)	Decimal	5 0.05

measuring items

description

measuring input port

measuring tools

set tolerance

**workpiece drawing**

workpiece drawing


Save \*\*\* Close Apply \*\*\*

Make measurement program for each one inspection computer. Maximum 200 dimensions can be measured by one inspection computer.

To be continued



Continued from previous page



**report**

**INSPECTION REPORT SHEET**

DATE: 2015-09-11 - 2015-09-11      No: \_\_\_\_\_

CUSTOMER NAME: JYDICE      VISUAL: \_\_\_\_\_      NUMBER PRODUCES: \_\_\_\_\_

PART NAME: HANDBHEEL      CHECK QUANTITY: 7


PART NO.: JYD-12033-A1      ACCEPT QUANTITY: 3

LOT NO.: 2      REJECT QUANTITY: 4


QUANTITY: \_\_\_\_\_      MACHINE: \_\_\_\_\_

NO.	TYPE	TOL.	INSTRUMENT	1	2	3	4	5	6	7
A	DEPTH	2.5	±0.1	DEPTH CALIPER	2.41	2.38	2.48	2.58	2.48	2.58
B	WIDTH	1.9-2.1	DEPTH CALIPER	2	2	2.08	2.08	2.08	2.05	
C	DIAMETER	10	+0.1	CALIPER	10.3	10.5	10.4	10.4	10.38	
D	DIAMETER	5	±0.05	CALIPER	10.27	4.98	5.01	4.94	5.06	5.01


**SOFTWARE FOR INSPECTION COMPUTER CODE 7311-2**




Measure the 1st dimension by following the yellow position indication.



Measure the 2nd dimension by following the yellow position indication. The 1st data will be shown in red or green according its tolerance.



Measure the 3rd dimension by following the yellow position indication. The 2nd data will be shown in red or green according its tolerance.






Measure the 4th dimension by following the yellow position indication. The 3rd data will be shown in red or green according its tolerance. The data of four measurements will be sent to the database computer.


# WIRELESS DATA TRANSFER SYSTEM

APPLICABLE FOR OTHER BRANDS




Code	Description	Applicable products
7306-1	receiver (with USB cable)	
7306-20	transmitter	 digital calipers and digital depth gages (not for 1103)
7306-30	transmitter	 digital micrometers (not for 3631, 3632, 3108, 3109, 3635)
7306-40	transmitter	 digital indicators  digital protractors

■ **CONNECTION:** one receiver can be connected to 10 transmitters.



■ **DATA COLLECTION:**

- 1) Single collection: press the read button once to collect the reading from measuring tool once.
- 2) Multi collection: press the read button once to start collecting readings from measuring tools continuously, press the button again to stop collecting. Total collection times and interval time can be adjusted.



■ **DISPLAY:** data can be input to Excel as keyboard signal.

measuring tools code A, B, C


	A	B	C	D	E	F	G
1	10.88-A						
2	5.963-B						
3	50.03-C						
4	25.48-D						
5	50.05-C						
6	10.89-A						
7	25.50-D						
8	5.965-B						
9	10.87-A						
10	50.04-C						
11	25.05-D						
12	50.03-C						
13	5.963-B						
14	50.05-C						
15							
16							

All data are displayed in the same column. Each measuring tool can be coded such as A, B, C, etc.







## DATA OUTPUT CABLE



- Connect to USB port of computer
- Without software, data can be input as keyboard signal to Excel, Word, etc.
- Press the red button or foot switch (optional) to input data



7304-2

Code	Description	Remark
7302-SPC1A	cable (length 2.5m)	 for digital calipers and digital depth gages (not for 1103)
7302-SPC1B	cable (length 2.5m)	 for digital calipers and digital depth gages (not for 1103)
7302-SPC2A	cable (length 2.5m)	 for digital micrometers (not for 3631, 3632, 3108, 3109, 3635)
7302-SPC3A	cable (length 2.5m)	 for digital indicators  digital protractors
7302-SPC4	cable (length 2.5m)	 for digital calipers 1103 series (for 1103 only)
7304-2	foot switch with cable (length 1.5m)	optional

# RS232 DATA OUTPUT CABLE



7305-SPC1A




USB power port

7305-SPC3

automatic judgment by setting tolerance

test result display (maximum value, minimum value, total quantity of workpiece, quantity of Go and No-Go, quantity of exceed upper tolerance and exceed lower tolerance)




manual sampling

automatic sampling

set auto sampling interval and tolerance



foot switch (optional)  
7304-2




red button

RS232 port

foot switch is optional

- Manual sampling and automatic sampling
- Press manual sampling button in software or red button on cable or foot switch once to collect the reading from measuring tool once
- Can be used in Windows Hyperterminal
- Supplied with software
- Voltage required: 5-10V
- Cable length 2.5m



Code	Applicable products	
7305-SPC1A		digital indicators  digital protractors
7305-SPC2		digital calipers and digital depth gages (not for 1103)
7305-SPC3		digital micrometers (not for 3631, 3632, 3108, 3109, 3635)
7304-2	foot switch with cable (length 1.5m), optional	



# WATERPROOF DIGITAL CALIPER

ATTENTION: IT IS NECESSARY TO SET ZERO AFTER POWER ON EACH TIME




ATTENTION: NO DATA OUTPUT

**IP67**  
WATERPROOF

1118-150BW

- IP67 dust/waterproof
- Resolution: 0.01mm/0.0005"
- Button function: zero, on/off, mm/inch, ABS/REL, hold
- Battery CR2032
- Meet DIN862
- Made of stainless steel



Code	Range	Accuracy	Thumb roller	L	a	b	c	d
1118-150BW *	0-150mm/0-6"	±0.03mm	without	236	21	16	16	40
1118-200BW *	0-200mm/0-8"	±0.03mm	without	286	24	19	16	50
1118-300BW *	0-300mm/0-12"	±0.03mm	without	400	25	20.5	17	60
1118-150B *	0-150mm/0-6"	±0.03mm	with	236	21	16	16	40
1118-200B *	0-200mm/0-8"	±0.03mm	with	286	24	19	16	50
1118-300B *	0-300mm/0-12"	±0.03mm	with	400	25	20.5	17	60

\* Supplied with manufacturer inspection certificate traceable to DKD Germany


Measuring Length		Permissible Error	Error	
			External	Internal
0.4 DIA		+0.0005 -0.0010	/	0.0005
2		±0.0010	-0.0005	/
4			-0.0005	/
6			-0.0010	/
8			/	/
10		±0.0015	/	/
12			/	/

Measuring Length		Permissible Error	Error	
			External	Internal
Φ10		+0.01 -0.02	/	0.01
50		±0.02	-0.01	/
100			-0.01	/
150			-0.02	/
200			/	/
250		±0.03	/	/
300			/	/

**MANUFACTURER INSPECTION  
CERTIFICATE TRACEABLE  
TO DKD GERMANY, FOR CALIPERS**

## DIGITAL CALIPER




HIGH  
PRECISION

ABSOLUTE  
SYSTEM

DATA  
OUTPUT

1103-150W

- Absolute system
- Resolution: 0.01mm/0.0005"
- Buttons: mm/inch, ABS/REL, on/off, origin set
- Battery CR2032, automatic power off
- After automatic power off, move the digital unit to turn on power
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code 7302-SPC4)



(mm)

Code	Range	Accuracy	Thumb roller	L	a	b	c	d
1103-150W*	0-150mm/0-6"	±0.02mm	without	234	21	16.5	16	40
1103-200W*	0-200mm/0-8"	±0.02mm	without	286	24	19	16	50
1103-300W*	0-300mm/0-12"	±0.03mm	without	390	26	21.5	16	60
1103-150*	0-150mm/0-6"	±0.02mm	with	234	21	16.5	16	40
1103-200*	0-200mm/0-8"	±0.02mm	with	286	24	19	16	50
1103-300*	0-300mm/0-12"	±0.03mm	with	390	26	21.5	16	60

\* Supplied with manufacturer inspection certificate traceable to DKD Germany


## DIGITAL CALIPER



ATTENTION:  
NO DATA OUTPUT

1114-150AW

- Zinc alloy house for digital unit
- Resolution: 0.01mm/0.0005"
- Buttons: zero, on/off, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Meet DIN862
- Made of stainless steel



(mm)

Code	Range	Accuracy	Thumb roller	L	a	b	c	d
1114-150AW*	0-150mm/0-6"	±0.03mm	without	236	21	16	16	40
1114-200AW*	0-200mm/0-8"	±0.03mm	without	286	24	19	16	50
1114-300AW*	0-300mm/0-12"	±0.03mm	without	400	25	20.5	17	60
1114-150A*	0-150mm/0-6"	±0.03mm	with	236	21	16	16	40
1114-200A*	0-200mm/0-8"	±0.03mm	with	286	24	19	16	50
1114-300A*	0-300mm/0-12"	±0.03mm	with	400	25	20.5	17	60

\* Supplied with manufacturer inspection certificate traceable to DKD Germany




## DIGITAL CALIPER



DATA OUTPUT

- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

1108-150W



Code	Range	Accuracy	Thumb roller	L	a	b	c	d
1108-150W *	0-150mm/0-6"	±0.03mm	without	236	21	16	16	40
1108-200W *	0-200mm/0-8"	±0.03mm	without	286	24	19	16	50
1108-300W *	0-300mm/0-12"	±0.03mm	without	400	25	20.5	17	60
1108-150 *	0-150mm/0-6"	±0.03mm	with	236	21	16	16	40
1108-200 *	0-200mm/0-8"	±0.03mm	with	286	24	19	16	50
1108-300 *	0-300mm/0-12"	±0.03mm	with	400	25	20.5	17	60

(mm)

\* Supplied with manufacturer inspection certificate traceable to DKD Germany




## METRIC DIGITAL CALIPER



DATA OUTPUT

- Resolution: 0.01mm
- Buttons: on/off, zero, ABS
- Absolute and incremental measurement
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

1109-150W



Code	Range	Accuracy	Thumb roller	L	a	b	c	d
1109-150W *	0-150mm	±0.03mm	without	236	21	16	16	40
1109-200W *	0-200mm	±0.03mm	without	286	24	19	16	50
1109-300W *	0-300mm	±0.03mm	without	400	25	20.5	17	60
1109-150 *	0-150mm	±0.03mm	with	236	21	16	16	40
1109-200 *	0-200mm	±0.03mm	with	286	24	19	16	50
1109-300 *	0-300mm	±0.03mm	with	400	25	20.5	17	60

(mm)

\* Supplied with manufacturer inspection certificate traceable to DKD Germany

## DIGITAL CALIPER WITH ROUND DEPTH BAR


DATA  
OUTPUT



round depth bar Ø1.6mm

1119-150W

- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)



thumb roller

Code	Range	Accuracy	Thumb roller	L	a	b	c	d	(mm)
1119-150W *	0-150mm/0-6"	±0.03mm	without	236	21	16	16	40	
1119-150 *	0-150mm/0-6"	±0.03mm	with	236	21	16	16	40	

\* Supplied with manufacturer inspection certificate traceable to DKD Germany


## DIGITAL CALIPER WITH CARBIDE TIPPED JAWS

DATA  
OUTPUT



1110-150AW

- Carbide tipped jaws for inside and outside measurements
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032, data output, meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)



thumb roller

Code	Range	Accuracy	Thumb roller	L	a	b	c	d	(mm)
1110-150AW *	0-150mm/0-6"	±0.03mm	without	236	21	16	16	40	
1110-200AW *	0-200mm/0-8"	±0.03mm	without	286	24	19	16	50	
1110-300AW *	0-300mm/0-12"	±0.03mm	without	400	25	20.5	17	60	
1110-150A *	0-150mm/0-6"	±0.03mm	with	236	21	16	16	40	
1110-200A *	0-200mm/0-8"	±0.03mm	with	286	24	19	16	50	
1110-300A *	0-300mm/0-12"	±0.03mm	with	400	25	20.5	17	60	

\* Supplied with manufacturer inspection certificate traceable to DKD Germany



## DIGITAL CALIPER WITH CERAMIC TIPPED JAWS




DATA  
OUTPUT



### 1193-150W

- Ceramic tipped jaws for outside measurement, extremely wear-resistant, non-magnetic, non-conductive
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032, data output, meet DIN862, made of stainless steel
- Optional accessory: data output cable (code **7306-20**, **7302-SPC1A/SPC1B**, **7305-SPC2**)



(mm)

Code	Range	Accuracy	Thumb roller	L	a	b	c	d
<b>1193-150W *</b>	0-150mm/0-6"	±0.03mm	without	235	21	16.5	16	40
<b>1193-200W *</b>	0-200mm/0-8"	±0.03mm	without	297	24	20	16	50
<b>1193-300W *</b>	0-300mm/0-12"	±0.03mm	without	390	26	21.5	16	60
<b>1193-150 *</b>	0-150mm/0-6"	±0.03mm	with	235	21	16.5	16	40
<b>1193-200 *</b>	0-200mm/0-8"	±0.03mm	with	297	24	20	16	50
<b>1193-300 *</b>	0-300mm/0-12"	±0.03mm	with	390	26	21.5	16	60

ceramic tipped jaws



\* Supplied with manufacturer inspection certificate traceable to DKD Germany

## LEFT HAND DIGITAL CALIPER




DATA  
OUTPUT



### 1130-150W

- Designed for left handers
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code **7306-20**, **7302-SPC1A/SPC1B**, **7305-SPC2**)



(mm)

Code	Range	Accuracy	Thumb roller	L	a	b	c	d
<b>1130-150W *</b>	0-150mm/0-6"	±0.03mm	without	236	21	16	16	40
<b>1130-200W *</b>	0-200mm/0-8"	±0.03mm	without	286	24	19	16	50
<b>1130-300W *</b>	0-300mm/0-12"	±0.03mm	without	400	25	20.5	17	60
<b>1130-150 *</b>	0-150mm/0-6"	±0.03mm	with	236	21	16	16	40
<b>1130-200 *</b>	0-200mm/0-8"	±0.03mm	with	286	24	19	16	50
<b>1130-300 *</b>	0-300mm/0-12"	±0.03mm	with	400	25	20.5	17	60

\* Supplied with manufacturer inspection certificate traceable to DKD Germany

# MINI DIGITAL CALIPER


ATTENTION:  
NO DATA OUTPUT



1111-100A

- Resolution: 0.01mm/0.0005"
- Buttons: zero, mm/inch, on/off
- Automatic power off, move the digital unit to turn on power
- Battery LR44
- Meet DIN862
- Made of stainless steel

Code	Range	Accuracy	L
1111-75A	0-75mm/0-3"	±0.02mm	144mm
1111-100A	0-100mm/0-4"	±0.02mm	170mm





# DIGITAL CALIPER

DATA  
OUTPUT



1171-300



- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

Code	Range	Accuracy	a	b	c	d	e	L
1171-200	0-200mm/0-8"	±0.03mm	12	38	17	60	10	320
1171-306	0-300mm/0-12"	±0.04mm	12	38	17	60	10	420
1171-300	0-300mm/0-12"	±0.04mm	12	38	17	90	10	420



(mm)

DATA  
OUTPUT

## DIGITAL CALIPER



1170-300



- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

(mm)

Code	Range	Accuracy	a	c	d	e	L
1170-200	0-200mm/0-8"	±0.03mm	12	17	60	10	320
1170-306	0-300mm/0-12"	±0.04mm	12	17	60	10	420
1170-300	0-300mm/0-12"	±0.04mm	12	17	90	10	420

ATTENTION:  
NO DATA OUTPUT


## PLASTIC DIGITAL CALIPER



1139-150

- Made of hard plastic, non-magnetic and non-conductive
- Prevent workpieces from scratching by calipers
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Battery CR2032, automatic power off

Unit: mm



Code	Range	Accuracy
1139-150	0-150mm/0-6"	±0.1mm

SHOCK  
PROOF



## DIAL CALIPER



1312-150A


Dial indicator graduation: 0.02mm (mm)

Code	Range	Accuracy	L	a	b	c	d	D
1312-150A*	0-150mm	±0.03mm	235	21	16.5	16	40	Ø39
1312-200A*	0-200mm	±0.03mm	288	24	19	16	48	Ø39
1312-300A*	0-300mm	±0.04mm	410	28	22	20	62	Ø44.5

- Shockproof dial indicator
- Made of stainless steel

Dial indicator graduation: 0.01mm (mm)

Code	Range	Accuracy	L	a	b	c	d	D
1311-150A*	0-150mm	±0.03mm	235	21	16.5	16	40	Ø39
1311-200A*	0-200mm	±0.03mm	288	24	19	16	48	Ø39
1311-300A*	0-300mm	±0.04mm	410	28	22	20	62	Ø44.5



\* Supplied with manufacturer inspection certificate traceable to DKD Germany





## MINI VERNIER CALIPER

- Meet DIN862
- Made of stainless steel
- Satin chrome plated reading surface

1204-70

Code	Range	Graduation	Accuracy
1204-70	0-70mm	0.05mm	±0.05mm




## MINI VERNIER CALIPER

- Meet DIN862
- Made of stainless steel
- Satin chrome plated reading surface

1203-1003

Code	Range	Graduation	Accuracy
1203-1003	0-100mm	0.05mm	±0.05mm




## MINI VERNIER CALIPER



- Meet DIN862
- Made of stainless steel
- Satin chrome plated reading surface

1201-1003



Code	Range	Graduation	Accuracy
1201-1003	0-100mm	0.05mm	±0.05mm

## VERNIER CALIPER



1205-150S

Graduation 0.05mm/1/128" (mm)

Code	Range	Accuracy	L	a	b	c	d
1205-150S	0-150mm/0-6"	±0.05mm	235	20.5	15.5	16	40
1205-200S	0-200mm/0-8"	±0.05mm	290	23.5	19	16	50
1205-300S	0-300mm/0-12"	±0.05mm	414	27.5	22	20	64

Graduation 0.05mm (mm)

Code	Range	Accuracy	L	a	b	c	d
1205-1503S	0-150mm	±0.05mm	235	20.5	15.5	16	40
1205-2003S	0-200mm	±0.05mm	290	23.5	19	16	50
1205-3003S	0-300mm	±0.05mm	414	27.5	22	20	64


Graduation 0.02mm/0.001" (mm)

Code	Range	Accuracy	L	a	b	c	d
1205-1502S	0-150mm/0-6"	±0.03mm	235	20.5	15.5	16	40
1205-2002S	0-200mm/0-8"	±0.03mm	290	23.5	19	16	50
1205-3002S	0-300mm/0-12"	±0.03mm	414	27.5	22	20	64


Graduation 0.02mm (mm)

Code	Range	Accuracy	L	a	b	c	d
1205-1501S	0-150mm	±0.03mm	235	20.5	15.5	16	40
1205-2001S	0-200mm	±0.03mm	290	23.5	19	16	50
1205-3001S	0-300mm	±0.03mm	414	27.5	22	20	64

- Meet DIN862
- Made of stainless steel
- Satin chrome plated reading surface



## VERNIER CALIPER WITH FINE ADJUSTMENT




1233-130

- Graduation 0.02mm/0.001"
- With fine adjustment
- Meet DIN862
- Made of stainless steel
- Satin chrome plated reading surface

(mm)

Code	Range	Accuracy	L	a	b	c	d
1233-130	0-130mm/0-5"	±0.03mm	230	20.5	16.5	16	40
1233-180	0-180mm/0-7"	±0.03mm	295	23.5	19	16	50
1233-280	0-280mm/0-11"	±0.03mm	410	26	20	20	60



## VERNIER CALIPER WITH THUMB CLAMP



1223-150

Graduation 0.05mm/1/128"


(mm)

Code	Range	Accuracy	L	a	b	c	d
1223-150	0-150mm/0-6"	±0.05mm	230	20.5	16.5	16	40
1223-200	0-200mm/0-8"	±0.05mm	295	23.5	19	16	50
1223-300	0-300mm/0-12"	±0.05mm	405	26	20	20	60

Graduation 0.02mm/0.001"

(mm)

Code	Range	Accuracy	L	a	b	c	d
1223-1502	0-150mm/0-6"	±0.03mm	230	20.5	16.5	16	40
1223-2002	0-200mm/0-8"	±0.03mm	295	23.5	19	16	50
1223-3002	0-300mm/0-12"	±0.03mm	405	26	20	20	60




- Meet DIN862
- With thumb clamp
- Made of stainless steel
- Satin chrome plated reading surface

## VERNIER CALIPER WITH ROUND DEPTH BAR



1202-150

- Graduation 0.05mm/1/128"
- Round depth bar
- Meet DIN862
- Made of stainless steel
- Satin chrome plated reading surface



Code	Range	Accuracy
1202-150	0-150mm/0-6"	±0.05mm

## VERNIER CALIPER WITH CARBIDE TIPPED JAWS



1238-150


- Carbide tipped jaws for inside and outside measurements
- Meet DIN862
- Made of stainless steel
- Satin chrome plated reading surface

Graduation 0.05mm/1/128" (mm)

Code	Range	Accuracy	L	a	b	c	d
1238-150	0-150mm/0-6"	±0.05mm	230	21	16.5	16	40
1238-200	0-200mm/0-8"	±0.05mm	295	24	19	16	50
1238-300	0-300mm/0-12"	±0.05mm	410	25	20	17	60

Graduation 0.02mm/0.001" (mm)

Code	Range	Accuracy	L	a	b	c	d
1238-1502	0-150mm/0-6"	±0.03mm	230	21	16.5	16	40
1238-2002	0-200mm/0-8"	±0.03mm	295	24	19	16	50
1238-3002	0-300mm/0-12"	±0.03mm	410	25	20	17	60




## DIGITAL CALIPER

DATA  
OUTPUT



(mm) 1106-501

Code	Range	Accuracy	a	c	d	e	L
1106-301	0-300mm/0-12"	±0.05mm	12	24	100	20	420
1106-302	0-300mm/0-12"	±0.05mm	12	24	150	20	420
1106-451	0-450mm/0-18"	±0.05mm	18	24	100	20	625
1106-501	0-500mm/0-20"	±0.05mm	18	24	100	20	675
1106-502	0-500mm/0-20"	±0.06mm	18	24	150	20	675
1106-503	0-500mm/0-20"	±0.06mm	18	31	200	20	675
1106-505	0-500mm/0-20"	±0.08mm	18	42	300	20	675
1106-601	0-600mm/0-24"	±0.05mm	18	24	100	20	770
1106-602	0-600mm/0-24"	±0.06mm	18	24	150	20	770
1106-603	0-600mm/0-24"	±0.06mm	18	31	200	20	770
1106-802	0-800mm/0-32"	±0.07mm	24	31	150	20	1025
1106-1002	0-1000mm/0-40"	±0.08mm	24	31	150	20	1220
1106-1003	0-1000mm/0-40"	±0.08mm	24	31	200	20	1220
1106-1005	0-1000mm/0-40"	±0.10mm	24	42	300	20	1220
1106-1502	0-1500mm/0-60"	±0.11mm	24	42	150	20	1780
1106-1503	0-1500mm/0-60"	±0.12mm	24	42	200	20	1780
1106-2002	0-2000mm/0-80"	±0.14mm	24	42	150	20	2290
1106-2003	0-2000mm/0-80"	±0.14mm	24	42	200	20	2290



- Resolution: 0.01mm/0.0005"
- Button function: on/off, zero, mm/inch, ABS, data preset
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

## DIGITAL CALIPER

DATA  
OUTPUT




1117-501

- Resolution: 0.01mm/0.0005"
- Button function: on/off, zero, mm/inch, ABS, data preset
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

Code	Range	Accuracy	a	b	c	d	e	L
1117-301	0-300mm/0-12"	±0.05mm	12	38	24	100	20	420
1117-501	0-500mm/0-20"	±0.05mm	18	56	24	100	20	675
1117-502	0-500mm/0-20"	±0.06mm	18	56	24	150	20	675
1117-601	0-600mm/0-24"	±0.05mm	18	56	24	100	20	770
1117-802	0-800mm/0-32"	±0.07mm	24	67	31	150	20	1025
1117-1002	0-1000mm/0-40"	±0.08mm	24	67	31	150	20	1220

(mm)





DATA  
OUTPUT

## DIGITAL CALIPER




1136-501

- Resolution: 0.01mm/0.0005"
- Button function: on/off, zero, mm/inch, ABS, data preset
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable  
(code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

(mm)

Code	Range	Accuracy	a	b	c	d	e	L
1136-301	0-300mm/0-12"	±0.05mm	12	28	24	100	20	420
1136-451	0-450mm/0-18"	±0.05mm	18	45	24	100	20	625
1136-501	0-500mm/0-20"	±0.05mm	18	45	24	100	20	675
1136-502	0-500mm/0-20"	±0.06mm	18	45	24	150	20	675
1136-503	0-500mm/0-20"	±0.06mm	18	45	31	200	20	675
1136-601	0-600mm/0-24"	±0.05mm	18	45	24	100	20	770
1136-1002	0-1000mm/0-40"	±0.08mm	24	60	31	150	20	1220
1136-1502	0-1500mm/0-60"	±0.11mm	24	60	42	150	20	1780
1136-2002	0-2000mm/0-80"	±0.14mm	24	60	42	150	20	2290



DATA  
OUTPUT

## DIGITAL CALIPER




1135-601

- Resolution: 0.01mm/0.0005"
- Button function: on/off, zero, mm/inch, ABS, data preset
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable  
(code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

(mm)

Code	Range	Accuracy	a	c	d	L
1135-451	0-450mm/0-18"	±0.05mm	45	24	100	625
1135-601	0-600mm/0-24"	±0.05mm	45	24	100	770
1135-1002	0-1000mm/0-40"	±0.08mm	60	31	150	1220



## VERNIER CALIPER



1236-521


Graduation 0.05mm/1/128" (mm)

Code	Range	Accuracy	a	b	c	d	e	L
1236-394	0-300mm/0-12"	±0.07mm	12	38	20	90	10	450
1236-514	0-500mm/0-20"	±0.07mm	18	45	24	100	20	670
1236-524	0-500mm/0-20"	±0.08mm	18	45	24	150	20	670
1236-614	0-600mm/0-24"	±0.08mm	18	45	24	100	20	770
1236-824	0-800mm/0-32"	±0.09mm	24	60	31	150	20	1030
1236-1024	0-1000mm/0-40"	±0.12mm	24	60	31	150	20	1230

Graduation 0.02mm (mm)

Code	Range	Accuracy	a	b	c	d	e	L
1236-511	0-500mm	±0.05mm	18	45	24	100	20	670
1236-521	0-500mm	±0.06mm	18	45	24	150	20	670
1236-1021	0-1000mm	±0.08mm	24	60	31	150	20	1230

- With fine adjustment
- Made of stainless steel
- Satin chrome plated reading surface



## VERNIER CALIPER




1207-514

- Graduation 0.05mm/1/128"
- With fine adjustment
- Made of stainless steel
- Satin chrome plated reading surface

(mm)

Code	Range	Accuracy	a	b	c	d	e	L
1207-394	0-300mm/0-12"	±0.07mm	12	40	20	90	10	440
1207-514	0-500mm/0-20"	±0.07mm	18	56	24	100	20	670
1207-524	0-500mm/0-20"	±0.08mm	18	56	24	150	20	670
1207-824	0-800mm/0-32"	±0.09mm	24	67	31	150	20	930
1207-1024	0-1000mm/0-40"	±0.12mm	24	67	31	150	20	1230



## VERNIER CALIPER





1208-511

Graduation 0.05mm/1/128" (mm)

Code	Range	Accuracy	a	c	d	e	L
1208-214	0-200mm/0-8"	±0.06mm	10	20	100	10	330
1208-394	0-300mm/0-12"	±0.07mm	12	20	90	10	410
1208-324	0-300mm/0-12"	±0.07mm	18	24	150	20	410
1208-524	0-500mm/0-20"	±0.08mm	18	24	150	20	670
1208-614	0-600mm/0-24"	±0.08mm	18	24	100	20	770
1208-624	0-600mm/0-24"	±0.09mm	18	24	150	20	770
1208-824	0-800mm/0-32"	±0.09mm	24	31	150	20	1030
1208-1024	0-1000mm/0-40"	±0.12mm	24	31	150	20	1230
1208-1524	0-1500mm/0-60"	±0.16mm	24	42	150	20	1820
1208-2024	0-2000mm/0-80"	±0.20mm	24	42	150	20	2330

- With fine adjustment
- Made of stainless steel
- Satin chrome plated reading surface



Graduation 0.02mm (mm)

Code	Range	Accuracy	a	c	d	e	L
1208-511	0-500mm	±0.05mm	18	24	100	20	670
1208-521	0-500mm	±0.06mm	18	24	150	20	670
1208-1021	0-1000mm	±0.08mm	24	31	150	20	1230
1208-1521	0-1500mm	±0.11mm	24	42	150	20	1820

## VERNIER CALIPER




1210-611

Graduation 0.05mm/1/128" (mm)

Code	Range	Accuracy	a	c	d	L
1210-614	0-600mm/0-24"	±0.08mm	45	24	100	770
1210-1024	0-1000mm/0-40"	±0.12mm	60	31	150	1230

Graduation 0.02mm (mm)

Code	Range	Accuracy	a	c	d	L
1210-611	0-600mm	±0.05mm	45	24	100	770
1210-1021	0-1000mm	±0.08mm	60	31	150	1230



- With fine adjustment
- Made of stainless steel
- Satin chrome plated reading surface




## VERNIER CALIPER

1214-500

Graduation 0.02mm/0.001" (mm)

Code	Range	Accuracy	a	c	d	e	L
1214-300	0-300mm/0-12"	±0.05mm	10	20	75	10	410
1214-450	0-450mm/0-18"	±0.05mm	18	24	100	20	620
1214-500	0-500mm/0-20"	±0.05mm	18	24	100	20	670
1214-600	0-600mm/0-24"	±0.05mm	18	24	100	20	770
1214-1000	0-1000mm/0-40"	±0.08mm	24	32	140	20	1216
1214-1500	0-1500mm/0-60"	±0.12mm	24	42	200	20	1830
1214-2000	0-2000mm/0-80"	±0.14mm	24	42	200	20	2320

- With fine adjustment
- Made of stainless steel
- Satin chrome plated reading surface



Graduation 0.05mm/1/128" (mm)

Code	Range	Accuracy	a	c	d	e	L
1214-6004	0-600mm/0-24"	±0.08mm	18	24	100	20	770
1214-1004	0-1000mm/0-40"	±0.12mm	24	32	140	20	1216




## LONG JAW VERNIER CALIPER

1215-1032

Graduation 0.02mm/0.001" (mm)

Code	Range	Accuracy	a	c	d	e	L
1215-392	0-300mm/0-12"	±0.05mm	10	17	90	10	410
1215-322	0-300mm/0-12"	±0.05mm	18	24	150	20	470
1215-522	0-500mm/0-20"	±0.06mm	18	24	150	20	670
1215-532	0-500mm/0-20"	±0.06mm	18	24	200	20	670
1215-622	0-600mm/0-24"	±0.06mm	18	24	150	20	770
1215-642	0-600mm/0-24"	±0.08mm	24	32	250	20	870
1215-822	0-800mm/0-32"	±0.07mm	24	32	150	20	1020
1215-832	0-800mm/0-32"	±0.07mm	24	32	200	20	1020
1215-1032	0-1000mm/0-40"	±0.08mm	24	32	200	20	1220
1215-1052	0-1000mm/0-40"	±0.11mm	24	32	300	20	1330
1215-3052	0-3000mm/0-120"	±0.26mm	24	50	300	20	3360

- With fine adjustment
- Made of stainless steel
- Satin chrome plated reading surface



Graduation 0.05mm/1/128" (mm)

Code	Range	Accuracy	a	c	d	e	L
1215-524	0-500mm/0-20"	±0.08mm	18	24	150	20	670
1215-1034	0-1000mm/0-40"	±0.12mm	24	32	200	20	1330


# CUSTOM-MADE CALIPER

- We are able to make calipers according to the design from customers




# SET BUTTON

- In some calipers, there is a "SET" button. It is possible to set a initial reading (instead of zero) on these calipers.
- For internal measurement, if the size L is unknown, it is necessary to set. After setting, you can get a direct reading, without adding L.
  - Step 1: Find a micrometer, set it at a number (for example, 25mm) and lock it.
  - Step 2: Press "SET", "+" and "-" buttons to set 25 on caliper. After setting, the initial reading will be 25 instead of zero, when "SET" is pressed anytime.
  - Step 3: Put caliper into the micrometer, press "SET", the reading is 25.



- For external measurement, if the tips are spherical, it is difficult to set zero because the two tips may not be aligned.
  - Step 1: Find a gage block (for example, 10mm).
  - Step 2: Press "SET", "+" and "-" buttons to set 10mm on caliper. After setting, the initial reading will be 10mm instead of zero, when SET is pressed anytime.
  - Step 3: Hold the gage block, press "SET", the reading is 10mm.




# UNIVERSAL CALIPER CODE 1125-600

DATA  
OUTPUT



1125-600



working with stands



working with measuring jaws





- Buttons: on/off, set, mm/inch, ABS, preset (+, -)
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)


Code	Range*	Resolution	Accuracy
1125-600	0-600mm/0-24"	0.01mm/0.0005"	±0.05mm

\*The range changes according to different points

## Half disk points (included)





Measuring external groove diameter with flat measuring face (depth  $h_1 \leq 2.5\text{mm}$ )



Measuring internal groove diameter with spherical measuring face (depth  $h_2 \leq 7.5\text{mm}$ )

## Conical points (optional)




Measuring center distance

Code

1125-T101

## Round shoulder points (optional)




Measuring inside diameter

Code

1125-T102

## Flat shoulder points (optional)



Measuring outside diameter


Code

1125-T103

To be continued

Continued from previous page


**Point sleeve (optional)**




**Code**  
1125-T104

Working with multifunctional points, ball points and screw thread points


**Spherical points (included)**




**Stands (included)**



**Measuring jaws (included)**



**Depth stop (included)**



**Multifunctional points 7392 (optional, page 26)**



**Ball points 7391 (optional, page 26)**





**Screw thread points 7381, 7321 (optional, page 26)**




# DIGITAL CALIPER WITH INTERCHANGEABLE POINTS CODE 1526-200


DATA  
OUTPUT




1526-200




### short spherical points (included)




### long spherical/flat points (included)




### spherical blade points (included)



### install points



### measure internal and external grooves



- Supplied with 3 pairs of points and zero setting block for external measurement
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, set, mm/inch, preset (+, -)
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: points (code 1526-T101, 7392, 7391, 7381, 7321), depth stop (code 6143), data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

### zero setting block for external measurement (included)



Point	Range	Accuracy	Application
short spherical points	12-212mm/0.5-8.5"(internal)	±0.03mm	for grooves inside small hole
long spherical/flat points	24-224mm/1-8.8"(internal) 0-187mm/0-7.5"(external)	±0.03mm	spherical points for grooves inside hole flat points for external grooves
spherical blade points	24-224mm/1-8.8"(internal) 0-187mm/0-7.5"(external)	±0.03mm	for narrow grooves inside hole

To be continued





Continued from previous page


**Depth stop (optional)**




**Code**  
**6143**



**Point sleeve (optional)**




**1526-T101**




**Code**  
**1526-T101**

**installation**




**Multifunctional points (optional)**



Code	Type
7392-T1	flat
7392-T2	spherical
7392-T3	spline
7392-T4	disk
7392-T5*	blade
7392-T6*	knife-edge
7392-T7	point
7392-T8*	knife-edge
7392-T9	point

\* It is necessary to use point sleeve (code 1526-T101) for these points


**Ball points (optional)**



**7391-T5**

Code	Ball dia.(D)	Module
7391-T1	SØ1mm	0.6-0.65
7391-T2	SØ1.5mm	0.9-1.0
7391-T3	SØ2.0mm	1.25
7391-T4	SØ2.5mm	1.5
7391-T5	SØ3.0mm	1.75
7391-T6	SØ3.5mm	2
7391-T7	SØ4.0mm	2.25
7391-T8	SØ4.5mm	2.5
7391-T9	SØ5.0mm	2.75
7391-T10	SØ6.0mm	3.5
7391-TS	10 pairs/set, including all above points	

**Screw thread points (optional)**



**7321-T16**

**7381-T11**

**Internal thread (60° thread angle)**

Code	Pitch
7321-T11*	0.4-0.5mm/64-48TPI
7321-T12*	0.6-0.9mm/44-28TPI
7321-T13*	1-1.75mm/24-14TPI
7321-T14*	2-3mm/13-9TPI
7321-T15*	3.5-5mm/8-5TPI
7321-T16*	5.5-7mm/4.5-3.5TPI
7321-T15*	6 pairs/set, including all above points



**External thread (60° thread angle)**

Code	Pitch
7381-T11*	0.4-0.5mm/ 64-48TPI
7381-T12*	0.6-0.9mm/ 44-28TPI
7381-T13*	1-1.75mm/ 24-14TPI
7381-T14*	2-3mm/ 13-9TPI
7381-T15*	3.5-5mm/ 8-5TPI
7381-T16*	5.5-7mm/ 4.5-3.5TPI
7381-TS*	6 pairs/set, including all above points

\* It is necessary to use point sleeve (code 1526-T101) for these points

# DIGITAL CALIPER WITH INTERCHANGEABLE POINTS CODE 1124-300A


DATA  
OUTPUT




1124-300A

Unit: mm


**short spherical/flat points (included)**





**long spherical/flat points (included)**



**short spherical blade points (included)**




**long spherical blade points (included)**



**depth stop 6143 (optional)**




**measure internal and external grooves**



- Supplied with 4 pairs of points and zero setting block for external measurement
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, set, mm/inch, preset (+, -)
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: points (code 1526-T101, 7392, 7391, 7381, 7321), depth stop (code 6143), data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

Point	Range	Accuracy	Application
short spherical/flat points	24-324mm/1-12.7"(internal) 0-288mm/0-11.3"(external)	±0.04mm	spherical points for grooves inside hole (small hole) flat points for external grooves
long spherical/flat points	40-340mm/1.5-13.3"(internal) 0-272mm/0-10.7"(external)	±0.04mm	spherical points for grooves inside hole (large hole) flat points for external grooves
short spherical blade points	24-324mm/1-12.7"(internal) 0-288mm/0-11.3"(external)	±0.04mm	for narrow grooves inside hole (small hole)
long spherical blade points	40-340mm/1.5-13.3"(internal) 0-272mm/0-10.7"(external)	±0.04mm	for narrow grooves inside hole (large hole)

**install points**



**Multifunctional points 7392 (optional, page 26)**



**Ball points 7391 (optional, page 26)**



**Screw thread points 7381, 7321 (optional, page 26)**



**zero setting block for external measurement (included)**



DATA  
OUTPUT

## DIGITAL INSIDE GROOVE CALIPER





1120-150A

depth stop 6143 (optional)




- Measure groove diameter
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, set, mm/inch, preset (+, -)
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: depth stop (code 6143), data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

preset buttons



Code	Range	Accuracy	L	a	b	c	d	e
1120-150A	22-150mm	±0.04mm	250	5	11	16	30	1
1120-200A	25-200mm	±0.04mm	310	5	12.5	16	40	1
1120-300A	30-300mm	±0.05mm	410	5	15	17	50	1.5

(mm)



DATA  
OUTPUT

## DIGITAL INSIDE POINT CALIPER





1121-150A

depth stop 6143 (optional)




- Measure groove diameter
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, set, mm/inch, preset (+, -)
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: depth stop (code 6143), data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

preset buttons




Code	Range	Accuracy	L	a	b	c	d	D
1121-150A	24-150mm	±0.04mm	250	5	12	16	30	∅2
1121-200A	25-200mm	±0.04mm	310	5	12.5	16	40	∅2
1121-3001A	50-300mm	±0.06mm	410	8	25	17	80	∅3

(mm)



## DIGITAL INSIDE GROOVE CALIPER




1176-150

- Measure diameter of grooves inside bores
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, set, mm/inch, preset (+, -)
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: depth stop (code 6143), data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

depth stop 6143 (optional)




DATA OUTPUT




Unit: mm

sizes to be measured (use upper jaws)



sizes to be measured (use lower jaws)



(mm)

D1	L1
Ø9	<8
Ø10	<15
Ø11~150	<30

D2	L2
Ø15	<10
Ø16	<18
Ø17	<26
Ø18	<34

D2	L2
Ø19	<42
Ø20	<50
Ø21	<58
Ø22~150	<70

Code	Range of upper jaw	Range of lower jaw	Accuracy
1176-150	9-150mm/0.35-6"	15-150mm/0.59-6"	±0.04mm

## DIGITAL INSIDE GROOVE CALIPER



1178-300


- Measure diameter of grooves inside bores
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, set, mm/inch, preset (+, -)
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: depth stop (code 6143), data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

DATA OUTPUT



depth stop 6143 (optional)



preset buttons



sizes to be measured



Unit: mm

(mm)

D1	L1
Ø25	<50
Ø26	<60
Ø27-300	<110

Code	Range	Accuracy
1178-300	25-300mm/1.18-12"	±0.05mm

DATA  
OUTPUT


## DIGITAL INSIDE GROOVE CALIPER



1520-150

- Measure diameter of grooves inside small bores
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, set, mm/inch, preset (+, -)
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: depth stop (code 6143), data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)


preset buttons



depth stop 6143 (optional)



Unit: mm



Code	Range	Accuracy
1520-150	11-150mm/0.43-6"	±0.04mm


DATA  
OUTPUT

## DIGITAL BLADE CALIPER




1188-150A

- The blade jaws fit into small grooves
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)



(mm)

Code	Range	Accuracy	L	a	b	c	d	e	g
1188-150A	0-150mm/0-6"	±0.03mm	235	21	16.5	16	40	0.75	17
1188-200A	0-200mm/0-8"	±0.03mm	297	24	20	16	50	0.75	17
1188-300A	0-300mm/0-12"	±0.04mm	390	26	21.5	16	60	1.00	17



## DIGITAL OUTSIDE NECK CALIPER


DATA OUTPUT

- Measure grooves and recesses
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: depth stop (code 6143), data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)



1187-150A

depth stop 6143 (optional)



Code	Range	Accuracy
1187-150A	0-150mm/0-6"	±0.04mm

## DIGITAL OUTSIDE POINT CALIPER


DATA OUTPUT

- Measure wall thickness inside bores and recesses
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: depth stop (code 6143), data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)



1185-150A

depth stop 6143 (optional)



Code	Range	Accuracy
1185-150A	0-150mm/0-6"	±0.04mm

## DEPTH STOP FOR CALIPERS



- Supplied in pair
- Made of stainless steel
- Suitable for caliper series 1124, 1526, 1520, 1176, 1178, 1120, 1121, 1187 and 1185

Code
6143



6143

Application




DATA  
OUTPUT


## DIGITAL SMALL POINT CALIPER



1169-150



- Small pointed jaws fit into small grooves and recesses
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable  
(code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)




Code	Range	Accuracy
1169-150	0-150mm/0-6"	±0.03mm

DATA  
OUTPUT


## DIGITAL POINT CALIPER



1183-150A



- Pointed jaws fit into small grooves and recesses
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable  
(code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)




Code	Range	Accuracy
1183-150A	0-150mm/0-6"	±0.03mm

## DIGITAL OFFSET CENTERLINE CALIPER

DATA  
OUTPUT





1192-150A



- Measure hole center distance in the same or offset planes
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, set, mm/inch, preset (+, -)
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable  
(code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

Code	Range	Accuracy	L (mm)
1192-150A	10-150mm	±0.05mm	236
1192-200A	10-200mm	±0.07mm	286
1192-300A	10-300mm	±0.09mm	396





## DIGITAL BACK-JAW CENTERLINE CALIPER

DATA  
OUTPUT




1177-200



- Measure hole center distance in the same or offset planes
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, set, mm/inch, preset (+, -)
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable  
(code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

Code	Range	Accuracy	L (mm)
1177-200	10-200mm/0.4-8"	±0.1mm	310
1177-300	10-300mm/0.4-12"	±0.1mm	410






DATA  
OUTPUT


## DIGITAL CENTERLINE/EDGE TO CENTER CALIPER



1525-300




preset buttons




Unit: mm

measure edge to  
hole center distance



measure hole center distance




- Measure hole center distance or edge to hole center distance
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, set, mm/inch, preset (+, -)
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

Code	Range of upper jaw (edge to center)	Range of lower jaw (center to center)	Accuracy
1525-300	5-300mm/0.2-12"	10-300mm/0.4-12"	$\pm 0.08\text{mm}$

DATA  
OUTPUT

## DIGITAL BACK-JAW EDGE TO CENTER CALIPER




1524-200


back-jaw




preset buttons



- Measure edge to hole center distance
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, set, mm/inch, preset (+, -)
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)




Code	Range	Accuracy	L (mm)
1524-200	5-200mm/0.2-8"	$\pm 0.1$	310
1524-300	5-300mm/0.2-12"	$\pm 0.1$	410



Unit: mm


## DIGITAL INSIDE KNIFE-EDGE CALIPER

DATA  
OUTPUT



1123-150A


- Measure diameter of deep step holes
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)



Code	Range	Accuracy
1123-150A	15-150mm/0.6-6"	±0.05mm


## DIGITAL HOOK CALIPER

DATA  
OUTPUT



1122-200A

- Measure width of groove inside bores
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)



Code	Range	Accuracy
1122-200A	3-200mm/0.12-8"	±0.03mm



## DIGITAL ARC RADIUS CALIPER

DATA  
OUTPUT



1189-150B

- Measure the radius of arc less than half round
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)




Code	Range (R)	Accuracy	L	c	d	(mm)
1189-150B	5-150mm/0.2-6"	±0.05mm	263	16	65	
1189-200B	5-200mm/0.2-8"	±0.07mm	313	16	85	

DATA  
OUTPUT




1186-150A

- The left jaw can slide up and down to facilitate measurement of stepped sections
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)



Code	Range	Accuracy	L	a	b	c	d	(mm)
1186-150A	0-150mm/0-6"	±0.04mm	239	40	16.5	16	110	
1186-200A	0-200mm/0-8"	±0.04mm	289	50	19.5	16	120	
1186-300A	0-300mm/0-12"	±0.05mm	389	60	20.5	17	130	




# DIGITAL TUBE THICKNESS CALIPER

DATA OUTPUT



- Measure wall thickness of tubes
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

1161-150A




Code	Range	Accuracy
1161-150A	0-150mm/0-6"	±0.05mm

# DIGITAL RTJ RING GROOVE CALIPER


DATA OUTPUT




1179-300



1179-600




1179-300




1179-600

- Measure ring grooves of flange
- Resolution: 0.01mm/0.0005"
- Button function: on/off, set, zero, mm/inch, data preset
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)


applicable for RTJ ring grooves with angle 23°



measure outside diameter of RTJ ring groove



measure inside diameter of RTJ ring groove



Code	Range (inside diameter of RTJ ring groove)	Range (outside diameter of RTJ ring groove)	Angle of RTJ ring groove	Accuracy
1179-300	10-300mm/0.4-12"	25-300mm/1-12"	23°	±0.06mm
1179-600	10-600mm/0.4-24"	25-600mm/1-24"	23°	±0.07mm

## DIGITAL CRIMP HEIGHT CALIPER

RELATIVE PRODUCT:  
CRIMP HEIGHT MICROMETER  
(CODE 3266-25BA, 3566-25BA)


DATA  
OUTPUT



1165-150A

- Measure crimp height
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

Code	Range	Accuracy
1165-150A	0-150mm/0-6"	±0.03mm



## DIGITAL CALIPER WITH LARGE MEASURING FACES


DATA  
OUTPUT




1172-200

- Measure diameter of wire ropes, and thickness of soft materials like rubber, sponge, etc.
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)


Code	Range	Accuracy
1172-200	0-200mm/0-8"	±0.07mm



measure diameter of wire ropes




measure thickness of rubber, sponge, etc.




## DIGITAL GEAR TOOTH CALIPER

DATA  
OUTPUT



1181-M25A



- Resolution: 0.01mm/0.0005"
- Carbide tips
- Buttons: zero, on/off, mm/inch
- Battery LR44
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

Code	Range	Accuracy	L1	L2	a	b1	b2	d
1181-M25A	M1-25mm	±0.04mm	170	165.5	21	16	16	30.5
1181-M50A	M5-50mm	±0.04mm	220	190	50.5	16	16	55

(mm)


## DIGITAL DISK BRAKE CALIPER

DATA  
OUTPUT

RELATIVE PRODUCT:  
DISK BRAKE MICROMETER  
(CODE 3288-, 3588-)




1162-125A



- Measure thickness of disk brakes
- Resolution 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

Code	Range	Accuracy
1162-125A	0-125mm/0-5"	±0.05mm



Unit:mm


DATA  
OUTPUT

## DIGITAL DISK BRAKE AND PAD CALIPER




1167-150A

RELATIVE PRODUCT:  
DISK BRAKE MICROMETER  
(CODE 3288-, 3588-)



- Measure thickness of disk brakes and pad wear
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

Code	Range	Accuracy
1167-150A	0-150mm/0-6"	±0.07mm




DATA  
OUTPUT

## DIGITAL DRUM BRAKE CALIPER



1168-300A

RELATIVE PRODUCT:  
DISK BRAKE MICROMETER  
(CODE 3288-, 3588-)



- Measure internal and external diameter of drum brakes
- Resolution 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

Code	Range	Accuracy
1168-300A	0-300mm/0-12"	±0.07mm



# WATERPROOF DIGITAL DEPTH GAGE

ATTENTION:  
NO DATA OUTPUT

IP67  
WATERPROOF


ATTENTION: IT IS NECESSARY TO SET  
ZERO AFTER POWER ON EACH TIME



- IP67 dust/waterproof
- Resolution: 0.01mm/0.0005"
- Button function: zero, on/off, mm/inch, ABS/REL, hold
- Meet DIN862
- Battery CR2032
- Made of stainless steel

1149-150

Code	Range	Accuracy	L	a	b	d	(mm)
1149-150	0-150mm/0-6"	±0.03mm	240	6	16	100	
1149-200	0-200mm/0-8"	±0.03mm	290	6	16	100	
1149-300	0-300mm/0-12"	±0.03mm	390	6	16	150	



# DIGITAL DEPTH GAGE


DATA  
OUTPUT



- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Meet DIN862 (except 1141-500A)
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

1141-150A

Code	Range	Accuracy	L	a	b	d	(mm)
1141-150A	0-150mm/0-6"	±0.03mm	230	6	14.5	100	
1141-200A	0-200mm/0-8"	±0.03mm	280	6	14.5	100	
1141-300A	0-300mm/0-12"	±0.03mm	380	6	14.5	150	
1141-500A	0-500mm/0-20"	±0.05mm	585	7	15	150	





CAN BE INSTALLED WITH EXTENSION BASE


DATA OUTPUT

## DIGITAL DEPTH GAGE



1147-300

- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Meet DIN862
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2), extension base (code 6141)




extension base (optional)



Code	Range	Accuracy	L (mm)
1147-150	0-150mm/0-6"	±0.03mm	237
1147-200	0-200mm/0-8"	±0.03mm	287
1147-300	0-300mm/0-12"	±0.03mm	403


DATA OUTPUT

## DIGITAL POINT DEPTH GAGE



1143-200A

- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Meet DIN862
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)



Code	Range	Accuracy
1143-200A	0-200mm/0-8"	±0.03mm

## DIGITAL DOUBLE HOOK DEPTH GAGE



DATA OUTPUT



- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Meet DIN862
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

1144-150A

Unit: mm



(mm)

Code	Range	Accuracy	L	d
1144-150A	0-150mm/0-6"	±0.03mm	233	100
1144-200A	0-200mm/0-8"	±0.03mm	283	100
1144-300A	0-300mm/0-12"	±0.03mm	383	150

## DIGITAL HOOK DEPTH GAGE



DATA OUTPUT



1142-150A

Unit: mm

- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)



(mm)

Code	Range	Accuracy	L	d
1142-150A	0-150mm/0-6"	±0.03mm	230	100
1142-200A	0-200mm/0-8"	±0.03mm	280	100
1142-300A	0-300mm/0-12"	±0.04mm	380	150

# DIGITAL DEPTH GAGE WITH ROUND DEPTH BAR



1148-100S



1148-200



1148-120

one-hand use of 1148-120



- Resolution: 0.01mm/0.0005"
- Supplied with three interchangeable points (flat, spherical, disk)
- Buttons: on/off, set, mm/inch, preset (+, -)
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory:  
data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2),  
disk points (see below table),  
extension base (code 6141, for 1148-120 and 1148-200)

Code	Range *	Accuracy	L	d	Remark
1148-100S	0-100mm/0-4"	±0.02mm	200	45	
1148-100	0-100mm/0-4"	±0.02mm	200	85	
1148-120	0-120mm/0-4.7"	±0.03mm	300	101	one-hand use, with clamp holes for extension base
1148-200	0-200mm/0-8"	±0.03mm	300	101	with clamp holes for extension base

\* When disk points are used, the range is reduced by 10mm


## OPTIONAL DISK POINTS

Code	Description	Remark
1148-P101	0.5mm disk point	for narrow grooves
1148-P102	0.7mm disk point	for narrow grooves
1148-P103	1mm disk point	for grooves inside blind hole


MEASURE WIDTH AND DEPTH OF GROOVES INSIDE BORE

MEASURE DEPTH OF SMALL HOLES (>Ø4mm)


DATA OUTPUT




measure depth of small holes (>Ø4mm)






measure depth of grooves inside bore




measure depth of grooves inside bore




measure width of grooves inside bore



flat point



spherical point



disk point

extension base for 1148-120 and 1148-200 (optional)




1148-P101 (optional)




1148-P103 (optional)




Unit: mm



1148-P101



1148-P102



1148-P103

## VERNIER DEPTH GAGE



1240-2001


Unit: mm

Graduation 0.05mm (mm)

Code	Range	Accuracy	L	d
1240-150	0-150mm	±0.05mm	245	100
1240-200	0-200mm	±0.05mm	282	100
1240-300	0-300mm	±0.08mm	382	100
1240-500	0-500mm	±0.09mm	585	150

Graduation 0.02mm (mm)

Code	Range	Accuracy	L	d
1240-1501	0-150mm	±0.03mm	245	100
1240-2001	0-200mm	±0.03mm	282	100
1240-3001	0-300mm	±0.04mm	382	100
1240-5001	0-500mm	±0.05mm	585	150



- Made of stainless steel
- Satin chrome plated reading surface

## VERNIER DEPTH GAGE



1247-1501


- Made of stainless steel
- Satin chrome plating finish on reading surface
- Optional accessory: extension base (code 6141)

extension base (optional)



6141 series

Unit: mm



Graduation 0.05mm

Code	Range	Accuracy
1247-150	0-150mm	±0.05mm
1247-200	0-200mm	±0.05mm
1247-300	0-300mm	±0.08mm
1247-600	0-600mm	±0.10mm
1247-1000	0-1000mm	±0.15mm

Graduation 0.02mm

Code	Range	Accuracy
1247-1501	0-150mm	±0.03mm
1247-2001	0-200mm	±0.03mm
1247-3001	0-300mm	±0.04mm
1247-6001	0-600mm	±0.05mm
1247-1001	0-1000mm	±0.07mm

(mm)

Range	L	c	d
0-150mm	240	16	100
0-200mm	290	16	100
0-300mm	390	16	100
0-600mm	704	16	150
0-1000mm	1124	18	200

## VERNIER DEPTH GAGE



1249-1501


- With fine adjustment
- Made of stainless steel
- Satin chrome plating finish on reading surface
- Optional accessory: extension base (code 6141)

### Graduation 0.05mm

Code	Range	Accuracy
1249-150	0-150mm	±0.05mm
1249-200	0-200mm	±0.05mm
1249-300	0-300mm	±0.08mm

### Graduation 0.02mm

Code	Range	Accuracy
1249-1501	0-150mm	±0.03mm
1249-2001	0-200mm	±0.03mm
1249-3001	0-300mm	±0.04mm




Range	L	c	d
0-150mm	256	16	100
0-200mm	306	16	100
0-300mm	406	16	100

## VERNIER HOOK DEPTH GAGE




1248-1501



- Made of stainless steel
- Satin chrome plating finish on reading surface
- Optional accessory: extension base (code 6141)

### Graduation 0.05mm

Code	Range	Accuracy	L
1248-150	0-150mm	±0.05mm	266mm
1248-200	0-200mm	±0.05mm	316mm
1248-300	0-300mm	±0.08mm	416mm





### Graduation 0.02mm

Code	Range	Accuracy	L
1248-1501	0-150mm	±0.03mm	266mm
1248-2001	0-200mm	±0.03mm	316mm
1248-3001	0-300mm	±0.04mm	416mm

## EXTENSION BASE




6141-260




Unit: mm

- Supplied with two screws
- Made of stainless steel
- Suitable for depth gages series 1147, 1148, 1247, 1248 and 1249



6141-260

Code	Length
6141-180	180mm
6141-260	260mm
6141-320	320mm




6141-320

## DEPTH BASE ATTACHMENT



6140



Unit: mm

- To increase the stability of depth measurement
- Suitable for digital calipers
- Made of stainless steel

Code	a	b	c	Application
6140	16.5	9	75	Suitable for digital calipers with beam width (w) 16mm
6140-300	17	10	125	Suitable for digital calipers with beam width (w) 17mm

(mm)



**ATTENTION:  
BASIC MODEL**


## VERNIER DEPTH GAGE



1244-30

- Graduation: 0.1mm
- Made of stainless steel

Code	Range	Accuracy
1244-30	0-30mm	±0.10mm



Unit: mm

**DATA  
OUTPUT**


## DIGITAL DEPTH GAGE




1145-25A

- Measure depth of small groove and hole, also measure depth of tire tread
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Supplied with zero set surface
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)


Code	Range	Accuracy
1145-25A	0-25mm/0-1"	±0.03mm



Unit: mm




## DIAL DEPTH GAGE



- Stainless steel base
- Pointed tip

Code	Range	Dial indicator stroke	Dial indicator graduation	Accuracy	Base
2343-101	0-10mm	10mm	0.01mm	±0.017mm	Ø16mm
2343-102	0-10mm	10mm	0.01mm	±0.017mm	Ø25mm

## DIGITAL DEPTH GAGE



- Button function: on/off, zero, mm/inch, ABS, data preset, change measuring direction
- CR2032 battery, automatic power off
- Data output
- Stainless steel base
- Pointed tip
- Optional accessory: data output cable (code 7306-40, 7302-SPC3A, 7305-SPC1A)

Code	Range	Digital indicator stroke	Digital indicator resolution	Accuracy	Base
2142-101	0-12.7mm/0-0.5"	12.7mm/0.5"	0.01mm/0.0005"	±0.02mm	Ø16mm
2142-102	0-12.7mm/0-0.5"	12.7mm/0.5"	0.01mm/0.0005"	±0.02mm	Ø25mm




## DIAL DEPTH GAGE

- Stainless steel base
- Supplied with pointed tip and ball tip



2341-101A



Code	Range	Dial indicator stroke	Dial indicator graduation	Accuracy
2341-101A	0-10mm	10mm	0.01mm	±0.017mm


## DIAL DEPTH GAGE



2342-202


- Dial indicator graduation: 0.01mm
- Accuracy: ±0.03mm
- Stainless steel base
- Extension rods: 25mm(1pc), 50mm(1pc), 75mm(1pc), 100mm(2pcs)
- Supplied with pointed tip and ball tip

Code	Range	Dial indicator stroke	Base
2342-201	0-300mm	30mm	63x17mm
2342-202	0-300mm	30mm	101.5x17mm



2342-201

2342-202



extension rods


# DIGITAL DEPTH GAGE

DATA OUTPUT



2141-202A

- Button function: on/off, zero, mm/inch, ABS, data preset, change measuring direction
- CR2032 battery, automatic power off
- Data output
- Stainless steel base
- Extension rods: 12.5mm(1pc), 25mm(1pc), 50mm(1pc), 75mm(1pc), 100mm(2pcs)
- Supplied with pointed tip and ball tip
- Optional accessory: data output cable (code 7306-40, 7302-SPC3A, 7305-SPC1A)




Unit: mm

Code	Range	Digital indicator stroke	Digital indicator resolution	Accuracy	Base
2141-201A	0-300mm/0-12"	12.7mm/0.5"	0.01mm/0.0005"	±0.02mm	63x17mm
2141-202A	0-300mm/0-12"	12.7mm/0.5"	0.01mm/0.0005"	±0.02mm	101.5x17mm

# DIGITAL DEPTH MICROMETER

IP54 WATERPROOF

DATA OUTPUT




Unit: mm



3540-50

- Resolution: 0.001mm/0.00005"
- Micrometer head accuracy: +/-3µm
- Rod accuracy: +/- (2+L/75)µm, L is the measuring range in mm
- Button function: on/off, set, mm/inch, ABS/INC, data output
- IP54 dust/waterproof
- Data output
- LR44 battery, automatic power off
- Rods with flat end
- Ratchet stop
- Optional accessory: data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)


Code	Range	Rods
3540-50	0-50mm/0-2"	2pcs
3540-150	0-150mm/0-6"	6pcs
3540-300	0-300mm/0-12"	12pcs



## DEPTH MICROMETER




3240-100



Unit: mm

Code	Range	Rods
3240-25	0-25mm	1pc
3240-50	0-50mm	2pcs
3240-75	0-75mm	3pcs
3240-100	0-100mm	4pcs
3240-150	0-150mm	6pcs
3240-200	0-200mm	8pcs
3240-300	0-300mm	12pcs


- Graduation: 0.01mm
- Micrometer head accuracy:  $\pm 3\mu\text{m}$
- Rod accuracy:  $\pm (2+L/75)\mu\text{m}$ , L is the measuring range in mm
- Rods with flat end
- Ratchet stop



## DEPTH MICROMETER



3241-100



Unit: mm


Base: HxW=101.5x17mm

Code	Range	Rods
3241-25	0-25mm	1pc
3241-50	0-50mm	2pcs
3241-75	0-75mm	3pcs
3241-100	0-100mm	4pcs
3241-150	0-150mm	6pcs
3241-200	0-200mm	8pcs
3241-300	0-300mm	12pcs

- Graduation: 0.01mm
- Micrometer head accuracy:  $\pm 3\mu\text{m}$
- Rod accuracy:  $\pm (2+L/75)\mu\text{m}$ , L is the measuring range in mm
- Rods with flat end
- Ratchet stop

Base: HxW=63x17mm

Code	Range	Rods
3241-B25	0-25mm	1pc



# DIGITAL HEIGHT GAGE


DATA OUTPUT




1150-1000




1150-500



- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch, ABS/INC, data hold, TOL, set
- ABS/INC is for absolute and incremental measurement
- TOL is for tolerance measurement
- Carbide tipped scriber
- Made of stainless steel (except the base)
- LR44 battery
- Data output
- Supplied with dial test indicator holder
- Optional accessory: data output cable (code 7301-SPC5)



type A



type B


Code	Range	Type	Accuracy	L	a1	a2	b	c1	c2	d
1150-300	0-300mm/0-12"	A	±0.04mm	470	135	45	80	76	25	23
1150-500	0-500mm/0-20"	A	±0.05mm	720	180	55	95	103	25	30
1150-600	0-600mm/0-24"	A	±0.05mm	820	180	55	95	103	25	30
1150-1000	0-1000mm/0-40"	B	±0.07mm	1275	250	80	125	110	39	50
1150-1500	0-1500mm/0-60"	B	±0.11mm	1790	280	80	125	110	39	50
1150-2000	0-2000mm/0-80"	B	±0.15mm	2290	280	80	125	110	39	50




# DIGITAL HEIGHT GAGE WITH DRIVING WHEEL

DATA OUTPUT

dial test indicator holder (optional)



- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch, preset +, preset -, hold
- Automatic power off, move the digital unit to turn on power
- Carbide tipped scriber
- Made of stainless steel
- Battery CR2032
- Data output
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2), dial test indicator holder (code 6293-6)




1156-300

Code	Range	Accuracy	L
1156-300	0-300mm/0-12"	±0.03mm	515mm
1156-600	0-600mm/0-24"	±0.05mm	815mm

DATA OUTPUT


# DIGITAL HEIGHT GAGE

- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Carbide tipped scriber
- With fine adjustment
- Made of stainless steel
- Battery CR2032
- Data output
- Optional accessory: data output cable, dial test indicator holder (code 7151-CL1)




1154-150

dial test indicator holder (optional)




Code	Range	Accuracy
1154-150	0-150mm/0-6"	±0.03mm

# DIAL HEIGHT GAGE



driving wheel

- Dial indicator graduation: 0.01mm
- One counter reads in the plus direction and another in the minus direction, so incremental measurement can be made in either direction
- Carbide tipped scriber
- Made of stainless steel (except the base)
- With driving wheel
- Optional accessory: dial test indicator holder (code 6293-6)




1351-300

(mm)

Code	Range	Accuracy	L	a1	a2	b	c	ØD
1351-300	0-300mm	±0.04mm	475	135	43	84	33	15
1351-450	0-450mm	±0.05mm	660	180	54	88	38	20
1351-600	0-600mm	±0.05mm	810	180	54	88	38	20



dial test indicator holder (optional)



# VERNIER HEIGHT GAGE

dial test indicator holder (optional)

- Graduation: 0.02mm/0.001"
- Adjustable main scale to set zero
- Carbide tipped scriber
- Made of stainless steel (except the base)
- Satin chrome plated scale
- Supplied with magnifier
- With fine adjustment
- Optional accessory: dial test indicator holder (code 6293-6)




1250-300


Code	Range	Accuracy	L	a1	a2	b	c1	c2	d
1250-300	0-300mm/0-12"	±0.04mm	545	135	43	75	80	30	28
1250-450	0-450mm/0-18"	±0.05mm	720	180	54	85	80	41	35
1250-600	0-600mm/0-24"	±0.05mm	870	180	54	85	80	41	35

## VERNIER HEIGHT GAGE


- Graduation 0.02mm/0.001"
- Carbide tipped scriber
- Made of stainless steel (except the base)
- Satin chrome plated scale
- Optional accessory: dial test indicator holder (code 7151-CL1)



1253-200



dial test indicator holder (optional)



Code	Range	Accuracy	L	a	b	d
1253-150	0-150mm/0-6"	±0.03mm	265	75	57	16
1253-200	0-200mm/0-8"	±0.03mm	325	90	70	20


(mm)

## SCRIBER FOR HEIGHT GAGES



7150-SC1

- Carbide tipped



Code	For height gages	Type	c1	c2	D	E
7150-SC1	1150-300	A	76	25	6	8
7150-SC2	1150-500, 1150-600	A	103	25	10	12
7150-SC3	1150-1000, 1150-1500, 1150-2000	A	110	39	10	15
7150-SC4	1351-300, 1351-450, 1351-600	B	78	15	9	9
7150-SC6	1250-300, 1156-300, 1156-600	A	80	30	9	9
7150-SC7	1250-450, 1250-600	A	80	41	9	9
7150-SC9	1253-150, 1253-200, 1154-150	B	55	12.5	6	8

(mm)

## NON-ROTATING SPINDLE DIGITAL MICROMETER

- Resolution: 0.001mm/0.00005"
- Repeatability: 1µm
- Measuring force: 5-10N
- Non-rotating spindle, suitable for cylinders
- Quick measurement: one turn of sleeve or ratchet stop makes 1mm spindle feed
- Carbide measuring faces
- Ratchet stop
- Data output
- Button function: mm/inch, max./min. value tracking, tolerance measurement, hold, on/off, zero
- CR2032 battery, automatic power off
- Supplied with setting standards (except 0-25mm/0-1")



QUICK MEASUREMENT  
ONE TURN OF SLEEVE OR RATCHET STOP  
MAKES 1MM SPINDLE FEED

NON-ROTATING  
SPINDLE


DATA  
OUTPUT



3631-25

Code	Range	Accuracy	L	a	b
3631-25	0-25mm/0-1"	±2µm	34	188	28.5
3631-50	25-50mm/1-2"	±2µm	59	211	30
3631-75	50-75mm/2-3"	±3µm	84	240	44
3631-100	75-100mm/3-4"	±3µm	109	264	56
3631-125	100-125mm/4-5"	±3µm	134	289	76
3631-150	125-150mm/5-6"	±3µm	160	314	89

(mm)



Unit: mm

## NON-ROTATING SPINDLE DIGITAL MICROMETER

- Resolution: 0.001mm/0.00005"
- Repeatability: 1µm
- Measuring force: 5-10N
- Lever device suitable for mass production
- Non-rotating spindle, suitable for cylinders
- Quick measurement: one turn of sleeve or ratchet stop makes 1mm spindle feed
- Carbide measuring faces
- Ratchet stop
- Data output
- Button function: mm/inch, max./min. value tracking, tolerance measurement, hold, on/off, zero
- CR2032 battery, automatic power off



LEVER DEVICE SUITABLE FOR  
MASS PRODUCTION

QUICK MEASUREMENT  
ONE TURN OF SLEEVE OR RATCHET STOP  
MAKES 1MM SPINDLE FEED

NON-ROTATING  
SPINDLE

DATA  
OUTPUT



3632-25

### lever device


Press lever device to retract the spindle 1.5mm (max.).  
Loose lever device to release the spindle to contact workpiece,  
measuring force is constant.

retracting stroke 1.5mm (max.)



Code	Range	Accuracy	L	a	b
3632-25	0-25mm/0-1"	±2µm	34	188	28.5

(mm)



Unit: mm



INSIZE		Inspection Certificate		
Product name	Outside Micrometer	Unit: $\mu\text{m}$		
Code No.	3203-25A	Measuring Length(mm)	Permissible Error	Error
Measuring range	0-25mm	0	4	0
Graduation	0.01mm	7.7		+1
Serial No.	0910120004	12.9		-1
Standard temperature	20 °C	17.6		0
Based on	DIN 863-1 (1999)	22.8		+1
Traceable to	Germany DKD No. D-K-15190-01-00	25		+1
Inspector	<i>Paulo</i>	Judgement: Passed		

**MANUFACTURER INSPECTION  
CERTIFICATE TRACEABLE  
TO DKD GERMANY,  
FOR MICROMETERS**




## DIGITAL OUTSIDE MICROMETER

- Resolution 0.001mm/0.00005"  
(resolution of **3101-275A** and **3101-300A** is 0.001mm/0.0001")
- IP65 dust/waterproof
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Carbide measuring faces
- Supplied with spherical anvil
- Setting standards are included (except 0-25mm/0-1")
- Optional accessory: data output cable (code **7306-30**, **7302-SPC2A**, **7305-SPC3**)



**3101-25A**





### Ratchet stop type

Code	Range	Accuracy	L	a	b	c
<b>3101-25A*</b>	0-25mm/0-1"	$\pm 2\mu\text{m}$	32.5	6	24	3
<b>3101-50A*</b>	25-50mm/1-2"	$\pm 2\mu\text{m}$	57.5	8	32	3
<b>3101-75A*</b>	50-75mm/2-3"	$\pm 3\mu\text{m}$	82.5	8	44.5	3
<b>3101-100A*</b>	75-100mm/3-4"	$\pm 3\mu\text{m}$	107.5	8	57	3
<b>3101-125A</b>	100-125mm/4-5"	$\pm 3\mu\text{m}$	133	10	70	3
<b>3101-150A</b>	125-150mm/5-6"	$\pm 3\mu\text{m}$	158.5	10	82	3
<b>3101-175A</b>	150-175mm/6-7"	$\pm 4\mu\text{m}$	184	12	94.5	5.5
<b>3101-200A</b>	175-200mm/7-8"	$\pm 4\mu\text{m}$	209.5	12	107	5.5
<b>3101-225A</b>	200-225mm/8-9"	$\pm 4\mu\text{m}$	234	19.4	129.5	5.5
<b>3101-250A</b>	225-250mm/9-10"	$\pm 4\mu\text{m}$	259.5	19.4	142.5	5.5
<b>3101-275A</b>	250-275mm/10-11"	$\pm 5\mu\text{m}$	285	19.4	155	5.5
<b>3101-300A</b>	275-300mm/11-12"	$\pm 5\mu\text{m}$	310.5	19.4	167.5	5.5

### Friction thimble type

Code	Range	Accuracy	L	a	b	c
<b>3101-25FA*</b>	0-25mm/0-1"	$\pm 2\mu\text{m}$	32.5	6	24	3

\* Supplied with manufacturer inspection certificate traceable to DKD Germany



## METRIC DIGITAL OUTSIDE MICROMETER



3108-25A

### Ratchet stop type (mm)


Code	Range	Accuracy	L	a	b	c
3108-25A*	0-25mm	±2µm	32.5	6	24	3
3108-50A*	25-50mm	±2µm	57.5	8	32	3
3108-75A*	50-75mm	±3µm	82.5	8	44.5	3
3108-100A*	75-100mm	±3µm	107.5	8	57	3
3108-125A	100-125mm	±3µm	133	10	70	3
3108-150A	125-150mm	±3µm	158.5	10	82	3
3108-175A	150-175mm	±4µm	184	12	94.5	5.5
3108-200A	175-200mm	±4µm	209.5	12	107	5.5

### Friction thimble type (mm)


Code	Range	Accuracy	L	a	b	c
3108-25FA*	0-25mm	±2µm	32.5	6	24	3

\* Supplied with manufacturer inspection certificate traceable to DKD Germany

**IP54**  
WATERPROOF



**ATTENTION:**  
NO DATA OUTPUT




- Resolution 0.001mm
- IP54 dust/waterproof
- Button function: on/off, set, ABS/INC
- Without data output
- LR44 battery, automatic power off
- Carbide measuring faces
- Supplied with spherical anvil
- Setting standards are included (except 0-25mm)

## DIGITAL OUTSIDE MICROMETER




3109-25B

**DATA**  
OUTPUT



Code	Range	Accuracy	L	a	b
3109-25B*	0-25mm/0-1"	±2µm	31.5	7.0	23
3109-50B*	25-50mm/1-2"	±2µm	57.0	8.7	32
3109-75B*	50-75mm/2-3"	±3µm	82.5	7.5	44
3109-100B*	75-100mm/3-4"	±3µm	106.5	8.2	56

\* Supplied with manufacturer inspection certificate traceable to DKD Germany



**INSIZE**  
MANUFACTURER  
INSPECTION CERTIFICATE  
TRACEABLE TO DKD


- Resolution 0.001mm/0.00005"
- Button function: on/off, set, mm/inch, ABS/INC
- Data output
- Battery CR2032, automatic power off
- Carbide measuring faces
- Friction thimble
- Supplied with spherical anvil
- Setting standards are included (except 0-25mm/0-1")
- Optional accessory: data output cable



## QUICK FEEDING OUTSIDE MICROMETER



3208-25B



Code	Range	Accuracy	L	a	b
3208-25B	0-25mm	4µm	32	6	24
3208-50B	25-50mm	4µm	57	8	32
3208-75B	50-75mm	5µm	82	8	45
3208-100B	75-100mm	5µm	107	8	57

- Graduation 0.01mm
- 1mm feeding of each turn
- Friction thimble
- Carbide measuring faces
- Meet DIN863
- Supplied with setting standards (except 0-25mm)

## OUTSIDE MICROMETER



3203-25A



3203-50A


- Graduation: 0.01mm
- Carbide measuring faces
- Meet DIN863
- Supplied with setting standards (except 0-25mm)

### Ratchet stop type

Code	Range	Accuracy	L	a	b
3203-25A *	0-25mm	4µm	32	9	28
3203-50A *	25-50mm	4µm	57	14	38
3203-75A *	50-75mm	5µm	82	15	49
3203-100A *	75-100mm	5µm	107	15	60
3203-125A	100-125mm	6µm	133	16.5	73
3203-150A	125-150mm	6µm	158	16.5	85
3203-175A	150-175mm	7µm	183	19.4	104
3203-200A	175-200mm	7µm	209	19.4	117
3203-225A	200-225mm	8µm	234	19.4	130
3203-250A	225-250mm	8µm	260	19.4	142
3203-275A	250-275mm	9µm	285	19.4	155
3203-300A	275-300mm	9µm	310	19.4	168

### Friction thimble type

Code	Range	Accuracy	L	a	b
3203-25FA *	0-25mm	4µm	32	9	28
3203-50FA *	25-50mm	4µm	57	14	38




### Micrometer set (ratchet stop type)

Code	Range	Micrometers included
3203-753A *	0-75mm	3203-25A, 3203-50A, 3203-75A
3203-1004A *	0-100mm	3203-25A, 3203-50A, 3203-75A, 3203-100A
3203-1506A	0-150mm	3203-25A, 3203-50A, 3203-75A, 3203-100A, 3203-125A, 3203-150A
3203-3006A	150-300mm	3203-175A, 3203-200A, 3203-225A, 3203-250A, 3203-275A, 3203-300A
3203-3012A	0-300mm	3203-25A, 3203-50A, 3203-75A, 3203-100A, 3203-125A, 3203-150A, 3203-175A, 3203-200A, 3203-225A, 3203-250A, 3203-275A, 3203-300A

\* Supplied with manufacturer inspection certificate traceable to DKD Germany

# 1µm GRADUATION OUTSIDE MICROMETER



3210-25A

**Ratchet stop type (mm)**

Code	Range	Accuracy	L	a	b
3210-25A*	0-25mm	4µm	32	9	28
3210-50A*	25-50mm	4µm	57	14	38
3210-75A*	50-75mm	5µm	82	15	49
3210-100A*	75-100mm	5µm	107	15	60
3210-125A	100-125mm	6µm	133	16.5	73
3210-150A	125-150mm	6µm	158	16.5	85
3210-175A	150-175mm	7µm	183	19.4	104
3210-200A	175-200mm	7µm	209	19.4	117

- Graduation 0.001mm
- Carbide measuring faces
- Meet DIN863
- Supplied with setting standards (except 0-25mm)

**Micrometer set (ratchet stop type)**


Code	Range	Micrometers included
3210-753A*	0-75mm	3210-25A, 3210-50A, 3210-75A
3210-1004A*	0-100mm	3210-25A, 3210-50A, 3210-75A, 3210-100A
3210-1506A	0-150mm	3210-25A, 3210-50A, 3210-75A, 3210-100A, 3210-125A, 3210-150A

\* Supplied with manufacturer inspection certificate traceable to DKD Germany

**Friction thimble type (mm)**

Code	Range	Accuracy	L	a	b
3210-25FA*	0-25mm	4µm	32	9	28
3210-50FA*	25-50mm	4µm	57	14	38

# OUTSIDE MICROMETER



3202-25A

- Graduation 0.01mm
- Carbide measuring faces
- Meet DIN863
- Supplied with setting standards (except 0-25mm)

**Micrometer set**

Code	Range	Micrometers included
3202-753A*	0-75mm	3202-25A, 3202-50A, 3202-75A
3202-1004A*	0-100mm	3202-25A, 3202-50A, 3202-75A, 3202-100A

\* Supplied with manufacturer inspection certificate traceable to DKD Germany

**(mm)**

Code	Range	Accuracy	L	a	b
3202-25A*	0-25mm	4µm	32	6	24
3202-50A*	25-50mm	4µm	57	8	32
3202-75A*	50-75mm	5µm	82	8	45
3202-100A*	75-100mm	5µm	107	8	57




## LONG SPINDLE OUTSIDE MICROMETER



3209-25

- Graduation 0.01mm
- Carbide measuring faces
- Meet DIN863
- Ratchet stop
- Supplied with setting standards (except 0-25mm)

Code	Range	Accuracy	L	a	b
3209-25	0-25mm	4 $\mu$ m	57	14	38
3209-50	25-50mm	4 $\mu$ m	82	15	49
3209-75	50-75mm	5 $\mu$ m	107	15	60
3209-100	75-100mm	5 $\mu$ m	133	16.5	73




## OUTSIDE MICROMETER FOR LEFT AND RIGHT HAND



front



back



3236-25B


Code	Range	Accuracy	L	a	b
3236-25B	0-25mm	4 $\mu$ m	32	6	24
3236-50B	25-50mm	4 $\mu$ m	57	8	32

- Graduation 0.01mm
- Graduations on two sides
- Ratchet stop
- Carbide measuring faces
- Meet DIN863
- Supplied with setting standards (except 0-25mm)


# OUTSIDE MICROMETER WITH INTERCHANGEABLE ANVILS




3206-150A



3206-400





type A



type B

Unit: mm



(mm)

Code	Range	Type	Accuracy	L	b	Setting standard (included)
3206-50A	0-50mm	A	4 $\mu$ m	58	35	25
3206-100A	0-100mm	A	5 $\mu$ m	108	57	25, 50, 75
3206-150A	0-150mm	A	6 $\mu$ m	158	82	25, 50, 75, 100, 125
3206-151A	50-150mm	A	6 $\mu$ m	158	82	50, 75, 100, 125
3206-200A	100-200mm	A	7 $\mu$ m	208	114	100, 125, 150, 175
3206-300A	150-300mm	A	9 $\mu$ m	308	165	150, 175, 200, 225, 250, 275
3206-301A	200-300mm	A	9 $\mu$ m	308	165	200, 225, 250, 275
3206-400	300-400mm	B	11 $\mu$ m	409	224	325, 375
3206-500	400-500mm	B	13 $\mu$ m	509	275	425, 475
3206-600	500-600mm	B	14 $\mu$ m	609	321	525, 575
3206-700	600-700mm	B	16 $\mu$ m	709	371	625, 675
3206-800	700-800mm	B	18 $\mu$ m	809	426	725, 775
3206-900	800-900mm	B	20 $\mu$ m	909	476	825, 875
3206-1000	900-1000mm	B	22 $\mu$ m	1009	576	925, 975

- Graduation 0.01mm
- Ratchet stop
- Carbide measuring faces
- Supplied with setting standards

# DIGITAL OUTSIDE MICROMETER WITH INTERCHANGEABLE ANVILS

**IP54**  
WATERPROOF



**DATA**  
OUTPUT



**3506-100A**




**3506-400A**



Unit: mm

- Resolution 0.001mm/0.0001" (resolution of **3506-100A** and **3506-150A** is 0.001mm/0.00005")
- IP54 dust/waterproof
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Carbide measuring faces
- Supplied with setting standards
- Optional accessory: data output cable (code **7306-30**, **7302-SPC2A**, **7305-SPC3**)






Code	Range	Type	Accuracy	L	b	Setting standard (included)
<b>3506-100A</b>	0-100mm/0-4"	A	±5µm	105	57	25, 50, 75
<b>3506-150A</b>	0-150mm/0-6"	A	±6µm	155	82	25, 50, 75, 100, 125
<b>3506-300A</b>	150-300mm/6-12"	A	±8µm	305	165	150, 175, 200, 225, 250, 275
<b>3506-301A</b>	200-300mm/8-12"	A	±8µm	305	165	200, 225, 250, 275
<b>3506-400A</b>	300-400mm/12-16"	B	±9µm	405	224	325, 375
<b>3506-500A</b>	400-500mm/16-20"	B	±11µm	505	275	425, 475
<b>3506-600A</b>	500-600mm/20-24"	B	±12µm	605	321	525, 575
<b>3506-700A</b>	600-700mm/24-28"	B	±13µm	705	371	625, 675
<b>3506-800A</b>	700-800mm/28-32"	B	±15µm	805	426	725, 775
<b>3506-900A</b>	800-900mm/32-36"	B	±16µm	905	476	825, 875
<b>3506-1000A</b>	900-1000mm/36-40"	B	±17µm	1005	576	925, 975


(mm)



# OUTSIDE MICROMETER WITH EXTENSION ANVIL COLLAR



Unit: mm



adjust collars for different measuring ranges

Code	Range	Type	Accuracy	L	b	Setting standard (included)
3205-400	300-400mm	A	11µm	410	250	325, 375
3205-500	400-500mm	A	13µm	510	295	425, 475
3205-600	500-600mm	A	14µm	610	345	525, 575
3205-700	600-700mm	A	16µm	710	395	625, 675
3205-800	700-800mm	A	18µm	810	445	725, 775,
3205-900	800-900mm	A	20µm	910	495	825, 875
3205-1000	900-1000mm	A	22µm	1010	545	925, 975
3205-1200	1000-1200mm	B	22µm	1210	645	1050, 1150
3205-1400	1200-1400mm	B	24µm	1410	745	1250, 1350
3205-1600	1400-1600mm	B	28µm	1610	845	1450, 1550
3205-1800	1600-1800mm	B	31µm	1810	945	1650, 1750
3205-2000	1800-2000mm	B	34µm	2010	1045	1850, 1950


- Graduation 0.01mm
- Adjust collars for different measuring ranges
- Ratchet stop
- Carbide measuring faces
- Supplied with setting standards



## INDICATING MICROMETER



3333-25



- Carbide measuring faces
- Measuring force 5-10N

Code	Micrometer head			Dial indicator		
	Range	Graduation	Accuracy	Range	Graduation	Accuracy
3333-25	0-25mm	0.01mm	2µm	±0.07mm	1µm	1µm


## INDICATING MICROMETER




3332-25



3332-25B



type A



type B

(mm)

Code	Micrometer head range	Micrometer head accuracy	Type	L	b	Remark
3332-25	0-25mm	4µm	A	28.5	19	with support
3332-50	25-50mm	4µm	A	53.5	30	with support
3332-75	50-75mm	5µm	A	78.5	45	without support
3332-100	75-100mm	5µm	A	103.5	57	without support
3332-25B	0-25mm	4µm	B	28.5	19	without support


- Micrometer head graduation: 0.002mm
- Dial indicator: range ±0.04mm, graduation 0.001mm, accuracy 0.001mm
- Carbide measuring faces
- Supplied with setting standards (except 0-25mm)

## LIMIT MICROMETER



3235-25A (mm)

Code	Range	Accuracy	L	a	b
3235-25A	0-25mm	4µm	32	12	24
3235-50A	25-50mm	4µm	57	15	32




- Used as Go/No-Go gauge by setting upper and lower limits
- Graduation 0.002mm
- Carbide measuring faces
- Supplied with setting standard (except 0-25mm)

## MICROMETER WITH DIAL INDICATOR

ATTENTION: NOT SUITABLE FOR 0.001MM INDICATORS



3296-100A




3296-400A


- Graduation 0.01mm
- Ratchet stop
- Carbide measuring faces
- Supplied with setting standards
- Optional accessory: dial indicators (graduation 0.01mm), digital indicators (resolution 0.01mm/0.0005")

(mm)

Code	Range	Type	Accuracy	L	b
3296-100A	0-100mm	A	6µm	115	68
3296-200A	100-200mm	A	7µm	215	120
3296-300A	200-300mm	A	8µm	315	170
3296-400A	300-400mm	B	9µm	415	225
3296-500A	400-500mm	B	10µm	515	275
3296-600A	500-600mm	B	11µm	615	325
3296-700A	600-700mm	B	12µm	715	375
3296-800A	700-800mm	B	13µm	815	430
3296-900A	800-900mm	B	14µm	915	480
3296-1000A	900-1000mm	B	15µm	1015	530



Type A



Type B


## MICROMETER WITH DIAL INDICATOR



3331-25A

- Micrometer head graduation 0.01mm
- Anvil retracting range: 8mm
- Carbide measuring faces
- Supplied with setting standards (except 0-25mm)
- Optional accessory:  
dial indicators (graduation 0.01mm),  
digital indicators (resolution 0.01mm/0.0005")

ATTENTION: NOT SUITABLE FOR 0.001MM INDICATORS



(mm)

Code	Micrometer head range	Micrometer head accuracy	L	b
3331-25A	0-25mm	4µm	67	38
3331-50A	25-50mm	4µm	92.4	50
3331-75A	50-75mm	5µm	117.6	62
3331-100A	75-100mm	5µm	143	70
3331-125A	100-125mm	6µm	168.2	82
3331-150A	125-150mm	6µm	192	94.5
3331-175A	150-175mm	7µm	217	107

## MICROMETER WITH DIAL INDICATOR




3633-300

(mm)

Code	Range	Frame type	L	b
3633-100	0-100mm	steel plate	116	65
3633-200	100-200mm	steel plate	217	109
3633-300	200-300mm	steel plate	317	159
3633-400	300-400mm	steel plate	417	209
3633-500	400-500mm	steel tube	517	259
3633-600	500-600mm	steel tube	617	310
3633-700	600-700mm	steel tube	717	360
3633-800	700-800mm	steel tube	817	408
3633-900	800-900mm	steel tube	917	460
3633-1000	900-1000mm	steel tube	1017	512


ATTENTION: SETTING STANDARDS ARE NOT INCLUDED



steel plate frame (0-400mm)

- Micrometer head range: 25mm
- Micrometer head graduation: 0.01mm
- Adjust collars for different measuring ranges
- Anvil retracting range: 3mm
- Carbide measuring faces
- Optional accessory: dial indicators or digital indicators, setting standards

## 3-WIRES



**Formula of pitch diameter E**  
 $E = M - 3d + 0.866025P$   
**M**=measured value of the micrometer  
**d**=diameter of the pin gage (choose diameter of pin gage according to pitch:  $d = 0.577P$ )  
**P**=screw thread pitch  
 The formula is suitable for 60° screw




7382-19

For outside micrometers with spindle Ø6.35mm (ØD)

Code	Pin gage diameter (Ød)	Applicable Pitch
7382-11	0.170mm	0.25mm
7382-12	0.195mm	0.35mm
7382-13	0.220mm	0.35mm
7382-14	0.250mm	0.4mm
7382-15	0.290mm	0.45mm, 0.5mm
7382-16	0.335mm	0.6mm
7382-17	0.390mm	0.7mm
7382-18	0.455mm	0.7mm, 0.75mm, 0.8mm
7382-19	0.530mm	0.9mm
7382-110	0.620mm	1mm
7382-111	0.725mm	1.25mm
7382-112	0.895mm	1.5mm
7382-113	1.100mm	1.75mm
7382-114	1.350mm	2mm
7382-115	1.650mm	2.5mm
7382-116	2.050mm	3mm, 3.5mm
7382-117	2.550mm	4mm, 4.5mm
7382-118	3.200mm	5mm, 5.5mm
7382-1S	18 pairs/set, including all above 3-wires	

For outside micrometers with spindle Ø6.50mm (ØD)

Code	Pin gage diameter (Ød)	Applicable Pitch
7382-21	0.170mm	0.25mm
7382-22	0.195mm	0.35mm
7382-23	0.220mm	0.35mm
7382-24	0.250mm	0.4mm
7382-25	0.290mm	0.45mm, 0.5mm
7382-26	0.335mm	0.6mm
7382-27	0.390mm	0.7mm
7382-28	0.455mm	0.7mm, 0.75mm, 0.8mm
7382-29	0.530mm	0.9mm
7382-210	0.620mm	1mm
7382-211	0.725mm	1.25mm
7382-212	0.895mm	1.5mm
7382-213	1.100mm	1.75mm
7382-214	1.350mm	2mm
7382-215	1.650mm	2.5mm
7382-216	2.050mm	3mm, 3.5mm
7382-217	2.550mm	4mm, 4.5mm
7382-218	3.200mm	5mm, 5.5mm
7382-2S	18 pairs/set, including all above 3-wires	



Unit: mm

- Used with standard outside micrometers with spindle Ø6.35mm or Ø6.50mm to measure pitch diameter of screw threads
- Diameter accuracy: ±0.5µm
- Cylindricity: 1µm
- Hardness: HRC60
- Supplied with manufacturer inspection certificate

## EXTERNAL SCREW THREAD MICROMETER



- Measure pitch diameter of screw thread
- Graduation 0.01mm
- Ratchet thimble
- Optional accessory: measuring tips for external screw thread micrometer (code 7384)

Code	Range	Accuracy	L	b
3639-25	0-25mm	4µm	45	31
3639-50	25-50mm	4µm	70	35
3639-75	50-75mm	5µm	95	48.5
3639-100	75-100mm	5µm	120	60
3639-125	100-125mm	6µm	145	72.5
3639-150	125-150mm	6µm	170	80
3639-175	150-175mm	7µm	195	97.5
3639-200	175-200mm	7µm	220	110
3639-225	200-225mm	8µm	245	122

tips are not included




3639-25



# MEASURING TIPS FOR EXTERNAL SCREW THREAD MICROMETER

TIPS FOR TRAPEZOIDAL, ACME  
THREAD ARE ALSO AVAILABLE



- Supplied in pair
- Made of hardened steel
- Suitable for 3639 series

7384-T108

## 60° thread angle

Code	Applicable pitch
7384-T101	0.2mm
7384-T102	0.225mm
7384-T103	0.25mm
7384-T104	0.3mm
7384-T105	0.35mm
7384-T106	0.4mm/0.45mm
7384-T107	0.5mm/0.6mm
7384-T108	0.7mm/0.75mm/0.8mm
7384-T109	1mm/1.25mm
7384-T110	1.5mm/1.75mm
7384-T111	2.0mm/2.5mm
7384-T112	3.0mm/3.5mm
7384-T113	4.0mm/4.5mm/5.0mm
7384-T114	5.5mm/6.0mm


## 55° thread angle

Code	Applicable pitch
7384-T201	80TPI
7384-T202	72TPI/64TPI
7384-T203	60TPI/48TPI
7384-T204	40TPI/32TPI
7384-T205	28TPI/26TPI/24TPI/22TPI
7384-T206	20TPI/19TPI/18TPI/16TPI
7384-T207	14TPI/12TPI/11TPI
7384-T208	10TPI/9TPI/8TPI
7384-T209	7TPI/6TPI
7384-T210	5TPI/4.5TPI/4TPI
7384-T211	3.5TPI/3.25TPI/3TPI/2.875TPI/2.75TPI
7384-T212	2.625TPI/2.5/2TPI

# SETTING STANDARD FOR EXTERNAL SCREW THREAD MICROMETER



7384-A100



## 60° thread angle

Code	L	Accuracy
7384-A25	25mm	±1.5µm
7384-A50	50mm	±2µm
7384-A75	75mm	±2.5µm
7384-A100	100mm	±3µm
7384-A125	125mm	±3.5µm
7384-A150	150mm	±4µm
7384-A175	175mm	±4.5µm
7384-A200	200mm	±5µm
7384-A225	225mm	±5.5µm
7384-A250	250mm	±6µm
7384-A275	275mm	±6.5µm
7384-A300	300mm	±7µm

## 55° thread angle


Code	L	Accuracy
7384-B25	25mm	±1.5µm
7384-B50	50mm	±2µm
7384-B75	75mm	±2.5µm
7384-B100	100mm	±3µm
7384-B125	125mm	±3.5µm
7384-B150	150mm	±4µm
7384-B175	175mm	±4.5µm
7384-B200	200mm	±5µm
7384-B225	225mm	±5.5µm
7384-B250	250mm	±6µm
7384-B275	275mm	±6.5µm
7384-B300	300mm	±7µm

# MEASURING TIPS FOR INTERNAL SCREW THREAD MICROMETER

- Supplied in pair
- Made of hardened steel
- Suitable for 3640, 3641series



TIPS FOR TRAPEZOIDAL, ACME THREAD ARE ALSO AVAILABLE



## 60° thread angle


Code		Applicable pitch
L=13.5mm	L=5mm	
7385-T101A	7385-T101B	0.35mm
7385-T102A	7385-T102B	0.4mm/0.45mm
7385-T103A	7385-T103B	0.5mm/0.6mm
7385-T104A	7385-T104B	0.7mm/0.75mm/0.8mm
7385-T105A	7385-T105B	1mm/1.25mm
7385-T106A	7385-T106B	1.5mm/1.75mm
7385-T107A	7385-T107B	2.0mm/2.5mm
7385-T108A	7385-T108B	3.0mm/3.5mm
7385-T109A	7385-T109B	4.0mm/4.5mm/5.0mm
7385-T110A	7385-T110B	5.5mm/6.0mm

## 55° thread angle

Code		Applicable pitch
L=13.5mm	L=5mm	
7385-T201A	7385-T201B	60/48TPI
7385-T202A	7385-T202B	40/32TPI
7385-T203A	7385-T203B	28/26/24/22TPI
7385-T204A	7385-T204B	20/19/18/16TPI
7385-T205A	7385-T205B	14/12/11TPI
7385-T206A	7385-T206B	10/9/8TPI
7385-T207A	7385-T207B	7/6TPI
7385-T208A	7385-T208B	5/4.5/4TPI
7385-T209A	7385-T209B	3.5/3.25/3/2.875/2.75TPI
7385-T210A	7385-T210B	2.625/2.5/2TPI




7385-T106A



7385-T106B

# SCREW THREAD MICROMETER

NON-ROTATING SPINDLE




measuring tips are not included




3281-25A

- Measure pitch diameter of screw threads
- Graduation 0.01mm
- Non-rotating spindle
- Ratchet stop
- Supplied with 60° setting standards (except 0-25mm)
- Optional accessory: 55° setting standards (code 3281-SP), measuring tips (code 7381)



Code	Range	(mm)	
		L	b
3281-25A	0-25mm	42	26
3281-50A	25-50mm	67	38
3281-75A	50-75mm	92	50
3281-100A	75-100mm	117.6	62
3281-125A	100-125mm	143	70
3281-150A	125-150mm	168.2	82
3281-175A	150-175mm	192	94.5
3281-200A	175-200mm	217	107

Pitch	accuracy of micrometer with tip (mm)					
	0-25	25-50	50-75	75-100	100-125	125-200
0.4~0.5	±0.01	-	-	-	-	-
0.6~0.8	±0.01	±0.013	-	-	-	-
1~1.25	±0.012	±0.015	±0.017	±0.017	-	-
1.5~2.0	±0.014	±0.017	±0.019	±0.019	±0.020	±0.023
2.5~3.5	±0.016	±0.019	±0.021	±0.021	±0.023	±0.025
4.0~7.0	-	±0.021	±0.023	±0.023	±0.025	±0.028



# DIGITAL SCREW THREAD MICROMETER



measuring tips are not included



DATA OUTPUT  
NON-ROTATING SPINDLE

3581-25A


- Measure pitch diameter of screw threads
- Resolution 0.001mm/0.00005"
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Non-rotating spindle
- Ratchet stop
- Supplied with 60° setting standards (except 0-25mm/0-1")
- Optional accessory: 55° setting standards (code 3281-SP), measuring tips (code 7381), data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)




accuracy of micrometer with tip (mm)

Pitch	Range			
	0-25	25-50	50-75	75-100
0.4-0.5	±0.01	-	-	-
0.6-0.8	±0.01	±0.013	-	-
1-1.25	±0.012	±0.015	±0.017	±0.017
1.5-2.0	±0.014	±0.017	±0.019	±0.019
2.5-3.5	±0.016	±0.019	±0.021	±0.021
4.0-7.0	-	±0.021	±0.023	±0.023

Code	Range	L	b
3581-25A	0-25mm/0-1"	42	26
3581-50A	25-50mm/1-2"	67	38
3581-75A	50-75mm/2-3"	92	50
3581-100A	75-100mm/3-4"	117.6	62



# MEASURING TIPS FOR SCREW THREAD MICROMETER



7381-T11


- Supplied in pair
- Suitable for 3281, 3581 series

Whitworth thread (55° thread angle)

Code	Pitch
7381-T21	60-48TPI
7381-T22	48-40TPI
7381-T23	40-32TPI
7381-T24	32-24TPI
7381-T25	24-18TPI
7381-T26	18-14TPI
7381-T27	14-10TPI
7381-T28	10-7TPI
7381-T29	7-4.5TPI
7381-T210	4.5-3.5TPI
7381-T2S	10 pairs/set, including all above tips

Metric and unified thread (60° thread angle)

Code	Pitch
7381-T11	0.4-0.5mm/ 64-48TPI
7381-T12	0.6-0.9mm/ 44-28TPI
7381-T13	1-1.75mm/ 24-14TPI
7381-T14	2-3mm/ 13-9TPI
7381-T15	3.5-5mm/ 8-5TPI
7381-T16	5.5-7mm/ 4.5-3.5TPI
7381-TS	6 pairs/set, including all above tips








ball tips are not included




3291-25

- Measure over-pin diameter of gears
- Graduation 0.01mm
- Ratchet stop
- Supplied with setting standards (except 0-25mm)
- Optional accessory: ball tips (code 7391)



## GEAR TOOTH MICROMETER



(mm)

Code	Range	Accuracy	L	b
3291-25	0-25mm	4µm	67	38
3291-50	25-50mm	4µm	92.4	50
3291-75	50-75mm	5µm	117.6	62
3291-100	75-100mm	5µm	143	70
3291-125	100-125mm	6µm	168.2	82
3291-150	125-150mm	6µm	192	94.5
3291-175	150-175mm	7µm	217	107

## DIGITAL GEAR TOOTH MICROMETER

ball tips are not included





3591-25A

DATA  
OUTPUT

IP54  
WATERPROOF

(mm)

Code	Range	Accuracy	L	b
3591-25A	0-25mm/0-1"	±4µm	67	38
3591-50A	25-50mm/1-2"	±4µm	92.4	50
3591-75A	50-75mm/2-3"	±5µm	117.6	62
3591-100A	75-100mm/3-4"	±5µm	143	70




- Measure over-pin diameter of gears
- Resolution 0.001mm/0.00005"
- IP54 dust/waterproof
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Supplied with setting standards (except 0-25mm/0-1")
- Optional accessory: ball tips (code 7391), data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)

- Supplied in pair
- Suitable for 3291, 3591 series

Code	Ball dia.(D)
7391-T1	SØ1mm
7391-T2	SØ1.5mm
7391-T3	SØ2.0mm
7391-T4	SØ2.5mm
7391-T5	SØ3.0mm
7391-T6	SØ3.5mm

Code	Ball dia.(D)
7391-T7	SØ4.0mm
7391-T8	SØ4.5mm
7391-T9	SØ5.0mm
7391-T10	SØ6.0mm
7391-TS	10 pairs/set, including all above tips


## BALL TIPS FOR GEAR TOOTH MICROMETER



## POINT MICROMETER





3230-25A



Unit: mm

Code	Range	Type	Accuracy	L	b
3230-25A	0-25mm	A	4µm	57	32
3230-50A	25-50mm	A	4µm	82	44.5
3230-75A	50-75mm	A	5µm	107	57
3230-100A	75-100mm	A	5µm	132.6	69.5
3230-25BA	0-25mm	B	4µm	57	32
3230-50BA	25-50mm	B	4µm	82	44.5
3230-75BA	50-75mm	B	5µm	107	57
3230-100BA	75-100mm	B	5µm	132.6	69.5

(mm)



- Measure the web thickness of drills, small grooves and keyways
- Graduation 0.01mm
- Ratchet stop
- Carbide tips
- Supplied with setting standards (except 0-25mm)


## DIGITAL POINT MICROMETER

IP54  
WATERPROOF



DATA  
OUTPUT



3530-25A



Unit: mm



Code	Range	Type	Accuracy	L	b
3530-25A	0-25mm/0-1"	A	±4µm	57	32
3530-50A	25-50mm/1-2"	A	±4µm	82	44.5
3530-75A	50-75mm/2-3"	A	±5µm	107	57
3530-100A	75-100mm/3-4"	A	±5µm	132.6	69.5
3530-25BA	0-25mm/0-1"	B	±4µm	57	32
3530-50BA	25-50mm/1-2"	B	±4µm	82	44.5
3530-75BA	50-75mm/2-3"	B	±5µm	107	57
3530-100BA	75-100mm/3-4"	B	±5µm	132.6	69.5

(mm)

- Measure the web thickness of drills, small grooves and keyways
- Resolution 0.001mm/0.00005"
- IP54 dust/waterproof
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Carbide tips
- Supplied with setting standards (except 0-25mm/0-1")
- Optional accessory: data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)





NON-ROTATING SPINDLE

## BLADE MICROMETER



3232-25A

Code	Range	Type	Accuracy	L	b
3232-25A	0-25mm	A	4μm	57	32
3232-50A	25-50mm	A	4μm	82	44.5
3232-75A	50-75mm	A	5μm	107	57
3232-100A	75-100mm	A	5μm	132.6	69.5
3232-125A	100-125mm	A	6μm	158	82
3232-150A	125-150mm	A	6μm	183.4	94.5
3232-175A	150-175mm	A	7μm	208.8	107
3232-25BA	0-25mm	B	4μm	57	32
3232-50BA	25-50mm	B	4μm	82	44.5



- Measure the groove diameter of shafts and keyways
- Graduation 0.01mm
- Non-rotating spindle
- Ratchet stop
- Supplied with setting standards (except 0-25mm)

DATA OUTPUT





NON-ROTATING SPINDLE

## DIGITAL BLADE MICROMETER



3532-25A

Code	Range	Type	Accuracy	L	b
3532-25A	0-25mm/0-1"	A	±4μm	57	32
3532-50A	25-50mm/1-2"	A	±4μm	82	44.5
3532-75A	50-75mm/2-3"	A	±5μm	107	57
3532-100A	75-100mm/3-4"	A	±5μm	132.6	69.5
3532-25BA	0-25mm/0-1"	B	±4μm	57	32
3532-50BA	25-50mm/1-2"	B	±4μm	82	44.5




- Measure the groove diameter of shafts and keyways
- Resolution 0.001mm/0.00005"
- Non-rotating spindle
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Supplied with setting standards (except 0-25mm/0-1")
- Optional accessory: data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)

## CRIMP HEIGHT MICROMETER

RELATIVE PRODUCT:  
DIGITAL CRIMP HEIGHT CALIPER  
(CODE 1165-150A)





3266-25BA



- Measure the height of crimp contact
- Graduation 0.01mm
- Ratchet stop

Code	Range	Accuracy
3266-25BA	0-25mm	4µm



## DIGITAL CRIMP HEIGHT MICROMETER


RELATIVE PRODUCT:  
DIGITAL CRIMP HEIGHT CALIPER  
(CODE 1165-150A)

**IP54**  
WATERPROOF

**DATA**  
OUTPUT





3566-25BA



- Measure the height of crimp contact
- Resolution 0.001mm/0.00005"
- IP54 dust/waterproof
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Optional accessory: data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)

Code	Range	Accuracy
3566-25BA	0-25mm/0-1"	±4µm







## SPLINE MICROMETER



3233-25BA

Code	Range	Type	Accuracy	L	b
3233-25A	0-25mm	A	4μm	57	32
3233-25BA	0-25mm	B	4μm	57	32
3233-50BA	25-50mm	B	4μm	82	44.5
3233-75BA	50-75mm	B	5μm	107	57
3233-100BA	75-100mm	B	5μm	132.6	69.5
3233-125BA	100-125mm	B	6μm	158	82
3233-150BA	125-150mm	B	6μm	183.4	94.5
3233-175BA	150-175mm	B	7μm	208.8	107

(mm)



- Measure splined shafts, slots and keyways
- Graduation 0.01mm
- Ratchet stop
- Carbide measuring faces
- Supplied with setting standards (except 0-25mm)

**IP54**  
WATERPROOF

**DATA**  
OUTPUT







3533-25BA

Code	Range	Type	Accuracy	L	b
3533-25A	0-25mm/0-1"	A	±4μm	57	32
3533-50A	25-50mm/1-2"	A	±4μm	82	44.5
3533-75A	50-75mm/2-3"	A	±5μm	107	57
3533-100A	75-100mm/3-4"	A	±5μm	132.6	69.5
3533-25BA	0-25mm/0-1"	B	±4μm	57	32
3533-50BA	25-50mm/1-2"	B	±4μm	82	44.5
3533-75BA	50-75mm/2-3"	B	±5μm	107	57
3533-100BA	75-100mm/3-4"	B	±5μm	132.6	69.5

(mm)

## DIGITAL SPLINE MICROMETER




- Measure splined shafts, slots and keyways
- Resolution 0.001mm/0.00005"
- IP54 dust/waterproof
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Carbide measuring faces
- Supplied with setting standards (except 0-25mm/0-1")
- Optional accessory: data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)



## CYLINDRICAL ANVIL TUBE MICROMETER



3261-25A



Code	Range	Type	Accuracy	L	b
3261-25A	0-25mm	A	6µm	31	24
3261-50A	25-50mm	A	6µm	57	32
3261-25BA	0-25mm	B	6µm	31	24
3261-50BA	25-50mm	B	6µm	57	32
3261-25CA	0-25mm	C	6µm	31	24
3261-25DA	0-25mm	D	6µm	31	24



- Measure wall thickness of tubes
- Graduation 0.01mm
- Ratchet stop
- Carbide spindle tip
- Supplied with setting standards (except 0-25mm)




## DIGITAL CYLINDRICAL ANVIL TUBE MICROMETER

DATA  
OUTPUT

IP54  
WATERPROOF



3561-25A



Code	Range	Type	Accuracy
3561-25A	0-25mm/0-1"	A	±6µm
3561-25BA	0-25mm/0-1"	B	±6µm
3561-25CA	0-25mm/0-1"	C	±6µm
3561-25DA	0-25mm/0-1"	D	±6µm




- Measure wall thickness of tubes
- Resolution 0.001mm/0.00005"
- IP54 dust/waterproof
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Carbide spindle tip
- Supplied with setting standards (except 0-25mm/0-1")
- Optional accessory: data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)

## SPHERICAL ANVIL TUBE MICROMETER



3260-25A

(mm)					
Code	Range	Type	Accuracy	L	b
3260-25A	0-25mm	A	4μm	32	24
3260-50A	25-50mm	A	4μm	57	32
3260-75A	50-75mm	A	5μm	82	44.5
3260-100A	75-100mm	A	5μm	107	57
3260-25SA	0-25mm	B	4μm	32	24
3260-50SA	25-50mm	B	4μm	57	32
3260-75SA	50-75mm	B	5μm	82	44.5
3260-100SA	75-100mm	B	5μm	107	57



- Measure wall thickness of tubes
- Graduation 0.01mm
- Ratchet stop
- Carbide measuring faces
- Supplied with setting standards (except 0-25mm)




DATA OUTPUT IP54 WATERPROOF

## DIGITAL SPHERICAL ANVIL TUBE MICROMETER



3560-25A


(mm)					
Code	Range	Type	Accuracy	L	b
3560-25A	0-25mm/0-1"	A	±4μm	32	24
3560-50A	25-50mm/1-2"	A	±4μm	57	32
3560-75A	50-75mm/2-3"	A	±5μm	82	44.5
3560-100A	75-100mm/3-4"	A	±5μm	107	57
3560-25SA	0-25mm/0-1"	B	±4μm	32	24
3560-50SA	25-50mm/1-2"	B	±4μm	57	32
3560-75SA	50-75mm/2-3"	B	±5μm	82	44.5
3560-100SA	75-100mm/3-4"	B	±5μm	107	57



- Measure wall thickness of tubes
- Resolution 0.001mm/0.00005"
- IP54 dust/waterproof
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Carbide measuring faces
- Supplied with setting standards (except 0-25mm/0-1")
- Optional accessory: data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)

## DISK BRAKE MICROMETER

RELATIVE PRODUCT:  
DIGITAL DISK BRAKE AND PAD CALIPER  
DIGITAL DRUM BRAKE CALIPER  
(CODE 1162-150A, 1167-150A, 1168-300A)



Unit: mm



3288-33A

Code	Range	Accuracy	L (mm)
3288-33A	7.6-33mm	5µm	64.5
3288-50A	25-50mm	5µm	82


- Measure thickness of disk brakes
- Graduation 0.01mm
- Ratchet stop
- Carbide measuring faces
- Supplied with setting standards

## DIGITAL DISK BRAKE MICROMETER

DATA  
OUTPUT

IP54  
WATERPROOF

RELATIVE PRODUCT:  
DIGITAL DISK BRAKE AND PAD CALIPER  
DIGITAL DRUM BRAKE CALIPER  
(CODE 1162-150A, 1167-150A, 1168-300A)



Unit: mm

3588-33A

Code	Range	Accuracy	L (mm)
3588-33A	7.6-33mm/0.3-1.3"	±5µm	64.5
3588-50A	25-50mm/1-2"	±5µm	82



- Measure thickness of disk brakes
- Resolution 0.001mm/0.00005"
- IP54 dust/waterproof
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Carbide measuring faces
- Supplied with setting standards
- Optional accessory: data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)



## SHEET METAL MICROMETER



3239-253



(mm)

Code	Range	Type	Accuracy	b
3239-253	0-25mm	A	5µm	155
3239-253F	0-25mm	B	5µm	155
3239-254F	0-25mm	B	6µm	310
3239-253S	0-25mm	C	5µm	155

- Deep frame suitable for sheet metal, paper and plastic
- Graduation 0.01mm
- Ratchet stop
- Carbide measuring faces



DATA  
OUTPUT

IP54  
WATERPROOF

## DIGITAL SHEET METAL MICROMETER



3539-253A



(mm)

Code	Range	Type	Accuracy	b
3539-253A	0-25mm/0-1"	A	±5µm	155
3539-253FA	0-25mm/0-1"	B	±5µm	155
3539-254FA	0-25mm/0-1"	B	±6µm	310
3539-253SA	0-25mm/0-1"	C	±5µm	155

- Deep frame suitable for sheet metal, paper and plastic
- Resolution 0.001mm/0.00005"
- IP54 dust/waterproof
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Carbide measuring faces
- Optional accessory: data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)




## INTERCHANGEABLE ANVIL MICROMETER



3262-25A

- Measure tube thickness, shoulder edge distance, rivet head height, etc.
- Supplied with flat anvil and rod anvil
- Graduation 0.01mm
- Ratchet stop
- Carbide spindle tip
- Setting standards are included (except 0-25mm)

Code	Range	Accuracy	L	d
3262-25A	0-25mm	4μm	28.5	Ø3
3262-50A	25-50mm	4μm	53.5	Ø5



## DIGITAL INTERCHANGEABLE ANVIL MICROMETER

DATA  
OUTPUT




IP54  
WATERPROOF



3562-25A

- Measure tube thickness, shoulder edge distance, rivet head height, etc.
- Supplied with flat anvil and rod anvil
- Resolution 0.001mm/0.00005"
- IP54 dust/waterproof
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Carbide spindle tip
- Setting standards are included (except 0-25mm/0-1")
- Optional accessory: data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)

Code	Range	Accuracy	L	d
3562-25A	0-25mm/0-1"	±4μm	28.5	Ø3
3562-50A	25-50mm/1-2"	±4μm	53.5	Ø5




## V-ANVIL MICROMETER




3290-153A

Code	Range	Flutes	Accuracy
3290-153A	1-15mm	3	4μm
3290-203A	5-20mm	3	4μm
3290-353A	20-35mm	3	5μm
3290-503A	35-50mm	3	5μm
3290-653A	50-65mm	3	6μm
3290-803A	65-80mm	3	6μm
3290-953A	80-95mm	3	7μm
3290-255A	5-25mm	5	4μm
3290-455A	25-45mm	5	5μm
3290-655A	45-65mm	5	6μm
3290-855A	65-85mm	5	7μm



3 flutes



5 flutes

- Measure the outside diameter of cutting tools (such as taps, reamers, end mills) with 3 or 5 flutes
- Graduation 0.01mm
- Ratchet stop
- Carbide measuring faces
- Supplied with setting standards

## DIGITAL V-ANVIL MICROMETER




3590-153A

DATA  
OUTPUT

IP54  
WATERPROOF

Code	Range	Flutes	Accuracy
3590-153A	1-15mm/0.04-0.6"	3	±4μm
3590-203A	5-20mm/0.2-0.8"	3	±4μm
3590-353A	20-35mm/0.8-1.4"	3	±5μm
3590-503A	35-50mm/1.4-2.0"	3	±5μm



- Measure the outside diameter of cutting tools (such as taps, reamers, end mills) with 3 flutes
- Resolution 0.001mm/0.00005"
- IP54 dust/waterproof
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Carbide measuring faces
- Supplied with setting standards
- Optional accessory: data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)



# GROOVE MICROMETER



- Graduation 0.01mm
- Measure width of grooves inside bores
- Non-rotating spindle
- Two graduations for inside and outside measurement

Code	Range (outside)	Range (inside)	Accuracy
3287-25A	0-25mm	1.6-26.5mm	10µm
3287-50A	25-50mm	26.5-51.5mm	10µm
3287-75A	50-75mm	51.5-76.5mm	10µm
3287-100A	75-100mm	76.5-101.5mm	10µm

3287-25A




# NON ROTATING SPINDLE UNIVERSAL MICROMETER



NON-ROTATING SPINDLE

3280-25A



- Graduation 0.01mm
- Non-rotating spindle
- Ratchet stop
- Supplied with 7 pairs of anvil/spindle tip
- Setting standards are included (except 0-25mm)
- Optional accessory: 55° anvil/spindle tip (code 3280-SP1 and 3280-SP2)

Code	Range	Accuracy	L	b
3280-25A	0-25mm	4µm	42	26
3280-50A	25-50mm	4µm	67	38

Anvil/spindle tip (included)

Unit: mm

Flat		
Spherical		
Spline		
Disk		
Blade		
Knife-edge		
Point		


55° anvil/spindle tip (optional)

Code 3280-SP1 Knife-edge		
Code 3280-SP2 Point		

- Resolution 0.001mm/0.00005"
- IP54 dust/waterproof
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Supplied with 7 pairs of anvil/spindle tip (same as series 3280)
- Setting standards are included (except 0-25mm/0-1")
- Optional accessory: 55° anvil/spindle tip code 3280-SP1 and 3280-SP2 (same as series 3280), data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)

**DATA OUTPUT**  
**IP54 WATERPROOF**

## DIGITAL UNIVERSAL MICROMETER




3580-25A

Code	Range	Accuracy	L	b
3580-25A	0-25mm/0-1"	±4μm	42	26
3580-50A	25-50mm/1-2"	±4μm	67	38



3282-25

## DISK MICROMETER



Code	Range	Accuracy	Parallelism	L	b	c	D	S	d
3282-25	0-25mm	4μm	5μm	34	24	3.3	Ø20	0.7	Ø8
3282-50	25-50mm	4μm	5μm	59	32	3.3	Ø20	0.7	Ø8
3282-75	50-75mm	5μm	5μm	85	45	3.3	Ø20	0.7	Ø8
3282-100	75-100mm	5μm	5μm	110	57	3.3	Ø20	0.7	Ø8


- Measure root tangent length of gear
- Graduation 0.01mm
- Ratchet stop
- Supplied with setting standards



3294-25

## NON ROTATING SPINDLE DISK MICROMETER

**NON-ROTATING SPINDLE**




Code	Range	Accuracy	Parallelism	L	b
3294-25	0-25mm	4μm	5μm	34	24
3294-50	25-50mm	4μm	5μm	59	32
3294-75	50-75mm	5μm	5μm	85	45
3294-100	75-100mm	5μm	5μm	110	57

- Measure root tangent length of gear
- Graduation 0.01mm
- Non-rotating spindle
- Ratchet stop
- Supplied with setting standards

# DIGITAL NON ROTATING SPINDLE DISK MICROMETER



DATA OUTPUT

NON-ROTATING SPINDLE



- Measure root tangent length of gear
- Resolution 0.001mm/0.00005"
- Non-rotating spindle
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Supplied with setting standards
- Optional accessory: data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)

3594-25A





Code	Range	Accuracy	Parallelism	L	b
3594-25A	0-25mm/0-1"	±4µm	5µm	43	32
3594-50A	25-50mm/1-2"	±4µm	5µm	68	44.5
3594-75A	50-75mm/2-3"	±5µm	5µm	93	57
3594-100A	75-100mm/3-4"	±5µm	5µm	118.5	70

# SHEET METAL MICROMETER




3263-25A



Code	Range	Accuracy
3263-25A	0-25mm	4µm


- Measure thickness of sheet metal, paper, plastic and rubber parts
- Graduation 0.01mm
- Ratchet stop
- Carbide measuring faces



## CALIPER TYPE MICROMETER




3238-25



(mm)			
Code	Range	Accuracy	L
3238-25	0-25mm	5 $\mu$ m	56
3238-50	25-50mm	6 $\mu$ m	81


- Graduation 0.01mm
- Non-rotating spindle
- Ratchet stop
- Carbide measuring faces
- Supplied with setting standards (except 0-25mm)



## HUB MICROMETER




3292-25



(mm)					
Code	Range	Accuracy	h1	h2	H
3292-25	0-25mm	4 $\mu$ m	6	9	18.7
3292-50	25-50mm	4 $\mu$ m	6.5	11	21.2
3292-75	50-75mm	5 $\mu$ m	6.5	11	21.2
3292-100	75-100mm	5 $\mu$ m	6.5	11	21.2


- Measure hub thickness and shoulder inside a bore
- Graduation 0.01mm
- Ratchet stop
- Carbide measuring faces
- Supplied with setting standards (except 0-25mm)




3285-10

- Measure diameter of wires and small balls
- Graduation 0.01mm
- Ratchet stop
- Carbide measuring faces

Code	Range	Accuracy
3285-10	0-10mm	4 $\mu$ m



## WIRE MICROMETER




# CAN SEAM MICROMETER


Unit: mm




3293-131




3293-131




3293-132







3293-132



3293-133



3293-133




Code	Range	Accuracy
3293-131	0-13mm	4µm
3293-132	0-13mm	4µm
3293-133	0-13mm	4µm

- Measure the width, height and depth of can seams
- Graduation 0.01mm

# MICROMETER MEASURING FORCE DETECTOR

Unit: mm



Code	Measuring force
6315	5-12N

- For outside micrometers 0-25mm/0-1", 25-50mm/1-2", 50-75mm/2-3" and 75-100mm/3-4"



## OPTICAL PARALLEL



4184-41A

Code	Parallels included	Applicable micrometer
4184-41A	15.62mm, 15.75mm, 15.87mm, 16.00mm	0-25mm
4184-42A	40.62mm, 40.75mm, 40.87mm, 41.00mm	25-50mm
4184-43B	65.62mm, 65.75mm, 65.87mm, 66.00mm	50-75mm
4184-44B	90.62mm, 90.75mm, 90.87mm, 91.00mm	75-100mm

- Check the flatness and parallelism of measuring faces of micrometer




6300

Code

6300

- Suitable for micrometers up to 100mm



## MICROMETER STAND




6301

Code

6301

- Suitable for micrometers up to 100mm



## MICROMETER STAND



# MICROMETER SETTING STANDARD

Code	Length	Type	Accuracy	D
6310-25	25mm	A	±1.5μm	Ø7mm
6310-50	50mm	A	±2μm	Ø7mm
6310-75	75mm	A	±2.5μm	Ø7mm
6310-100	100mm	A	±3μm	Ø8mm
6310-125	125mm	A	±3.5μm	Ø8mm
6310-150	150mm	A	±4μm	Ø8mm
6310-175	175mm	A	±4.5μm	Ø8mm
6310-200	200mm	A	±5μm	Ø8mm
6310-225	225mm	A	±5.5μm	Ø8mm
6310-250	250mm	A	±6μm	Ø8mm
6310-275	275mm	A	±6.5μm	Ø8mm
6310-300	300mm	B	±7μm	Ø16mm
6310-325	325mm	B	±7.5μm	Ø16mm
6310-350	350mm	B	±8μm	Ø16mm
6310-375	375mm	B	±8.5μm	Ø16mm
6310-400	400mm	B	±9μm	Ø16mm
6310-425	425mm	B	±9.5μm	Ø16mm
6310-450	450mm	B	±10μm	Ø16mm
6310-475	475mm	B	±10.5μm	Ø16mm
6310-500	500mm	B	±11μm	Ø16mm
6310-525	525mm	B	±11.5μm	Ø16mm
6310-575	575mm	B	±12.5μm	Ø16mm
6310-625	625mm	B	±13.5μm	Ø16mm
6310-675	675mm	B	±14.5μm	Ø16mm
6310-725	725mm	B	±15.5μm	Ø16mm
6310-775	775mm	B	±16.5μm	Ø16mm
6310-825	825mm	B	±17.5μm	Ø16mm
6310-875	875mm	B	±18.5μm	Ø16mm
6310-925	925mm	B	±19.5μm	Ø16mm
6310-975	975mm	B	±20.5μm	Ø16mm
6310-1050	1050mm	B	±22μm	Ø23mm
6310-1150	1150mm	B	±24μm	Ø23mm
6310-1250	1250mm	B	±26μm	Ø23mm
6310-1350	1350mm	B	±28μm	Ø23mm
6310-1450	1450mm	B	±30μm	Ø23mm
6310-1550	1550mm	B	±32μm	Ø23mm
6310-1650	1650mm	B	±34μm	Ø23mm
6310-1750	1750mm	B	±36μm	Ø23mm
6310-1850	1850mm	B	±38μm	Ø23mm
6310-1950	1950mm	B	±40μm	Ø23mm




6310-100



type A



6310-300



type B

DATA  
OUTPUT

IP54  
WATERPROOF

## DIGITAL MICROMETER HEAD



6353-25W

- Resolution 0.001mm/0.00005"
- IP54 dust/waterproof
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Optional accessory: data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)


### Rotating spindle

Code	Range	Stem	Spindle tip	Accuracy
6353-25	0-25mm/0-1"	with clamp nut	flat (carbide)	±2μm
6353-25W	0-25mm/0-1"	plain	flat (carbide)	±2μm
6353-25S	0-25mm/0-1"	with clamp nut	spherical (SR5)	±2μm
6353-25WS	0-25mm/0-1"	plain	spherical (SR5)	±2μm
6353-50W	0-50mm/0-2"	plain	flat (carbide)	±4μm


### Non-rotating spindle

Code	Range	Stem	Spindle tip	Accuracy
6354-25W	0-25mm/0-1"	plain	flat (carbide)	±2μm


Unit: mm




6353-25



6353-25WS



6353-50W



6354-25W




6372-5WS

- Graduation 0.02mm

Code	Range	Stem	Spindle tip	Accuracy
6372-5WS	0-5mm	plain	spherical (SR1.5)	5μm

## SMALL MICROMETER HEAD

Unit: mm




## SMALL MICROMETER HEAD




- Graduation 0.01mm

6385-65W



6385-65



6385-65WS

Code	Range	Stem	Spindle tip	Accuracy
6385-65	0-6.5mm	with clamp nut	flat (carbide)	5µm
6385-65W	0-6.5mm	plain	flat (carbide)	5µm
6385-65S	0-6.5mm	with clamp nut	spherical (SR3)	5µm
6385-65WS	0-6.5mm	plain	spherical (SR3)	5µm


## LARGE THIMBLE MICROMETER HEAD




6373-65



6373-13




6373-65




6373-65WS

Code	Range	Stem	Spindle tip	Accuracy
6373-65	0-6.5mm	with clamp nut	flat (carbide)	3µm
6373-65W	0-6.5mm	plain	flat (carbide)	3µm
6373-65S	0-6.5mm	with clamp nut	spherical (SR3)	3µm
6373-65WS	0-6.5mm	plain	spherical (SR3)	3µm
6373-13	0-13mm	with clamp nut	flat (carbide)	3µm
6373-13W	0-13mm	plain	flat (carbide)	3µm



6373-13



6373-13W

- Large thimble diameter for easy reading
- Graduation 0.01mm


## MICROMETER HEAD WITH ZERO ADJUSTABLE THIMBLE




6384-13W

- Graduation 0.01mm
- The thimble can be set to zero at any position

Code	Range	Stem	Spindle tip	Accuracy
6384-13	0-13mm	with clamp nut	flat (carbide)	3µm
6384-13W	0-13mm	plain	flat (carbide)	3µm



6384-13





6384-13W

## MICROMETER HEAD



Unit: mm



6386-13W



6386-13P



■ Graduation 0.01mm

Code	Range	Stem	Spindle tip	Remark	Accuracy
6386-13	0-13mm	with clamp nut	flat (carbide)		3 $\mu$ m
6386-13W	0-13mm	plain	flat (carbide)		3 $\mu$ m
6386-13S	0-13mm	with clamp nut	spherical (SR5)		3 $\mu$ m
6386-13WS	0-13mm	plain	spherical (SR5)		3 $\mu$ m
6386-13P	0-13mm	with clamp nut	flat (carbide)	with spindle lock	3 $\mu$ m
6386-13WP	0-13mm	plain	flat (carbide)	with spindle lock	3 $\mu$ m

## MICROMETER HEAD



Unit: mm



6387-15WS

■ Graduation 0.01mm

Code	Range	Stem	Spindle tip	Accuracy
6387-15	0-15mm	with clamp nut	flat (carbide)	3 $\mu$ m
6387-15W	0-15mm	plain	flat (carbide)	3 $\mu$ m
6387-15S	0-15mm	with clamp nut	spherical (SR5)	3 $\mu$ m
6387-15WS	0-15mm	plain	spherical (SR5)	3 $\mu$ m




## MICROMETER HEAD




6381-25




6381-25P




6381-25P



6381-25



6381-25WS



6381-25WP

Unit: mm

Code	Range	Stem	Spindle tip	Remark	Accuracy
6381-25	0-25mm	with clamp nut	flat (carbide)		3µm
6381-25W	0-25mm	plain	flat (carbide)		3µm
6381-25S	0-25mm	with clamp nut	spherical (SR5)		3µm
6381-25WS	0-25mm	plain	spherical (SR5)		3µm
6381-25P	0-25mm	with clamp nut	flat (carbide)	with spindle lock	3µm
6381-25WP	0-25mm	plain	flat (carbide)	with spindle lock	3µm


- Graduation 0.01mm
- Ratchet stop

## NON ROTATING SPINDLE MICROMETER HEAD



6377-25W

- Graduation 0.01mm
- Ratchet stop
- Non rotating spindle




Unit: mm

Code	Range	Stem	Spindle tip	Accuracy
6377-25W	0-25mm	plain	flat (carbide)	3µm


## LARGE MICROMETER HEAD



6388-50AW



6388-50A



6388-50AW

Unit: mm

Code	Range	Stem	Spindle tip	Accuracy
6388-50A	0-50mm	with clamp nut	flat (carbide)	5µm
6388-50AW	0-50mm	plain	flat (carbide)	5µm

- Graduation 0.01mm
- Ratchet stop


## QUICK SPINDLE FEEDING MICROMETER HEAD




6375-15W




6375-25W




6375-50W



6375-15W



6375-25W



6375-50W

Unit: mm

Code	Range	Stem	Spindle tip	Accuracy
6375-15W	0-15mm	plain	flat (carbide)	3µm
6375-25W	0-25mm	plain	flat (carbide)	3µm
6375-50W	0-50mm	plain	flat (carbide)	5µm

- Graduation 0.01mm
- Quick spindle feed of 1mm/rev.
- Ratchet stop


## INSIDE MICROMETER



3220-50

- Graduation 0.01mm
- Ratchet stop
- Carbide measuring faces
- Optional accessory: setting ring (code 6312)

Code	Range	Type	Setting ring	Accuracy
3220-30	5-30mm	A	5mm(included)	7μm
3220-50	25-50mm	B	25mm(included)	8μm
3220-75	50-75mm	B	50mm(optional)	9μm
3220-100	75-100mm	C	75mm(optional)	10μm




## DIGITAL INSIDE MICROMETER

DATA  
OUTPUT



3520-30

Code	Range	Type	Setting ring	Accuracy
3520-30	5-30mm/0.2-1.2"	A	5mm(included)	±5μm
3520-50	25-50mm/1-2"	B	25mm(included)	±6μm
3520-75	50-75mm/2-3"	B	50mm(optional)	±7μm
3520-100	75-100mm/3-4"	C	75mm(optional)	±8μm



- Resolution 0.001mm/0.00005"
- Button function: on/off, set, mm/inch, ABS/INC, data output
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Carbide measuring faces
- Optional accessory: data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3), setting ring (code 6312)



# INTERNAL SCREW THREAD MICROMETER


tips are not included



3640-45




- Measure pitch diameter of screw thread
- Graduation 0.01mm
- Ratchet stop
- Optional accessory: measuring tips for internal screw thread micrometer (code 7385)



Unit: mm

Code	Range	Accuracy	Applicable tips
3640-45	20-45mm	4µm	stem length L=5mm
3640-70	45-70mm	5µm	stem length L=5mm
3640-95	70-95mm	5µm	stem length L=13.5mm
3640-120	95-120mm	6µm	stem length L=13.5mm




# INTERNAL GEAR TOOTH MICROMETER

before ball tips are installed



ball tips are not included




3637-50

RELATIVE PRODUCT:  
GEAR BORE GAGE (CODE 2428)




- Measure over-pin diameter of gears
- Graduation 0.01mm
- Ratchet stop
- Optional accessory: ball tips (code 7383)



Unit: mm

(mm)


Code	Range	Accuracy
3637-50	25-50mm	4µm
3637-75	50-75mm	5µm



# THREE POINTS INTERNAL MICROMETER




3227- 8



**Type A**  
6-12mm, steel  
measuring points




3227- 16



**Type B**  
12-50mm, carbide  
measuring points



3227- 125



**Type C**  
50-300mm, carbide  
measuring points

**setting ring**



6-100mm: included  
100-300mm: optional

**extension rod**



included

**interchangeable jaws**



100-300mm: have two sets of jaws for  
different measuring range (For example, 3227-125  
has 100-112.5mm and 112.5-125mm jaws)

To be continued

Continued from previous page

### Manufacturer Inspection Certificate

INSIZE		Inspection Certificate	
Product name	Three Points Internal Micrometer	Standard temperature	20 °C
Code No.	3227-30	Traceable to	Germany 10339/D-K-15015-01-02/2012-09
Measuring range	25-30mm	Judgement	Germany 31-0830/DKD-K-06901/2012-09
Graduation	0.005mm	Inspector	Passed
Serial No.	0910120004		<i>Paulo</i>
Unit: µm			
Actual Ring Size(mm)	Permissible Error	Measured Deviation	
25.0007	4	0	
25.9994		1	
27.9978		1	
29.9992		-1	

- 6-12mm: graduation 0.001mm
- 12-300mm: graduation 0.005mm
- Ratchet stop
- Optional accessory: setting rings (code **6312**)

#### Individual

(mm)

Code	Range	Type	Accuracy	Setting ring	Extension rod (included)	L	a	b	c
3227-8 *	6-8mm	A	4µm	Ø6mm(included)	100mm	54.5	1.5	2.5	—
3227-10 *	8-10mm	A	4µm	Ø8mm(included)	100mm	54.5	1.5	2.5	—
3227-12 *	10-12mm	A	4µm	Ø10mm(included)	100mm	54.5	1.5	2.5	—
3227-16 *	12-16mm	B	4µm	Ø16mm(included)	150mm	80	0.5	6	4.5
3227-20 *	16-20mm	B	4µm	Ø16mm(included)	150mm	80	0.5	6	4.5
3227-25 *	20-25mm	B	4µm	Ø25mm(included)	150mm	90	0.5	8	6
3227-30 *	25-30mm	B	4µm	Ø25mm(included)	150mm	90	0.5	8	6
3227-40 *	30-40mm	B	4µm	Ø40mm(included)	150mm	97	0.5	14	12
3227-50 *	40-50mm	B	5µm	Ø40mm(included)	150mm	97	0.5	14	12
3227-63 *	50-63mm	C	5µm	Ø62mm(included)	150mm	114	0.5	17.5	14.5
3227-75 *	62-75mm	C	5µm	Ø62mm(included)	150mm	114	0.5	17.5	14.5
3227-88 *	75-88mm	C	5µm	Ø87mm(included)	150mm	114	0.5	17.5	14.5
3227-100 *	87-100mm	C	5µm	Ø87mm(included)	150mm	114	0.5	17.5	14.5
3227-125 *	100-125mm	C	5µm	Ø112.5mm(optional)	150mm	145	0.5	19.5	14.5
3227-150 *	125-150mm	C	5µm	Ø137.5mm(optional)	150mm	145	0.5	19.5	14.5
3227-175 *	150-175mm	C	5µm	Ø162.5mm(optional)	150mm	145	0.5	19.5	14.5
3227-200 *	175-200mm	C	5µm	Ø187.5mm(optional)	150mm	145	0.5	19.5	14.5
3227-225	200-225mm	C	7µm	Ø212.5mm(optional)	150mm	145	0.5	19.5	14.5
3227-250	225-250mm	C	7µm	Ø237.5mm(optional)	150mm	145	0.5	19.5	14.5
3227-275	250-275mm	C	7µm	Ø262.5mm(optional)	150mm	145	0.5	19.5	14.5
3227-300	275-300mm	C	7µm	Ø287.5mm(optional)	150mm	145	0.5	19.5	14.5

#### Set

Code	Range	Micrometers included	Setting ring (included)	Extension rod (included)
3227-123 *	6-12mm	6-8mm, 8-10mm, 10-12mm	Ø6mm, Ø8mm, Ø10mm	100mm
3227-202 *	12-20mm	12-16mm, 16-20mm	Ø16mm	150mm
3227-504 *	20-50mm	20-25mm, 25-30mm, 30-40mm, 40-50mm	Ø25mm, Ø40mm	150mm
3227-1004 *	50-100mm	50-63mm, 62-75mm, 75-88mm, 87-100mm	Ø62mm, Ø87mm	150mm

\* Supplied with manufacturer inspection certificate

# DIGITAL THREE POINTS INTERNAL MICROMETER




DATA  
OUTPUT

IP54  
WATERPROOF




3127-12



**Type A**  
6-12mm, steel  
measuring points




3127-40



**Type B**  
12-50mm, carbide  
measuring points



3127-125



**Type C**  
50-300mm, carbide  
measuring points

setting ring



6-100mm: included  
100-300mm: optional

extension rod



included

interchangeable jaws



100-300mm: have two sets of jaws for  
different measuring range (For example, 3127-125  
has 100-112.5mm and 112.5-125mm jaws)

To be continued

Continued from previous page

### Manufacturer Inspection Certificate

- Resolution 0.001mm/0.00005"
- IP54 dust/waterproof
- Buttons: on/off, set, mm/inch, ABS/INC
- Data output
- LR44 battery, automatic power off
- Ratchet stop
- Optional accessory: data output cable (code **7306-30**, **7302-SPC2A**, **7305-SPC3**), setting ring (code **6312**)

INSIZE		Inspection Certificate	
Product name	Digital Three Points Internal Micrometer	Standard temperature	20 °C
Code No.	3127-30	Traceable to	Germany 10339/D-K-15015-01-02/2012-09
Measuring range	25-30mm / 0.98-1.18"		Germany 31-0830/DKD-K-06901/2012-09
Resolution	0.001mm / 0.00005"	Judgement	Passed
Serial No.	0910120004	Inspector	<i>Paulo</i>
		Unit: µm	
Actual Ring Size(mm)	Permissible Error	Measured Deviation	
25.0007	4	0	
25.9994		1	
27.9978		1	
29.9992		-1	

#### Individual

(mm)

Code	Range	Type	Accuracy	Setting ring	Extension rod (included)	L	a	b	c
3127-8 *	6-8mm/0.24-0.31"	A	4µm	Ø6mm(included)	100mm	54.5	1.5	2.5	—
3127-10 *	8-10mm/0.31-0.39"	A	4µm	Ø8mm(included)	100mm	54.5	1.5	2.5	—
3127-12 *	10-12mm/0.39-0.47"	A	4µm	Ø10mm(included)	100mm	54.5	1.5	2.5	—
3127-16 *	12-16mm/0.47-0.63"	B	4µm	Ø16mm(included)	150mm	80	0.5	6	4.5
3127-20 *	16-20mm/0.63-0.79"	B	4µm	Ø16mm(included)	150mm	80	0.5	6	4.5
3127-25 *	20-25mm/0.79-0.98"	B	4µm	Ø25mm(included)	150mm	90	0.5	8	6
3127-30 *	25-30mm/0.98-1.18"	B	4µm	Ø25mm(included)	150mm	90	0.5	8	6
3127-40 *	30-40mm/1.18-1.57"	B	4µm	Ø40mm(included)	150mm	97	0.5	14	12
3127-50 *	40-50mm/1.57-1.97"	B	5µm	Ø40mm(included)	150mm	97	0.5	14	12
3127-63 *	50-63mm/1.97-2.48"	C	5µm	Ø62mm(included)	150mm	114	0.5	17.5	14.5
3127-75 *	62-75mm/2.44-2.95"	C	5µm	Ø62mm(included)	150mm	114	0.5	17.5	14.5
3127-88 *	75-88mm/2.95-3.46"	C	5µm	Ø87mm(included)	150mm	114	0.5	17.5	14.5
3127-100 *	87-100mm/3.43-3.94"	C	5µm	Ø87mm(included)	150mm	114	0.5	17.5	14.5
3127-125 *	100-125mm/3.94-4.92"	C	5µm	Ø112.5mm(optional)	150mm	150	0.5	19.5	14.5
3127-150 *	125-150mm/4.92-5.91"	C	5µm	Ø137.5mm(optional)	150mm	150	0.5	19.5	14.5
3127-175 *	150-175mm/5.91-6.89"	C	5µm	Ø162.5mm(optional)	150mm	150	0.5	19.5	14.5
3127-200 *	175-200mm/6.89-7.87"	C	5µm	Ø187.5mm(optional)	150mm	150	0.5	19.5	14.5
3127-225	200-225mm/7.87-8.86"	C	7µm	Ø212.5mm(optional)	150mm	150	0.5	19.5	14.5
3127-250	225-250mm/8.86-9.84"	C	7µm	Ø237.5mm(optional)	150mm	150	0.5	19.5	14.5
3127-275	250-275mm/9.84-10.83"	C	7µm	Ø262.5mm(optional)	150mm	150	0.5	19.5	14.5
3127-300	275-300mm/10.83-11.81"	C	7µm	Ø287.5mm(optional)	150mm	150	0.5	19.5	14.5

#### Set

Code	Range	Micrometers included	Setting ring (included)	Extension rod (included)
3127-123 *	6-12mm/0.24-0.47"	6-8mm, 8-10mm, 10-12mm	Ø6mm, Ø8mm, Ø10mm	100mm
3127-202 *	12-20mm/0.47-0.79"	12-16mm, 16-20mm	Ø16mm	150mm
3127-504 *	20-50mm/0.79-1.97"	20-25mm, 25-30mm, 30-40mm, 40-50mm	Ø25mm, Ø40mm	150mm
3127-1004 *	50-100mm/1.97-3.94"	50-63mm, 62-75mm, 75-88mm, 87-100mm	Ø62mm, Ø87mm	150mm

\* Supplied with manufacturer inspection certificate

## WIDE RANGE THREE POINTS INTERNAL MICROMETER




- Graduation 0.001mm
- Carbide measuring faces
- Ratchet stop
- Setting rings are included (except 200-300mm)



Code	Range	Accuracy	Setting ring
3228-70*	50-70mm	5μm	Ø50mm(included)
3228-100*	70-100mm	5μm	Ø70mm(included)
3228-150*	100-150mm	6μm	Ø100mm(included)
3228-250*	150-250mm	8μm	Ø150mm(included)
3228-300*	200-300mm	9μm	Ø200mm(optional)

\* Supplied with manufacturer inspection certificate




3228-70

## DIGITAL WIDE RANGE THREE POINTS INTERNAL MICROMETER




- Resolution 0.001mm/0.00005"
- IP54 dust/waterproof
- Buttons: on/off, set, mm/inch, ABS/INC
- Data output
- LR44 battery, automatic power off
- Carbide measuring faces
- Ratchet stop
- Supplied with extension rods
- Setting rings are included (except 200-300mm)
- Optional accessory: data output cable (code 7306-30, 7302-SPC2A, 7305-SPC3)



Code	Range	Accuracy	Setting ring	Extension rod (included)
3128-70*	50-70mm/1.97-2.76"	5μm	Ø50mm(included)	150mm
3128-100*	70-100mm/2.76-3.94"	5μm	Ø70mm(included)	150mm
3128-150*	100-150mm/3.94-5.91"	6μm	Ø100mm(included)	150mm
3128-250*	150-250mm/5.91-9.84"	8μm	Ø150mm(included)	150mm
3128-300*	200-300mm/7.87-11.81"	9μm	Ø200mm(optional)	150mm

\* Supplied with manufacturer inspection certificate




3128-70


# TUBULAR INSIDE MICROMETER




3229-225



type A



type B



type C

- Graduation 0.01mm
- Carbide measuring faces

Code	Range	Type	Accuracy
3229-75	50-75mm	A	5µm
3229-100	75-100mm	B	5µm
3229-125	100-125mm	C	6µm
3229-150	125-150mm	C	6µm
3229-175	150-175mm	C	7µm
3229-200	175-200mm	C	7µm
3229-225	200-225mm	C	8µm
3229-250	225-250mm	C	8µm
3229-275	250-275mm	C	9µm
3229-300	275-300mm	C	9µm
3229-325	300-325mm	C	9µm
3229-350	325-350mm	C	9µm
3229-375	350-375mm	C	10µm
3229-400	375-400mm	C	10µm
3229-425	400-425mm	C	10µm
3229-450	425-450mm	C	10µm
3229-475	450-475mm	C	11µm
3229-500	475-500mm	C	11µm

Code	Range	Type	Accuracy
3229-525	500-525mm	C	11µm
3229-550	525-550mm	C	11µm
3229-575	550-575mm	C	11µm
3229-600	575-600mm	C	12µm
3229-625	600-625mm	C	12µm
3229-650	625-650mm	C	12µm
3229-675	650-675mm	C	13µm
3229-700	675-700mm	C	13µm
3229-725	700-725mm	C	13µm
3229-750	725-750mm	C	14µm


Code	Range	Type	Accuracy
3229-775	750-775mm	C	14µm
3229-800	775-800mm	C	14µm
3229-825	800-825mm	C	15µm
3229-850	825-850mm	C	15µm
3229-875	850-875mm	C	15µm
3229-900	875-900mm	C	16µm
3229-925	900-925mm	C	16µm
3229-950	925-950mm	C	16µm
3229-975	950-975mm	C	17µm
3229-1000	975-1000mm	C	17µm

## TUBULAR INSIDE MICROMETER



3221-200

Code	Range	Travel of micrometer head	Extension rods
3221-32	25-32mm	7mm	—
3221-50	25-50mm	7mm	2pcs
3221-63	50-63mm	13mm	—
3221-200	50-200mm	13mm	6pcs
3221-300	50-300mm	13mm	10pcs
3221-225	200-225mm	25mm	—
3221-500	200-500mm	25mm	3pcs
3221-1000	200-1000mm	25mm	8pcs



- Graduation 0.01mm
- Accuracy:  $(6+L/50)\mu\text{m}$   
L=maximum measuring length (mm)
- Optional accessory: setting ring (code 6312)


## TUBULAR INSIDE MICROMETER



3222-150


- Graduation 0.01mm
- Accuracy:  $(3+n+L/50)\mu\text{m}$   
n=number of rods, L=maximum measuring length(mm)
- Supplied with setting standards
- Carbide measuring faces

Code	Range	Travel of micrometer head	Extension rods
3222-63	50-63mm	13mm	—
3222-150	50-150mm	13mm	13mm, 25mm, 50mm
3222-300	50-300mm	13mm	13mm, 25mm, 50mm (2pcs), 100mm
3222-500	50-500mm	13mm	13mm, 25mm, 50mm (2pcs), 100mm, 200mm
3222-600	50-600mm	13mm	13mm, 25mm, 50mm, 100mm, 150mm, 200mm
3222-1000	50-1000mm	13mm	13mm, 25mm, 50mm (2pcs), 100mm, 200mm (2pcs), 300mm
3222-1500	50-1500mm	13mm	13mm, 25mm, 50mm (2pcs), 100mm, 200mm (3pcs), 300mm (2pcs)





## TUBULAR INSIDE MICROMETER



- Graduation 0.01mm
- Accuracy:  $(3+n+L/50)\mu\text{m}$   
n=number of rods, L=maximum measuring length(mm)
- Supplied with setting standards
- Carbide measuring faces




3225-500

Code	Range	Travel of micrometer head	Extension rods
3225-125	100-125mm	25mm	—
3225-500	100-500mm	25mm	25mm, 50mm, 100mm, 200mm
3225-900	100-900mm	25mm	25mm, 50mm, 100mm, 200mm, 400mm
3225-1300	100-1300mm	25mm	25mm, 50mm, 100mm, 200mm, 400mm (2pcs)
3225-1700	100-1700mm	25mm	25mm, 50mm, 100mm, 200mm, 400mm (3pcs)
3225-2100	100-2100mm	25mm	25mm, 50mm, 100mm, 200mm, 400mm (4pcs)

## TUBULAR INSIDE MICROMETER



3224-2000



- Graduation 0.01mm
- Accuracy:  $(7+n+L/50)\mu\text{m}$   
n=number of rods, L=maximum measuring length(mm)
- Carbide measuring faces

Code	Range	Travel of micrometer head	Extension rods
3224-2000	1000-2000mm	50mm	50mm, 100mm (2pcs), 200mm, 500mm
3224-3000	1000-3000mm	50mm	50mm, 100mm (2pcs), 200mm, 500mm, 1000mm
3224-4000	1000-4000mm	50mm	50mm, 100mm (2pcs), 200mm, 500mm, 1000mm (2pcs)
3224-5000	1000-5000mm	50mm	50mm, 100mm (2pcs), 200mm, 500mm, 1000mm (3pcs)

# DIGITAL NON-ROTATING SPINDLE TUBULAR INSIDE MICROMETER




SPRING LOADED MEASURING POINT

NON-ROTATING SPINDLE


DATA OUTPUT




3635-950



non-rotating spindle, spring loaded point and max./min. value tracking make it easy to find the right measuring position



1m carbon fiber extension rod, light weight, no deform



- Carbide measuring faces for micrometer head and extension rods
- Points of extension rods are spring loaded
- Data output
- Button function: mm/inch, max./min. value tracking, tolerance measurement, hold, on/off, zero
- CR2032 battery, automatic power off

## Micrometer head

Range	Resolution	Accuracy	Repeatability	Measuring force	Weight
150-175mm	0.01mm/0.0005" 0.001mm/0.00005" (switchable)	±4µm	1µm	5-10N	275g

## Extension rods

Length (L)	Accuracy	Weight	Material
25mm	±1.25µm	37g	steel
50mm	±1.25µm	65g	steel
100mm	±2µm	113g	steel
200mm	±3.5µm	208g	steel
400mm	±4.5µm	402g	steel
1000mm	±7.5µm	909g	carbon fiber


Code	Range	Micrometer head	Extension rods
3635-350	150-350mm	150-175mm	25mm, 50mm, 100mm
3635-550	150-550mm	150-175mm	25mm, 50mm, 100mm, 200mm
3635-950	150-950mm	150-175mm	25mm, 50mm, 100mm, 200mm, 400mm
3635-1550	150-1550mm	150-175mm	25mm, 50mm, 100mm, 200mm(2pcs), 400mm(2pcs)
3635-2150	150-2150mm	150-175mm	25mm, 50mm, 100mm, 200mm, 400mm(4pcs)
3635-3150	150-3150mm	150-175mm	25mm, 50mm, 100mm, 200mm(2pcs), 400mm, 1000mm(2pcs)
3635-4150	150-4150mm	150-175mm	25mm, 50mm, 100mm, 200mm(2pcs), 400mm, 1000mm(3pcs)
3635-5150	150-5150mm	150-175mm	25mm, 50mm, 100mm, 200mm(2pcs), 400mm, 1000mm(4pcs)
3635-6150	150-6150mm	150-175mm	25mm, 50mm, 100mm, 200mm(2pcs), 400mm, 1000mm(5pcs)




# TUBULAR INSIDE MICROMETER



3634-1300



1m carbon fiber extension rod,  
light weight, no deform



- Carbide measuring faces for micrometer head and extension rods
- Points of extension rods are spring loaded

### Micrometer head

Range	Graduation	Accuracy	Weight
100-125mm	0.01mm	±4µm	154g

### Extension rods

Length (L)	Accuracy	Weight	Material
25mm	±1.25µm	37g	steel
50mm	±1.25µm	65g	steel
100mm	±2µm	113g	steel
200mm	±3.5µm	208g	steel
400mm	±4.5µm	402g	steel
1000mm	±7.5µm	909g	carbon fiber


Code	Range	Micrometer head	Extension rods
3634-350	100-350mm	100-125mm	25mm, 50mm, 50mm, 100mm
3634-500	100-500mm	100-125mm	25mm, 50mm, 100mm, 200mm
3634-1300	100-1300mm	100-125mm	25mm, 50mm, 100mm, 200mm, 400mm(2pcs)
3634-1500	100-1500mm	100-125mm	25mm, 50mm, 100mm, 200mm(2pcs), 400mm(2pcs)
3634-2100	100-2100mm	100-125mm	25mm, 50mm, 100mm, 200mm, 400mm(4pcs)
3634-3100	100-3100mm	100-125mm	25mm, 50mm, 100mm, 200mm(2pcs), 400mm, 1000mm(2pcs)
3634-4100	100-4100mm	100-125mm	25mm, 50mm, 100mm, 200mm(2pcs), 400mm, 1000mm(3pcs)
3634-5100	100-5100mm	100-125mm	25mm, 50mm, 100mm, 200mm(2pcs), 400mm, 1000mm(4pcs)
3634-6100	100-6100mm	100-125mm	25mm, 50mm, 100mm, 200mm(2pcs), 400mm, 1000mm(5pcs)

## INTERNAL GEAR TOOTH MICROMETER




3638-200


ball tips are not included



RELATIVE PRODUCT:  
GEAR BORE GAGE (CODE 2428)



micrometer head (100-115mm)



extension rod

Unit: mm

(mm)

- Measure over-pin diameter of gears
- Points of extension rods are spring loaded
- Optional accessory: ball tips (code 7383)

### Micrometer head


Range	Graduation	Accuracy
100-115mm	0.01mm	±4µm
150-175mm	0.01mm	±4µm

### Extension rod


Length (L)	Accuracy
15mm	±1µm
25mm	±1.25µm
30mm	±1.25µm
50mm	±1.25µm
100mm	±2µm
200mm	±3.5µm
400mm	±4.5µm

Code	Range	Micrometer head	Extension rod (L)
3638-200	100-205mm	100-115mm	15, 25, 30
3638-500	100-505mm	100-115mm	15, 25, 50, 100, 200
3638-900	100-905mm	100-115mm	15, 25, 50, 100, 200, 400
3638-1100	150-1150mm	150-175mm	25, 50, 100, 200, 200, 400

## INTERNAL SCREW THREAD MICROMETER



micrometer head (100-115mm)



extension rod




tips are not included



3641-200

tips are not included

- Measure pitch diameter of screw thread
- Points of extension rods are spring loaded
- Optional accessory: measuring tips for internal screw thread micrometer (code 7385)



### Micrometer head

Range	Graduation	Accuracy
100-115mm	0.01mm	±4µm
150-175mm	0.01mm	±4µm

### Extension rod

Length (A)	Accuracy
15mm	±1µm
25mm	±1.25µm
50mm	±1.25µm
100mm	±2µm
200mm	±3.5µm
400mm	±4.5µm

Code	Range	Micrometer head	Extension rod (A)	Applicable tips
3641-200	100-205mm	100-115mm	15, 25, 50mm	stem length L=13.5mm
3641-500	100-505mm	100-115mm	15, 25, 50, 100, 200mm	stem length L=13.5mm
3641-900	100-905mm	100-115mm	15, 25, 50, 100, 200, 400mm	stem length L=13.5mm
3641-1100	150-1150mm	150-175mm	25, 50, 100, 200, 200, 400mm	stem length L=13.5mm

# INTERNAL SCREW THREAD MICROMETER

- Graduation: 0.01mm
- Optional accessory: measuring tips for internal screw thread micrometer (code 7321), zero block (code 3226-SP)



Code	Range	Zero Block (optional)
3226-1001	75-100mm	100mm (code 3226-SP100)
3226-1251	100-125mm	100mm (code 3226-SP100)
3226-1501	125-150mm	150mm (code 3226-SP150)
3226-1751	150-175mm	150mm (code 3226-SP150)
3226-2001	175-200mm	200mm (code 3226-SP200)
3226-2251	200-225mm	200mm (code 3226-SP200)
3226-2501	225-250mm	250mm (code 3226-SP250)
3226-2751	250-275mm	250mm (code 3226-SP250)
3226-3001	275-300mm	300mm (code 3226-SP300)



# MEASURING TIPS FOR INTERNAL SCREW THREAD MICROMETER

## Metric and unified screw (60° thread angle)


Code	Pitch
7321-T11	0.4-0.5mm/64-48TPI
7321-T12	0.6-0.9mm/44-28TPI
7321-T13	1-1.75mm/24-14TPI
7321-T14	2-3mm/13-9TPI
7321-T15	3.5-5mm/8-5TPI
7321-T16	5.5-7mm/4.5-3.5TPI
7321-T1S	6 pairs/set, including all above tips



7321-T1S

## Whitworth screw (55° thread angle)

Code	Pitch
7321-T21	60-48TPI
7321-T22	48-40TPI
7321-T23	40-32TPI
7321-T24	32-24TPI
7321-T25	24-18TPI
7321-T26	18-14TPI
7321-T27	14-10TPI
7321-T28	10-7TPI
7321-T29	7-4.5TPI
7321-T210	4.5-3.5TPI
7321-T2S	10 pairs/set, including all above tips




- Supplied in pair
- Suitable for 3226 series

# BORE GAGE FOR SMALL HOLES

ATTENTION: NOT SUITABLE FOR 0.001MM DIAL INDICATORS





2852-10



2152-18


DATA OUTPUT




6-10mm

10-18.5mm

Read the diameter directly, after inputting the size of setting ring.



The minimum value tracking function can find the diameter automatically.



Optional accessory: setting ring (code 6312)

Code	Range	Indicator	Accuracy	Repeatability
2852-10	6-10mm	dial indicator, range 3mm, graduation 0.01mm(code 2311-3F)	±0.012mm	0.003mm
2852-18	10-18.5mm		±0.012mm	0.003mm

Code	Range	Indicator	Accuracy	Repeatability
2152-10	6-10mm	digital indicator, range 12.7mm/0.5", resolution 0.002mm/0.0001" (code 2108-10F)	±0.012mm	0.003mm
2152-18	10-18.5mm		±0.012mm	0.003mm

ATTENTION: NOT SUITABLE FOR 0.001MM DIAL INDICATORS

# BORE GAGE

2322-160A



2122-35A

DATA OUTPUT

ceramic contact point

ceramic anvil



ceramic anvil



- Optional accessory: setting ring (code 6312), long handle (code 7351)

Code	Range	Indicator	Accuracy	Repeatability
2322-35A	18-35mm	dial indicator, range 10mm, graduation 0.01mm (code 2308-10FA)	±0.015mm	0.003mm
2322-60A	35-60mm		±0.018mm	0.003mm
2322-100A	50-100mm		±0.018mm	0.003mm
2322-160A	50-160mm		±0.018mm	0.003mm
2322-161A	100-160mm		±0.018mm	0.003mm
2322-250A	160-250mm		±0.018mm	0.003mm
2322-450A	250-450mm		±0.018mm	0.003mm

Code	Range	Indicator	Accuracy	Repeatability
2122-35A	18-35mm	digital indicator, range 12.7mm/0.5", resolution 0.002mm/0.0001" (code 2108-10F)	±0.015mm	0.003mm
2122-60A	35-60mm		±0.018mm	0.003mm
2122-100A	50-100mm		±0.018mm	0.003mm
2122-160A	50-160mm		±0.018mm	0.003mm
2122-161A	100-160mm		±0.018mm	0.003mm
2122-250A	160-250mm		±0.018mm	0.003mm
2122-450A	250-450mm		±0.018mm	0.003mm



Range	A	B	C	ØD	ØE	F	L
35-60mm	12.2	6.4	27	13	12.8	SR2	141
50-100mm	26	9	27	13	12.8	SR2	141
50-160mm	26	9	35	13	12.8	SR2	141
100-160mm	26	9	35	13	12.8	SR2	141
160-250mm	56.5	13	74.5	15	12.8	SR2	241
250-450mm	86.5	15	101.5	15	14.5	SR2.5	241

## BORE GAGE SET



ATTENTION: NOT SUITABLE FOR 0.001MM DIAL INDICATORS


- Optional accessory: setting ring (code 6312)

2824-S3


Code	Range	Indicator	Bore gages included	Accuracy	Repeatability
2824-S3	18-160mm	dial indicator code 2308-10FA range 10mm, graduation 0.01mm	18-35mm 35-60mm 50-160mm	18-35mm ±0.015mm 35-60mm ±0.018mm 50-160mm ±0.018mm	0.003mm

## BORE GAGE

ATTENTION: NOT SUITABLE FOR 0.001MM DIAL INDICATORS



2827-160A



Unit: mm

- Optional accessory: setting ring (code 6312)

Code	Range	Indicator	Accuracy	Repeatability
2827-160A	50-160mm	dial indicator code 2308-10FA	±0.018mm	0.003mm
2827-250A	160-250mm	range 10mm, graduation 0.01mm	±0.018mm	0.003mm
2827-450A	250-450mm		±0.018mm	0.003mm

Range	ØA	B	C	ØD	E	L	L1
50-160mm	12.8	28.5	9.2	13	35	141	76.2
160-250mm	14.5	62.0	12.7	13	74.5	391	100
250-450mm	14.5	91.5	15.0	15	101.5	391	100




ATTENTION: NOT SUITABLE FOR 0.001MM DIAL INDICATORS

# BORE GAGE

Unit: mm

2828-800A



Code	Range	Indicator	Accuracy	Repeatability
2828-800A	400-800mm	dial indicator code 2308-10FA range 10mm, graduation 0.01mm	±0.025mm	0.003mm

# LONG HANDLE


- To assist deep-hole measurement
- Can be used for bore gages 2322 and 2122

(mm)

Code	Applicable bore gages	A	ØD	Remark
7351-EX11	35-60mm, 50-100mm, 50-160mm, 100-160mm	475	13	one piece
7351-EX12		980	13	
7351-EX13		1480	14.5	consist of two pieces
7351-EX14		1980	14.5	
7351-EX21	160-250mm, 250-450mm	480	14.5	one piece
7351-EX22		980	14.5	
7351-EX23		1480	14.5	consist of two pieces
7351-EX24		1980	14.5	



7351-EX11



## ANVIL FOR BORE GAGES




- For 2852, 2152, 2322, 2122, 2824, 2827

7350-160

Code	Applicable bore gages	Material of measuring face	Quantity per set	Measuring range of anvil (mm)
7350-10	6-10mm	steel	9pcs	6, 6.5, 7, 7.5, 8, 8.5, 9, 9.5, 10
7350-18	10-18.5mm	ceramic	9pcs	10, 11, 12, 13, 14, 15, 16, 17, 18
7350-35	18-35mm	ceramic	9pcs	18, 20, 22, 24, 26, 28, 30, 32, 34
7350-60	35-60mm	ceramic	6pcs	35, 40, 45, 50, 55, 60
7350-100	50-100mm	ceramic	11pcs	50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100
7350-160	50-160mm	ceramic	12pcs	50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 105
7350-161	100-160mm	ceramic	12pcs	50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 105
7350-250	160-250mm	ceramic	5pcs	160, 170, 180, 190, 200
7350-450	250-450mm	ceramic	5pcs	250, 260, 270, 280, 290


## BORE GAGE SETTER



- Used together with gage blocks to set bore gages



Unit: mm



2395-400

Code	Setting range
2395-400	18-400mm

# SETTING RING



CAN SUPPLY CUSTOM SETTING RING FROM Ø1.500MM TO Ø315.000MM, FOR EXAMPLE, Ø17.085MM



Manufacturer Inspection Certificate

INSIZE		Inspection Certificate			
		Unit: mm			
Product name	Setting Ring	Marked Size	19.998		
Code No.	6312-20	Calibration Results	Diameter		
Serial No.	0512110112		at 0°	at 90°	
Standard temperature	20°		Top	19.9987	19.9985
Traceable to	Germany 10339/D-K-15015 01.02.2012.09		Middle	19.9984	19.9985
Judgement	Passed		Bottom	19.9985	19.9986
Inspector	<i>S. Young</i>		Average	19.9985	
		Cylindricity	0.0003		
		Roundness	0.0002		

Diameter**	Deviation	Roundness and cylindricity
Ø1.5-3mm	±2.0µm	0.3µm
Ø3-10mm	±2.0µm	0.4µm
Ø10-18mm	±3.0µm	0.5µm
Ø18-25mm	±3.0µm	0.6µm
Ø25-30mm	±4.0µm	0.6µm
Ø30-50mm	±4.0µm	0.7µm
Ø50-80mm	±4.0µm	0.8µm
Ø80-100mm	±4.0µm	1.0µm
Ø100-120mm	±5.0µm	1.0µm
Ø120-180mm	±6.0µm	1.2µm
Ø180-250mm	±7.0µm	1.4µm
Ø250-315mm	±8.0µm	1.6µm

\*\* For example Ø3-10mm means Ø3mm < Ød ≤ Ø10mm

Code	Size	Code	Size	Code	Size	Code	Size	Code	Size
6312-1D5*	Ø1.5mm	6312-15*	Ø15mm	6312-29*	Ø29mm	6312-43*	Ø43mm	6312-80*	Ø80mm
6312-2*	Ø2mm	6312-16*	Ø16mm	6312-30*	Ø30mm	6312-44*	Ø44mm	6312-85*	Ø85mm
6312-3*	Ø3mm	6312-17*	Ø17mm	6312-31*	Ø31mm	6312-45*	Ø45mm	6312-87*	Ø87mm
6312-4*	Ø4mm	6312-18*	Ø18mm	6312-32*	Ø32mm	6312-46*	Ø46mm	6312-90*	Ø90mm
6312-5*	Ø5mm	6312-19*	Ø19mm	6312-33*	Ø33mm	6312-47*	Ø47mm	6312-95*	Ø95mm
6312-6*	Ø6mm	6312-20*	Ø20mm	6312-34*	Ø34mm	6312-48*	Ø48mm	6312-100*	Ø100mm
6312-7*	Ø7mm	6312-21*	Ø21mm	6312-35*	Ø35mm	6312-49*	Ø49mm	6312-125*	Ø125mm
6312-8*	Ø8mm	6312-22*	Ø22mm	6312-36*	Ø36mm	6312-50*	Ø50mm	6312-150*	Ø150mm
6312-9*	Ø9mm	6312-23*	Ø23mm	6312-37*	Ø37mm	6312-55*	Ø55mm	6312-175*	Ø175mm
6312-10*	Ø10mm	6312-24*	Ø24mm	6312-38*	Ø38mm	6312-60*	Ø60mm	6312-200*	Ø200mm
6312-11*	Ø11mm	6312-25*	Ø25mm	6312-39*	Ø39mm	6312-62*	Ø62mm	6312-225*	Ø225mm
6312-12*	Ø12mm	6312-26*	Ø26mm	6312-40*	Ø40mm	6312-65*	Ø65mm	6312-250*	Ø250mm
6312-13*	Ø13mm	6312-27*	Ø27mm	6312-41*	Ø41mm	6312-70*	Ø70mm	6312-275*	Ø275mm
6312-14*	Ø14mm	6312-28*	Ø28mm	6312-42*	Ø42mm	6312-75*	Ø75mm	6312-300*	Ø300mm

\* Supplied with manufacturer inspection certificate



# SMALL HOLE GAGE SET



4208-1


- 4 gages per set
- For small holes, slots and grooves, etc.
- Satin chrome finish

Code	Total range	Gages included
4208-1	3-13mm	3-5mm, 5-7.5mm, 7.5-10mm, 10-13mm



Range	L	a	Øb
3-5mm	90	22.5	5.5
5-7.5mm	97.6	30	5.5
7.5-10mm	102.8	35	8.5
10-13mm	108	40	8.5

## TELESCOPING GAGE SET




4206-1

(mm)				
Range	L	Øa	Øb	Øc
8-12.7mm	115	3.9	2.9	6.2
12.7-19mm	115	5.3	3.8	6.2
19-32mm	115	5.3	3.8	6.2
32-54mm	137	7.6	6.1	7.2
54-90mm	137	7.6	6.1	7.2
90-150mm	137	7.6	6.1	7.2


Code	Total range	Gages included
4206-1	8-150mm	8-12.7mm, 12.7-19mm 19-32mm, 32-54mm 54-90mm, 90-150mm

- 6 gages per set
- For quick measurement of inside diameter of holes and width of slots
- Satin chrome finish


## LONG HANDLE TELESCOPING GAGE



- For quick measurement of inside diameter of deep holes and width of slots
- Satin chrome finish



4209-6




(mm)					
Code	Range	L	Øa	Øb	Øc
4209-1	8-12.7mm	250	3.9	2.9	6.2
4209-2	12.7-19mm	250	5.3	3.8	6.2
4209-3	19-32mm	250	5.3	3.8	6.2
4209-4	32-54mm	300	7.6	6.1	7.2
4209-5	54-90mm	300	7.6	6.1	7.2
4209-6	90-150mm	300	7.6	6.1	7.2

ATTENTION:  
NO DATA OUTPUT

## DIGITAL RADIUS GAGE




2183



- Measure radius of internal and external arcs
- Supplied with 5 jaws for different sizes of arc
- Battery CR2032

Code	Range of radius (R)	Resolution	Accuracy (mm)
2183	5-700mm/0.2-27.5"	0.005mm/0.00005"	±0.01R*

\* R is the radius to be measured




ATTENTION:  
BASIC MODEL

## CIRCUMFERENCE TAPE





7114-950

- Measure diameter and circumference of pipes, trees, tires, etc.
- Laser engraved scale
- Made of stainless steel



Code	Circumference range	Diameter range	Graduation	Accuracy	
				Circumference	Diameter
7114-950	60-950mm	Ø20-300mm	0.1mm	±1.5mm	±0.5mm
7114-2200	940-2200mm	Ø300-700mm	0.1mm	±1.5mm	±0.5mm
7114-3460	2190-3460mm	Ø700-1100mm	0.1mm	±1.5mm	±0.5mm






**MANUFACTURER INSPECTION  
CERTIFICATE TRACEABLE  
TO NIST USA, FOR DIAL INDICATORS,  
DIGITAL INDICATORS AND  
DIAL TEST INDICATORS**

## DIGITAL INDICATOR




DATA  
OUTPUT


Unit: mm



2112-10F



2112-25F



2112-501F

spindle lift knob is included



- Button function: on/off, inch/mm, zero
- CR2032 battery, automatic power off
- Data output
- Optional accessory: data output cable (code 7306-40, 7302-SPC3A, 7305-SPC1A), backs (page 135), contact points (page 131-134)

### Resolution 0.001mm/0.00005"

Code	Range	Accuracy	Hysteresis	Remark
2112-101F *	12.7mm/0.5"	5µm	2µm	flat back
2112-251F *	25.4mm/1"	5µm	3µm	flat back
2112-501F *	50.8mm/2"	6µm	3µm	flat back
2112-101 *	12.7mm/0.5"	5µm	2µm	lug back
2112-251 *	25.4mm/1"	5µm	3µm	lug back
2112-501 *	50.8mm/2"	6µm	3µm	lug back

### Resolution 0.01mm/0.0005"

Code	Range	Accuracy	Hysteresis	Remark
2112-10F *	12.7mm/0.5"	20µm	10µm	flat back
2112-25F *	25.4mm/1"	20µm	10µm	flat back
2112-50F *	50.8mm/2"	30µm	10µm	flat back
2112-10 *	12.7mm/0.5"	20µm	10µm	lug back
2112-25 *	25.4mm/1"	20µm	10µm	lug back
2112-50 *	50.8mm/2"	30µm	10µm	lug back

\* Supplied with manufacturer inspection certificate traceable to NIST USA



# DIGITAL INDICATOR

DATA OUTPUT



2103-10F




2104-25F




2103-50F


Unit: mm




2103-10  
2104-10



2103-25  
2104-25



2103-50  
2104-50



## Resolution 0.001mm/0.0005"

Code	Range	Accuracy	Hysteresis	Remark
2103-10F *	12.7mm/0.5"	5µm	2µm	flat back
2103-25F *	25.4mm/1"	5µm	3µm	flat back
2103-50F *	50.8mm/2"	6µm	3µm	flat back
2103-10 *	12.7mm/0.5"	5µm	2µm	lug back
2103-25 *	25.4mm/1"	5µm	3µm	lug back
2103-50 *	50.8mm/2"	6µm	3µm	lug back

## Resolution 0.01mm/0.0005"

Code	Range	Accuracy	Hysteresis	Remark
2104-10F *	12.7mm/0.5"	20µm	10µm	flat back
2104-25F *	25.4mm/1"	20µm	10µm	flat back
2104-50F *	50.8mm/2"	30µm	10µm	flat back
2104-10 *	12.7mm/0.5"	20µm	10µm	lug back
2104-25 *	25.4mm/1"	20µm	10µm	lug back
2104-50 *	50.8mm/2"	30µm	10µm	lug back

spindle lift knob is included



- Reading in digit and analog
- Display can be rotated by 320°
- Button function: tolerance Go and No-Go display, data preset, measuring direction change, max./min./TIR measurement, inch/metric conversion, absolute/incremental measurement
- CR2032 battery, automatic power off
- Data output
- Optional accessory: data output cable (code 7306-40, 7302-SPC3A, 7305-SPC1A), backs (page 135), contact points (page 131~134)

\* Supplied with manufacturer inspection certificate traceable to NIST USA

# METRIC DIGITAL INDICATOR

DATA  
OUTPUT



2116-10F




2116-251F




2116-501F


Unit: mm



2116-10  
2116-101



2116-25  
2116-251



2116-50  
2116-501

spindle lift knob is included



- Button function: on/off, +/-, zero
- CR2032 battery, automatic power off
- Data output
- Optional accessory: data output cable (code **7306-40**, **7302-SPC3A**, **7305-SPC1A**), backs (page 135), contact points (page 131~134)

## Resolution 0.001mm

Code	Range	Accuracy	Hysteresis	Remark
2116-101F*	12.7mm	5µm	2µm	flat back
2116-251F*	25.4mm	5µm	3µm	flat back
2116-501F*	50.8mm	6µm	3µm	flat back
2116-101*	12.7mm	5µm	2µm	lug back
2116-251*	25.4mm	5µm	3µm	lug back
2116-501*	50.8mm	6µm	3µm	lug back

## Resolution 0.01mm

Code	Range	Accuracy	Hysteresis	Remark
2116-10F*	12.7mm	20µm	10µm	flat back
2116-25F*	25.4mm	20µm	10µm	flat back
2116-50F*	50.8mm	30µm	10µm	flat back
2116-10*	12.7mm	20µm	10µm	lug back
2116-25*	25.4mm	20µm	10µm	lug back
2116-50*	50.8mm	30µm	10µm	lug back

\* Supplied with manufacturer inspection certificate traceable to NIST USA





DATA  
OUTPUT

WATERPROOF

# WATERPROOF DIGITAL INDICATOR



2115-10F




2115-25F




2115-50F


Unit: mm



2115-10  
2115-101



2115-25  
2115-251



2115-50  
2115-501

spindle lift knob is included  
(except 2115-101/101F, 2115-10/10F)



## Resolution 0.001mm/0.00005"

Code	Range	Dust/waterproof	Accuracy	Hysteresis	Remark
2115-101F*	12.7mm/0.5"	IP65	5µm	2µm	flat back
2115-251F*	25.4mm/1"	IP54	5µm	3µm	flat back
2115-501F*	50.8mm/2"	IP54	6µm	3µm	flat back
2115-101*	12.7mm/0.5"	IP65	5µm	2µm	lug back
2115-251*	25.4mm/1"	IP54	5µm	3µm	lug back
2115-501*	50.8mm/2"	IP54	6µm	3µm	lug back

## Resolution 0.01mm/0.0005"

Code	Range	Dust/waterproof	Accuracy	Hysteresis	Remark
2115-10F*	12.7mm/0.5"	IP65	20µm	10µm	flat back
2115-25F*	25.4mm/1"	IP54	20µm	10µm	flat back
2115-50F*	50.8mm/2"	IP54	30µm	10µm	flat back
2115-10*	12.7mm/0.5"	IP65	20µm	10µm	lug back
2115-25*	25.4mm/1"	IP54	20µm	10µm	lug back
2115-50*	50.8mm/2"	IP54	30µm	10µm	lug back

- Dust/waterproof
- Button function: on/off, zero, mm/inch
- CR2032 battery, automatic power off
- Data output
- Optional accessory: data output cable (code 7306-40, 7302-SPC3A, 7305-SPC1A), backs (page 135), contact points (page 131~134)

\* Supplied with manufacturer inspection certificate traceable to NIST USA

ONE BATTERY FOR  
4000 WORKING HOURS

DATA  
OUTPUT

INSIZE  
MANUFACTURER  
INSPECTION CERTIFICATE  
TRACEABLE TO NIST




2113-10F



2113-251F

## NO AUTO POWER OFF DIGITAL INDICATOR



Unit: mm

- No auto power off, tracking the deformation of mould and steel structure for a long time
- Low power consumption
- Button function: on/off, zero, inch/mm
- CR2032 battery
- Data output
- Optional accessory: backs (page 135), contact points (page 131~134), data output cable (code 7305-SPC1A)

spindle lift knob is included



data output cable (optional)



Resolution 0.001mm/0.00005"

Code	Range	Accuracy	Hysteresis	Remark
2113-101F*	12.7mm/0.5"	5µm	2µm	flat back
2113-251F*	25.4mm/1"	5µm	3µm	flat back
2113-101*	12.7mm/0.5"	5µm	2µm	lug back
2113-251*	25.4mm/1"	5µm	3µm	lug back

Resolution 0.01mm/0.0005"

Code	Range	Accuracy	Hysteresis	Remark
2113-10F*	12.7mm/0.5"	20µm	10µm	flat back
2113-25F*	25.4mm/1"	20µm	10µm	flat back
2113-10*	12.7mm/0.5"	20µm	10µm	lug back
2113-25*	25.4mm/1"	20µm	10µm	lug back

\* Supplied with manufacturer inspection certificate traceable to NIST USA

## DIGITAL INDICATOR FOR BORE GAGES


- Specially designed for bore gages
- The minimum value tracking function can find the diameter automatically
- Read the diameter directly, after inputting the size of setting ring
- Reading in digit and analog
- Display can be rotated by 320°
- Button function: minimum value tracking, calibration, data preset, inch/metric conversion, absolute/incremental measurement
- CR2032 battery, automatic power off
- Data output
- Optional accessory: data output cable (code 7306-40, 7302-SPC3A, 7305-SPC1A), backs (page 135), contact points (page 131~134)

INSIZE  
MANUFACTURER  
INSPECTION CERTIFICATE  
TRACEABLE TO NIST

DATA  
OUTPUT



2108-10F



Unit: mm

Code	Range	Resolution	Accuracy	Hysteresis	Remark
2108-10F*	12.7mm/0.5"	0.002mm/0.0001"	20µm	10µm	flat back
2108-101F*	12.7mm/0.5"	0.001mm/0.00005"	5µm	2µm	flat back


\* Supplied with manufacturer inspection certificate traceable to NIST USA

# COMPACT DIGITAL INDICATOR



- Button function:
  - in/mm: short press for inch/metric conversion  
long press to change measuring direction
  - ABS: short press for absolute/incremental measurement  
long press to preset data
  - 0/ON: short press to turn on when power is off  
short press to set zero when power is on  
long press to turn off
- CR1632 battery, automatic power off
- Data output
- Optional accessory: data output cable (code **7306-40**, **7302-SPC3A**, **7305-SPC1A**), contact points (page 131~134)

DATA OUTPUT



2114-51F

Code	Range	Resolution	Accuracy	Hysteresis	Remark
2114-5F*	5mm/0.2"	0.01mm/0.0005"	20µm	10µm	flat back
2114-51F*	5mm/0.2"	0.001mm/0.00005"	5µm	2µm	flat back

\* Supplied with manufacturer inspection certificate traceable to NIST USA


# LARGE STROKE DIGITAL INDICATOR

DATA OUTPUT

spindle lift knob is included



- Button function: on/off, zero, mm/inch
- CR2032 battery, automatic power off
- Data output
- Optional accessory: data output cable (code **7306-40**, **7302-SPC3A**, **7305-SPC1A**), backs (page 135), contact points (page 131~134)



2117-100

Resolution 0.01mm/0.0005"

Code	Range	Accuracy	Hysteresis	Remark
2117-100	100mm/4"	30µm	10µm	lug back

Resolution 0.001mm/0.00005"

Code	Range	Accuracy	Hysteresis	Remark
2117-1001	100mm/4"	9µm	3µm	lug back

## PRECISION DIAL INDICATOR




JEWELLED BEARING



2313-1FA

- Graduation: 0.001mm
- Jeweled bearing
- Supplied with limit pointers and bezel clamp
- Optional accessory: backs (page 135), contact points (page 131~134)



							(mm)			
Code	Range	Accuracy	Hysteresis	Range/rev	Dial reading	Remark	A	B	C	D
2313-1FA *	1mm	5 $\mu$ m	2 $\mu$ m	0.2mm	0-100-0	flat back	45	62.5	19.5	15
2313-2FA *	2mm	8 $\mu$ m	2.5 $\mu$ m	0.2mm	0-100-0	flat back	45	62.5	19.5	15
2313-1A *	1mm	5 $\mu$ m	2 $\mu$ m	0.2mm	0-100-0	lug back	45	62.5	19.5	15
2313-2A *	2mm	8 $\mu$ m	2.5 $\mu$ m	0.2mm	0-100-0	lug back	45	62.5	19.5	15

\* Supplied with manufacturer inspection certificate traceable to NIST USA

## COMPACT DIAL INDICATOR




JEWELLED BEARING



2311-5F

- Jeweled bearing
- Supplied with limit pointers
- Optional accessory: backs (page 135), contact points (page 131~134)



							(mm)		
Code	Range	Graduation	Accuracy	Hysteresis	Range/rev	Dial reading	Remark	B	D
2311-3F *	3mm	0.01mm	14 $\mu$ m	3 $\mu$ m	0.5mm	0-50	flat back	46	10.5
2311-5F *	5mm	0.01mm	16 $\mu$ m	3 $\mu$ m	0.5mm	0-50	flat back	48	12.5
2311-3 *	3mm	0.01mm	14 $\mu$ m	3 $\mu$ m	0.5mm	0-50	lug back	46	10.5
2311-5 *	5mm	0.01mm	16 $\mu$ m	3 $\mu$ m	0.5mm	0-50	lug back	48	12.5

\* Supplied with manufacturer inspection certificate traceable to NIST USA

## DIAL INDICATOR

carton box




2301-10

ATTENTION:  
PROMOTION MODEL



- Jeweled bearing
- Supplied with limit hands and bezel clamp
- Packed in carton box
- Optional accessory: backs (page 135), contact points (page 131~134)



Code	Range	Graduation	Accuracy	Hysteresis	Range/rev	Dial reading	Remark
2301-10*	10mm	0.01mm	17µm	3µm	1mm	0-100	lug back
2301-10F*	10mm	0.01mm	17µm	3µm	1mm	0-100	flat back

\* Supplied with manufacturer inspection certificate traceable to NIST USA




JEWELLED  
BEARING



2308-10FA

## DIAL INDICATOR

- Jeweled bearing
- Supplied with limit pointers and bezel clamp
- Optional accessory: backs (page 135), contact points (page 131~134)



Code	Range	Graduation	Accuracy	Hysteresis	Range/rev	Dial reading	Remark
2308-3FA*	3mm	0.01mm	14µm	3µm	1mm	0-100	flat back
2308-5FA*	5mm	0.01mm	16µm	3µm	1mm	0-100	flat back
2308-10FA*	10mm	0.01mm	17µm	3µm	1mm	0-100	flat back
2308-3A*	3mm	0.01mm	14µm	3µm	1mm	0-100	lug back
2308-5A*	5mm	0.01mm	16µm	3µm	1mm	0-100	lug back
2308-10A*	10mm	0.01mm	17µm	3µm	1mm	0-100	lug back

\* Supplied with manufacturer inspection certificate traceable to NIST USA

## SHOCKPROOF DIAL INDICATOR




SHOCK PROOF

JEWELLED BEARING



2314-10FA



- Shockproof
- Jeweled bearing
- Supplied with limit pointers and bezel clamp
- Optional accessory: backs (page 135), contact points (page 131~134)

Code	Range	Graduation	Accuracy	Hysteresis	Range/rev	Dial reading	Remark
2314-3FA *	3mm	0.01mm	14µm	3µm	1mm	0-100	flat back
2314-5FA *	5mm	0.01mm	16µm	3µm	1mm	0-100	flat back
2314-10FA *	10mm	0.01mm	20µm	3µm	1mm	0-100	flat back
2314-3A *	3mm	0.01mm	14µm	3µm	1mm	0-100	lug back
2314-5A *	5mm	0.01mm	16µm	3µm	1mm	0-100	lug back
2314-10A *	10mm	0.01mm	20µm	3µm	1mm	0-100	lug back

\* Supplied with manufacturer inspection certificate traceable to NIST USA

## WATERPROOF DIAL INDICATOR




IP54 WATERPROOF

JEWELLED BEARING



2324-10F



- IP54 dust/waterproof
- Jeweled bearing

Code	Range	Graduation	Accuracy	Hysteresis	Range/rev	Dial reading	Remark
2324-10F *	10mm	0.01mm	17µm	3µm	1mm	0-100	flat back
2324-10 *	10mm	0.01mm	17µm	3µm	1mm	0-100	lug back

\* Supplied with manufacturer inspection certificate traceable to NIST USA




## DOUBLE FACE DIAL INDICATOR



front

2328-10

back



- Read from both sides
- Jeweled bearing
- Supplied with limit pointers
- Optional accessory: contact points (page 131~134)


Code	Range	Graduation	Accuracy	Hysteresis	Range/rev	Dial reading
2328-10*	10mm	0.01mm	17µm	3µm	1mm	0-100

\* Supplied with manufacturer inspection certificate traceable to NIST USA



2318-30F

## DIAL INDICATOR



- Supplied with limit pointers and bezel clamp
- Optional accessory: backs (page 135), contact points (page 131~134)


(mm)

Code	Range	Graduation	Accuracy	Hysteresis	Range/rev	Dial reading	Remark	B	D
2318-10F	10mm	0.1mm	40µm	20µm	10mm	0-10	flat back	70	20
2318-20F	20mm	0.1mm	50µm	20µm	10mm	0-10	flat back	85	35
2318-25F	25mm	0.1mm	60µm	20µm	10mm	0-10	flat back	85	35
2318-30F	30mm	0.1mm	60µm	20µm	10mm	0-10	flat back	90	40
2318-10	10mm	0.1mm	40µm	20µm	10mm	0-10	lug back	70	20
2318-20	20mm	0.1mm	50µm	20µm	10mm	0-10	lug back	85	35
2318-25	25mm	0.1mm	60µm	20µm	10mm	0-10	lug back	85	35
2318-30	30mm	0.1mm	60µm	20µm	10mm	0-10	lug back	90	40

## DIAL INDICATOR



2310-30FA



- Supplied with limit pointers and bezel clamp
- Optional accessory: backs (page 135), contact points (page 131~134)

Code	Range	Graduation	Accuracy	Hysteresis	Range/rev	Dial reading	Remark	B	D
2310-20FA*	20mm	0.01mm	25µm	5µm	1mm	0-100	flat back	83mm	35mm
2310-30FA*	30mm	0.01mm	35µm	7µm	1mm	0-100	flat back	88mm	40mm
2310-20A*	20mm	0.01mm	25µm	5µm	1mm	0-100	lug back	83mm	35mm
2310-30A*	30mm	0.01mm	35µm	7µm	1mm	0-100	lug back	88mm	40mm

\* Supplied with manufacturer inspection certificate traceable to NIST USA

## ONE REVOLUTION DIAL INDICATOR




2316-05F

- Shock proof
- Optional accessory: backs (page 135), contact points (page 131~134)

Code	Range	Graduation	Accuracy	Hysteresis	Dial reading	Remark
2316-05F*	0.5mm	0.01mm	9µm	3µm	25-0-25	flat back
2316-1F*	1mm	0.01mm	9µm	3µm	50-0-50	flat back
2316-05*	0.5mm	0.01mm	9µm	3µm	25-0-25	lug back
2316-1*	1mm	0.01mm	9µm	3µm	50-0-50	lug back

\* Supplied with manufacturer inspection certificate traceable to NIST USA





JEWELLED BEARING

SHOCK PROOF

# DIAL INDICATOR




2309-50

- Shockproof
- Jeweled bearing
- Supplied with limit pointers
- Optional accessory: backs (page 135), contact points (page 131~134)

back of type B



stem clamp Ø10mm for 2309-100D



(mm)

Code	Type	A	B	C	D	E
2309-30	A	37.5	89.5	40.9	19.5	Ø8
2309-30F	A	37.5	89.5	40.9	19.5	Ø8
2309-50	A	108.3	126.2	57.7	39.5	Ø8
2309-50D	B	108.3	126.2	57.7	29.5	Ø8
2309-80	A	138.4	168.4	88	51.3	Ø8
2309-80D	B	138.4	168.4	88	41.3	Ø8
2309-100D	B	167.6	207.8	108	60.8	Ø10

Code	Range	Graduation	Type	Accuracy	Hysteresis	Range/rev	Dial reading	Remark
2309-30F*	30mm	0.01mm	A	35µm	7µm	1mm	0-100	flat back
2309-30*	30mm	0.01mm	A	35µm	7µm	1mm	0-100	lug back
2309-50*	50mm	0.01mm	A	40µm	8µm	1mm	0-100	flat back with spare lug back
2309-50D*	50mm	0.01mm	B	40µm	8µm	1mm	0-100	flat back with spare lug back
2309-80	80mm	0.01mm	A	50µm	9µm	1mm	0-100	flat back with spare lug back
2309-80D	80mm	0.01mm	B	50µm	9µm	1mm	0-100	flat back with spare lug back
2309-100D	100mm	0.01mm	B	50µm	9µm	1mm	0-100	flat back with spare lug back


- Note: 1) 2309-80, 2309-80D and 2309-100D can only be used vertically  
 2) 2309-100D is supplied with stem clamp Ø10mm for magnetic stands (code 6200-60, 6201-60, 6202-80, 6202-100)  
 3) 2309-30 and 2309-30F can not accept optional backs (page 135)

\* Supplied with manufacturer inspection certificate traceable to NIST USA

## BALL POINT




6282-0101



Code	Material of measuring face	L (mm)
6282-0101	carbide	7.3
6282-0103	ceramic	7.3
6282-0104	carbide	8.3
6282-0106	carbide	12.1
6282-0107	carbide	14
6282-0108	carbide	15
6282-0109	ceramic	15
6282-0110	carbide	17
6282-0111	carbide	19.3
6282-0112	carbide	20
6282-0113	ceramic	20
6282-0114	carbide	22
6282-0115	carbide	25
6282-0116	ceramic	25
6282-0117	carbide	30
6282-0118	ceramic	30



6282-0303




Code	Material of measuring face	SØD (mm)
6282-0301	steel	1
6282-0302	carbide	1.5
6282-0303	carbide	1.8
6282-0304	carbide	2.5
6282-0305	carbide	4

## SHELL TYPE POINT



6282-0202




Code	Material of measuring face	L (mm)
6282-0202	steel	5
6282-0203	steel	10
6282-0205	steel	15
6282-0207	steel	20
6282-0208	steel	25
6282-0210	steel	30

## SPHERICAL POINT



6282-0401




Code	Material of measuring face
6282-0401	steel


## CONICAL POINT




6282-0601





6282-0801



6282-0701




6282-0901




Code	Material of measuring face
6282-0601	steel
6282-0701	steel
6282-0801	steel
6282-0901	steel





6282-1101



6282-1201



6282-1301



Code	Material of measuring face	L (mm)
6282-1101	steel	8
6282-1102	steel	10

Code	Material of measuring face	ØD (mm)
6282-1201	steel	10
6282-1202	steel	15
6282-1203	steel	20
6282-1204	steel	25
6282-1205	steel	30

Code	Material of measuring face
6282-1301	carbide

## NEEDLE POINT

(mm)



Code	Material of measuring face	ØD	L
6282-1701	steel	0.45	3
6282-1702	steel	0.45	5
6282-1703	carbide	1	3
6282-1704	carbide	1	5
6282-1705	carbide	1	8
6282-1706	carbide	1	10
6282-1707	carbide	1	20
6282-1708	carbide	1	40
6282-1709	carbide	1.5	5
6282-1710	carbide	1.5	10
6282-1711	carbide	1.5	13
6282-1712	carbide	1.5	20
6282-1713	carbide	1.5	40
6282-1714	carbide	2	8
6282-1715	carbide	2	18
6282-1716	carbide	2	28
6282-1717	carbide	2	40



6282-1711




6282-1601



(mm)




Code	Material of measuring face	L1	L	SR
6282-1601	steel	11	15	0.4
6282-1602	steel	13	17	0.2
6282-1603	steel	21	25	0.4
6282-1604	steel	31	35	0.4



## KNIFE EDGE POINT



6282-1001






Code	Material of measuring face
6282-1001	steel

## BLADE POINT



6282-1801




(mm)

Code	Material of measuring face	D	W
6282-1801	steel	0.4	2
6282-1802	steel	0.6	2
6282-1803	steel	1	4



6282-1901



## ROLLER POINT



Code	Material of measuring face
6282-1901	steel

			(mm)		
Code	Material	L	Code	Material	L
6282-2001	steel	10	6282-2010	steel	55
6282-2002	steel	15	6282-2011	steel	60
6282-2003	steel	20	6282-2012	steel	65
6282-2004	steel	25	6282-2013	steel	70
6282-2005	steel	30	6282-2014	steel	75
6282-2006	steel	35	6282-2015	steel	80
6282-2007	steel	40	6282-2016	steel	90
6282-2008	steel	45	6282-2017	steel	100
6282-2009	steel	50			


## EXTENSION ROD




6282-2010




Flat Point




Flat Point




Needle Point



Spherical Point



Shell Type Point



Shell Type Point

## POINT SET



6282-S6

Code	Material of measuring face
6282-S6	steel



Code

7332

7332



## SPINDLE LIFT KNOB


■ For dial/digital indicators with spindle diameter Ø4.5mm or Ø5mm

# LUG BACK

Code	For digital/dial indicators	Page
7330-L1	2311	125
7330-L2	2301	126
	2308	126
	2309 (except 2309-30, 2309-30F)	130
	2313	125
	2314	127
	2316	129
7330-L5	2103	120
	2104	120
	2108	123
	2112	119
	2113	123
	2115	122
	2116	121
2117	124	
7330-L6	2318	128
7330-L10	2310	129



7330-L2




# FLAT BACK

Code	For digital/dial indicators	Page
7330-F1	2311	125
7330-F2	2301	126
	2308	126
	2309 (except 2309-30, 2309-30F)	130
	2313	125
	2314	127
	2316	129
7330-F5	2103	120
	2104	120
	2108	123
	2112	119
	2113	123
	2115	122
	2116	121
2117	124	
7330-F6	2318	128
7330-F10	2310	129



7330-F2







## DIAL TEST INDICATOR



2380-08

- Jeweled bearing
- Carbide contact point
- Two measuring directions
- Anti magnetic body
- Supplied with two clamps: diameter Ø4mm and Ø8mm
- Optional accessory: styli (page 138)

Unit: mm




JEWELLED BEARING

(mm)

Code	Range	Graduation	Accuracy	Hysteresis	Dial reading	A	L
2380-08*	0.8mm	0.01mm	13µm	3µm	0-40-0	Ø30	13.5
2381-08*	0.8mm	0.01mm	13µm	3µm	0-40-0	Ø37.5	13.5
2380-02*	0.2mm	0.002mm	6µm	2µm	0-100-0	Ø30	12.5
2381-02*	0.2mm	0.002mm	6µm	2µm	0-100-0	Ø37.5	12.5

\* Supplied with manufacturer inspection certificate traceable to NIST USA

clamps





## BACK PLUNGER TYPE DIAL TEST INDICATOR



2398-08


- Jeweled bearing
- Carbide contact point
- Two measuring directions
- Anti magnetic body
- Supplied with two clamps: diameter Ø4mm and Ø8mm
- Optional accessory: styli (page 138)

Unit: mm



JEWELLED BEARING

clamps



Code	Range	Graduation	Accuracy	Hysteresis	Dial Reading
2398-08*	0.8mm	0.01mm	13µm	3µm	0-40-0

\* Supplied with manufacturer inspection certificate traceable to NIST USA

## DIAL TEST INDICATOR




2399-08


- Jeweled bearing
- Carbide contact point
- Two measuring directions
- Anti magnetic body
- Supplied with two clamps: diameter  $\varnothing 4\text{mm}$  and  $\varnothing 8\text{mm}$
- Optional accessory: styli (page 138)

Code	Range	Graduation	Accuracy	Hysteresis	Dial Reading
2399-08*	0.8mm	0.01mm	13 $\mu\text{m}$	3 $\mu\text{m}$	0-40-0

\* Supplied with manufacturer inspection certificate traceable to NIST USA



JEWELLED BEARING



## LARGE RANGE DIAL TEST INDICATOR




2386-16A


- Jeweled bearing
- Carbide contact point
- Two measuring directions
- Anti magnetic body
- Supplied with two clamps: diameter  $\varnothing 4\text{mm}$  and  $\varnothing 8\text{mm}$
- Optional accessory: styli (page 138)

Code	Range	Graduation	Accuracy	Hysteresis	Dial reading
2386-16A*	1.6mm	0.01mm	25 $\mu\text{m}$	8 $\mu\text{m}$	0-40-0

\* Supplied with manufacturer inspection certificate traceable to NIST USA



JEWELLED BEARING








## ROUND BODY DIAL TEST INDICATOR


JEWELLED BEARING

- Jeweled bearing
- Carbide contact point
- Adjustable two measuring directions
- Anti magnetic body
- Supplied with two clamps: diameter  $\varnothing 4\text{mm}$  and  $\varnothing 8\text{mm}$
- Optional accessory: styli (page 138)



2391-08

clamps



Code	Range	Graduation	Accuracy	Hysteresis	Dial reading
2391-08 *	0.8mm	0.01mm	13 $\mu\text{m}$	3 $\mu\text{m}$	0-40-0

\* Supplied with manufacturer inspection certificate traceable to NIST USA


## STYLI FOR DIAL TEST INDICATORS

(mm)

Code	For dial test indicator	Material of contact point	L	D
6284-1	2380-08, 2398-08 2381-08, 2399-08	steel	13.5	SØ1
6284-3		carbide	13.5	SØ2
6284-4		ruby	13.5	SØ2
6284-8		carbide	13.5	SØ3
6284-21	2380-02 2381-02	steel	12.5	SØ1
6284-22		carbide	12.5	SØ2
6284-23		carbide	12.5	SØ3
6284-44	2880-02 2880-02R 2895-08 2897-02 2898-08	carbide	11.7	SØ0.4
6284-41		carbide	11.7	SØ1
6284-42		carbide	11.7	SØ2
6284-45		ruby	11.7	SØ2
6284-43	2896-05 2899-05	carbide	11.7	SØ3
6284-51		carbide	34.6	SØ1
6284-52		carbide	34.6	SØ2
6284-55		ruby	34.6	SØ2
6284-53	2899-05	carbide	34.6	SØ3
6284-71		2391-08	carbide	10.8



6284-3



## DIAL TEST INDICATOR HOLDER




6293-1



6293-2

Code	Stem section	Stem length (L)
6293-1	9x9mm	100mm
6293-6	9x9mm	50mm
6293-2	Ø8mm	115mm





## DIAL TEST INDICATOR HOLDER



6296-1

- Supplied with fixing spanner

Code
6296-1




## DIAL TEST INDICATOR UNIVERSAL HOLDER



6297-1

Code
6297-1

- Set the indicators at the desired attitude to the workpiece



## DIAL TEST INDICATOR CENTERING HOLDER




6291-1

Code

6291-1

- Center cylinders or holes on machine tools



## DIAL TEST INDICATOR CENTERING HOLDER


- Center cylinders or holes on machine tools
- Can be used with dial test indicators

Code

6295-1A



6295-1A



## INDICATOR CENTERING HOLDER




Code

6294-1A


- Center cylinders or holes on machine tools
- Can be used with dial test indicators or dial indicators



6294-1A



## UNIVERSAL MAGNETIC STAND



- For digital/dial indicators and dial test indicators

Code	Magnetic force	Applicable holding stem	Remark
6210-81	80kgf	Ø8mm	with fine adjustment and dovetail groove
6210-80	80kgf	Ø8mm	with fine adjustment and dovetail groove
6210-100	100kgf	Ø8mm	with fine adjustment and dovetail groove


## UNIVERSAL MAGNETIC STAND

ATTENTION: LOW LOCKING FORCE



6208-80A

- For digital/dial indicators and dial test indicators



Code	Magnetic force	Applicable holding stem	Remark
6208-80A	80kgf	Ø8mm	with fine adjustment and dovetail groove

# MAGNETIC STAND



6200-60







6201-60



6202-80




6202-100



Code	Magnetic force	Applicable holding stem	Remark
6200-60	60kgf	Ø8mm, Ø4mm, 3/8" DIA.	without fine adjustment
6201-60	60kgf	Ø8mm, Ø4mm, 3/8" DIA.	with fine adjustment
6202-80	80kgf	Ø8mm, Ø4mm, 3/8" DIA.	with fine adjustment
6202-100	100kgf	Ø8mm, Ø4mm, 3/8" DIA.	with fine adjustment


■ For digital/dial indicators and dial test indicators

# MAGNETIC STAND FOR UNEVEN SURFACE



- For digital/dial indicators and dial test indicators
- With fine adjustment

Code	Magnetic force	Applicable holding stem
6215-60	60kgf	Ø8mm, Ø4mm, 3/8" DIA.




6215-60

## UNIVERSAL STAND

- For digital/dial indicators and dial test indicators
- With fine adjustment

Code	Applicable holding stem
6214-A	Ø8mm, Ø4mm, 3/8" DIA.




6214-A

## FLEX ARM MAGNETIC STAND

- For dial test indicators

Code	Magnetic force	Applicable holding stem
6207-80A	80kgf	Ø8mm, Ø4mm, 3/8" DIA.




6207-80A

## MINI MAGNETIC STAND


- For dial test indicators
- With fine adjustment and dovetail groove

Code	Magnetic force	Applicable holding stem
6224-40	40kgf	Ø8mm



6224-40

6211-10




## MINI MAGNETIC STAND

- For dial test indicators
- With dovetail groove

Code	Magnetic force	Applicable holding stem
6211-10	10kgf	Ø6mm, Ø8mm

6866-150



## GRANITE DIAL INDICATOR STAND


- Vertical travel of holder: 150mm
- Fine adjustment range: 2mm

Code	Applicable holding stem	Base
6866-150	Ø8mm	flatness 2.5µm

6867-250



## GRANITE DIAL INDICATOR STAND



- Vertical travel of holder: 250mm
- Fine adjustment range: entire stroke



Code	Applicable holding stem	Base
6867-250	Ø8mm	flatness 2.8µm

## DIAL INDICATOR STAND

6863-150

- Vertical travel of holder: 150mm
- Fine adjustment range: 2mm

Code	Applicable holding stem	Anvil
6863-150	Ø8mm	serrated, flatness 1.5µm, hardness HRC60±2




## DIAL INDICATOR STAND

6864-250


- Vertical travel of holder: 250mm
- Fine adjustment range: entire stroke

Code	Applicable holding stem	Anvil
6864-250	Ø8mm	serrated, flatness 1.5µm, hardness HRC60±2




## DIAL INDICATOR STAND

Unit: mm



6862-1001



6862-1002



6862-1001



6862-1002

- Vertical travel of holder: 100mm
- Fine adjustment range: 2mm

Code	Applicable holding stem	Anvil
6862-1001	Ø8mm	serrated, flatness 1.5µm, hardness HRC60±2
6862-1002	Ø8mm	plain, flatness 1.5µm, hardness HRC60±2




# TRANSFER STAND

## Application



- Vertical travel of holder: 335mm
- Fine adjustment range: 2mm

rigid construction, designed to make comparison height measurement (set zero with gage block then measure height of workpiece) with dial indicators or digital indicators (variation of measuring force is high)



6865-300




Code	Applicable holding stem	Anvil
6865-300	Ø8mm	plain, flatness 1.5µm, hardness HRC60±2


# CONCENTRICITY GAGE



4789-1




4789-3



maximum workpiece length 75mm, maximum outstretch length 30mm

- Accuracy 2µm
- Optional accessory: dial test indicator, mini magnetic stand (code 6224-40)

Code	Applicable diameter
4789-1	Ø3.5mm - 25mm
4789-3	Ø1mm - 25mm




# CONCENTRICITY GAGE

dial test indicator is not included

HIGH STABILITY,  
LONG WORKING LIFE





4725-45



Unit: mm


- With ball bearing
- High stability, long working life

Code	Accuracy	Diameter range	Load
4725-45	2μm	3-45mm	6kg



# CONCENTRICITY GAGE

dial test indicator is not included




Unit: mm



4724-25

Code	Accuracy	Diameter range	Workpiece length		Load
			Without optional stand	With optional stand	
4724-25	3μm	3-25mm	0-220mm	0-120mm	5kg

### Application




Stand (optional)




4724-STAND

Code
4724-STAND

## MINI BENCH CENTER




4721-75




(mm)

Code	Horizontal parallelism	Vertical parallelism	Center height (H)	Distance between two centers (D)	Taper of center	Weight	Load
4721-75	0.003mm	0.003mm	40	75	MT1	3.7kgs	4kg

## VERTICAL AND HORIZONTAL BENCH CENTER




horizontal use



vertical use

4783-380




- For vertical and horizontal use
- Move tailstock via driving wheel

(mm)

Code	Horizontal parallelism	Vertical parallelism	Center height (H)	Distance between two centers(D)	Taper of upper center	Taper of lower center	Weight	Load
4783-380	0.01mm	0.01mm	130	380	MT2	MT3	80kg	60kg

## VERTICAL AND HORIZONTAL BENCH CENTER



- For vertical, side and horizontal use


(mm)

Code	Horizontal parallelism	Vertical parallelism	Center height (H)	Distance between two centers (D)	Taper of center	Weight	Load
4722-200	0.004mm	0.005mm	80	200	MT1/MT3	22kg	25kg


## BENCH CENTER WITH STRAIGHTNESS MEASUREMENT



- Hardened cast-iron guide surface




straightness measurement



(mm)


Code	Horizontal parallelism	Vertical parallelism	Accuracy of straightness measurement	Center height(H)	Distance between two centers(D)	Diameter of center(Ød)	Taper of center	Weight	Load
4723-300	0.004mm	0.006mm	0.01mm	90	300	12.3	MT1	38kg	25kg

# BENCH CENTER WITH ROLLER TAILSTOCKS




4720-300

- Hardened cast-iron guide surface
- Supplied with V slot/center tailstocks and roller tailstocks
- V slot for cylinder  $\varnothing 4 \sim \varnothing 22\text{mm}$
- Roller for cylinder  $\varnothing 5 \sim \varnothing 100\text{mm}$




roller tailstocks (included)



(mm)


Code	Horizontal parallelism	Vertical parallelism	Center height	Distance between two centers	Taper of center	Load
4720-300	0.01mm	0.015mm	80	300	MT1	25kg (40kg for roller tailstocks)

# BENCH CENTER



4782-300

- Hardened cast-iron guide surface
- Movable column
- V slot for cylinder  $\varnothing 4 \sim \varnothing 22\text{mm}$



(mm)

Code	Horizontal parallelism	Vertical parallelism	Center height	Distance between two centers	Taper of center	Load
4782-300	0.01mm	0.015mm	80	300	MT1	25kg


# BENCH CENTER

HIGH PRECISION

HEAVY DUTY



4788-300




- Hardened cast-iron guide surface
- Movable column

(mm)



Code	Horizontal parallelism	Vertical parallelism	Center height(H)	Distance between two centers(D)	Length (L)	Width (W)	Height (H1)	Diameter of center(Ød)	Taper of center	Weight	Load
4788-300	0.01mm	0.01mm	90	300	590	192	175	12.2	MT2	34kg	25kg
4788-400	0.01mm	0.01mm	130	400	770	206	241	18.0	MT3	66kg	60kg
4788-600	0.01mm	0.01mm	130	600	930	220	250	18.0	MT3	90kg	60kg
4788-600H2	0.01mm	0.01mm	200	600	930	220	325	24.1	MT3	105kg	60kg
4788-1000	0.01mm	0.01mm	130	1000	1330	220	262	18.0	MT3	112kg	60kg
4788-1000H2	0.01mm	0.01mm	200	1000	1330	220	337	24.1	MT3	125kg	85kg
4788-1000H3	0.01mm	0.01mm	300	1000	1330	220	442	31.6	MT3	165kg	85kg

# SINE BENCH CENTER



4157-200

- Check taper or runout of taper bars
- Sine bar accuracy ( $\alpha=30^\circ$ ):  $\pm 5$  seconds




Code	Accuracy	Center height (H)	Center distance (L)
4157-200	0.01mm	65mm	200mm

## INTERNAL DIAL CALIPER GAGE



2222-15




(mm)

Code	Range	Graduation	Accuracy	L	H	W	R
2222-15	5-15mm	0.01mm	±0.03mm	20	2	2.5	R0.3
2222-25	5-25mm	0.01mm	±0.03mm	35	1.5	1.0	R0.3
2222-301	10-30mm	0.01mm	±0.03mm	55	5.5	2.5	R0.5
2222-401	20-40mm	0.01mm	±0.03mm	80	6.0	3.0	R0.5
2222-501	30-50mm	0.01mm	±0.03mm	80	8.0	3.0	R0.5
2222-60	40-60mm	0.01mm	±0.03mm	80	8.0	3.0	R0.5

## EXTERNAL DIAL CALIPER GAGE



2333-401




(mm)

Code	Range	Graduation	Accuracy	L	H	W	R
2333-201	0-20mm	0.01mm	±0.03mm	80	25	6.5	R0.5
2333-301	10-30mm	0.01mm	±0.03mm	80	25	6.5	R0.5
2333-401	20-40mm	0.01mm	±0.03mm	80	25	6.5	R0.5
2333-501	30-50mm	0.01mm	±0.03mm	80	25	6.5	R0.5
2333-601	40-60mm	0.01mm	±0.03mm	80	25	6.5	R0.5

## INTERNAL DIAL CALIPER GAGE




2321-35



(mm)

Code	Range	Graduation	Accuracy	L	A	D
2321-35	15-35mm	0.01mm	±0.04mm	50	3	Ø3
2321-AL35	15-35mm	0.01mm	±0.04mm	200	3	Ø3
2321-55	35-55mm	0.01mm	±0.04mm	80	6	Ø3
2321-AL55	35-55mm	0.01mm	±0.04mm	250	8	Ø3
2321-75	55-75mm	0.01mm	±0.04mm	90	8	Ø3
2321-AL75	55-75mm	0.01mm	±0.04mm	250	8	Ø3
2321-95	75-95mm	0.01mm	±0.04mm	100	8	Ø3
2321-115	95-115mm	0.01mm	±0.04mm	120	10	Ø3.2
2321-135	115-135mm	0.01mm	±0.04mm	120	10	Ø3.2




■ Carbide measuring tips


## EXTERNAL DIAL CALIPER GAGE



2332-20



Code	Range	Graduation	Accuracy	L (mm)
2332-20	0-20mm	0.01mm	±0.04mm	60
2332-40	20-40mm	0.01mm	±0.04mm	60
2332-60	40-60mm	0.01mm	±0.04mm	55
2332-80	60-80mm	0.01mm	±0.04mm	55
2332-100	80-100mm	0.01mm	±0.04mm	55



■ Carbide measuring tips





DATA  
OUTPUT

## DIGITAL INTERNAL CALIPER GAGE



2151-35



Code	Range	Resolution	Accuracy	L	A	D
2151-35	15-35mm/0.6-1.4"	0.01mm/0.0005"	±0.04mm	50	3	∅3
2151-AL35	15-35mm/0.6-1.4"	0.01mm/0.0005"	±0.04mm	200	3	∅3
2151-55	35-55mm/1.4-2.2"	0.01mm/0.0005"	±0.04mm	80	6	∅3
2151-AL55	35-55mm/1.4-2.2"	0.01mm/0.0005"	±0.04mm	250	8	∅3
2151-75	55-75mm/2.2-3"	0.01mm/0.0005"	±0.04mm	90	8	∅3
2151-AL75	55-75mm/2.2-3"	0.01mm/0.0005"	±0.04mm	250	8	∅3
2151-95	75-95mm/3-3.8"	0.01mm/0.0005"	±0.04mm	100	8	∅3
2151-115	95-115mm/3.8-4.6"	0.01mm/0.0005"	±0.04mm	120	10	∅3.2
2151-135	115-135mm/4.6-5.4"	0.01mm/0.0005"	±0.04mm	120	10	∅3.2

(mm)


- Carbide measuring tips
- Reading in digit and analog
- Display can be rotated by 320°
- Button function: tolerance Go and No-Go display, data preset, measuring direction change, max./min./range measurement, inch/metric conversion, absolute/incremental measurement
- CR2032 battery, automatic power off
- Data output
- Optional accessory: data output cable (code 7306-40, 7302-SPC3A, 7305-SPC1A)

DATA  
OUTPUT

## DIGITAL EXTERNAL CALIPER GAGE



2132-20



Unit: mm

Code	Range	Resolution	Accuracy	L(mm)
2132-20	0-20mm/0-0.8"	0.01mm/0.0005"	±0.04mm	60
2132-40	20-40mm/0.8-1.6"	0.01mm/0.0005"	±0.04mm	60
2132-60	40-60mm/1.6-2.4"	0.01mm/0.0005"	±0.04mm	55
2132-80	60-80mm/2.4-3.2"	0.01mm/0.0005"	±0.04mm	55
2132-100	80-100mm/3.2-4"	0.01mm/0.0005"	±0.04mm	55

- Carbide measuring tips
- Reading in digit and analog
- Display can be rotated by 320°
- Button function: tolerance Go and No-Go display, data preset, measuring direction change, max./min./range measurement, inch/metric conversion, absolute/incremental measurement
- CR2032 battery, automatic power off
- Data output
- Optional accessory: data output cable (code 7306-40, 7302-SPC3A, 7305-SPC1A)


## DIGITAL THICKNESS GAGE

DATA  
OUTPUT



2871-101

- Ceramic spindle tip and anvil
- Buttons: on/off, zero, mm/inch
- Battery CR2032, automatic power off
- Data output
- Optional accessory: data output cable (code 7306-40, 7302-SPC3A, 7305-SPC1A)





Code	Range	Resolution	Accuracy
2871-10	0-10mm/0-0.4"	0.01mm/0.0005"	±0.02mm
2871-101	0-10mm/0-0.4"	0.001mm/0.00005"	±0.005mm

## THICKNESS GAGE



2364-10



Code	Range	Graduation	Accuracy	Type
2364-10	0-10mm	0.01mm	±0.02mm	A
2364-10B	0-10mm	0.01mm	±0.02mm	B


DATA  
OUTPUT

## DIGITAL THICKNESS GAGE

Unit: mm



2872-10



Code	Range	Resolution	Accuracy
2872-10	0-10mm/0-0.4"	0.01mm/0.0005"	±0.02mm


- Ceramic spindle tip and anvil
- Buttons: on/off, zero, mm/inch
- Battery CR2032, automatic power off
- Data output
- Optional accessory: data output cable (code 7306-40, 7302-SPC3A, 7305-SPC1A)

## THICKNESS GAGE



Unit: mm



2365-10




Code	Range	Graduation	Accuracy	Type
2365-10	0-10mm	0.01mm	±0.02mm	A
2365-20	0-20mm	0.01mm	±0.03mm	A
2365-10B	0-10mm	0.01mm	±0.02mm	B
2365-20B	0-20mm	0.01mm	±0.03mm	B





## THICKNESS GAGE



2366-30



Unit: mm




Code	Range	Graduation	Accuracy	Type
2366-30	0-30mm	0.01mm	±0.035mm	A
2366-30B	0-30mm	0.01mm	±0.035mm	B

## THICKNESS GAGE


SUITABLE FOR JEWELLERY



2361-10



Unit: mm



Code	Range	Graduation	Accuracy
2361-10	0-10mm	0.1mm	±0.05mm



DATA  
OUTPUT

## DIGITAL TUBE THICKNESS GAGE




2873-10

- Buttons: on/off, zero, mm/inch
- Battery CR2032, automatic power off
- Data output
- Optional accessory: data output cable (code 7306-40, 7302-SPC3A, 7305-SPC1A)




Unit: mm

measure wall  
thickness of groove



Code	Range	Resolution	Accuracy
2873-10	0-10mm/0-0.4"	0.01mm/0.0005"	±0.02mm

## TUBE THICKNESS GAGE




- Measure tube wall thickness

Code	Range	Graduation	Accuracy
2367-10A	0-10mm	0.01mm	±0.02mm




2367-10A



Unit: mm

## THICKNESS GAGE



- Stainless steel spindle tip and anvil



2363-10

Code	Range	Graduation	Accuracy
2363-10	0-10mm	0.01mm	±0.03mm



## THICKNESS GAGE



2862-101

Code	Range	Graduation	Accuracy	(mm)	
				L	L1
2862-101	0-10mm	0.05mm	±0.1mm	35	85
2862-102	0-10mm	0.05mm	±0.1mm	60	110


## THICKNESS GAGE




2863-10

Code	Range	Graduation	Accuracy
2863-10	0-10mm	0.05mm	±0.1mm

## THICKNESS GAGE WITH POINTED TIPS




- Pointed tips fit into small grooves and recesses





2866-10

Code	Range	Graduation	Accuracy
2866-10	0-10mm	0.05mm	±0.1mm


## DIAL SNAP GAGE



3337-40



3337-60



- For quick Go/No-Go judgement
- Carbide measuring faces
- Height of support is adjustable
- Optional accessory: dial indicators (graduation 0.001mm) and digital indicators (resolution 0.001mm)


Code	Range	Parallelism of measuring faces	Retracting stroke	Remark
3337-40	0-40mm	1µm	6mm	
3337-60	0-60mm	3µm	6mm	jaw type measuring tips

Stand (optional)

Code
3337-STAND





3337-STAND



## DIAL SNAP GAGE


IP54  
WATERPROOF




3335-25

- Quick Go/No-Go measurement for mass production
- Anvil retracting stroke: 2.5mm
- Dial indicator: measuring range  $\pm 0.07\text{mm}$ , graduation  $1\mu\text{m}$ , accuracy  $1\mu\text{m}$
- Constant measuring force over the whole range: 8.5N
- Carbide measuring faces
- IP54 dust/waterproof
- Zero position of dial indicator is adjustable and can be locked (supplied with locking wrench)
- Adjustable platform height

(mm)				
Code	Range	L	a	b
3335-25	0-25mm	35	191	<15
3335-50	25-50mm	60	215	<25
3335-75	50-75mm	84	239	<37.5
3335-100	75-100mm	110	265	<50




## DIAL SNAP GAGE



3336-25

- Quick Go/No-Go judgement for mass production
- Carbide measuring faces
- Adjustable platform height
- Optional accessory: dial comparator (code 2881-01)

(mm)		
Code	Range	Diameter of measuring faces( $\varnothing d$ )
3336-25	0-25mm	8
3336-50	25-50mm	8
3336-100	50-100mm	15






ATTENTION: NOT SUITABLE FOR 0.001MM INDICATORS

## DIAL SNAP GAGE



dial indicator is not included

2184-50W



Code	Range	A	B
2184-25W	0-25mm	34	18
2184-50W	0-50mm	62	32
2184-100W	50-100mm	112	62
2184-150W	100-150mm	162	85
2184-200W	150-200mm	212	110

(mm)

- For quick Go/No-Go judgment of diameter of cylinders and shafts
- Anvil retracting stroke: 3mm
- Measuring force: 6-9N
- Carbide measuring faces
- Optional accessory: dial indicators (graduation 0.01mm), digital indicators (resolution 0.01mm/0.0005")


ATTENTION: BASIC MODEL

IP54 WATERPROOF

## DIAL SNAP GAGE



3334-25



Code	Range	L	D
3334-25	0-25mm	28.5	25
3334-50	25-50mm	53.5	35
3334-75	50-75mm	78.5	47.5
3334-100	75-100mm	103.5	60

(mm)

- Go/No-Go judgement for mass production
- Dial indicator: range  $\pm 0.04$ mm, graduation 0.001mm, accuracy 0.001mm
- IP54 dust/waterproof
- Measuring force: 5-10N
- Carbide measuring faces
- Supplied with setting standards (except 0-25mm)



# DIAL SNAP GAGE



2186-25

- For quick Go/No-Go judgement of diameter of cylinders and shafts
- Left anvil retracting stroke: 2mm
- Measuring force: 6-8N
- Flatness of anvil: 1.5µm
- Repeatability: 1µm
- Carbide measuring faces for anvils
- Front edges of anvils are chamfered for easy workpiece insertion
- Optional accessory: dial indicators and digital indicators (reading 0.001mm or 0.01mm)

Unit: mm



(mm)

Code	Range	Parallelism of measuring faces	A	B	C
2186-25	0-25mm	4µm	42	11-18	20
2186-50	25-50mm	4µm	69	11-32	41
2186-75	50-75mm	5µm	94	17-41	51
2186-100	75-100mm	6µm	119	31-55	65
2186-125	100-125mm	6µm	144	42-70	75
2186-150	125-150mm	8µm	169	55-82	90
2186-175	150-175mm	8µm	194	68-95	100
2186-200	175-200mm	10µm	219	85-110	115
2186-225	200-225mm	10µm	244	95-120	130
2186-250	225-250mm	10µm	269	110-135	145
2186-275	250-275mm	12µm	294	120-150	160
2186-300	275-300mm	12µm	319	128-160	170


# ADJUSTABLE SNAP GAGE




2187-6



2187-19



0-6mm



over 6mm

- Used as Go/No-Go gage by setting upper and lower limits
- Flatness of anvil: 1.5µm
- Parallelism of measuring faces:
  - range 0-32mm: 3µm
  - range 32-89mm: 4µm
  - range 89-300mm: 5µm

(mm)

Code	Range	L	A	B	E	F	H	Ød
2187-6	0-6mm	74	15	23.5	12.2	27.2	71.5	7
2187-13	6-13mm	85	15	26	12.2	27.2	79.5	12.3
2187-19	13-19mm	93	15	30	12.2	27.2	83	12.3
2187-25	19-25mm	100	15	33.5	12.2	27.2	89.5	12.3
2187-32	25-32mm	111	18	38.5	15.2	35.2	104	15.3
2187-38	32-38mm	117	18	41.5	15.2	35.2	105	15.3
2187-44	38-44mm	123	18	44.5	15.2	35.2	109	15.3
2187-51	44-51mm	130	18	48	15.2	35.2	117	15.3
2187-57	51-57mm	136	18	51	15.2	35.2	119	15.3
2187-63	57-63mm	143	18	54.5	15.2	35.2	122	15.3
2187-70	63-70mm	156	20	58	15.2	35.2	132	15.3
2187-76	70-76mm	163	20	60.5	15.2	35.2	137	15.3
2187-82	76-82mm	169	20	64.5	15.2	35.2	140	15.3
2187-89	82-89mm	175	20	66.5	15.2	35.2	146	15.3
2187-95	89-95mm	181	20	69.5	15.2	35.2	149	15.3
2187-101	95-101mm	188	20	73	15.2	35.2	154	15.3
2187-108	101-108mm	198	24	79	15.2	35.2	166	15.3
2187-114	108-114mm	204	24	81	15.2	39.2	172	15.3


Code	Range	L	A	B	E	F	H	Ød
2187-120	114-120mm	210	24	86	15.2	39.2	179	15.3
2187-127	120-127mm	217	24	89.5	15.2	39.2	186	15.3
2187-133	127-133mm	223	24	92.5	15.2	39.2	192	15.3
2187-139	133-139mm	229	24	95.5	15.2	39.2	197	15.3
2187-146	139-146mm	235	24	98.5	15.2	39.2	201	15.3
2187-152	146-152mm	242	24	102	15.2	39.2	205	15.3
2187-163	152-163mm	273	21.4	106.7	18.2	39.2	211	18.3
2187-175	163-175mm	273	21.4	106.7	18.2	39.2	211	18.3
2187-188	175-188mm	298.5	21.4	119.7	18.2	39.2	227	18.3
2187-200	188-200mm	298.5	21.4	119.7	18.2	39.2	227	18.3
2187-213	200-213mm	324	21.4	131.7	18.2	39.2	242	18.3
2187-225	213-225mm	324	21.4	131.7	18.2	39.2	242	18.3
2187-238	225-238mm	349.5	21.4	144.7	18.2	39.2	250	18.3
2187-250	238-250mm	349.5	21.4	144.7	18.2	39.2	250	18.3
2187-263	250-263mm	375.5	21.4	157.7	18.2	39.2	278	18.3
2187-275	263-275mm	375.5	21.4	157.7	18.2	39.2	278	18.3
2187-288	275-288mm	400	21.4	170.7	18.2	39.2	291	18.3
2187-300	288-300mm	400	21.4	170.7	18.2	39.2	291	18.3

## DIGITAL SNAP GAGE

DATA OUTPUT



2166-12



Code	Range	Resolution	Accuracy
2166-12	0-12mm/0-0.5"	0.01mm/0.0005"	±0.03mm


- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

## DIGITAL SNAP GAGE

ATTENTION:  
NO DATA OUTPUT



2167-25




Code	Range	Resolution	Accuracy
2167-25	0-25mm/0-1"	0.01mm/0.0005"	±0.03mm

## DIGITAL SNAP GAGE

DATA OUTPUT




2163-25



- Resolution: 0.01mm/0.0005"
- Accuracy: ±0.04mm
- For thickness and tube wall thickness measurement
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

Code	Thickness range	Tube wall thickness range
2163-25	0-25mm/0-1"	0-2mm/0.08"




DATA  
OUTPUT

## DIGITAL SNAP GAGE



1163-50A

- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable  
(code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)



Code	Range	Resolution	Accuracy
1163-50A	0-50mm/0-2"	0.01mm/0.0005"	±0.03mm

SUITABLE FOR  
JEWELLERY



ATTENTION:  
NO DATA OUTPUT

## DIGITAL 3-PURPOSE SNAP GAGE



2164-25A

- Buttons: zero, mm/inch, on/off
- Battery LR44
- Made of stainless steel



Code	Range	Resolution	Accuracy
2164-25A	0-25mm/0-1"	0.01mm/0.0005"	±0.03mm

# STEP AND GAP GAGE




front



back

DATA OUTPUT




Unit: mm

- Measure step height and gap width
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Supplied with zero setting block
- Optional accessory: data output cable (code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)

2168-12


zero setting block




Code	Range	Accuracy
2168-12	0-12.7mm/0-0.5"	±0.03mm

# CRANKSHAFT TESTER

Unit: mm




dial indicator



balance block


extension rods



anvils



2841-500



- To test crankshaft deflection
- The balance block is mounted on the back of dial indicator to keep the dial indicator facing up

Code	Range	Dial indicator range	Graduation	Extension rods	Accuracy
2841-300	60-300mm	3mm	0.01mm	16mm, 32mm, 64mm, 128mm	±0.016mm
2841-500	60-500mm	3mm	0.01mm	16mm, 32mm, 64mm, 96mm, 128mm, 192mm	±0.016mm

# GAGE BLOCKS


## Accuracy according to ISO3650

Nominal length (mm)	Grade 0		Grade 1		Grade 2	
	Limit deviation of length	Tolerance for the variation in length	Limit deviation of length	Tolerance for the variation in length	Limit deviation of length	Tolerance for the variation in length
over 0.5 to 10	±0.12µm	0.10µm	±0.20µm	0.16µm	±0.45µm	0.30µm
over 10 to 25	±0.14µm	0.10µm	±0.30µm	0.16µm	±0.60µm	0.30µm
over 25 to 50	±0.20µm	0.10µm	±0.40µm	0.18µm	±0.80µm	0.30µm
over 50 to 75	±0.25µm	0.12µm	±0.50µm	0.18µm	±1.00µm	0.35µm
over 75 to 100	±0.30µm	0.12µm	±0.60µm	0.20µm	±1.20µm	0.35µm
over 100 to 150	±0.40µm	0.14µm	±0.80µm	0.20µm	±1.60µm	0.40µm
over 150 to 200	±0.50µm	0.16µm	±1.00µm	0.25µm	±2.00µm	0.40µm
over 200 to 250	±0.60µm	0.16µm	±1.20µm	0.25µm	±2.40µm	0.45µm
over 250 to 300	±0.70µm	0.18µm	±1.40µm	0.25µm	±2.80µm	0.50µm
over 300 to 400	±0.90µm	0.20µm	±1.80µm	0.30µm	±3.60µm	0.50µm
over 400 to 500	±1.10µm	0.25µm	±2.20µm	0.35µm	±4.40µm	0.60µm
over 500 to 600	±1.30µm	0.25µm	±2.60µm	0.40µm	±5.00µm	0.70µm
over 600 to 700	±1.50µm	0.30µm	±3.00µm	0.45µm	±6.00µm	0.70µm
over 700 to 800	±1.70µm	0.30µm	±3.40µm	0.50µm	±6.50µm	0.80µm
over 800 to 900	±1.90µm	0.35µm	±3.80µm	0.50µm	±7.50µm	0.90µm
over 900 to 1000	±2.00µm	0.40µm	±4.20µm	0.60µm	±8.00µm	1.00µm

## Grade and application

Grade	Application
0	To be used as basic standards in calibration laboratories by skilled inspection staff, to calibrate or set high accuracy measuring instruments, to calibrate gage blocks of grade 1 and 2.
1	To be used in inspection rooms, to check gages, inspect high accuracy parts and set measuring instruments.
2	To be used in workshops, to check production gages, set measuring instruments and mount tools.

## Inspection certificate




**INSIZE**

**INSPECTION CERTIFICATE**

CODE: 4100-32  
GRADE: 0

**GAGE BLOCKS**

Nominal Size (mm)	Identification No.	Deviation (µm)	Nominal Size (mm)	Identification No.	Deviation (µm)	Nominal Size (mm)	Identification No.	Deviation (µm)
1.005	118456	+0.04	1.20	108960	+0.08	4	115718	+0.08
1.01	119466	0.00	1.30	091140	+0.03	5	114033	-0.02
1.02	101529	+0.08	1.40	112170	-0.02	6	111940	+0.07
1.03	112855	+0.08	1.5	116887	-0.02	7	116970	0.00
1.04	112140	0.00	1.6	102449	+0.05	8	119266	+0.05
1.05	106748	0.00	1.7	114888	+0.07	9	114947	+0.02
1.06	113899	-0.03	1.8	101023	+0.02	10	111703	+0.08
1.07	092053	+0.03	1.9	111542	+0.05	20	115586	+0.02
1.08	111782	0.00	1	115273	0.00	30	101817	+0.09
1.09	108008	-0.02	2	114741	+0.05	50	115454	0.00
1.10	110489	+0.07	3	116618	+0.05			

Set Serial No.: 110019      Material: Steel      Date: Jun. 8th 2011  
 Standard ISO3650      Standard reference temperature: 20°C      Inspector: 

# CERAMIC GAGE BLOCK SET



4105-87

- Made of ceramic, extremely wear resistance and corrosion resistance, excellent dimension stability
- Meet ISO3650
- Supplied with manufacturer inspection certificate

Blocks per set	Blocks included in set			Code	
	Size (mm)	Step (mm)	Quantity	Grade 0	Grade 1
112	1.0005		1	4105-112	4105-1112
	1.001-1.009	0.001	9		
	1.01-1.49	0.01	49		
	0.5-24.5	0.5	49		
	25-100	25	4		
103	1.005		1	4105-103	4105-1103
	1.01-1.49	0.01	49		
	0.5-24.5	0.5	49		
	25-100	25	4		
88	1.0005		1	4105-88	4105-188
	1.001-1.009	0.001	9		
	1.01-1.49	0.01	49		
	0.5-9.5	0.5	19		
	10-100	10	10		
87	1.001-1.009	0.001	9	4105-87	4105-187
	1.01-1.49	0.01	49		
	0.5-9.5	0.5	19		
	10-100	10	10		
76	1.005		1	4105-76	4105-176
	1.01-1.49	0.01	49		
	0.5-9.5	0.5	19		
	10-40	10	4		
	50-100	25	3		
56	0.5		1	4105-56	4105-156
	1.001-1.009	0.001	9		
	1.01-1.09	0.01	9		
	1.1-1.9	0.1	9		
	1-24	1	24		
	25-100	25	4		

Blocks per set	Blocks included in set			Code	
	Size (mm)	Step (mm)	Quantity	Grade 0	Grade 1
47	1.005		1	4105-47A	4105-147A
	1.01-1.09	0.01	9		
	1.1-1.9	0.1	9		
	1-24	1	24		
	25-100	25	4		
47	1.005		1	4105-47	4105-147
	1.01-1.19	0.01	19		
	1.2-1.9	0.1	8		
	1-9	1	9		
46	1.001-1.009	0.001	9	4105-46	4105-146
	1.01-1.09	0.01	9		
	1.1-1.9	0.1	9		
	1-9	1	9		
	10-100	10	10		
34	1.0005		1	4105-34	4105-134
	1.001-1.009	0.001	9		
	1.01-1.09	0.01	9		
	1.1-1.9	0.1	9		
	1-5	1	5		
32	1.005		1	4105-32	4105-132
	1.01-1.09	0.01	9		
	1.1-1.9	0.1	9		
	1-9	1	9		
	10-30	10	3		
	50		1		
8	125-175	25	3	4105-8	4105-18
	200-250	50	2		
	300-500	100	3		





## CARBIDE GAGE BLOCK SET



4164-32

- Made of carbide, extremely wear resistance and corrosion resistance, excellent dimension stability
- Meet ISO3650
- Supplied with manufacturer inspection certificate

Blocks per set	Blocks included in set			Code	
	Size (mm)	Step (mm)	Quantity	Grade 0	Grade 1
122	1.0005		1	4164-122	4164-1122
	1.001-1.009	0.001	9		
	1.01-1.49	0.01	49		
	1.6-1.9	0.1	4		
	0.5-24.5	0.5	49		
	30-100	10	8		
	25-75	50	2		
112	1.0005		1	4164-112	4164-1112
	1.001-1.009	0.001	9		
	1.01-1.49	0.01	49		
	0.5-24.5	0.5	49		
	25-100	25	4		
103	1.005		1	4164-103	4164-1103
	1.01-1.49	0.01	49		
	0.5-24.5	0.5	49		
	25-100	25	4		
87	1.001-1.009	0.001	9	4164-87	4164-187
	1.01-1.49	0.01	49		
	0.5-9.5	0.5	19		
	10-100	10	10		
83	0.5		1	4164-83	4164-183
	1		1		
	1.005		1		
	1.01-1.49	0.01	49		
	1.5-1.9	0.1	5		
	2-9.5	0.5	16		
	10-100	10	10		

Blocks per set	Blocks included in set			Code	
	Size (mm)	Step (mm)	Quantity	Grade 0	Grade 1
76	1.005		1	4164-76	4164-176
	1.01-1.49	0.01	49		
	0.5-9.5	0.5	19		
	10-40	10	4		
	50-100	25	3		
47	1.005		1	4164-47A	4164-147A
	1.01-1.09	0.01	9		
	1.1-1.9	0.1	9		
	25-100	25	4		
47	1.005		1	4164-47	4164-147
	1.01-1.19	0.01	19		
	1.2-1.9	0.1	8		
	10-100	10	10		
46	1.001-1.009	0.001	9	4164-46	4164-146
	1.01-1.09	0.01	9		
	1.1-1.9	0.1	9		
	1-9	1	9		
	10-100	10	10		
32	1.005		1	4164-32	4164-132
	1.01-1.09	0.01	9		
	1.1-1.9	0.1	9		
	1-9	1	9		
	10-30	10	3		
	50		1		

# STEEL GAGE BLOCK SET



4100-87

- Made of alloy steel
- Meet ISO3650
- Supplied with manufacturer inspection certificate

Blocks per set	Blocks included in set			Code		
	Size (mm)	Step (mm)	Quantity	Grade 0	Grade 1	Grade 2
122	1.0005		1	4100-122	4100-1122	4100-2122
	1.001-1.009	0.001	9			
	1.01-1.49	0.01	49			
	1.6-1.9	0.1	4			
	0.5-24.5	0.5	49			
	30-100	10	8			
	25-75	50	2			
112	1.0005		1	4100-112	4100-1112	4100-2112
	1.001-1.009	0.001	9			
	1.01-1.49	0.01	49			
	0.5-24.5	0.5	49			
	25-100	25	4			
103	1.005		1	4100-103	4100-1103	4100-2103
	1.01-1.49	0.01	49			
	0.5-24.5	0.5	49			
	25-100	25	4			
88	1.0005		1	4100-88	4100-188	4100-288
	1.001-1.009	0.001	9			
	1.01-1.49	0.01	49			
	0.5-9.5	0.5	19			
	10-100	10	10			
87	1.001-1.009	0.001	9	4100-87	4100-187	4100-287
	1.01-1.49	0.01	49			
	0.5-9.5	0.5	19			
	10-100	10	10			
83	0.5		1	4100-83	4100-183	4100-283
	1		1			
	1.005		1			
	1.01-1.49	0.01	49			
	1.5-1.9	0.1	5			
	2-9.5	0.5	16			
	10-100	10	10			

To be continued

Continued from previous page


Blocks per set	Blocks included in set			Code		
	Size (mm)	Step (mm)	Quantity	Grade 0	Grade 1	Grade 2
76	1.005		1	4100-76	4100-176	4100-276
	1.01-1.49	0.01	49			
	0.5-9.5	0.5	19			
	10-40	10	4			
	50-100	25	3			
56	0.5		1	4100-56	4100-156	4100-256
	1.001-1.009	0.001	9			
	1.01-1.09	0.01	9			
	1.1-1.9	0.1	9			
	1-24	1	24			
	25-100	25	4			
47	1.005		1	4100-47A	4100-147A	4100-247A
	1.01-1.09	0.01	9			
	1.1-1.9	0.1	9			
	1-24	1	24			
	25-100	25	4			
47	1.005		1	4100-47	4100-147	4100-247
	1.01-1.19	0.01	19			
	1.2-1.9	0.1	8			
	1-9	1	9			
	10-100	10	10			
46	1.001-1.009	0.001	9	4100-46	4100-146	4100-246
	1.01-1.09	0.01	9			
	1.1-1.9	0.1	9			
	1-9	1	9			
	10-100	10	10			
34	1.0005		1	4100-34	4100-134	4100-234
	1.001-1.009	0.001	9			
	1.01-1.09	0.01	9			
	1.1-1.9	0.1	9			
	1-5	1	5			
	10		1			
32	1.005		1	4100-32	4100-132	4100-232
	1.01-1.09	0.01	9			
	1.1-1.9	0.1	9			
	1-9	1	9			
	10-30	10	3			
	50		1			
9	1.001-1.009	0.001	9	4100-9	4100-19	4100-29
9	0.991-0.999	0.001	9	4100-9A	4100-19A	4100-29A
8	125-175	25	3	4100-8	4100-18	4100-28
	200-250	50	2			
	300-500	100	3			

# INDIVIDUAL CERAMIC GAGE BLOCK



4106-A80

Code explanation:



Code examples:

Size	Grade	Code
0.5mm	0	4106-AD5
10mm	1	4106-B10

- Made of ceramic, extremely wear resistance and corrosion resistance
- Meet ISO3650
- Supplied with manufacturer inspection certificate

Size	Code
0.5mm	4106- <u>X</u> D5
1mm	4106- <u>X</u> 1
1.0005mm	4106- <u>X</u> 1D0005
1.001mm	4106- <u>X</u> 1D001
1.002mm	4106- <u>X</u> 1D002
1.003mm	4106- <u>X</u> 1D003
1.004mm	4106- <u>X</u> 1D004
1.005mm	4106- <u>X</u> 1D005
1.006mm	4106- <u>X</u> 1D006
1.007mm	4106- <u>X</u> 1D007
1.008mm	4106- <u>X</u> 1D008
1.009mm	4106- <u>X</u> 1D009
1.01mm	4106- <u>X</u> 1D01
1.02mm	4106- <u>X</u> 1D02
1.03mm	4106- <u>X</u> 1D03
1.04mm	4106- <u>X</u> 1D04
1.05mm	4106- <u>X</u> 1D05
1.06mm	4106- <u>X</u> 1D06
1.07mm	4106- <u>X</u> 1D07
1.08mm	4106- <u>X</u> 1D08
1.09mm	4106- <u>X</u> 1D09
1.1mm	4106- <u>X</u> 1D1
1.11mm	4106- <u>X</u> 1D11
1.12mm	4106- <u>X</u> 1D12
1.13mm	4106- <u>X</u> 1D13
1.14mm	4106- <u>X</u> 1D14
1.15mm	4106- <u>X</u> 1D15
1.16mm	4106- <u>X</u> 1D16
1.17mm	4106- <u>X</u> 1D17
1.18mm	4106- <u>X</u> 1D18
1.19mm	4106- <u>X</u> 1D19
1.2mm	4106- <u>X</u> 1D2
1.21mm	4106- <u>X</u> 1D21
1.22mm	4106- <u>X</u> 1D22

Size	Code
1.23mm	4106- <u>X</u> 1D23
1.24mm	4106- <u>X</u> 1D24
1.25mm	4106- <u>X</u> 1D25
1.26mm	4106- <u>X</u> 1D26
1.27mm	4106- <u>X</u> 1D27
1.28mm	4106- <u>X</u> 1D28
1.29mm	4106- <u>X</u> 1D29
1.3mm	4106- <u>X</u> 1D3
1.31mm	4106- <u>X</u> 1D31
1.32mm	4106- <u>X</u> 1D32
1.33mm	4106- <u>X</u> 1D33
1.34mm	4106- <u>X</u> 1D34
1.35mm	4106- <u>X</u> 1D35
1.36mm	4106- <u>X</u> 1D36
1.37mm	4106- <u>X</u> 1D37
1.38mm	4106- <u>X</u> 1D38
1.39mm	4106- <u>X</u> 1D39
1.4mm	4106- <u>X</u> 1D4
1.41mm	4106- <u>X</u> 1D41
1.42mm	4106- <u>X</u> 1D42
1.43mm	4106- <u>X</u> 1D43
1.44mm	4106- <u>X</u> 1D44
1.45mm	4106- <u>X</u> 1D45
1.46mm	4106- <u>X</u> 1D46
1.47mm	4106- <u>X</u> 1D47
1.48mm	4106- <u>X</u> 1D48
1.49mm	4106- <u>X</u> 1D49
1.5mm	4106- <u>X</u> 1D5
1.6mm	4106- <u>X</u> 1D6
1.7mm	4106- <u>X</u> 1D7
1.8mm	4106- <u>X</u> 1D8
1.9mm	4106- <u>X</u> 1D9
2mm	4106- <u>X</u> 2
2.5mm	4106- <u>X</u> 2D5

Size	Code
3mm	4106- <u>X</u> 3
3.5mm	4106- <u>X</u> 3D5
4mm	4106- <u>X</u> 4
4.5mm	4106- <u>X</u> 4D5
5mm	4106- <u>X</u> 5
5.1mm	4106- <u>X</u> 5D1
5.5mm	4106- <u>X</u> 5D5
6mm	4106- <u>X</u> 6
6.5mm	4106- <u>X</u> 6D5
7mm	4106- <u>X</u> 7
7.5mm	4106- <u>X</u> 7D5
7.7mm	4106- <u>X</u> 7D7
8mm	4106- <u>X</u> 8
8.5mm	4106- <u>X</u> 8D5
9mm	4106- <u>X</u> 9
9.5mm	4106- <u>X</u> 9D5
10mm	4106- <u>X</u> 10
10.3mm	4106- <u>X</u> 10D3
10.5mm	4106- <u>X</u> 10D5
11mm	4106- <u>X</u> 11
11.5mm	4106- <u>X</u> 11D5
12mm	4106- <u>X</u> 12
12.5mm	4106- <u>X</u> 12D5
12.9mm	4106- <u>X</u> 12D9
13mm	4106- <u>X</u> 13
13.5mm	4106- <u>X</u> 13D5
14mm	4106- <u>X</u> 14
14.5mm	4106- <u>X</u> 14D5
15mm	4106- <u>X</u> 15
15.5mm	4106- <u>X</u> 15D5
16mm	4106- <u>X</u> 16
16.5mm	4106- <u>X</u> 16D5
17mm	4106- <u>X</u> 17
17.5mm	4106- <u>X</u> 17D5

Size	Code
17.6mm	4106- <u>X</u> 17D6
18mm	4106- <u>X</u> 18
18.5mm	4106- <u>X</u> 18D5
19mm	4106- <u>X</u> 19
19.5mm	4106- <u>X</u> 19D5
20mm	4106- <u>X</u> 20
20.2mm	4106- <u>X</u> 20D2
20.5mm	4106- <u>X</u> 20D5
21mm	4106- <u>X</u> 21
21.5mm	4106- <u>X</u> 21D5
22mm	4106- <u>X</u> 22
22.5mm	4106- <u>X</u> 22D5
22.8mm	4106- <u>X</u> 22D8
23mm	4106- <u>X</u> 23
23.5mm	4106- <u>X</u> 23D5
24mm	4106- <u>X</u> 24
24.5mm	4106- <u>X</u> 24D5
25mm	4106- <u>X</u> 25
30mm	4106- <u>X</u> 30
40mm	4106- <u>X</u> 40
41.3mm	4106- <u>X</u> 41D3
50mm	4106- <u>X</u> 50
60mm	4106- <u>X</u> 60
70mm	4106- <u>X</u> 70
75mm	4106- <u>X</u> 75
80mm	4106- <u>X</u> 80
90mm	4106- <u>X</u> 90
100mm	4106- <u>X</u> 100
125mm	4106- <u>X</u> 125
131.4mm	4106- <u>X</u> 131D4
150mm	4106- <u>X</u> 150

## CUSTOM-MADE

CAN SUPPLY ANY SIZES WITHIN 0.5 ~ 1000MM, SUCH AS 72.672MM  
 SIZE<100MM: MOQ 6PCS PER SIZE  
 SIZE>100MM: MOQ 3PCS PER SIZE

## INDIVIDUAL STEEL GAGE BLOCK



Code explanation:

4101-X□□□□□

- A for grade 0
- B for grade 1
- C for grade 2

Code examples:

Size	Grade	Code
0.5mm	0	4101-AD5
1mm	1	4101-B1
10.5mm	2	4101-C10D5



4101-A70

- Made of alloy steel
- Meet ISO3650
- Supplied with manufacturer inspection certificate


Size	Code
0.5mm	4101-XD5
0.991mm	4101-XD991
0.992mm	4101-XD992
0.993mm	4101-XD993
0.994mm	4101-XD994
0.995mm	4101-XD995
0.996mm	4101-XD996
0.997mm	4101-XD997
0.998mm	4101-XD998
0.999mm	4101-XD999
1mm	4101-X1
1.0005mm	4101-X1D0005
1.001mm	4101-X1D001
1.002mm	4101-X1D002
1.003mm	4101-X1D003
1.004mm	4101-X1D004
1.005mm	4101-X1D005
1.006mm	4101-X1D006
1.007mm	4101-X1D007
1.008mm	4101-X1D008
1.009mm	4101-X1D009
1.01mm	4101-X1D01
1.02mm	4101-X1D02
1.03mm	4101-X1D03
1.04mm	4101-X1D04
1.05mm	4101-X1D05
1.06mm	4101-X1D06
1.07mm	4101-X1D07
1.08mm	4101-X1D08
1.09mm	4101-X1D09
1.1mm	4101-X1D1
1.11mm	4101-X1D11
1.12mm	4101-X1D12
1.13mm	4101-X1D13
1.14mm	4101-X1D14
1.15mm	4101-X1D15
1.16mm	4101-X1D16
1.17mm	4101-X1D17
1.18mm	4101-X1D18

Size	Code
1.19mm	4101-X1D19
1.2mm	4101-X1D2
1.21mm	4101-X1D21
1.22mm	4101-X1D22
1.23mm	4101-X1D23
1.24mm	4101-X1D24
1.25mm	4101-X1D25
1.26mm	4101-X1D26
1.27mm	4101-X1D27
1.28mm	4101-X1D28
1.29mm	4101-X1D29
1.3mm	4101-X1D3
1.31mm	4101-X1D31
1.32mm	4101-X1D32
1.33mm	4101-X1D33
1.34mm	4101-X1D34
1.35mm	4101-X1D35
1.36mm	4101-X1D36
1.37mm	4101-X1D37
1.38mm	4101-X1D38
1.39mm	4101-X1D39
1.4mm	4101-X1D4
1.41mm	4101-X1D41
1.42mm	4101-X1D42
1.43mm	4101-X1D43
1.44mm	4101-X1D44
1.45mm	4101-X1D45
1.46mm	4101-X1D46
1.47mm	4101-X1D47
1.48mm	4101-X1D48
1.49mm	4101-X1D49
1.5mm	4101-X1D5
1.6mm	4101-X1D6
1.7mm	4101-X1D7
1.8mm	4101-X1D8
1.9mm	4101-X1D9
2mm	4101-X2
2.5mm	4101-X2D5
3mm	4101-X3


Size	Code
3.5mm	4101-X3D5
4mm	4101-X4
4.5mm	4101-X4D5
5mm	4101-X5
5.1mm	4101-X5D1
5.5mm	4101-X5D5
6mm	4101-X6
6.5mm	4101-X6D5
7mm	4101-X7
7.5mm	4101-X7D5
7.7mm	4101-X7D7
8mm	4101-X8
8.5mm	4101-X8D5
9mm	4101-X9
9.5mm	4101-X9D5
10mm	4101-X10
10.3mm	4101-X10D3
10.5mm	4101-X10D5
11mm	4101-X11
11.5mm	4101-X11D5
12mm	4101-X12
12.5mm	4101-X12D5
12.9mm	4101-X12D9
13mm	4101-X13
13.5mm	4101-X13D5
14mm	4101-X14
14.5mm	4101-X14D5
15mm	4101-X15
15.5mm	4101-X15D5
16mm	4101-X16
16.5mm	4101-X16D5
17mm	4101-X17
17.5mm	4101-X17D5
17.6mm	4101-X17D6
18mm	4101-X18
18.5mm	4101-X18D5
19mm	4101-X19
19.5mm	4101-X19D5
20mm	4101-X20

Size	Code
20.2mm	4101-X20D2
20.5mm	4101-X20D5
21mm	4101-X21
21.5mm	4101-X21D5
22mm	4101-X22
22.5mm	4101-X22D5
22.8mm	4101-X22D8
23mm	4101-X23
23.5mm	4101-X23D5
24mm	4101-X24
24.5mm	4101-X24D5
25mm	4101-X25
30mm	4101-X30
35mm	4101-X35
40mm	4101-X40
41.3mm	4101-X41D3
45mm	4101-X45
50mm	4101-X50
60mm	4101-X60
70mm	4101-X70
75mm	4101-X75
80mm	4101-X80
90mm	4101-X90
100mm	4101-X100
125mm	4101-X125
131.4mm	4101-X131D4
150mm	4101-X150
175mm	4101-X175
200mm	4101-X200
250mm	4101-X250
300mm	4101-X300
400mm	4101-X400
500mm	4101-X500
600mm	4101-X600
700mm	4101-X700
750mm	4101-X750
800mm	4101-X800
900mm	4101-X900
1000mm	4101-X1000

## WEAR BLOCK SET



4111-2



Blocks per set	Size	Material	Code	
			Grade 0	Grade 1
2	1.0mm	ceramic	4111-1	4111-11
2	1.0mm	alloy steel	4111-1A	4111-11A
2	2.0mm	ceramic	4111-2	4111-12
2	2.0mm	alloy steel	4111-2A	4111-12A

- Protect the measuring surfaces of gage blocks from excessive wear
- Meet ISO3650
- Supplied with manufacturer inspection certificate

## MICROMETER INSPECTION GAGE BLOCK SET



4107-10

- One piece of optical flat is included in 4107-10, 4107-101
- Meet ISO3650/grade 0
- Supplied with manufacturer inspection certificate

Code	Material	Blocks included in set	Applicable micrometer	Optical flat
4107-10	ceramic	2.5mm, 5.1mm, 7.7mm, 10.3mm, 12.9mm, 15mm, 17.6mm, 20.2mm, 22.8mm, 25mm, optical flat	0-25mm	included
4107-101	alloy steel	2.5mm, 5.1mm, 7.7mm, 10.3mm, 12.9mm, 15mm, 17.6mm, 20.2mm, 22.8mm, 25mm, optical flat	0-25mm	included
4107-112	alloy steel	25mm, 27.5mm, 30.1mm, 32.7mm, 35.3mm, 37.9mm, 40mm, 42.6mm, 45.2mm, 47.8mm, 50mm	25-50mm	not included
4107-113	alloy steel	50mm, 52.5mm, 55.1mm, 57.7mm, 60.3mm, 62.9mm, 65mm, 67.6mm, 70.2mm, 72.8mm, 75mm	50-75mm	not included
4107-114	alloy steel	75mm, 77.5mm, 80.1mm, 82.7mm, 85.3mm, 87.9mm, 90mm, 92.6mm, 95.2mm, 97.8mm, 100mm	75-100mm	not included



## CALIPER INSPECTION GAGE BLOCK SET



- Meet ISO3650/grade 2
- Supplied with manufacturer inspection certificate

**4108-3005**

Code	Material	Blocks per set	Blocks included in set (mm)	Applicable caliper (mm)
4108-3005	alloy steel	5	30, 41.3, 131.4, 243.5, 281.2	0-150, 0-200, 0-300




**6883-4**

- Made of aluminum
- To be used with individual steel gage block (code 4101) as Go and No-Go gage

Code	Applicable gage block size
6883-1	1.5-5mm
6883-2	5-10mm
6883-3	10-15mm
6883-4	15-20mm
6883-5	20-25mm

## GAGE BLOCK HOLDER




To be used as Go and No-Go gage



# GAGE BLOCK ACCESSORY



6881-A3




Code	Name	Clamping range* (L)
6881-A1	holder	0-25mm
6881-A2	holder	25-50mm
6881-A3	holder	50-100mm
6881-A4	holder	100-200mm
6881-A5	holder	200-300mm
6881-A6**	holder	300-500mm

\* The actual clamping range should deduct the width of jaws

\*\* Not suitable for base 6881-B




6881-C



Code	Name	Remark
6881-C	plain jaw	made of carbide, supplied in pair



6881-D




Code	Name	Remark
6881-D	parallel jaw	made of carbide




6881-B


Code	Name
6881-B	base




6881-E2



6881-E1



6881-E2




6881-E3

Code	Name	Size	Remark
6881-E1	half round jaw	2.5mm	made of carbide, supplied in pair
6881-E2	half round jaw	5.0mm	made of carbide, supplied in pair
6881-E3	half round jaw	6.0mm	made of carbide, supplied in pair




6881-F



Code	Name	Remark
6881-F	scriber	made of carbide



6881-G



Code	Name	Remark
6881-G	centre point	the tip is made of carbide

To be continued



Continued from previous page

**GAGE BLOCK ACCESSORY SET**

Code	Mark
6881-S17	17pcs (including the below items)

holder, 0-25mm (code 6881-A1)	1pc
holder, 25-50mm (code 6881-A2)	1pc
holder, 50-100mm (code 6881-A3)	1pc
holder, 100-200mm (code 6881-A4)	1pc
holder, 200-300mm (code 6881-A5)	1pc
base (code 6881-B)	1pc
plain jaw (code 6881-C)	1 pair
parallel jaw (code 6881-D)	1pc
half round jaw, 2.5mm (code 6881-E1)	1 pair
half round jaw, 5.0mm (code 6881-E2)	1 pair
half round jaw, 6.0mm (code 6881-E3)	1 pair
scriber (code 6881-F)	1pc
centre point (code 6881-G)	1pc



6881-S17

**application**

<p>(plain jaw+holder) set zero</p>	<p>(base+holder+scriber) measure height or scribe</p>
<p>(half round jaw+holder) measure size A</p>	<p>(plain jaw+parallel jaw+holder) Go and No Go inspection</p>
<p>(half round jaw+holder) measure inside diameter</p>	<p>(scriber+centre point+holder) scribe circle</p>


# CYLINDER GAGE BLOCK

**CUSTOM-MADE**  
CAN SUPPLY ANY LENGTH, SUCH AS 80.672MM



Code	Length(L)
4001-25*	25mm
4001-50*	50mm
4001-75*	75mm
4001-100*	100mm
4001-200*	200mm
4001-300*	300mm
4001-400*	400mm
4001-500*	500mm

- Made of special alloy steel, hardness HRC64, high stability, wear resistance and easy combination
- Meet ISO3650 grade 1
- Can be connected with M6x1 screw and combined to any sizes up to 4m



\* Supplied with manufacturer inspection certificate

can be combined to any sizes up to 4m

Combination 1: combined by several standard size cylinder gage blocks and one custom size cylinder gage block  
For example: 500 (standard) + 200 (standard) + 25.832 (custom)=725.832mm  
Note: in order to reduce cost, custom size should be within 100mm




Combination 2: combined by standard size cylinder gage blocks and rectangular gage blocks  
For example: 500 (cylinder) + 200 (cylinder) + 21.5 (rectangular) + 2.33 (rectangular) + 2.002 (rectangular)=725.832mm




high stability in vertical position, suitable for checking height gages



connected with M6x1 screw



## INTERNAL BLOCKS




4001-A


- Can be attached to cylinder and rectangular gage blocks
- Made of special alloy steel, hardness HRC64, high stability, wear resistance and easy combination
- Supplied in a matched pair

Code	Size	Flatness
4001-A	12mm	0.2µm

Combination 1: combined by several standard size cylinder gage blocks and one custom size cylinder gage block  
For example: 500 (standard) + 200 (standard) + 25.832 (custom)=725.832mm  
Note: in order to reduce cost, custom size should be within 100mm



Combination 2: combined by standard size cylinder gage blocks and rectangular gage blocks  
For example: 500 (cylinder) + 200 (cylinder) + 50 (rectangular) - 20 (rectangular) - 2.16 (rectangular) - 2.008 (rectangular)=725.832mm



# CALIPER/HEIGHT GAGE CHECKER





horizontal

vertical




6884-300






6884-300

check upper jaws of caliper






check lower jaws of caliper



6884-600

check height gage



6884-1000

- To check calipers and height gages
- Constructed with steel gage blocks

(mm)

Code	Size	Range of inside measurement	Range of outside measurement	Range of height measurement	Accuracy
6884-300*	0-300mm	20,50,100,150,200,250,300	20,50,100,150,200,250,300	20,50,100,150,200,250,300,330,370	±5µm
6884-600*	0-600mm	20,50,100,150,200,250,300,350,400,450,500,550,600	20,50,100,150,200,250,300,350,400,450,500,550,600,630,660	20,50,100,150,200,250,300,350,400,450,500,550,600,630,660	±7µm
6884-1000*	0-1000mm	20,50,100,150,200,250,300,350,400,450,500,550,600,650,700,750,800,850,900,950,1000	30,50,100,150,200,250,300,350,400,450,500,550,600,650,700,750,800,850,900,950,1000,1030,1070	30,50,100,150,200,250,300,350,400,450,500,550,600,650,700,750,800,850,900,950,1000,1030,1070	±7µm

\* Supplied with manufacturer inspection certificate

## INSIDE MICROMETER ACCESSORY




6884-A3

- Supplied with a pair of 5mm carbide gage blocks, ISO3650 grade 0




Code	Applicable caliper/height gage checker
6884-A3*	0-300mm
6884-A6*	0-600mm
6884-A10*	0-1000mm

\* Supplied with manufacturer inspection certificate

set inside micrometer



# CHECK MASTER



6882-600A

- To check the accuracy of table movement of machine tools, to calibrate height gages and CMMs
- Ceramic gage blocks
- Can be used in either vertical and horizontal orientation
- Supplied with manufacturer inspection certificate

Code	Range	Step	Accuracy	Parallelism of blocks	L	L1	H	W
6882-300A	300mm	10mm	±2.5µm	1.2µm	350	310	49	45
6882-450A	450mm	10mm	±3.5µm	1.5µm	510	470	54	50
6882-600A	600mm	10mm	±3.5µm	1.5µm	650	610	54	50

# ANGLE GAGE BLOCK SET

Code	Blocks per set	Angle	Step	Quantity
4109-7A	7	15°10'		1
		30°20'		1
		45°30'		1
		50°		1
		60°40'		1
		75°50'		1
		90°/90°/90°/90°		1
4109-36A	36	10° - 20°	1°	11
		30° - 70°	10°	5
		45°		1
		15°10' - 15°50'	10'	5
		15°1' - 15°9'	1'	9
		10°00'30"		1
		80°/81°/100°/99°		1
		89°10'/89°20'/90°50'/90°40'		1
		89°30'/89°40'/90°30'/90°20'		1
		90°/90°/90°/90°		1




4109-7A

- Standard for angle measurement
- Accuracy ±10"



## ANGLE GAGE BLOCK

Unit: mm



- Accuracy:  $\pm 2''$
- To inspect protractor, taper gage, index plate, index head and goniometer, can also be used to set angle
- Made of special alloy steel, hardness HRC64, high stability, wear resistance and easy combination
- Can be combined to any angle with interval 6 seconds after combination (6", 12", 18", ... , 360°)



4002-15




### Individual

Code	Angle ( $\alpha$ )	H(mm)
4002-A1 *	1°	11.5
4002-A3 *	3°	14.0
4002-A5 *	5°	16.5
4002-A9 *	9°	22.0
4002-A15 *	15°	30.5
4002-A27 *	27°	48.0
4002-A30 *	30°	53.5
4002-A41 *	41°	75.0
4002-A45 *	45°	84.0
4002-B1 *	1'	10.0
4002-B3 *	3'	10.0
4002-B5 *	5'	10.0
4002-B9 *	9'	10.0
4002-B20 *	20'	10.0
4002-B27 *	27'	10.0
4002-B30 *	30'	10.0
4002-C6 *	6"	10.0
4002-C12 *	12"	10.0
4002-C18 *	18"	10.0
4002-C30 *	30"	10.0
4002-D *	90°/90°/90°/90°	75.0

### Set

Code	Angle ( $\alpha$ )	Total Quantity
4002-13 *	1°, 3°, 9°, 27°, 41°, 1', 3', 9', 27', 6", 18", 30", 90°/90°/90°/90°	13
4002-15 *	1°, 3°, 5°, 15°, 30°, 45°, 1', 3', 5', 20', 30', 6", 12", 30", 90°/90°/90°/90°	15


\* Supplied with manufacturer inspection certificate



# PIN GAGE SET



4166-6D



- Made of alloy steel
- Hardness HRC62-65
- Diameter accuracy:  $\pm 1\mu\text{m}$

Code	Diameter Ød (mm)	Step	Pin gages per set
4166-411	1.0, 1.1, 1.2, ..., 5.0	0.1mm	41
4166-511	5.0, 5.1, 5.2, ..., 10.0	0.1mm	51
4166-512	10.0, 10.1, 10.2, ..., 15.0	0.1mm	51
4166-513	15.0, 15.1, 15.2, ..., 20.0	0.1mm	51

Code	Diameter Ød (mm)	Step	Pin gages per set
4166-0D	0.20, 0.21, 0.22, ..., 0.50	0.01mm	31
4166-1	0.50, 0.51, 0.52, ..., 1.00	0.01mm	51
4166-1D	1.00, 1.01, 1.02, ..., 1.50	0.01mm	51
4166-2	1.50, 1.51, 1.52, ..., 2.00	0.01mm	51
4166-2D	2.00, 2.01, 2.02, ..., 2.50	0.01mm	51
4166-3	2.50, 2.51, 2.52, ..., 3.00	0.01mm	51
4166-3D	3.00, 3.01, 3.02, ..., 3.50	0.01mm	51
4166-4	3.50, 3.51, 3.52, ..., 4.00	0.01mm	51
4166-4D	4.00, 4.01, 4.02, ..., 4.50	0.01mm	51
4166-5	4.50, 4.51, 4.52, ..., 5.00	0.01mm	51
4166-5D	5.00, 5.01, 5.02, ..., 5.50	0.01mm	51
4166-6	5.50, 5.51, 5.52, ..., 6.00	0.01mm	51
4166-6D	6.00, 6.01, 6.02, ..., 6.50	0.01mm	51
4166-7	6.50, 6.51, 6.52, ..., 7.00	0.01mm	51
4166-7D	7.00, 7.01, 7.02, ..., 7.50	0.01mm	51
4166-8	7.50, 7.51, 7.52, ..., 8.00	0.01mm	51
4166-8D	8.00, 8.01, 8.02, ..., 8.50	0.01mm	51
4166-9	8.50, 8.51, 8.52, ..., 9.00	0.01mm	51
4166-9D	9.00, 9.01, 9.02, ..., 9.50	0.01mm	51
4166-10	9.50, 9.51, 9.52, ..., 10.00	0.01mm	51

Code	Diameter Ød (mm)	Step	Pin gages per set
4166-2S	1.00, 1.01, 1.02, ..., 2.00	0.01mm	101
4166-3S	2.00, 2.01, 2.02, ..., 3.00	0.01mm	101
4166-4S	3.00, 3.01, 3.02, ..., 4.00	0.01mm	101
4166-5S	4.00, 4.01, 4.02, ..., 5.00	0.01mm	101
4166-6S	5.00, 5.01, 5.02, ..., 6.00	0.01mm	101
4166-7S	6.00, 6.01, 6.02, ..., 7.00	0.01mm	101
4166-8S	7.00, 7.01, 7.02, ..., 8.00	0.01mm	101
4166-9S	8.00, 8.01, 8.02, ..., 9.00	0.01mm	101
4166-10S	9.00, 9.01, 9.02, ..., 10.00	0.01mm	101

Code	Diameter Ød (mm)	Step	Pin gages per set
4166-10D	10.00, 10.01, 10.02, ..., 10.50	0.01mm	51
4166-11	10.50, 10.51, 10.52, ..., 11.00	0.01mm	51
4166-11D	11.00, 11.01, 11.02, ..., 11.50	0.01mm	51
4166-12	11.50, 11.51, 11.52, ..., 12.00	0.01mm	51
4166-12D	12.00, 12.01, 12.02, ..., 12.50	0.01mm	51
4166-13	12.50, 12.51, 12.52, ..., 13.00	0.01mm	51
4166-13D	13.00, 13.01, 13.02, ..., 13.50	0.01mm	51
4166-14	13.50, 13.51, 13.52, ..., 14.00	0.01mm	51
4166-14D	14.00, 14.01, 14.02, ..., 14.50	0.01mm	51
4166-15	14.50, 14.51, 14.52, ..., 15.00	0.01mm	51
4166-15D	15.00, 15.01, 15.02, ..., 15.50	0.01mm	51
4166-16	15.50, 15.51, 15.52, ..., 16.00	0.01mm	51
4166-16D	16.00, 16.01, 16.02, ..., 16.50	0.01mm	51
4166-17	16.50, 16.51, 16.52, ..., 17.00	0.01mm	51
4166-17D	17.00, 17.01, 17.02, ..., 17.50	0.01mm	51
4166-18	17.50, 17.51, 17.52, ..., 18.00	0.01mm	51
4166-18D	18.00, 18.01, 18.02, ..., 18.50	0.01mm	51
4166-19	18.50, 18.51, 18.52, ..., 19.00	0.01mm	51
4166-19D	19.00, 19.01, 19.02, ..., 19.50	0.01mm	51
4166-20	19.50, 19.51, 19.52, ..., 20.00	0.01mm	51

## INDIVIDUAL PIN GAGE


- Diameter range:  $\varnothing 0.20 - \varnothing 20.00$ mm
- Diameter accuracy:  $\pm 1\mu\text{m}$
- Made of alloy steel
- Hardness HRC62-65
- Optional accessory: wooden box

Diameter $\varnothing d$ (mm)
0.20, 0.21, 0.22, 0.23, ..., 1.00
1.01, 1.02, 1.03, 1.04, ..., 2.00
2.01, 2.02, 2.03, 2.04, ..., 3.00
3.01, 3.02, 3.03, 3.04, ..., 4.00
4.01, 4.02, 4.03, 4.04, ..., 5.00
5.01, 5.02, 5.03, 5.04, ..., 6.00
6.01, 6.02, 6.03, 6.04, ..., 7.00
7.01, 7.02, 7.03, 7.04, ..., 8.00
8.01, 8.02, 8.03, 8.04, ..., 9.00
9.01, 9.02, 9.03, 9.04, ..., 10.00

Diameter $\varnothing d$ (mm)
10.01, 10.02, 10.03, 10.04, ..., 11.00
11.01, 11.02, 11.03, 11.04, ..., 12.00
12.01, 12.02, 12.03, 12.04, ..., 13.00
13.01, 13.02, 13.03, 13.04, ..., 14.00
14.01, 14.02, 14.03, 14.04, ..., 15.00
15.01, 15.02, 15.03, 15.04, ..., 16.00
16.01, 16.02, 16.03, 16.04, ..., 17.00
17.01, 17.02, 17.03, 17.04, ..., 18.00
18.01, 18.02, 18.03, 18.04, ..., 19.00
19.01, 19.02, 19.03, 19.04, ..., 20.00



4110-9D98



Code  
4110-xxxx

Ordering examples:

Diameter	Code
0.21mm	4110-0D21
5.56mm	4110-5D56
16.00mm	4110-16D00


Note : "D" stands for "."

## CUSTOM-MADE PIN GAGE

- Custom-made pin gages, diameter range  $\varnothing 0.200 \sim \varnothing 30.000$ mm with three decimal, for example 0.211mm, 5.562mm, 16.298mm
- Diameter accuracy:  $\pm 1\mu\text{m}$
- Made of alloy steel
- Hardness HRC62-65
- Optional accessory: wooden box



4118-8D015



Code	Diameter range $\varnothing d$ (mm)
4118-xxxxx *	0.200 ~ 30.000

\* Supplied with manufacturer inspection certificate

Ordering examples:

Diameter	Code
0.211mm	4118-0D211
5.562mm	4118-5D562
16.298mm	4118-16D298

Note : "D" stands for "."

## BOX FOR PIN GAGES


- For individual pin gages (4110 and 4118 series)

Code	Applicable pin gage diameter $\varnothing d$ (mm)	Quantity of pin gages
7340	0.20 - 10.00	51pcs
7340-101	0.20 - 10.00	101pcs
7340-201	10.00 - 15.00	51pcs
7340-202	15.00 - 20.00	51pcs



7340

# PIN GAGE HANDLE



Handle

clamping bush

Code	Applicable pin gage diameter (mm)	Including	
		Handle	Clamping bush (mm)
7341-0S	0.2 - 1.02	1pc	6 pairs (the clamping range are 0.2-0.38, 0.38-0.51, 0.51-0.64, 0.64-0.76, 0.76 - 0.89, 0.89 - 1.02)
7341-1S	1.02 - 1.91	1pc	7 pairs (the clamping range are 1.02 - 1.14, 1.14 - 1.27, 1.27 - 1.40, 1.40 - 1.52, 1.52 - 1.65, 1.65 - 1.78, 1.78 - 1.91)
7341-2S	1.91 - 3.33	1pc	8 pairs (the clamping range are 1.91 - 2.08, 2.08 - 2.26, 2.26 - 2.44, 2.44 - 2.62, 2.62 - 2.79, 2.79 - 2.97, 2.97 - 3.15, 3.15 - 3.33)
7341-3S	3.33 - 4.57	1pc	7 pairs (the clamping range are 3.33 - 3.51, 3.51 - 3.68, 3.68 - 3.86, 3.86 - 4.04, 4.04 - 4.22, 4.22 - 4.39, 4.39 - 4.57)
7341-4S	4.57 - 5.79	1pc	6 pairs (the clamping range are 4.57 - 4.78, 4.78 - 4.98, 4.98 - 5.18, 5.18 - 5.38, 5.38 - 5.59, 5.59 - 5.79)
7341-5S	5.79 - 7.14	1pc	6 pairs (the clamping range are 5.79 - 5.99, 5.99 - 6.20, 6.20 - 6.40, 6.40 - 6.63, 6.63 - 6.88, 6.88 - 7.14)
7341-6S	7.14 - 8.66	1pc	6 pairs (the clamping range are 7.14 - 7.39, 7.39 - 7.65, 7.65 - 7.90, 7.90 - 8.15, 8.15 - 8.41, 8.41 - 8.66)

Code	Applicable pin gage diameter (mm)	Including	
		Handle	Clamping bush (mm)
7341-7S	8.66 - 10.31	1pc	6 pairs (the clamping range are 8.66 - 8.92, 8.92 - 9.17, 9.17 - 9.42, 9.42 - 9.70, 9.70 - 10.01, 10.01 - 10.31)
7341-8S	10.31 - 11.81	1pc	4 pairs (the clamping range are 10.31 - 10.67, 10.67 - 11.05, 11.05 - 11.43, 11.43 - 11.81)
7341-9S	11.81 - 12.95	1pc	3 pairs (the clamping range are 11.81 - 12.19, 12.19 - 12.57, 12.57 - 12.95)
7341-10S	12.95 - 14.71	1pc	4 pairs (the clamping range are 12.95 - 13.51, 13.51 - 13.89, 13.89 - 14.30, 14.30 - 14.71)
7341-11S	14.71 - 16.13	1pc	4 pairs (the clamping range are 14.71 - 15.09, 15.09 - 15.49, 15.49 - 15.88, 15.88 - 16.13)
7341-12S	16.13 - 17.88	1pc	4 pairs (the clamping range are 16.13 - 16.66, 16.66 - 17.07, 17.07 - 17.48, 17.48 - 17.88)
7341-13S	17.88 - 19.30	1pc	4 pairs (the clamping range are 17.88 - 18.26, 18.26 - 18.67, 18.67 - 19.05, 19.05 - 19.30)
7341-14S	19.30 - 20.62	1pc	2 pairs (the clamping range are 19.30 - 19.84, 19.84 - 20.62)



## CUSTOM-MADE

OTHER CLASSES ARE AVAILABLE, SUCH AS H8, H9  
OTHER DIAMETERS ARE AVAILABLE, SUCH AS 19.003mm  
OTHER LENGTHS ARE AVAILABLE, SUCH AS 70mm

## PLAIN PLUG GAGE



4124-12

- Supplied with Go and No-Go gages together
- Class H7
- Hardness HRC 60±2
- Standard DIN7150-2

Type A



Type B



### Size tolerance of H7

Diameter Ød (mm)	Size tolerance of Go gage (mm)	Size tolerance of No-Go gage (mm)
≥2 ≤3	+0.0005/+0.0025	+0.009/+0.011
>3 ≤6	+0.00075/+0.00325	+0.01075/+0.01325
>6, ≤10	+0.00075/+0.00325	+0.01375/+0.01625
>10, ≤18	+0.001/+0.004	+0.0165/+0.0195
>18, ≤30	+0.001/+0.005	+0.019/+0.023
>30, ≤50	+0.0015/+0.0055	+0.023/+0.027
>50, ≤80	+0.0015/+0.0065	+0.0275/+0.0325
>80, ≤100	+0.002/+0.008	+0.032/+0.038

Code	Diameter Ød	Type
4124-2	2mm	A
4124-3	3mm	A
4124-4	4mm	A
4124-5	5mm	A
4124-6	6mm	A
4124-7	7mm	A
4124-8	8mm	A
4124-9	9mm	A
4124-10	10mm	A
4124-11	11mm	A
4124-12	12mm	A
4124-13	13mm	A
4124-14	14mm	A
4124-15	15mm	A
4124-16	16mm	A

Code	Diameter Ød	Type
4124-17	17mm	A
4124-18	18mm	A
4124-19	19mm	A
4124-20	20mm	A
4124-21	21mm	A
4124-22	22mm	A
4124-23	23mm	A
4124-24	24mm	A
4124-25	25mm	A
4124-26	26mm	A
4124-27	27mm	A
4124-28	28mm	A
4124-29	29mm	A
4124-30	30mm	A
4124-31	31mm	A

Code	Diameter Ød	Type
4124-32	32mm	A
4124-33	33mm	A
4124-34	34mm	A
4124-35	35mm	A
4124-36	36mm	A
4124-37	37mm	A
4124-38	38mm	A
4124-39	39mm	A
4124-40	40mm	A
4124-41	41mm	A
4124-42	42mm	A
4124-43	43mm	A
4124-44	44mm	A
4124-45	45mm	A
4124-46	46mm	A

Code	Diameter Ød	Type
4124-47	47mm	A
4124-48	48mm	A
4124-49	49mm	A
4124-50	50mm	A
4124-52	52mm	B
4124-55	55mm	B
4124-60	60mm	B
4124-65	65mm	B
4124-70	70mm	B
4124-75	75mm	B
4124-80	80mm	B
4124-85	85mm	B
4124-90	90mm	B
4124-95	95mm	B
4124-100	100mm	B

## THREAD PLUG GAGE

- Supplied with Go and No-Go gages together
- Class 6H
- Standard ISO1502



4130-10

ATTENTION:  
BASIC MODEL



### Individual

Code	Size (mm)
4130-2*	M2x0.4
4130-2D2*	M2.2x0.45
4130-2D5*	M2.5x0.45
4130-3*	M3x0.5
4130-3D5*	M3.5x0.6
4130-4*	M4x0.7
4130-5*	M5x0.8

Code	Size (mm)
4130-6*	M6x1
4130-7*	M7x1
4130-8*	M8x1.25
4130-9*	M9x1.25
4130-10*	M10x1.5
4130-11*	M11x1.5
4130-12*	M12x1.75

Code	Size (mm)
4130-14*	M14x2
4130-16*	M16x2
4130-18*	M18x2.5
4130-20*	M20x2.5
4130-22*	M22x2.5
4130-24*	M24x3
4130-27*	M27x3

Code	Size (mm)
4130-30*	M30x3.5
4130-33*	M33x3.5
4130-36*	M36x4
4130-39*	M39x4
4130-42*	M42x4.5
4130-45*	M45x4.5
4130-48*	M48x5

Code	Size (mm)
4130-52*	M52x5
4130-56*	M56x5.5
4130-60*	M60x5.5

\* Supplied with manufacturer inspection certificate

### Set

Code	Thread plug gages included
4130-S7*	M3x0.5(4130-3), M4x0.7(4130-4), M5x0.8(4130-5), M6x1(4130-6), M8x1.25(4130-8), M10x1.5(4130-10), M12x1.75(4130-12)

# FINE THREAD PLUG GAGE



ATTENTION:  
BASIC MODEL



4139-20G

- Supplied with Go and No-Go gages together
- Class 6H
- Standard ISO1502

Code	Size (mm)
4139-2B *	M2x0.25
4139-2D2B *	M2.2x0.25
4139-2D5D *	M2.5x0.35
4139-3D *	M3x0.35
4139-3D5D *	M3.5x0.35
4139-4G *	M4x0.5
4139-5G *	M5x0.5
4139-6G *	M6x0.5
4139-6L *	M6x0.75
4139-7G *	M7x0.5
4139-7L *	M7x0.75
4139-8G *	M8x0.5
4139-8L *	M8x0.75
4139-8P *	M8x1
4139-9G *	M9x0.5
4139-9L *	M9x0.75
4139-9P *	M9x1
4139-10G *	M10x0.5
4139-10L *	M10x0.75
4139-10P *	M10x1
4139-10Q *	M10x1.25
4139-11G *	M11x0.5
4139-11L *	M11x0.75
4139-11P *	M11x1
4139-12G *	M12x0.5
4139-12L *	M12x0.75
4139-12P *	M12x1
4139-12Q *	M12x1.25

Code	Size (mm)
4139-12R *	M12x1.5
4139-14G *	M14x0.5
4139-14L *	M14x0.75
4139-14P *	M14x1
4139-14Q *	M14x1.25
4139-14R *	M14x1.5
4139-16G *	M16x0.5
4139-16L *	M16x0.75
4139-16P *	M16x1
4139-16R *	M16x1.5
4139-18G *	M18x0.5
4139-18L *	M18x0.75
4139-18P *	M18x1
4139-18R *	M18x1.5
4139-18T *	M18x2
4139-20G *	M20x0.5
4139-20L *	M20x0.75
4139-20P *	M20x1
4139-20R *	M20x1.5
4139-20T *	M20x2
4139-22G *	M22x0.5
4139-22L *	M22x0.75
4139-22P *	M22x1
4139-22R *	M22x1.5
4139-22T *	M22x2
4139-24L *	M24x0.75
4139-24P *	M24x1
4139-24R *	M24x1.5

Code	Size (mm)
4139-24T *	M24x2
4139-27L *	M27x0.75
4139-27P *	M27x1
4139-27R *	M27x1.5
4139-27T *	M27x2
4139-30L *	M30x0.75
4139-30P *	M30x1
4139-30R *	M30x1.5
4139-30T *	M30x2
4139-30V *	M30x3
4139-33L *	M33x0.75
4139-33P *	M33x1
4139-33R *	M33x1.5
4139-33T *	M33x2
4139-33V *	M33x3
4139-36P *	M36x1
4139-36R *	M36x1.5
4139-36T *	M36x2
4139-36V *	M36x3
4139-39P *	M39x1
4139-39R *	M39x1.5
4139-39T *	M39x2
4139-39V *	M39x3
4139-42P *	M42x1
4139-42R *	M42x1.5
4139-42T *	M42x2
4139-42V *	M42x3
4139-42X *	M42x4

Code	Size (mm)
4139-45P *	M45x1
4139-45R *	M45x1.5
4139-45T *	M45x2
4139-45V *	M45x3
4139-45X *	M45x4
4139-48P *	M48x1
4139-48R *	M48x1.5
4139-48T *	M48x2
4139-48V *	M48x3
4139-48X *	M48x4
4139-52P *	M52x1
4139-52R *	M52x1.5
4139-52T *	M52x2
4139-52V *	M52x3
4139-52X *	M52x4
4139-56P *	M56x1
4139-56R *	M56x1.5
4139-56T *	M56x2
4139-56V *	M56x3
4139-56X *	M56x4
4139-60P *	M60x1
4139-60R *	M60x1.5
4139-60T *	M60x2
4139-60V *	M60x3
4139-60X *	M60x4

\* Supplied with manufacturer inspection certificate



# THREAD RING GAGE

ATTENTION:  
BASIC MODEL



4120-16



4120-16N

- Go and No-Go gages are supplied separately
- Class 6g
- Standard ISO1502

## Individual

Code Go	Code No Go	Size (mm)
4120-2*	4120-2N*	M2x0.4
4120-2D2*	4120-2D2N*	M2.2x0.45
4120-2D5*	4120-2D5N*	M2.5x0.45
4120-3*	4120-3N*	M3x0.5
4120-3D5*	4120-3D5N*	M3.5x0.6
4120-4*	4120-4N*	M4x0.7
4120-5*	4120-5N*	M5x0.8
4120-6*	4120-6N*	M6x1
4120-7*	4120-7N*	M7x1
4120-8*	4120-8N*	M8x1.25
4120-9*	4120-9N*	M9x1.25

Code Go	Code No Go	Size (mm)
4120-10*	4120-10N*	M10x1.5
4120-11*	4120-11N*	M11x1.5
4120-12*	4120-12N*	M12x1.75
4120-14*	4120-14N*	M14x2
4120-16*	4120-16N*	M16x2
4120-18*	4120-18N*	M18x2.5
4120-20*	4120-20N*	M20x2.5
4120-22*	4120-22N*	M22x2.5
4120-24*	4120-24N*	M24x3
4120-27*	4120-27N*	M27x3
4120-30*	4120-30N*	M30x3.5

Code Go	Code No Go	Size (mm)
4120-33*	4120-33N*	M33x3.5
4120-36*	4120-36N*	M36x4
4120-39*	4120-39N*	M39x4
4120-42*	4120-42N*	M42x4.5
4120-45*	4120-45N*	M45x4.5
4120-48*	4120-48N*	M48x5
4120-52*	4120-52N*	M52x5
4120-56*	4120-56N*	M56x5.5
4120-60*	4120-60N*	M60x5.5

## Go ring gage set

Code	Thread ring gages included
4120-S7*	M3x0.5(4120-3), M4x0.7(4120-4), M5x0.8(4120-5), M6x1(4120-6), M8x1.25(4120-8), M10x1.5(4120-10), M12x1.75(4120-12)

## No Go ring gage set

Code	Thread ring gages included
4120-S7N*	M3x0.5(4120-3N), M4x0.7(4120-4N), M5x0.8(4120-5N), M6x1(4120-6N), M8x1.25(4120-8N), M10x1.5(4120-10N), M12x1.75(4120-12N)

\* Supplied with manufacturer inspection certificate

# FINE THREAD RING GAGE

ATTENTION:  
BASIC MODEL

- Go and No-Go gages are supplied separately
- Class 6g
- Standard ISO1502



4129-10P



4129-10PN



Code Go	Code No Go	Size (mm)
4129-2B*	4129-2BN*	M2x0.25
4129-2D2B*	4129-2D2BN*	M2.2x0.25
4129-2D5D*	4129-2D5DN*	M2.5x0.35
4129-3D*	4129-3DN*	M3x0.35
4129-3D5D*	4129-3D5DN*	M3.5x0.35
4129-4G*	4129-4GN*	M4x0.5
4129-5G*	4129-5GN*	M5x0.5
4129-6G*	4129-6GN*	M6x0.5
4129-6L*	4129-6LN*	M6x0.75
4129-7G*	4129-7GN*	M7x0.5
4129-7L*	4129-7LN*	M7x0.75
4129-8G*	4129-8GN*	M8x0.5
4129-8L*	4129-8LN*	M8x0.75
4129-8P*	4129-8PN*	M8x1
4129-9G*	4129-9GN*	M9x0.5
4129-9L*	4129-9LN*	M9x0.75
4129-9P*	4129-9PN*	M9x1
4129-10G*	4129-10GN*	M10x0.5
4129-10L*	4129-10LN*	M10x0.75
4129-10P*	4129-10PN*	M10x1
4129-10Q*	4129-10QN*	M10x1.25
4129-11G*	4129-11GN*	M11x0.5
4129-11L*	4129-11LN*	M11x0.75
4129-11P*	4129-11PN*	M11x1
4129-12G*	4129-12GN*	M12x0.5
4129-12L*	4129-12LN*	M12x0.75
4129-12P*	4129-12PN*	M12x1
4129-12Q*	4129-12QN*	M12x1.25
4129-12R*	4129-12RN*	M12x1.5
4129-14G*	4129-14GN*	M14x0.5
4129-14L*	4129-14LN*	M14x0.75
4129-14P*	4129-14PN*	M14x1
4129-14Q*	4129-14QN*	M14x1.25
4129-14R*	4129-14RN*	M14x1.5
4129-16G*	4129-16GN*	M16x0.5
4129-16L*	4129-16LN*	M16x0.75
4129-16P*	4129-16PN*	M16x1

Code Go	Code No Go	Size (mm)
4129-16R*	4129-16RN*	M16x1.5
4129-18G*	4129-18GN*	M18x0.5
4129-18L*	4129-18LN*	M18x0.75
4129-18P*	4129-18PN*	M18x1
4129-18R*	4129-18RN*	M18x1.5
4129-18T*	4129-18TN*	M18x2
4129-20G*	4129-20GN*	M20x0.5
4129-20L*	4129-20LN*	M20x0.75
4129-20P*	4129-20PN*	M20x1
4129-20R*	4129-20RN*	M20x1.5
4129-20T*	4129-20TN*	M20x2
4129-22G*	4129-22GN*	M22x0.5
4129-22L*	4129-22LN*	M22x0.75
4129-22P*	4129-22PN*	M22x1
4129-22R*	4129-22RN*	M22x1.5
4129-22T*	4129-22TN*	M22x2
4129-24L*	4129-24LN*	M24x0.75
4129-24P*	4129-24PN*	M24x1
4129-24R*	4129-24RN*	M24x1.5
4129-24T*	4129-24TN*	M24x2
4129-27L*	4129-27LN*	M27x0.75
4129-27P*	4129-27PN*	M27x1
4129-27R*	4129-27RN*	M27x1.5
4129-27T*	4129-27TN*	M27x2
4129-30L*	4129-30LN*	M30x0.75
4129-30P*	4129-30PN*	M30x1
4129-30R*	4129-30RN*	M30x1.5
4129-30T*	4129-30TN*	M30x2
4129-30V*	4129-30VN*	M30x3
4129-33L*	4129-33LN*	M33x0.75
4129-33P*	4129-33PN*	M33x1
4129-33R*	4129-33RN*	M33x1.5
4129-33T*	4129-33TN*	M33x2
4129-33V*	4129-33VN*	M33x3
4129-36P*	4129-36PN*	M36x1
4129-36R*	4129-36RN*	M36x1.5
4129-36T*	4129-36TN*	M36x2

Code Go	Code No Go	Size (mm)
4129-36V*	4129-36VN*	M36x3
4129-39P*	4129-39PN*	M39x1
4129-39R*	4129-39RN*	M39x1.5
4129-39T*	4129-39TN*	M39x2
4129-39V*	4129-39VN*	M39x3
4129-42P*	4129-42PN*	M42x1
4129-42R*	4129-42RN*	M42x1.5
4129-42T*	4129-42TN*	M42x2
4129-42V*	4129-42VN*	M42x3
4129-42X*	4129-42XN*	M42x4
4129-45P*	4129-45PN*	M45x1
4129-45R*	4129-45RN*	M45x1.5
4129-45T*	4129-45TN*	M45x2
4129-45V*	4129-45VN*	M45x3
4129-45X*	4129-45XN*	M45x4
4129-48P*	4129-48PN*	M48x1
4129-48R*	4129-48RN*	M48x1.5
4129-48T*	4129-48TN*	M48x2
4129-48V*	4129-48VN*	M48x3
4129-48X*	4129-48XN*	M48x4
4129-52P*	4129-52PN*	M52x1
4129-52R*	4129-52RN*	M52x1.5
4129-52T*	4129-52TN*	M52x2
4129-52V*	4129-52VN*	M52x3
4129-52X*	4129-52XN*	M52x4
4129-56P*	4129-56PN*	M56x1
4129-56R*	4129-56RN*	M56x1.5
4129-56T*	4129-56TN*	M56x2
4129-56V*	4129-56VN*	M56x3
4129-56X*	4129-56XN*	M56x4
4129-60P*	4129-60PN*	M60x1
4129-60R*	4129-60RN*	M60x1.5
4129-60T*	4129-60TN*	M60x2
4129-60V*	4129-60VN*	M60x3
4129-60X*	4129-60XN*	M60x4

\* Supplied with manufacturer inspection certificate

# AMERICAN STANDARD THREAD PLUG GAGE



ATTENTION:  
BASIC MODEL



- Class 2B
- Standard ANSI B1.2

4131-1B1

Code	Size
4131-41*	4-40UNC
4131-61*	6-32UNC
4131-81*	8-32UNC
4131-102*	10-32UNF
4131-1B1*	1/4-20UNC
4131-1B2*	1/4-28UNF

Code	Size
4131-5D1*	5/16-18UNC
4131-5D2*	5/16-24UNF
4131-3C1*	3/8-16UNC
4131-3C2*	3/8-24UNF
4131-7D2*	7/16-20UNF
4131-1A1*	1/2-13UNC

Code	Size
4131-1A2*	1/2-20UNF
4131-9D2*	9/16-18UNF
4131-5C1*	5/8-11UNC
4131-5C2*	5/8-18UNF
4131-3B1*	3/4-10UNC
4131-3B2*	3/4-16UNF

\* Supplied with manufacturer inspection certificate

# AMERICAN STANDARD THREAD RING GAGE



ATTENTION: INSPECTED BY MASTER  
PLUG GAGES INSTEAD OF LENGTH MACHINE



4121-1B1



4121-1B1N

ATTENTION:  
BASIC MODEL

- Class 2A
- Standard ANSI B1.2

Code (GO)	Code (NOGO)	Size
4121-41*	4121-41N*	4-40UNC
4121-61*	4121-61N*	6-32UNC
4121-81*	4121-81N*	8-32UNC
4121-102*	4121-102N*	10-32UNF
4121-1B1*	4121-1B1N*	1/4-20UNC
4121-1B2*	4121-1B2N*	1/4-28UNF
4121-5D1*	4121-5D1N*	5/16-18UNC
4121-5D2*	4121-5D2N*	5/16-24UNF
4121-3C1*	4121-3C1N*	3/8-16UNC

Code (GO)	Code (NOGO)	Size
4121-3C2*	4121-3C2N*	3/8-24UNF
4121-7D2*	4121-7D2N*	7/16-20UNF
4121-1A1*	4121-1A1N*	1/2-13UNC
4121-1A2*	4121-1A2N*	1/2-20UNF
4121-9D2*	4121-9D2N*	9/16-18UNF
4121-5C1*	4121-5C1N*	5/8-11UNC
4121-5C2*	4121-5C2N*	5/8-18UNF
4121-3B1*	4121-3B1N*	3/4-10UNC
4121-3B2*	4121-3B2N*	3/4-16UNF

\* Supplied with manufacturer inspection certificate

## METRIC THREAD PLUG GAGE



- Class 6H
- Standard ISO1502
- Material: OHNS (Oil Hardened Non-shrinking Steel), stable dimension and wear resistance
- Hardness HRC60-62

4641-6

CLASS 5H OF M1.0, M1.1, M1.2, M1.4 ARE AVAILABLE

Code	Size (mm)
4641-1D6*	M1.6x0.35
4641-2*	M2x0.4
4641-2D5*	M2.5x0.45
4641-3*	M3x0.5
4641-3D5*	M3.5x0.6
4641-4*	M4x0.7

Code	Size (mm)
4641-5*	M5x0.8
4641-6*	M6x1
4641-8*	M8x1.25
4641-10*	M10x1.5
4641-12*	M12x1.75
4641-14*	M14x2

Code	Size (mm)
4641-16*	M16x2
4641-18*	M18x2.5
4641-20*	M20x2.5
4641-22*	M22x2.5
4641-24*	M24x3
4641-27*	M27x3

Code	Size (mm)
4641-30*	M30x3.5
4641-33*	M33x3.5
4641-36*	M36x4
4641-42*	M42x4.5
4641-48*	M48x5

\* Supplied with manufacturer calibration certificate

## METRIC FINE THREAD PLUG GAGE



- Class 6H
- Standard ISO1502
- Material: OHNS (Oil Hardened Non-shrinking Steel), stable dimension and wear resistance
- Hardness HRC60-62

4642-12R

Code	Size (mm)
4642-8G*	M8x0.5
4642-8L*	M8x0.75
4642-8P*	M8x1
4642-10L*	M10x0.75
4642-10P*	M10x1
4642-10Q*	M10x1.25
4642-12P*	M12x1
4642-12Q*	M12x1.25
4642-12R*	M12x1.5
4642-14P*	M14x1
4642-14Q*	M14x1.25
4642-14R*	M14x1.5
4642-16P*	M16x1
4642-16R*	M16x1.5

Code	Size (mm)
4642-18P*	M18x1
4642-18R*	M18x1.5
4642-20P*	M20x1
4642-20R*	M20x1.5
4642-22R*	M22x1.5
4642-24P*	M24x1
4642-24R*	M24x1.5
4642-24T*	M24x2
4642-25R*	M25x1.5
4642-26R*	M26x1.5
4642-27R*	M27x1.5
4642-27T*	M27x2
4642-28R*	M28x1.5
4642-30P*	M30x1

Code	Size (mm)
4642-30R*	M30x1.5
4642-30T*	M30x2
4642-32R*	M32x1.5
4642-33R*	M33x1.5
4642-33T*	M33x2
4642-35R*	M35x1.5
4642-36R*	M36x1.5
4642-36T*	M36x2
4642-38R*	M38x1.5
4642-40R*	M40x1.5
4642-40T*	M40x2
4642-42R*	M42x1.5
4642-42T*	M42x2
4642-45R*	M45x1.5

Code	Size (mm)
4642-45T*	M45x2
4642-48R*	M48x1.5
4642-48T*	M48x2
4642-50R*	M50x1.5
4642-50T*	M50x2
4642-52R*	M52x1.5
4642-52T*	M52x2
4642-55R*	M55x1.5
4642-55T*	M55x2
4642-58R*	M58x1.5
4642-60T*	M60x2

\* Supplied with manufacturer calibration certificate

## METRIC THREAD RING GAGE

CLASS 6h OF M1.2, M1.4  
ARE AVAILABLE



4631-12



4631-12N

- Class 6g
- Standard ISO1502
- Material: OHNS (Oil Hardened Non-shrinking Steel), stable dimension and wear resistance
- Hardness HRC60-62

Code (GO)	Code (NOGO)	Size (mm)
4631-1D2 *	4631-1D2N *	M1.2x0.25
4631-1D4 *	4631-1D4N *	M1.4x0.30
4631-1D6 *	4631-1D6N *	M1.6x0.35
4631-2 *	4631-2N *	M2x0.4
4631-2D5 *	4631-2D5N *	M2.5x0.45
4631-3 *	4631-3N *	M3x0.5
4631-3D5 *	4631-3D5N *	M3.5x0.6
4631-4 *	4631-4N *	M4x0.7
4631-5 *	4631-5N *	M5x0.8

Code (GO)	Code (NOGO)	Size (mm)
4631-6 *	4631-6N *	M6x1
4631-8 *	4631-8N *	M8x1.25
4631-10 *	4631-10N *	M10x1.5
4631-12 *	4631-12N *	M12x1.75
4631-14 *	4631-14N *	M14x2
4631-16 *	4631-16N *	M16x2
4631-18 *	4631-18N *	M18x2.5
4631-20 *	4631-20N *	M20x2.5
4631-22 *	4631-22N *	M22x2.5

Code (GO)	Code (NOGO)	Size (mm)
4631-24 *	4631-24N *	M24x3
4631-27 *	4631-27N *	M27x3
4631-30 *	4631-30N *	M30x3.5
4631-33 *	4631-33N *	M33x3.5
4631-36 *	4631-36N *	M36x4
4631-42 *	4631-42N *	M42x4.5
4631-48 *	4631-48N *	M48x5

\* Supplied with manufacturer calibration certificate

## METRIC FINE THREAD RING GAGE

- Class 6g
- Standard ISO1502
- Material: OHNS (Oil Hardened Non-shrinking Steel), stable dimension and wear resistance
- Hardness HRC60-62



4632-10Q



4632-10QN

Code (GO)	Code (NOGO)	Size (mm)
4632-8G *	4632-8GN *	M8x0.5
4632-8L *	4632-8LN *	M8x0.75
4632-8P *	4632-8PN *	M8x1
4632-10L *	4632-10LN *	M10x0.75
4632-10P *	4632-10PN *	M10x1
4632-10Q *	4632-10QN *	M10x1.25
4632-12P *	4632-12PN *	M12x1
4632-12Q *	4632-12QN *	M12x1.25
4632-12R *	4632-12RN *	M12x1.5
4632-14P *	4632-14PN *	M14x1
4632-14Q *	4632-14QN *	M14x1.25
4632-14R *	4632-14RN *	M14x1.5
4632-16P *	4632-16PN *	M16x1
4632-16R *	4632-16RN *	M16x1.5
4632-18P *	4632-18PN *	M18x1
4632-18R *	4632-18RN *	M18x1.5
4632-20P *	4632-20PN *	M20x1
4632-20R *	4632-20RN *	M20x1.5

Code (GO)	Code (NOGO)	Size (mm)
4632-22R *	4632-22RN *	M22x1.5
4632-24P *	4632-24PN *	M24x1
4632-24R *	4632-24RN *	M24x1.5
4632-24T *	4632-24TN *	M24x2
4632-25R *	4632-25RN *	M25x1.5
4632-26R *	4632-26RN *	M26x1.5
4632-27R *	4632-27RN *	M27x1.5
4632-27T *	4632-27TN *	M27x2
4632-28R *	4632-28RN *	M28x1.5
4632-30P *	4632-30PN *	M30x1
4632-30R *	4632-30RN *	M30x1.5
4632-30T *	4632-30TN *	M30x2
4632-32R *	4632-32RN *	M32x1.5
4632-33R *	4632-33RN *	M33x1.5
4632-33T *	4632-33TN *	M33x2
4632-35R *	4632-35RN *	M35x1.5
4632-36R *	4632-36RN *	M36x1.5
4632-36T *	4632-36TN *	M36x2

Code (GO)	Code (NOGO)	Size (mm)
4632-38R *	4632-38RN *	M38x1.5
4632-40R *	4632-40RN *	M40x1.5
4632-40T *	4632-40TN *	M40x2
4632-42R *	4632-42RN *	M42x1.5
4632-42T *	4632-42TN *	M42x2
4632-45R *	4632-45RN *	M45x1.5
4632-45T *	4632-45TN *	M45x2
4632-48R *	4632-48RN *	M48x1.5
4632-48T *	4632-48TN *	M48x2
4632-50R *	4632-50RN *	M50x1.5
4632-50T *	4632-50TN *	M50x2
4632-52R *	4632-52RN *	M52x1.5
4632-52T *	4632-52TN *	M52x2
4632-55R *	4632-55RN *	M55x1.5
4632-55T *	4632-55TN *	M55x2
4632-58R *	4632-58RN *	M58x1.5
4632-60T *	4632-60TN *	M60x2

\* Supplied with manufacturer calibration certificate

## AMERICAN STANDARD THREAD PLUG GAGE



- Class 2B
- Standard ANSI B1.2
- Material: OHNS (Oil Hardened Non-shrinking Steel), stable dimension and wear resistance
- Hardness HRC60-62



4643-1B1

Code	Size
4643-41*	4-40UNC
4643-61*	6-32UNC
4643-81*	8-32UNC
4643-102*	10-32UNF
4643-1B1*	1/4-20UNC
4643-1B2*	1/4-28UNF

Code	Size
4643-5D1*	5/16-18UNC
4643-5D2*	5/16-24UNF
4643-3C1*	3/8-16UNC
4643-3C2*	3/8-24UNF
4643-7D2*	7/16-20UNF
4643-1A1*	1/2-13UNC

Code	Size
4643-1A2*	1/2-20UNF
4643-9D2*	9/16-18UNF
4643-5C1*	5/8-11UNC
4643-5C2*	5/8-18UNF
4643-3B1*	3/4-10UNC
4643-3B2*	3/4-16UNF

\* Supplied with manufacturer inspection certificate

## AMERICAN STANDARD THREAD RING GAGE



- Class 2A
- Standard ANSI B1.2
- Material: OHNS (Oil Hardened Non-shrinking Steel), stable dimension and wear resistance
- Hardness HRC60-62



4633-1B1



4633-1B1N

Code (GO)	Code (NOGO)	Size
4633-41*	4633-41N*	4-40UNC
4633-61*	4633-61N*	6-32UNC
4633-81*	4633-81N*	8-32UNC
4633-102*	4633-102N*	10-32UNF
4633-1B1*	4633-1B1N*	1/4-20UNC
4633-1B2*	4633-1B2N*	1/4-28UNF
4633-5D1*	4633-5D1N*	5/16-18UNC
4633-5D2*	4633-5D2N*	5/16-24UNF
4633-3C1*	4633-3C1N*	3/8-16UNC

Code (GO)	Code (NOGO)	Size
4633-3C2*	4633-3C2N*	3/8-24UNF
4633-7D2*	4633-7D2N*	7/16-20UNF
4633-1A1*	4633-1A1N*	1/2-13UNC
4633-1A2*	4633-1A2N*	1/2-20UNF
4633-9D2*	4633-9D2N*	9/16-18UNF
4633-5C1*	4633-5C1N*	5/8-11UNC
4633-5C2*	4633-5C2N*	5/8-18UNF
4633-3B1*	4633-3B1N*	3/4-10UNC
4633-3B2*	4633-3B2N*	3/4-16UNF

\* Supplied with manufacturer inspection certificate





## NPT THREAD PLUG GAGE



4644-1B18

- American tapered pipe thread for threads with sealant
- Standard ANSI / ASME B1.20.1
- Taper 1:16
- Material: OHNS (Oil Hardened Non-shrinking Steel), stable dimension and wear resistance
- Hardness HRC60-62

Code	Size
4644-1D27 *	1/16x27NPT
4644-1C27 *	1/8x27NPT
4644-1B18 *	1/4x18NPT
4644-3C18 *	3/8x18NPT
4644-1A14 *	1/2x14NPT

Code	Size
4644-3B14 *	3/4x14NPT
4644-112 *	1x11.5NPT
4644-1G12 *	1-1/4x11.5NPT
4644-1H12 *	1-1/2x11.5NPT
4644-212 *	2x11.5NPT

Code	Size
4644-1J8 *	2-1/2x8NPT
4644-38 *	3x8NPT
4644-1N8 *	3-1/2x8NPT
4644-48 *	4x8NPT


\* Supplied with manufacturer inspection certificate



## NPT THREAD RING GAGE



front



back

4634-3C18

- American tapered pipe thread for threads with sealant
- Standard ANSI / ASME B1.20.1
- Taper 1:16
- Material: OHNS (Oil Hardened Non-shrinking Steel), stable dimension and wear resistance
- Hardness HRC60-62

Code	Size
4634-1D27 *	1/16x27NPT
4634-1C27 *	1/8x27NPT
4634-1B18 *	1/4x18NPT
4634-3C18 *	3/8x18NPT
4634-1A14 *	1/2x14NPT

Code	Size
4634-3B14 *	3/4x14NPT
4634-112 *	1x11.5NPT
4634-1G12 *	1-1/4x11.5NPT
4634-1H12 *	1-1/2x11.5NPT
4634-212 *	2x11.5NPT

Code	Size
4634-1J8 *	2-1/2x8NPT
4634-38 *	3x8NPT
4634-1N8 *	3-1/2x8NPT
4634-48 *	4x8NPT

\* Supplied with manufacturer inspection certificate




## DIGITAL PROTRACTOR



2171-250

- Buttons: ON/OFF, HOLD (keep the reading), ZERO, ABS (absolute and incremental measurement)
- Fix the locking screw at 4 positions for different measuring ranges: 0°~225°, -225°~0°, -45°~180°, -180°~45°
- Remove the locking screw for 360° range
- With level vial
- Battery CR2032
- Automatic power off

Code	Size (L)	Range	Resolution	Accuracy
2171-250	250mm	0 - 360°	0.05°	±0.15°





## DIGITAL PROTRACTOR



2176-300

- Buttons: ON/OFF, ZERO
- With clamping screw to lock the blades
- Graduation of blade: 1mm and 1/32"
- CR2032 battery
- Automatic power off

Code	Size (L)	Range	Resolution	Accuracy
2176-200	200mm	0 - 360°	0.1°	±0.3°
2176-300	300mm	0 - 360°	0.1°	±0.3°




## PROTRACTOR




4780-85

- Made of stainless steel
- Satin chrome plated scale
- With clamping screw




Code	Size	Range	Graduation	Accuracy
4780-85	85x150mm	0 - 180°	1°	±0.3°

## PROTRACTOR




4781-85

- Made of stainless steel
- Satin chrome plated scale
- With clamping screw



4 working edges



Code	Size	Range	Graduation	Accuracy
4781-85	85x158mm	0 - 180°	1°	±0.3°


## PROTRACTOR



4799-180

- Made of stainless steel (4799-1300 is made of carbon steel)
- Satin chrome plated scale
- With clamping screw

Code	Size(AxB)	Range	Graduation	Accuracy	L	C
4799-180	80x120mm	0 - 180°	1°	±0.3°	168	11
4799-1120	120x150mm	0 - 180°	1°	±0.3°	220	14
4799-1150	150x200mm	0 - 180°	1°	±0.3°	285	16
4799-1200	200x300mm	0 - 180°	1°	±0.3°	413	20
4799-1300	300x500mm	0 - 180°	1°	±0.3°	675	30





## PROTRACTOR




4797-100

- Made of carbon steel
- Satin chrome plated
- With clamping screw
- The blade is moveable

Code	Size (AxB)	Range	Graduation	Accuracy	C
4797-100	100x150mm	10 - 170°	1°	±0.3°	18
4797-150	150x300mm	10 - 170°	1°	±0.3°	22
4797-200	200x400mm	10 - 170°	1°	±0.3°	24
4797-250	250x500mm	10 - 170°	1°	±0.3°	28
4797-300	300x600mm	10 - 170°	1°	±0.3°	32





# PROTRACTOR



2374-320

- Made of stainless steel
- Satin chrome plated scale

Code	Range	Graduation	Accuracy
2374-320	0-320°	2'	±2'



# UNIVERSAL PROTRACTOR



150mm blade (included)



2372-360


- Parallax-free reading
- Made of stainless steel
- Optional accessory: clamp (code 2372-CLAMP), suitable for height gages 1156 and 1351

Code	Range	Graduation	Accuracy
2372-360	0-360°	5'	±5'


clamp for height gages



2372-CLAMP



## DIAL PROTRACTOR




150mm blade (included)



2373-360

- Made of stainless steel
- Optional accessory: clamp (code 2372-CLAMP), suitable for height gages 1156 and 1351

Code	Range	Graduation	Accuracy
2373-360	0-360°	5'	±5'



clamp for height gages



2372-CLAMP

## DIGITAL PROTRACTOR



DATA  
OUTPUT



2172-360A


- Display in degree (for example 32.655°) and degree/minute/second (for example 32°39'30")
- SET button: preset the reading, change measuring direction
- MODE button: choose 0-90°, 0-180° or 0-360° display
- ZERO/ON/OFF button: zero and power on/off
- Battery CR2032, automatic power off
- Data output
- Supplied with square to set 90°
- Made of stainless steel
- Optional accessory: data output cable (code 7305-SPC1A)

Code	Range	Resolution	Accuracy
2172-360A	0-360°	10"/0.005°	±5'




150mm blade (included)

square (included)




# COMBINATION SQUARE SET

Unit: mm



2278-180



## Code


2278-180

- Center head:  
To locate center of cylinder with diameter ( $\varnothing$ d): 30 - 100mm  
Accuracy:  $\pm 0.15$ mm
- Protractor head:  
To set the blade at desired angle to an edge of a workpiece, and can be used to measure angles  
Range: 0-180°  
Accuracy:  $\pm 7$ min.
- Square head:  
To set the blade at 90° or 45° to an edge of a workpiece  
Accuracy:  $\pm 8$ min for 90° square,  $\pm 10$ min for 45° square
- Blade:  
Range: 300mm/12",  
Graduation: 0.5mm and 1/32" on front face, 1mm and 1/64" on back face
- Optional accessory: rigid rule (code 7113)

## GRANITE SQUARE



4141-250




Code	Size (HxW)	Flatness of A	Flatness of B	Squareness of A to B	D
4141-250	250x160mm	1 $\mu$ m	1 $\mu$ m	2 $\mu$ m	25mm
4141-400	400x250mm	1.5 $\mu$ m	1 $\mu$ m	3 $\mu$ m	40mm
4141-630	630x400mm	2 $\mu$ m	1.5 $\mu$ m	4 $\mu$ m	63mm

## GRANITE SQUARE



4144-315



Code	Size (HxW)	Flatness of A, B, C and D	Squareness and parallelism between A, B, C and D
4144-315	315x315mm	1.1 $\mu$ m	2.6 $\mu$ m







## CYLINDER SQUARE



4710-200



inspect 90° internal and external angles



Code	Length(L)	Squareness
4710-200 *	200mm	1 $\mu$ m
4710-300 *	300mm	2 $\mu$ m

- Made of special alloy steel, hardness HRC58~60
- The handle can be removed


\* Supplied with manufacturer inspection certificate

## PERPENDICULARITY TESTER



4770-300

dial test indicator is not included




Code	Range(H)	Perpendicularity( $\alpha$ )	Side perpendicularity( $\beta$ )	L
4770-300	0-300mm	3 $\mu$ m	10 $\mu$ m	460mm
4770-600	0-600mm	5 $\mu$ m	20 $\mu$ m	760mm

- Optional accessory:  
dial test indicators (graduation: 1 $\mu$ m or 2 $\mu$ m),  
cylinder square (code 4710, for calibration),  
granite square (code 4141, for calibration)

## 90° TOOL MAKER SQUARE



4794-040



(mm)

Code	Size (LxW)	Squareness		C	D	H
		Inside ( $\alpha$ )	Outside ( $\beta$ )			
4794-025	25x20mm	2.2 $\mu$ m	2.3 $\mu$ m	4	6.5	3.5
4794-040	40x28mm	2.3 $\mu$ m	2.4 $\mu$ m	5.5	8.5	3.5

- DIN875 grade 00
- Beveled edge for inside measurement
- Made of hardened stainless steel

## 90° BEVELED EDGE SQUARE

- Satin chrome plating
- Beveled edges for inside and outside measurement
- Made of hardened stainless steel

DIN875 grade 00 (mm)


Code	Size (LxW)	Squareness		C	D	H
		Inside ( $\alpha$ )	Outside ( $\beta$ )			
4790-050	50x40mm	2.4 $\mu$ m	2.5 $\mu$ m	13	13	4
4790-075	75x50mm	2.6 $\mu$ m	2.8 $\mu$ m	15	15	4
4790-0100	100x70mm	2.8 $\mu$ m	3.0 $\mu$ m	20	20	5
4790-0150	150x100mm	3.2 $\mu$ m	3.5 $\mu$ m	30	30	6
4790-0200	200x130mm	3.7 $\mu$ m	4.0 $\mu$ m	34	34	7
4790-0250	250x165mm	4.2 $\mu$ m	4.5 $\mu$ m	35	35	7
4790-0300	300x200mm	4.6 $\mu$ m	5.0 $\mu$ m	40	40	8

DIN875 grade 0 (mm)

Code	Size (LxW)	Squareness		C	D	H
		Inside ( $\alpha$ )	Outside ( $\beta$ )			
4790-500	50x40mm	6 $\mu$ m	6 $\mu$ m	13	13	4
4790-750	75x50mm	6 $\mu$ m	7 $\mu$ m	15	15	4
4790-1000	100x70mm	7 $\mu$ m	7 $\mu$ m	20	20	5
4790-1500	150x100mm	7 $\mu$ m	8 $\mu$ m	30	30	6
4790-2000	200x130mm	8 $\mu$ m	9 $\mu$ m	34	34	7
4790-2500	250x165mm	9 $\mu$ m	10 $\mu$ m	35	35	7
4790-3000	300x200mm	10 $\mu$ m	11 $\mu$ m	40	40	8




4790-0100





4791-100

## 90° FLAT EDGE SQUARE




Code	Size (LxW)	Squareness		C	D	H
		Inside ( $\alpha$ )	Outside ( $\beta$ )			
4791-50	50x40mm	6 $\mu$ m	6 $\mu$ m	13	13	4
4791-75	75x50mm	6 $\mu$ m	7 $\mu$ m	15	15	4
4791-100	100x70mm	7 $\mu$ m	7 $\mu$ m	20	20	5
4791-150	150x100mm	7 $\mu$ m	8 $\mu$ m	30	30	6
4791-200	200x130mm	8 $\mu$ m	9 $\mu$ m	30	30	7
4791-250	250x165mm	9 $\mu$ m	10 $\mu$ m	35	35	7
4791-300	300x200mm	10 $\mu$ m	11 $\mu$ m	40	40	8

- DIN875 grade 0
- Made of hardened stainless steel



4793-100

## 90° FLAT EDGE SQUARE WITH WIDE BASE



Code	Size (LxW)	Squareness		C	D	H	E
		Inside ( $\alpha$ )	Outside ( $\beta$ )				
4793-50	50x40mm	6 $\mu$ m	6 $\mu$ m	13	13	4	13
4793-75	75x50mm	6 $\mu$ m	7 $\mu$ m	15	15	4	15
4793-100	100x70mm	7 $\mu$ m	7 $\mu$ m	20	20	5	20
4793-150	150x100mm	7 $\mu$ m	8 $\mu$ m	30	30	6	30
4793-200	200x130mm	8 $\mu$ m	9 $\mu$ m	30	30	7	30
4793-250	250x165mm	9 $\mu$ m	10 $\mu$ m	35	35	7	35
4793-300	300x200mm	10 $\mu$ m	11 $\mu$ m	40	40	8	40

- DIN875 grade 0
- Made of hardened stainless steel



## 90° FLAT EDGE SQUARE WITH WIDE BASE



4792-100


(mm)

Code	Size (LxW)	Squareness		C	D	H	E
		Inside ( $\alpha$ )	Outside ( $\beta$ )				
4792-50	50x40mm	6 $\mu$ m	6 $\mu$ m	12	12	3	10
4792-75	75x50mm	6 $\mu$ m	7 $\mu$ m	14	14	3	10
4792-100	100x70mm	7 $\mu$ m	7 $\mu$ m	18	18	3	10
4792-150	150x100mm	8 $\mu$ m	8 $\mu$ m	22	22	4	12
4792-200	200x130mm	9 $\mu$ m	9 $\mu$ m	25	25	4	12



- DIN875 grade 0
- Made of hardened stainless steel


## 90° BEVELED EDGE SQUARE WITH WIDE BASE



4795-100

(mm)

Code	Size (LxW)	Squareness		C	D	H	E
		Inside ( $\alpha$ )	Outside ( $\beta$ )				
4795-50	50x40mm	6 $\mu$ m	6 $\mu$ m	12	12	3	10
4795-75	75x50mm	6 $\mu$ m	7 $\mu$ m	14	14	3	10
4795-100	100x70mm	7 $\mu$ m	7 $\mu$ m	18	18	3	10
4795-150	150x100mm	8 $\mu$ m	8 $\mu$ m	22	22	4	12
4795-200	200x130mm	9 $\mu$ m	9 $\mu$ m	25	25	4	12



- DIN875 grade 0
- Beveled edges for inside and outside measurement
- Made of hardened stainless steel


**ATTENTION:  
LOW ACCURACY**

## MACHINIST SQUARE WITH WIDE BASE

- Economic model
- DIN875 grade 2
- Made of carbon steel, no anti-rust treatment, not hardend

(mm)

Code	Size (LxW)	Squareness		C	D	H	E
		Inside ( $\alpha$ )	Outside ( $\beta$ )				
4707-50	50x40mm	24 $\mu$ m	25 $\mu$ m	16	12	3	9
4707-75	75x50mm	26 $\mu$ m	28 $\mu$ m	16	16	3	9
4707-100	100x70mm	28 $\mu$ m	30 $\mu$ m	19	19	3	12
4707-150	150x100mm	33 $\mu$ m	35 $\mu$ m	25	25	3	16
4707-200	200x130mm	37 $\mu$ m	40 $\mu$ m	30	32	4	16
4707-250	250x165mm	42 $\mu$ m	45 $\mu$ m	30	32	4	19
4707-300	300x200mm	47 $\mu$ m	50 $\mu$ m	32	32	4	19
4707-400	400x250mm	56 $\mu$ m	60 $\mu$ m	38	38	5	22
4707-500	500x300mm	65 $\mu$ m	70 $\mu$ m	45	50	6	25
4707-600	600x350mm	75 $\mu$ m	80 $\mu$ m	50	50	6	30
4707-750	750x400mm	90 $\mu$ m	95 $\mu$ m	55	55	6	50
4707-900	900x500mm	103 $\mu$ m	110 $\mu$ m	65	75	9	50
4707-1000	1000x550mm	113 $\mu$ m	120 $\mu$ m	65	75	9	50






## ADJUSTABLE SQUARE

Unit: mm



4701-1

- The straight edge can move and can be locked by the clamping screw
- Made of hardened stainless steel




Code	Squareness (a, b, c, d)
4701-1	7 $\mu$ m

## 45° SQUARE



4745-1100



Code	Size (LxW)	Accuracy		C	D	H
		Inside ( $\alpha$ )	Outside ( $\beta$ )			
4745-1100	100x70mm	27 $\mu$ m	30 $\mu$ m	20	20	5
4745-1120	120x80mm	29 $\mu$ m	32 $\mu$ m	20	20	5
4745-1150	150x100mm	32 $\mu$ m	35 $\mu$ m	20	20	5
4745-1200	200x130mm	36 $\mu$ m	40 $\mu$ m	25	25	5


(mm)

- Made of hardened stainless steel

## 45° SQUARE WITH WIDE BASE



4747-100



Code	Size (LxW)	Accuracy		C	D	H	E
		Inside ( $\alpha$ )	Outside ( $\beta$ )				
4747-100	100x70mm	27 $\mu$ m	31 $\mu$ m	20	20	5	20
4747-120	120x80mm	29 $\mu$ m	33 $\mu$ m	20	20	5	20
4747-150	150x100mm	32 $\mu$ m	36 $\mu$ m	20	20	5	20
4747-200	200x130mm	36 $\mu$ m	41 $\mu$ m	25	25	5	25


(mm)

- Made of hardened stainless steel



4760-1100

## 60° SQUARE



(mm)


Code	Size (LxW)	Accuracy		C	D	H
		Inside ( $\alpha$ )	Outside ( $\beta$ )			
4760-1100	100x70mm	28 $\mu$ m	30 $\mu$ m	20	20	5
4760-1120	120x80mm	30 $\mu$ m	32 $\mu$ m	20	20	5
4760-1150	150x100mm	32 $\mu$ m	35 $\mu$ m	20	20	5
4760-1200	200x130mm	37 $\mu$ m	40 $\mu$ m	25	25	5

- Made of hardened stainless steel



4762-100

## 60° SQUARE WITH WIDE BASE



(mm)


Code	Size (LxW)	Accuracy		C	D	H	E
		Inside ( $\alpha$ )	Outside ( $\beta$ )				
4762-100	100x70mm	28 $\mu$ m	31 $\mu$ m	20	20	5	20
4762-120	120x80mm	30 $\mu$ m	33 $\mu$ m	20	20	5	20
4762-150	150x100mm	33 $\mu$ m	36 $\mu$ m	20	20	5	20
4762-200	200x130mm	37 $\mu$ m	41 $\mu$ m	25	25	5	25

- Made of hardened stainless steel

## 120° SQUARE



4706-1100



(mm)


Code	Size (LxW)	Accuracy		C	D	H
		Inside ( $\alpha$ )	Outside ( $\beta$ )			
4706-150	50x50mm	24 $\mu$ m	25 $\mu$ m	15	15	5
4706-175	75x75mm	26 $\mu$ m	28 $\mu$ m	20	20	5
4706-1100	100x100mm	29 $\mu$ m	30 $\mu$ m	20	20	5
4706-1150	150x150mm	34 $\mu$ m	35 $\mu$ m	25	25	5
4706-1200	200x200mm	38 $\mu$ m	40 $\mu$ m	30	30	7

- Made of hardened stainless steel

## 135° SQUARE WITH WIDE BASE



4754-3120



(mm)

Code	Size (LxW)	Accuracy		C	D	H	E
		Inside ( $\alpha$ )	Outside ( $\beta$ )				
4754-3100	100x70mm	29 $\mu$ m	31 $\mu$ m	20	20	5	20
4754-3120	120x80mm	31 $\mu$ m	33 $\mu$ m	20	20	5	20
4754-3150	150x100mm	34 $\mu$ m	36 $\mu$ m	20	20	5	20
4754-3200	200x130mm	39 $\mu$ m	41 $\mu$ m	30	30	7	30
4754-3250	250x165mm	44 $\mu$ m	46 $\mu$ m	30	30	7	30
4754-3300	300x175mm	49 $\mu$ m	51 $\mu$ m	35	35	7	35

- Made of hardened stainless steel




## STRAIGHT EDGE

- DIN874
- Beveled edge
- Made of hardened stainless steel
- Satin chrome plating

(mm)				
Code	Size (L)	Straightness	W	H
4700-50	50mm	2.2µm	5	20
4700-75	75mm	2.3µm	5	25
4700-100	100mm	2.4µm	5	25
4700-125	125mm	2.5µm	5	25
4700-150	150mm	2.6µm	6	30
4700-200	200mm	2.8µm	6	30
4700-250	250mm	3.0µm	8	40
4700-300	300mm	3.2µm	8	40
4700-400	400mm	3.6µm	10	50
4700-500	500mm	4.0µm	10	50



4700-100





## SQUARE SET



4702-1

- Includes:
  - 90° tool maker square 25x20mm DIN875 grade 00 (code **4794-025**)
  - 90° tool maker square 40x28mm DIN875 grade 00 (code **4794-040**)
  - 90° beveled edge square 75x50mm DIN875 grade 00 (code **4790-075**)
  - straight edge 100mm DIN874 (code **4700-100**)
  - scriber
- Made of hardened stainless steel




Code

4702-1

## GRANITE STRAIGHT EDGE



4147-500A




Code	Length (L)	Flatness of A and B	Parallelism between A and B	D	H
4147-500A	500mm	2.1 $\mu$ m	3.2 $\mu$ m	50mm	80mm
4147-1000A	1000mm	3 $\mu$ m	4.5 $\mu$ m	60mm	120mm

## MAGNALIUM STRAIGHT EDGE



4180-500

- Made of magnalium, light weight, non-deform, no rusty




Code	Length (L)	Flatness of top and bottom	Parallelism between top and bottom	H	W	D
4180-500	500mm	3 $\mu$ m	4 $\mu$ m	60mm	30mm	5mm
4180-1000	1000mm	5 $\mu$ m	8 $\mu$ m	60mm	30mm	5mm
4180-1500	1500mm	15 $\mu$ m	22 $\mu$ m	100mm	40mm	5mm
4180-2000	2000mm	18 $\mu$ m	27 $\mu$ m	100mm	40mm	8mm

## PRECISION STRAIGHT EDGE



7117-300



- Check flatness, straightness and for marking
- Made of tool steel
- Hardness HRC58



(mm)

Code	Range(L)	Straightness and parallelism of A and B	Straightness and parallelism of C and D	W	H
7117-300	305	0.005	0.05	41	6.3
7117-600	610	0.006	0.06	51	7.9
7117-900	914	0.007	0.06	64	9.5

## PRECISION STRAIGHT EDGE WITH BEVELED EDGE



7118-300




- Check flatness, straightness and for marking
- Made of tool steel
- Hardness HRC58

(mm)

Code	Range (L)	Straightness and parallelism of A and B	Straightness and parallelism of C and D	W	H
7118-300	305	0.005	0.05	41	6.5
7118-600	610	0.006	0.06	51	8
7118-900	914	0.007	0.06	64	10

## FEELER GAGE




4601-25

- Made of hardened alloy steel
- Meet DIN2275
- Accuracy:  $\pm(3+T/80)$   $\mu\text{m}$ , 'T' is the thickness of leaves in  $\mu\text{m}$

Code	Range	Thickness of leaves included (mm)	Quantity of leaves
4601-25	0.04 - 1.00mm	0.04, 0.05, 0.06, 0.07, 0.08, 0.09, 0.10, 0.15, 0.20, 0.25, 0.30, 0.35, 0.40, 0.45, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 0.95, 1.00	25

## FEELER GAGE



4602-20


- Made of hardened alloy steel
- Meet DIN2275
- Accuracy:  $\pm(3+T/80)$   $\mu\text{m}$ , 'T' is the thickness of leaves in  $\mu\text{m}$

Code	Range	Thickness of leaves included (mm)	Quantity of leaves
4602-13A	0.03 - 0.50mm	0.03, 0.04, 0.05, 0.06, 0.07, 0.08, 0.09, 0.10, 0.15, 0.20, 0.30, 0.40, 0.50	13
4602-13	0.05 - 1.00mm	0.05, 0.10, 0.15, 0.20, 0.25, 0.30, 0.40, 0.50, 0.60, 0.70, 0.80, 0.90, 1.00	13
4602-17	0.02 - 1.00mm	0.02, 0.03, 0.04, 0.05, 0.06, 0.07, 0.08, 0.09, 0.10, 0.15, 0.20, 0.25, 0.30, 0.40, 0.50, 0.75, 1.00	17
4602-20	0.05 - 1.00mm	0.05, 0.10, 0.15, 0.20, 0.25, 0.30, 0.35, 0.40, 0.45, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 0.95, 1.00	20
4602-28	0.05 - 1.00mm	0.05, 0.06, 0.07, 0.08, 0.09, 0.10, 0.11, 0.12, 0.13, 0.14, 0.15, 0.20, 0.25, 0.30, 0.35, 0.40, 0.45, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 0.95, 1.00	28
4602-32	0.03 - 1.00mm	0.03, 0.04, 0.05, 0.06, 0.07, 0.08, 0.09, 0.10, 0.13, 0.15, 0.18, 0.20, 0.23, 0.25, 0.28, 0.30, 0.33, 0.35, 0.38, 0.40, 0.45, 0.50, 0.55, 0.60, 0.63, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 1.00	32

## LONG FEELER GAGE



4605-20



Unit: mm

- Made of hardened alloy steel
- Meet DIN2275
- Accuracy:  $\pm(3+T/80)$   $\mu\text{m}$ , 'T' is the thickness of leaves in  $\mu\text{m}$


(mm)

Code	Range	Thickness of leaves included (mm)	Quantity of leaves	L	A	B
4605-13	0.05 - 1.00mm	0.05, 0.10, 0.15, 0.20, 0.25, 0.30, 0.40, 0.50, 0.60, 0.70, 0.80, 0.90, 1.00	13	150	135	295
4605-131	0.05 - 1.00mm		13	200	185	395
4605-132	0.05 - 1.00mm		13	300	285	590
4605-20	0.05 - 1.00mm	0.05, 0.10, 0.15, 0.20, 0.25, 0.30, 0.35, 0.40, 0.45, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 0.95, 1.00	20	150	135	295
4605-201	0.05 - 1.00mm		20	200	185	395
4605-202	0.05 - 1.00mm		20	300	285	590




4622-10

Unit: mm



## FEELER GAGE STOCK



- Used as shims to accurately set spacing
- Made of hardened alloy steel
- Length 300mm
- Width 13mm
- 10pcs/set

Code	Thickness (T)	Accuracy
4622-02	0.02mm	$\pm 3\mu\text{m}$
4622-03	0.03mm	$\pm 3\mu\text{m}$
4622-04	0.04mm	$\pm 3\mu\text{m}$
4622-05	0.05mm	$\pm 3\mu\text{m}$
4622-06	0.06mm	$\pm 3\mu\text{m}$
4622-07	0.07mm	$\pm 4\mu\text{m}$
4622-08	0.08mm	$\pm 4\mu\text{m}$
4622-09	0.09mm	$\pm 4\mu\text{m}$
4622-10	0.10mm	$\pm 4\mu\text{m}$
4622-12	0.12mm	$\pm 5\mu\text{m}$


Code	Thickness (T)	Accuracy
4622-15	0.15mm	$\pm 5\mu\text{m}$
4622-18	0.18mm	$\pm 6\mu\text{m}$
4622-20	0.20mm	$\pm 6\mu\text{m}$
4622-25	0.25mm	$\pm 6\mu\text{m}$
4622-30	0.30mm	$\pm 7\mu\text{m}$
4622-35	0.35mm	$\pm 7\mu\text{m}$
4622-40	0.40mm	$\pm 8\mu\text{m}$
4622-45	0.45mm	$\pm 8\mu\text{m}$
4622-50	0.50mm	$\pm 9\mu\text{m}$
4622-55	0.55mm	$\pm 9\mu\text{m}$

Code	Thickness (T)	Accuracy
4622-60	0.60mm	$\pm 9\mu\text{m}$
4622-65	0.65mm	$\pm 9\mu\text{m}$
4622-70	0.70mm	$\pm 12\mu\text{m}$
4622-75	0.75mm	$\pm 12\mu\text{m}$
4622-80	0.80mm	$\pm 13\mu\text{m}$
4622-85	0.85mm	$\pm 13\mu\text{m}$
4622-90	0.90mm	$\pm 14\mu\text{m}$
4622-95	0.95mm	$\pm 14\mu\text{m}$
4622-100	1.00mm	$\pm 16\mu\text{m}$

## FEELER GAGE TAPE



Unit: mm




- Used as shims to accurately set spacing
- Made of hardened alloy steel
- Length 5m
- Width 13mm

Code	Thickness (T)	Accuracy
4621-02	0.02mm	±4µm
4621-03	0.03mm	±4µm
4621-04	0.04mm	±4µm
4621-05	0.05mm	±4µm
4621-06	0.06mm	±4µm
4621-07	0.07mm	±5µm
4621-08	0.08mm	±5µm
4621-09	0.09mm	±5µm
4621-10	0.10mm	±5µm
4621-12	0.12mm	±5µm
4621-15	0.15mm	±6µm
4621-18	0.18mm	±7µm
4621-20	0.20mm	±8µm
4621-25	0.25mm	±9µm
4621-30	0.30mm	±9µm

Code	Thickness (T)	Accuracy
4621-35	0.35mm	±11µm
4621-40	0.40mm	±12µm
4621-45	0.45mm	±12µm
4621-50	0.50mm	±14µm
4621-55	0.55mm	±14µm
4621-60	0.60mm	±14µm
4621-65	0.65mm	±14µm
4621-70	0.70mm	±17µm
4621-75	0.75mm	±17µm
4621-80	0.80mm	±19µm
4621-85	0.85mm	±19µm
4621-90	0.90mm	±22µm
4621-95	0.95mm	±22µm
4621-100	1.00mm	±24µm

## PITCH GAGE




- Check the pitch of screw thread
- Accuracy: ±0.07mm

4824-12

Code	Range	Thread type	Pitch of leaves included	Quantity of leaves
4824-12	2-20mm	Tr 30°	2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 16, 20mm	12
4824-16	1-12TPI	ACME 29°	1, 1-1/3, 1-1/2, 1-3/4, 2, 2-1/2, 3, 3-1/2, 4, 5, 6, 7, 8, 9, 10, 12TPI	16

# PITCH GAGE



- Check the pitch of screw thread
- Accuracy:  $\pm 0.07\text{mm}$

**4820-122**

## Metric 60° screw

Code	Range	Pitch of leaves included	Quantity of leaves
4820-122	0.4-7.0mm	0.4, 0.5, 0.6, 0.7, 0.75, 0.8, 0.9, 1, 1.25, 1.5, 1.75, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6, 6.5, 7mm	22
4820-124	0.25-7.0mm	0.25, 0.3, 0.35, 0.4, 0.5, 0.7, 0.75, 0.8, 0.9, 1, 1.25, 1.5, 1.75, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6, 6.5, 7mm	24
4820-1241	0.25-6.0mm	0.25, 0.3, 0.35, 0.4, 0.45, 0.5, 0.6, 0.7, 0.75, 0.8, 0.9, 1, 1.25, 1.5, 1.75, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6mm	24

## Unified 60° screw

Code	Range	Pitch of leaves included	Quantity of leaves
4820-230	4-42TPI	4, 4-1/2, 5, 5-1/2, 6, 7, 8, 9, 10, 11, 11-1/2, 12, 13, 14, 15, 16, 18, 20, 22, 24, 26, 27, 28, 30, 32, 34, 36, 38, 40, 42TPI	30

## Whitworth 55° screw

Code	Range	Pitch of leaves included	Quantity of leaves
4820-330	4-42TPI	4, 4-1/2, 5, 5-1/2, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 18, 19, 20, 22, 24, 26, 27, 28, 30, 32, 34, 36, 38, 40, 42TPI	30
4820-328	4-62TPI	4, 4-1/2, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 16, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32, 36, 40, 48, 60, 62TPI	28


## Metric 60° and Whitworth 55° screw

Code	Range	Pitch of leaves included	Quantity of leaves
4820-452	0.25-6.0mm	0.25, 0.3, 0.35, 0.4, 0.45, 0.5, 0.6, 0.7, 0.75, 0.8, 0.9, 1, 1.25, 1.5, 1.75, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6mm	52
	4-62TPI	4, 4-1/2, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 16, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32, 36, 40, 48, 60, 62TPI	
4820-450	0.4-7.0mm	0.4, 0.5, 0.6, 0.7, 0.75, 0.8, 0.9, 1, 1.25, 1.5, 1.75, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6, 6.5, 7mm	50
	4-62TPI	4, 4-1/2, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 16, 18, 19, 20, 22, 24, 25, 26, 28, 30, 32, 36, 40, 48, 60, 62TPI	



## Metric 60° and Unified 60° screw

Code	Range	Pitch of leaves included	Quantity of leaves
4820-552	0.4-7.0mm	0.4, 0.5, 0.6, 0.7, 0.75, 0.8, 0.9, 1, 1.25, 1.5, 1.75, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6, 6.5, 7mm	52
	4-42TPI	4, 4-1/2, 5, 5-1/2, 6, 7, 8, 9, 10, 11, 11-1/2, 12, 13, 14, 15, 16, 18, 20, 22, 24, 26, 27, 28, 30, 32, 34, 36, 38, 40, 42TPI	

## CENTER GAGE



4810-602





- To check and set screw cutting tools, and check the angle and pitch of screw thread
- Angle accuracy:  $\pm 30\text{min}$ .

Code	Thread type	Angle ( $\alpha$ )	Graduation
4810-601	METRIC 60°	60°	0.5mm and 1mm
4810-602	UNIFIED 60°	60°	14ths and 20ths on front side, 24ths and 32ths on back side
4810-55	WHITWORTH 55°	55°	14ths and 20ths on front side, 24ths and 32ths on back side

## THREAD GAGE



4812-E



- To check and set screw cutting tools
- Angle accuracy:  $\pm 10\text{min}$ .


Code	Range	Thread type	Pitch
4812-12	2-12mm	Tr 30°	2, 3, 4, 5, 6, 7, 8, 9, 10, 12mm
4812-E	1-10TPI	ACME 29°	1, 1-1/3, 1-1/2, 1-3/4, 2, 2-1/2, 3, 4, 5, 6, 7, 8, 9, 10TPI



## ANGLE GAGE



4806-20



Code	Range	Angle of leaves included	Quantity of leaves	Accuracy
4806-20	1°-45°	1°, 2°, 3°, 4°, 5°, 6°, 7°, 8°, 9°, 10°, 12°, 14°, 16°, 18°, 20°, 25°, 30°, 35°, 40°, 45°	20	±30'

## ANGLE GAGE SET


- Each blade checks primary, 1/2 primary and complementary angles

Code	Quantity of leaves	Accuracy
4807	18	±10'

Primary angle	1/2 primary angle	Complementary angle	Type
5°	2°30'	175°	A
10°	5°	170°	A
15°	7°30'	165°	A
20°	10°	160°	B
25°	12°30'	155°	B
30°	15°	150°	B
35°	17°30'	145°	B
40°	20°	140°	B
45°	22°30'	135°	B
50°	25°	130°	B
55°	27°30'	125°	B
60°	30°	120°	B
65°	32°30'	115°	B
70°	35°	110°	B
75°	37°30'	105°	B
80°	40°	100°	B
85°	42°30'	95°	B
90°	45°	90°	B




4807



Angle 1, 2 are primary angle  
Angle 3 is complementary angle  
Angle 4, 5 are 1/2 primary angle


type A



Angle 1, 2, 3, 4 are primary angle  
Angle 5, 6 are complementary angle  
Angle 7, 8 are 1/2 primary angle

type B


## RADIUS GAGE



4801-17

Code	Range	Radius of leaves included (mm)	Quantity of leaves (internal + external)	Accuracy
4801-17	1-7mm	1, 1.25, 1.5, 1.75, 2, 2.25, 2.5, 2.75, 3, 3.5, 4, 4.5, 5, 5.5, 6, 6.5, 7	17+17	±0.03mm
4801-16	7.5-15mm	7.5, 8, 8.5, 9, 9.5, 10, 10.5, 11, 11.5, 12, 12.5, 13, 13.5, 14, 14.5, 15	16+16	±0.035mm
4801-15	15.5-25mm	15.5, 16, 16.5, 17, 17.5, 18, 18.5, 19, 19.5, 20, 21, 22, 23, 24, 25	15+15	±0.042mm

## RADIUS GAGE SET



- Each piece has 3 concave and 2 convex gauging surfaces
- Supplied with handle




4804-26

Code	Range	Radius of leaves included (mm)	Quantity of leaves	Accuracy
4804-26	0.5-13mm	0.5, 1, 1.5, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6, 6.5, 7, 7.5, 8, 8.5, 9, 9.5, 10, 10.5, 11, 11.5, 12, 12.5, 13	26	±0.05mm

## CHAMFER GAGE





4844-1



- To measure internal and external chamfers
- Made of stainless steel

Code	Graduation	Accuracy
4844-1	0.5mm	±0.25mm




## CHAMFER GAGE




1267-6

measure 45° chamfer dimension




- Measure 45° chamfer dimension
- Graduation 0.02mm
- Made of stainless steel
- Satin chrome plated reading surface


Code	Range	Accuracy
1267-6	0-6mm	±0.06mm



## TAPER GAGE




4630-1




- For quick measurement of gap width
- Stain chrome plated reading surface
- Made of stainless steel



Code	Range	Graduation	Accuracy	L	a	b
4630-3	0.4 - 6mm	0.05mm	±0.04mm	164	12.5	6.5
4630-1	0.5 - 10mm	0.05mm	±0.07mm	220	10	10.5
4630-2	0.5 - 15mm	0.1mm	±0.08mm	184	12.5	16.5



## TAPER GAGE



4833-2




- Measure opening, slot width, hole size, etc.
- Made of stainless steel

Code	Range	Graduation	Accuracy	L	W
4833-1	0.8 - 15mm (1/32" - 5/8")	0.1mm (1/64")	±0.1mm (0.004")	146	17
4833-2	15 - 30mm (5/8" - 1-3/16")	0.1mm (1/64")	±0.1mm (0.004")	159	30.4
4833-3	30 - 45mm (1-3/16" - 1-3/4")	0.1mm (1/64")	±0.1mm (0.004")	166	45.4
4833-4	45 - 60mm (1-13/16" - 2-3/8")	0.1mm (1/64")	±0.1mm (0.004")	170	60.5

# TAPER GAGE SET



- Include 4pcs (1-8mm, 8-15mm, 15-22mm, 22-29mm)
- Measure opening, slot width, hole size, etc.
- Made of stainless steel




4837-1

Code	Range	Graduation	Accuracy
4837-1	1 - 29mm	0.05mm	±0.05mm

# WELDING GAGE



4830




Code	Measurement	Range	Graduation	Accuracy
4830	crown height	0 - 8mm	0.1mm	±0.1mm
	fillet weld throat size	0 - 20mm	0.1mm	±0.3mm
	angle	60°, 70°, 80°, 90°	—	±1°


- Made of stainless steel
- Stain chrome plated reading surface

# DIGITAL WELDING GAGE

ATTENTION:  
NO DATA OUTPUT



4831-20A




Code	Measurement	Range	Resolution	Accuracy
4831-20A	crown height	0 - 7mm	0.01mm/0.0005"	±0.03mm
	fillet weld throat size	0 - 20mm	0.01mm/0.0005"	±0.1mm
	angle	60°, 70°, 80°, 90°	—	±1°

- Buttons: zero, mm/inch, on/off
- Battery LR44
- Made of stainless steel

# FILLET WELDING GAGE





4832-1



- Made of stainless steel
- Sizes marked on both faces

Code	Throat size (mm)	Leg length (mm)	Accuracy
4832-1	4, 5, 6, 7, 8, 9, 10, 12	4, 6, 7.5, 10, 12, 14, 16, 18	±0.5mm




## FILLET WELDING GAGE



4836-1




4836-2



- Measure concave and convex weld sizes
- 7 blades are included
- Made of stainless steel


Code	Size	Accuracy
4836-1	3mm, 4mm, 5mm, 6mm, 8mm, 9mm, 10mm, 11mm, 12mm, 14mm, 16mm, 19mm, 22mm, 25mm	±0.5mm
4836-2	1/8" (3.2mm), 3/16" (4.8mm), 1/4" (6.4mm), 5/16" (7.9mm), 3/8" (9.5mm), 7/16" (11.1mm), 1/2" (12.7mm), 5/8" (15.9mm), 3/4" (19.1mm), 7/8" (22.2mm), 1" (25.4mm)	±0.02" (0.5mm)



## WELDING GAGE




4834-1



- Pointer can be locked for later reference
- Made of stainless steel

Code	Measurement	Range	Graduation	Accuracy
4834-1	undercut depth	0-6mm	0.5mm	±0.5mm
	crown height	0-6mm	0.5mm	±0.5mm
	porosity size comparison	1.5mm, 3mm	—	±0.2mm
	amount of porosity per 25mm	25mm	1mm	—




# WELDING GAGE



front


4838-1

back



■ Made of stainless steel

Code	Measurement	Range	Graduation	Accuracy
4838-1	crown height	0 - 10mm	1mm	±0.5mm
	leg height	0 - 14mm	1mm	±0.5mm
	undercut depth	0 - 5mm	0.05mm	±0.05mm
	throat size	0 - 13mm	1mm	±0.5mm
	weld length	0 - 40mm	1mm	±1mm
	angle	90° - 150°	5°	±1°
	gap	0.5 - 5mm	1mm	±0.5mm
	length	0 - 40mm	1mm	±0.5mm






# WELDING GAGE




front




back

4835-1




- Adjustable scale to compensate pointer wear
- Made of stainless steel



Code	Measurement	Range	Graduation	Accuracy
4835-1	crown height	0 - 25mm (0 - 1")	1mm (1/16")	±0.5mm
	fillet weld leg height	0 - 25mm (0 - 1")	1mm (1/16")	±0.5mm
	misalignment (high-low)	0 - 25mm (0 - 1")	1mm (1/16")	±0.5mm
	undercut depth	0 - 2mm (0 - 1/8")	1mm (1/16")	±0.5mm
	fillet weld throat size	0 - 20mm (0 - 3/4")	1mm (1/16")	±0.5mm
	angle of preparation	0 - 60°	5°	±1°
	length	0 - 60mm (0-2")	1mm (1/16")	±0.5mm
	45° angle	—	—	±1°



## WELDING GAGE




4840-1




- Made of stainless steel

Code	Graduation	Accuracy
4840-1	0.2mm	±0.3mm

## PIPE WELDING GAGE




fit-up gap



internal misalignment


- Made of stainless steel

Code	Measurement	Range	Graduation	Accuracy
4841-1	internal misalignment	0-30mm	1mm	±0.5mm
	fit-up gap	0.7-4mm	0.1mm	±0.1mm




4841-1

# PIPE WELDING GAGE



4839-1



■ Made of stainless steel



Code	Measurement	Range	Graduation	Accuracy
4839-1	bevel on end preparation	37.5°	—	±1°
	pipe wall thickness	0-45mm (0-1-3/4")	1mm (1/16")	±0.5mm
	internal misalignment	0-35mm (0-1-3/8")	1mm (1/32")	±0.5mm
	fit-up gap	1.6mm, 2.4mm	—	±0.1mm
	crown height	0-35mm (0-1-3/8")	1mm (1/32")	±0.5mm
	distance between two marking lines of socket weld	0-60mm (0-2-3/8")	1mm (1/16")	±0.5mm
	fillet weld length	0-30mm (0-1-1/4")	1mm (1/16")	±0.5mm
	fillet weld height	0-35mm (0-1-3/8")	1mm (1/32")	±0.5mm

## DRILL POINT GAGE



4843-1

- For twist drills with 118° angle, to check if the center of tip is concentric with the drill body
- Made of stainless steel





Code	Accuracy	
	Angle	Length
4843-1	±0.5°	±0.05mm

## DRILL ANGLE GAGE



4842-1

- Check drills with angle 60°, 70°, 90°, 118°, 125°, 135°, 150° or 160°
- Made of stainless steel



Code	Accuracy
4842-1	±0.5°





7261-150

- Made of carbon steel

Code	Size (L)	Range (W)
7261-150	150mm	20 - 170mm
7261-200	200mm	22 - 220mm
7261-250	245mm	30 - 270mm
7261-300	300mm	30 - 320mm




## INSIDE SPRING CALIPER





7262-150

- Made of carbon steel

Code	Size (L)	Range (W)
7262-150	155mm	0 - 140mm
7262-200	210mm	0 - 210mm
7262-250	265mm	0 - 270mm
7262-300	310mm	0 - 320mm




## OUTSIDE SPRING CALIPER



## SPRING DIVIDER




7260-150



- Made of carbon steel
- Hardened points


Code	Size (L)	Range (W)
7260-150	150mm	0 - 150mm
7260-200	200mm	0 - 210mm
7260-250	245mm	0 - 260mm
7260-300	300mm	0 - 320mm



## DIVIDER




7247-150



- Made of carbon steel
- Hardened points

Code	Size (L)	Range (W)	(mm)	
			a	b
7247-150	150mm	0 - 140mm	8.5	7
7247-200	200mm	0 - 190mm	10	7
7247-300	300mm	0 - 290mm	12	7






## FLEXIBLE RULE



7121-150



flexible use



- Flexible use
- Graduation on both sides
- Made of special alloy steel
- Satin chrome plated


Code	Range (L)	Graduation	Accuracy	W
7121-150	150mm	0.5mm/1mm	+0.10/-0.09mm	12.50mm
7121-300	300mm	0.5mm/1mm	+0.13/-0.09mm	12.50mm
7121-600	600mm	0.5mm/1mm	+0.18/-0.09mm	19.50mm



## RIGID RULE



7122-300



- Rigid rule
- Graduation on both sides
- Made of special alloy steel
- Satin chrome plated

Code	Range (L)	Graduation	Accuracy	W
7122-150	150mm	0.5mm/1mm	+0.10/-0.09mm	18.50mm
7122-300	300mm	0.5mm/1mm	+0.13/-0.09mm	24.50mm
7122-600	600mm	0.5mm/1mm	+0.18/-0.09mm	29.50mm


# STEEL RULE

ATTENTION:  
BASIC MODEL



7110-300

- Graduation: 0.5mm, 1mm, 1/64", 1/32", 1/16"
- Semi-flexible rules
- Made of stainless steel
- Non-glare surface



(mm)


Code	Range	Accuracy	L	W	H	Remark
7110-150	150mm/6"	±0.08mm	170	18	1.0	graduation on front and back
7110-200	200mm/8"	±0.08mm	220	18	1.0	graduation on front and back
7110-300	300mm/12"	±0.11mm	330	25	1.0	graduation on front and back
7110-500	500mm/20"	±0.14mm	530	30	1.2	graduation on front and back
7110-600	600mm/24"	±0.15mm	630	30	1.2	graduation on front and back
7110-1000	1000mm/40"	±0.20mm	1040	32	1.5	graduation on front and back
7110-1200	1200mm/48"	±0.24mm	1240	35	1.8	graduation on front
7110-1500	1500mm/60"	±0.35mm	1550	38	1.8	graduation on front
7110-2000	2000mm/80"	±0.45mm	2065	40	2.0	graduation on front

# RIGID RULE




7113-300A

- Rigid rules
- With groove on the back, suitable for combination square set (code 2278-180)
- Satin chrome plated



Unit: mm

Code	Range	Graduation		Accuracy	L
		front	back		
7113-300A	300mm/12"	0.5mm and 1/32"	1mm and 1/64"	±0.15mm	300mm




groove on the back



## STRAIGHT EDGE




7111-300A



- Check flatness and straightness, as well as for marking
- Graduation on the beveled edge
- Made of hardened tool steel
- Chrome plated

Code	Range (L)	Straightness of A	L1	W
7111-300A	300mm	0.02mm	320mm	40mm
7111-500A	500mm	0.03mm	520mm	40mm
7111-1000A	1000mm	0.04mm	1020mm	50mm





## MARKING GAGE



7120-200A

- Made of carbon steel
- Satin chrome plated

Code	Range	Graduation	Accuracy	L	W
7120-200A	0-200mm	0.1mm	±0.1mm	250	40
7120-250A	0-250mm	0.1mm	±0.1mm	300	40
7120-300A	0-300mm	0.1mm	±0.1mm	350	40





## T-SHAPE MARKING GAGE



1275-150A

- Made of stainless steel
- Satin chrome plated reading surface


Code	Range	Graduation	Accuracy
1275-150A	0-150mm	0.05mm	±0.05mm



## CENTER MARKING GAGE




7205-100



- Marking the center of round plates and shafts
- Made of stainless steel
- Satin chrome plated


Code	Size (AxB)	Diameter of shafts (Ød)	Accuracy	C	L
7205-100	100X70mm	4 - 90mm	±0.15mm	12	153
7205-150	150x130mm	4 - 190mm	±0.15mm	15	245
7205-200	200x150mm	6 - 220mm	±0.15mm	15	310



## SCRIBING CALIPER



7202-200A




the position of scriber tip can be adjusted



- Made of stainless steel
- Satin chrome plated reading surface
- Carbide scriber tip

Code	Range	Graduation	Accuracy
7202-200A	0-200mm/0-8"	0.1mm, 1/128"	±0.1mm




DATA  
OUTPUT

## DIGITAL SCRIBING CALIPER




1166-150A

- The carbide-tipped jaws facilitate scribing on workpieces
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable  
(code 7306-20, 7302-SPC1A/SPC1B, 7305-SPC2)



Code	Range	Accuracy	L	a	b	c	d1	d2
1166-150A	0-150mm/0-6"	±0.03mm	236	21	16.5	16	40	33
1166-200A	0-200mm/0-8"	±0.03mm	286	24	19.5	16	50	43
1166-300A	0-300mm/0-12"	±0.04mm	400	25	20.5	17	60	53




## SCRIBING CALIPER




7203-300A

- Made of stainless steel
- Satin chrome plated reading surface
- Hardened scriber tips






Code	Range	Graduation	Accuracy
7203-300A	51-300mm	0.1mm	±0.1mm



# HEIGHT SCRIBER



6990-300A



Code
6990-300A

- Grooved bottom for cylinder
- Two pins to be set against the edge of surface plate

# SCRIBER





7230



7231



7232



- Nickel plated


Code	Tip
7230	hardened tips
7231	hardened tip
7232	carbide tip

**CUSTOM-MADE**  
CAN SUPPLY PLATES  
ACCORDING TO CUSTOMER DESIRE

## GRANITE SURFACE PLATE



6900-132



- Made of granite, free from deterioration or dimensional change over time, minimal changes in dimension due to temperature changes
- Meet DIN876, grade 00 is for inspection room or lab, grade 0 is for workshop
- Optional accessory: stand for granite surface plate (code **6902**), jack for granite surface plate (code **6903**)

### Grade 00


Code	Size (LxWxH)	Flatness	Weight (Kg)	Load (Kg)
6900-132*	300x200x60mm	2.7µm	11	30
6900-142*	400x250x60mm	2.9µm	18	50
6900-144*	400x400x60mm	3.1µm	29	60
6900-153*	500x315x70mm	3.2µm	33	60
6900-164*	630x400x80mm	3.5µm	60	65
6900-166*	630x630x100mm	3.8µm	119	75
6900-185*	800x500x100mm	3.9µm	120	100
6900-1106*	1000x630x140mm	4.4µm	265	200
6900-1101*	1000x1000x150mm	4.8µm	450	400
6900-1128*	1200x800x160mm	4.9µm	461	500
6900-1161*	1600x1000x180mm	5.8µm	864	600
6900-1201*	2000x1000x220mm	6.5µm	1320	650
6900-1202*	2000x1500x250mm	7.0µm	2250	750

### Grade 0

Code	Size (LxWxH)	Flatness	Weight (Kg)	Load (Kg)
6900-032*	300x200x60mm	5.4µm	11	60
6900-042*	400x250x60mm	5.9µm	18	100
6900-044*	400x400x60mm	6.3µm	29	120
6900-053*	500x315x70mm	6.4µm	33	120
6900-064*	630x400x80mm	7.0µm	60	130
6900-066*	630x630x100mm	7.6µm	119	150
6900-085*	800x500x100mm	7.8µm	120	200
6900-0106*	1000x630x140mm	8.7µm	265	400
6900-0101*	1000x1000x150mm	9.7µm	450	800
6900-0128*	1200x800x160mm	9.8µm	461	1000
6900-0161*	1600x1000x180mm	11.5µm	864	1200
6900-0201*	2000x1000x220mm	12.9µm	1320	1300
6900-0202*	2000x1500x250mm	14.0µm	2250	1500

\* Supplied with manufacturer inspection certificate

## STAND FOR GRANITE SURFACE PLATE



- For medium size granite surface plates
- Adjusting range of jacks: 25mm
- One foot on the bottom is adjustable



### Low stands

(mm)

Code	For granite surface plate	W	D	H (with granite surface plate)	h (without granite surface plate)
6902-64A	630x400x80mm (code 6900-064 and 6900-164)	352	224	775-800	695-720
6902-66A	630x630x100mm (code 6900-066 and 6900-166)	352	352	775-800	675-700
6902-85A	800x500x100mm (code 6900-085 and 6900-185)	448	280	775-800	675-700
6902-106A	1000x630x140mm (code 6900-0106 and 6900-1106)	560	352	755-780	615-640
6902-101A	1000x1000x150mm (code 6900-0101 and 6900-1101)	560	560	755-780	605-630
6902-128A	1200x800x160mm (code 6900-0128 and 6900-1128)	672	448	755-780	595-620
6902-161A	1600x1000x180mm (code 6900-0161 and 6900-1161)	896	560	755-780	575-600

### High stands


(mm)

Code	For granite surface plate	W	D	H (with granite surface plate)	h (without granite surface plate)
6902-64H	630x400x80mm (code 6900-064 and 6900-164)	352	224	1000-1025	920-945
6902-66H	630x630x100mm (code 6900-066 and 6900-166)	352	352	1000-1025	900-925
6902-85H	800x500x100mm (code 6900-085 and 6900-185)	448	280	1000-1025	900-925
6902-106H	1000x630x140mm (code 6900-0106 and 6900-1106)	560	352	1000-1025	860-885
6902-101H	1000x1000x150mm (code 6900-0101 and 6900-1101)	560	560	1000-1025	850-875
6902-128H	1200x800x160mm (code 6900-0128 and 6900-1128)	672	448	1000-1025	840-865
6902-161H	1600x1000x180mm (code 6900-0161 and 6900-1161)	896	560	1000-1025	820-845

## JACK SET FOR GRANITE SURFACE PLATE

Code
6903-B

- 5 jacks per set
- Adjustable height
- For large granite surface plates:  
2000x1000x220mm (code 6900-0201 and 6900-1201)  
2000x1500x250mm (code 6900-0202 and 6900-1202)



6903-B



HARDENED SURFACES

HIGH PRECISION

STRONG MAGNETIC FORCE

## MAGNETIC RECTANGULAR BLOCKS

Unit: mm




- For grinding, light milling, drilling and inspection of round and square jobs
- Hardened, high accuracy, strong magnetic force
- Working surfaces are hardened to HRC58-62
- Magnetic force on top, bottom and back sides
- Supplied in matched pair


6898-150

Code	Size (LxWxH)	Magnetic force	Parallelism of top to bottom side	Squareness of top and bottom to back side	Height difference of a matched pair
6898-100	100x70x70mm	100kgf	5μm	5μm	5μm
6898-150	150x70x85mm	125kgf	5μm	5μm	5μm

## V-BLOCK SET




- Hold cylindrical workpieces for inspection and machining
- Two V-blocks per set
- Made of alloy steel
- Hardened to HRC60±2
- V groove on the top for large shafts
- V groove on the bottom for small shafts (except 6896-10)




Code	Size (LxWxH)	Range of shafts (Ød)	Parallelism of both V grooves to top and bottom sides	Squareness of both V grooves to front and back sides	Height difference of a matched pair
6896-10	25x20x20mm	3-20mm	3μm	3μm	3μm
6896-11	50x40x40mm	5-30mm	5μm	5μm	5μm
6896-12	80x63x63mm	7-63mm	5μm	5μm	5μm
6896-13	100x80x80mm	7-80mm	5μm	5μm	5μm
6896-14	140x70x140mm	9-140mm	5μm	5μm	5μm

## V-BLOCK SET




SIDE LIE-DOWN USE IS POSSIBLE

6802-1




- Hold cylindrical or rectangular workpieces for inspection and machining
- Two V-blocks per set
- Made of alloy steel
- Hardened to HRC60±2
- Applicable for cylinder with diameter (Ød): 5 - 50mm
- Applicable for rectangular workpieces with thickness: ≤35mm


Code	Size (LxWxH)	Parallelism of V groove to top, bottom, left, right sides	Squareness of V groove to front and back sides	Height difference of a matched pair
6802-1	65x70x50mm	5µm	5µm	5µm



## V-BLOCK



6804-1



- Hold cylindrical workpieces for inspection and machining
- Hardened to HRC60±2

Code	Size (LxWxH)	Range of shafts (Ød1 and Ød2)	Parallelism of upper groove to bottom, left and right sides	Squareness of upper groove to back side	Parallelism of side groove to back side
6804-1	90x48x48mm	5-33mm	5µm	5µm	5µm




SIDE LIE-DOWN  
USE IS POSSIBLE



6803-1

## V-BLOCK SET



side lie-down use is possible



- Hold cylindrical workpieces for inspection and machining
- Two V-blocks per set
- Made of alloy steel
- Hardened to HRC60±2
- V groove on the top for large shafts
- V groove on the bottom for small shafts


Code	Size (LxWxH)	Range of shafts ( $\varnothing d$ )	Parallelism of both V grooves to top, bottom, left, right sides	Squareness of both V grooves to front and back sides	Height difference of a matched pair
6803-1	25x20x20mm	4-35mm	5 $\mu$ m	5 $\mu$ m	5 $\mu$ m
6803-2	50x40x40mm	4-47mm	5 $\mu$ m	5 $\mu$ m	5 $\mu$ m



6887-3

(mm)


## V-BLOCK SET



- Two V-blocks per set
- Made of hardened tool steel

Code	Size (LxWxH)	Range of shafts( $\varnothing d_1$ )	Range of shafts( $\varnothing d_2$ )	Range of shafts( $\varnothing d_3$ )
6887-1	50x19x24	3-32	3-16	3-22
6887-2	75x24x35	3-50	3-20	3-32
6887-3	100x33x52	3-68	3-26	3-40
6887-4	125x44x69	3-87	3-34	3-50



Code	Parallelism of three V grooves to top and bottom sides	Squareness of three V grooves to front and back sides	Height difference of a matched pair
6887-1	5 $\mu$ m	5 $\mu$ m	5 $\mu$ m
6887-2	5 $\mu$ m	5 $\mu$ m	5 $\mu$ m
6887-3	5 $\mu$ m	5 $\mu$ m	5 $\mu$ m
6887-4	5 $\mu$ m	5 $\mu$ m	5 $\mu$ m



## ROLLER BEARING V-BLOCK SET



6888-1



Unit: mm


- Two V-blocks per set
- Workpieces don't get damaged due to bearings
- Suitable for heavy workpieces

Code	W1	W2	h1	h2	h3	L1	L2	S
6888-1	22	44	20	85	12	100	-	60
6888-2	40	60	22	85	12	100	-	50
6888-3	60	80	30	124	20	180	90	120

(mm)

Code	Size (LxWxH)	Diameter of bearings ( $\varnothing D$ )	Range of shafts ( $\varnothing d$ )	Parallelism of bearings to bottom	Load capacity
6888-1	150x60x100mm	42mm	25 - 70mm	12 $\mu$ m	500kg
6888-2	150x80x100mm	47mm	5 - 55mm	12 $\mu$ m	1000kg
6888-3	230x100x150mm	72mm	70 - 200mm	12 $\mu$ m	1000kg


## GRANITE V-BLOCK SET



6897-1

- Two V-blocks per set

Code	Size (LxWxH)	Range of shafts ( $\varnothing d$ )	Parallelism of V groove to bottom	Height difference of a matchet pair
6897-1	70x50x70mm	6 - 75mm	4 $\mu$ m	5 $\mu$ m
6897-2	100x50x70mm	6 - 99mm	4 $\mu$ m	5 $\mu$ m



STRONG  
MAGNETIC FORCE

HARDENED  
SURFACES

HIGH  
PRECISION



## MAGNETIC V-BLOCK



6889-11



6889-1



- Hardened, high accuracy, strong magnetic force, for grinding, light milling, drilling and inspection of round and square jobs
- All working surfaces are hardened to HRC60±2
- Magnetic force on top, bottom and two V grooves
- V groove on the top for large shafts
- V groove on the bottom for small shafts
- Suitable for cast iron surface plates and granite surface plates

### Individual

Code	Size (LxWxH)	Range of shafts (Ød)	Magnetic force	Parallelism of V groove to top, bottom, left, right sides	Squareness of V groove to back side
6889-11	75x56x75mm	5 - 40mm	75kgf	5µm	5µm
6889-22	100x70x95mm	5 - 65mm	100kgf	5µm	5µm
6889-33	150x75x100mm	5 - 70mm	125kgf	5µm	5µm
6889-44	200x124x150mm	10 - 140mm	175kgf	10µm	10µm

### Matched pair

Code	Size (LxWxH)	Range of shafts (Ød)	Magnetic force	Parallelism of both V grooves to top, bottom, left, right sides	Squareness of both V grooves to back side	Height difference of a matched pair
6889-1	75x56x75mm	5 - 40mm	75kgf	5µm	5µm	5µm
6889-2	100x70x95mm	5 - 65mm	100kgf	5µm	5µm	5µm
6889-3	150x75x100mm	5 - 70mm	125kgf	5µm	5µm	5µm
6889-4	200x124x150mm	10 - 140mm	175kgf	10µm	10µm	10µm


## MAGNETIC V-BLOCK

ATTENTION: NOT SUITABLE FOR STEEL OR IRON SURFACE


ATTENTION: NOT HARDENED



6890-702



- Hold cylindrical workpieces for inspection and machining
- Supplied in single piece
- Not hardened
- Not suitable for steel or iron surface



Code	Size (LxWxH)	Range of shafts ( $\varnothing d$ )	Magnetic force	Parallelism of V groove to top, bottom, left and right sides	Squareness of V groove to back side
6890-702	70x60x73mm	6-44mm	56kgf	10 $\mu$ m	10 $\mu$ m


## MAGNETIC V-BLOCK

ATTENTION: NOT SUITABLE FOR STEEL OR IRON SURFACE


ATTENTION: NOT HARDENED



6801-1201



- Hold cylindrical workpieces for inspection and machining
- Supplied in single piece
- Not hardened
- V groove on the top for large shafts
- V groove on the bottom for small shafts
- Not suitable for steel or iron surface




Code	Size (LxWxH)	Range of shafts ( $\varnothing d$ )	Magnetic force	Parallelism of both V grooves to top, bottom, left, right side	Squareness of both V grooves to back side
6801-1201	80x70x95mm	6-67mm	64kgf	10 $\mu$ m	10 $\mu$ m
6801-1202	100x70x95mm	6-67mm	80kgf	10 $\mu$ m	10 $\mu$ m
6801-1203	120x70x95mm	6-67mm	96kgf	10 $\mu$ m	10 $\mu$ m

ATTENTION: LOW  
MAGNETIC FORCE


## MAGNETIC V-BLOCK SET



6891-1



- Hold cylindrical workpieces for inspection, not suitable for machining due to low magnetic force
- Two V-blocks per set




Code	Size (LxWxH)	Range of shafts (Ød)	Magnetic force	Parallelism of V groove to bottom and back sides	Height difference of a matched pair
6891-1	70x40x50mm	6-46mm	8kgf	10µm	10µm
6891-3	150x50x100mm	6-125mm	14kgf	10µm	10µm


## MAGNETIC INDUCTION V-BLOCK



6892-1




- Hold cylindrical workpieces for inspection and machining
- To be used on magnetic chucks
- Supplied in single piece
- V groove on the top for large shafts
- V groove on the bottom for small shafts




Code	Size (LxWxH)	Range of shafts (Ød)	Pole pitch	Parallelism of both V grooves to top, bottom, left, right sides
6892-1	110x60x48mm	6-50mm	2.5+3mm	10µm


## MAGNETIC INDUCTION V-BLOCK SET



6899-1



- Hold cylindrical workpieces for inspection and machining
- To be used on magnetic chucks
- Two V-blocks per set
- V groove on the top for large shafts
- V groove on the bottom for small shafts




Code	Size (LxWxH)	Range of shafts ( $\varnothing d$ )	Pole pitch	Parallelism of both V grooves to top, bottom, left and right sides	Height difference of a matched pair
6899-1	50x60x48mm	6 - 50mm	2.5+3mm	10 $\mu$ m	10 $\mu$ m

## PARALLEL SET



6533-144

- Parallelism between top and bottom: 5 $\mu$ m
- Height difference of a matched pair: 5 $\mu$ m
- Hardened to HRC55-60




Code	Parallels per set	Length (L)	Thickness (W)	Height (H)
6533-10	10 pairs	150	3	13, 16, 19, 22, 25, 28, 31, 35, 38, 41
6533-144	14 pairs	150	10	14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 35, 40, 45, 50
6533-6	6 pairs	200	9.5	35, 40, 45, 50, 55, 58

## PARALLEL SET




6534-6




- Parallelism between top and bottom: 5µm
- Height difference of a matched pair: 5µm
- Hardened to HRC55-60

Unit: mm


Code	Parallels per set	Height (H)
6534-6	6 pairs	25, 30, 35, 40, 45, 48



## MAGNETIC INDUCTION PARALLEL SET




6894-1





6894-2



Unit: mm



6894-1



6894-2




- To be used on magnetic chucks
- Two parallels per set

Code	Size (LxWxH)	Pole pitch	Parallelism between A and B	Parallelism between C and D	Height difference of a matched pair
6894-1	100x50x25mm	2.5+3mm	10µm	10µm	10µm
6894-2	50x100x25mm	2.5+3mm	10µm	10µm	10µm


## GRANITE PARALLEL SET



4143-250




- Made of granite, hard and no rusty, no dimensional change over time or temperature change
- Two parallels per set




Code	Size (LxWxH)	Parallelism between A and B	Parallelism between C and D	Height difference of a matched pair
4143-250	250x25x40mm	3 $\mu$ m	3 $\mu$ m	3 $\mu$ m

## ANGLE PLATE SET



4003-12

unit:mm




- For angle set-up in tooling, production and inspection
- Hardness HRC55



Code	Angle plates included	Angle $\alpha$	Accuracy
4003-10	10	1°, 2°, 3°, 4°, 5°, 10°, 15°, 20°, 25°, 30°	$\pm 9''$
4003-12	12	1/4°, 1/2°, 1°, 2°, 3°, 4°, 5°, 10°, 15°, 20°, 25°, 30°	$\pm 9''$





## UNIVERSAL ANGLE PLATE SET



4004-9



type A




type B


- For angle set-up in tooling, production and inspection
- Hardness HRC55

Code	Angle plates included	Angle $\alpha$	Type	Accuracy
4004-9	9	$\frac{1}{2}^\circ, 1^\circ, 2^\circ, 3^\circ, 4^\circ, 5^\circ$	type A	$\pm 9''$
		$10^\circ, 15^\circ, 30^\circ$	type B	

## ADJUSTABLE ANGLE BLOCK



6535-30



- Made of hardened tool steel
- With locking screw

Code	Size (LxWxH)	h	Adjustable angle	Graduation of angle	Accuracy of angle
6535-25	75x25x36mm	25mm	$30^\circ \sim 0^\circ \sim 60^\circ$	10'	10'
6535-30	102x30x49mm	30mm	$30^\circ \sim 0^\circ \sim 60^\circ$	10'	10'

## RIGHT ANGLE PLATE




6547-1

V groove

- Hardened to HRC60±2
- V groove for cylinders
- Parallelism and squareness between A, B, C, D, E, F, G and H: 6µm
- Parallelism and squareness of V groove to A, B, C, D, E, F, G and H: 6µm

Code	Size (LxWxH)
6547-1	100x100x115mm




Unit: mm

## SINE BAR

HIGH  
PRECISION





4155-100



- High precision

The front and back ends and two sides have mounting holes to install plate



Code	Roller distance (E)	Table size (AxB)	C	Accuracy of $\alpha$ at 30°
4155-100	100mm	130x30mm	40mm	±5 seconds
4155-200	200mm	230x30mm	40mm	±5 seconds
4155-300	300mm	345x40mm	50mm	±8 seconds


## SINE TABLE




6527-100

- Accuracy of angle:  $\pm 15''$
- Hardness HRC58-60

Code	Roller distance (E)	Table size (LxW)	Adjustable angle
6527-100	100mm	150x150mm	0-60°



## PRECISION SINE VISE




6522-80

There is a 1mm step (accuracy  $\pm 0.002\text{mm}$ ). Gage blocks smaller than 0.5mm are not available. If small gage blocks are needed (for example, 0.25mm), a gage block 1.25mm can be used in order to make  $1.25\text{mm} - 1\text{mm} = 0.25\text{mm}$ .





- Parallelism:  $3\mu\text{m}/100\text{mm}$
- Squareness:  $5\mu\text{m}/100\text{mm}$
- Accuracy of angle:  $\pm 15''$
- Made of SKS tool steel, subzero treatment
- Hardness HRC58-60

Code	Jaw opening (Q)	Jaw width (W)	Adjustable angle
6522-80	0-80mm	73mm	0-46°



## PRECISION SINE VISE


There is a 1mm step (accuracy  $\pm 0.002\text{mm}$ ). Gage blocks smaller than 0.5mm are not available. If small gage blocks are needed (for example, 0.25mm), a gage block 1.25mm can be used in order to make  $1.25\text{mm} - 1\text{mm} = 0.25\text{mm}$ .



6523-80


- Parallelism:  $3\mu\text{m}/100\text{mm}$
- Squareness:  $5\mu\text{m}/100\text{mm}$
- Accuracy of angle:  $\pm 15^\circ$
- Made of SKS tool steel, subzero treatment
- Hardness HRC58-60

Code	Jaw opening (Q)	Jaw width (W)	Adjustable angle
6523-80	0-80mm	73mm	0-46°



## PRECISION COMPOUND SINE VISE



There is a 1mm step (accuracy  $\pm 0.002\text{mm}$ ). Gage blocks smaller than 0.5mm are not available. If small gage blocks are needed (for example, 0.25mm), a gage block 1.25mm can be used in order to make  $1.25\text{mm} - 1\text{mm} = 0.25\text{mm}$ .




6524-80

- Parallelism:  $3\mu\text{m}/100\text{mm}$
- Squareness:  $5\mu\text{m}/100\text{mm}$
- Accuracy of angle:  $\pm 15^\circ$
- Made of SKS tool steel, subzero treatment
- Hardness HRC58-60

Code	Jaw opening (Q)	Jaw width (W)	Adjustable angle
6524-80	0-80mm	73mm	0-46°




## PRECISION UNIVERSAL VISE




6521-80

- Horizontal rotary: range 360°, graduation 0.05°
- Vertical incline: range 45°, graduation 0.05°
- With vertical incline adjust knob
- Parallelism and squareness between A, B, C and D: 5µm/100mm, parallelism between D and E at 0°: 10µm/100mm
- Made of tool steel
- Hardness HRC56-58

Code	Jaw opening(Q)	Jaw width(W)
6521-80	0-80mm	70mm




Unit: mm



## PRECISION VISE



6525-76




Code	Jaw opening (Q)	Jaw width (W)	L	H	M
6525-73	0-73mm	63mm	176	63	30
6525-76	0-76mm	73mm	190	73	35
6525-120	0-120mm	98mm	255	82	40

(mm)



- Parallelism: 4µm/100mm
- Squareness: 6µm/100mm
- Made of SK2 tool steel
- Hardness HRC52-58

## PRECISION VISE



- Parallelism: 3µm/100mm
- Squareness: 5µm/100mm
- Made of SK2 tool steel
- Hardness HRC55-60

6526-80







Code	Jaw opening (Q)	Jaw width (W)	Overall length (L)	(mm)	
				H	M
6526-80	0-80mm	50mm	150mm	53	25
6526-100	0-100mm	73mm	190mm	70	35


## CENTERING INDICATOR




2385-3




Unit: mm




external feeler



internal feeler



small hole feeler



Code

2385-3

- Provides quick and accurate centering in boring and milling set-up



COMPACT DESIGN



ANTI MAGNETIC CARBIDE CONTACT POINT

# 3D TESTER




2842-3D

Unit: mm




If probe tip is pressed too much, the probe breaks at the breaking point, in order to prevent damage of main body




Code	Range	Graduation
2842-3D	1.5mm	0.01mm

radial setting




axial setting



Probe (optional)

Code	Name	L (mm)	D (mm)
2842-N1	standard probe	27	SØ3
2842-N2	long probe	62	SØ6



2842-N1



2842-N2

## 2D ELECTRONIC EDGE FINDER




6570-1




6570-2

LED light

LED light




6570-1



6570-2

Unit: mm



- The shank is electrically conducted to the metal workpiece through the chuck and table, the LED lights up, when the ball touches the workpiece
- Not suitable for rotary use
- Hardened contact ball

Code	Shank	Contact ball	Accuracy	Battery
6570-1	Ø16mm	SØ10mm	10µm	A23S, 12Vx1pc
6570-2	Ø20mm	SØ10mm	10µm	A23S, 12Vx1pc

## 3D ELECTRONIC EDGE FINDER




6571-1




6571-2

LED light

LED light




6571-1



6571-2


Unit: mm




- The shank is electrically conducted to the metal workpiece through the chuck and table, the LED lights up, when the ball touches the workpiece
- Not suitable for rotary use
- Hardened contact ball

Code	Shank	Contact ball	Accuracy	Battery
6571-1	Ø16mm	SØ10mm	10µm	A23S, 12Vx1pc
6571-2	Ø20mm	SØ10mm	10µm	A23S, 12Vx1pc

X-Y edge finder




Z axial setting






## ELECTRONIC EDGE FINDER



- The shank is electrically conducted to the metal workpiece through the chuck and table, the LED lights up and the beeper sounds (only for **6566-3**), when the ball touches the workpiece
- Not suitable for rotary use
- Hardened shank and contact ball


Code	Shank (A)	Contact ball (B)	Accuracy	Beeper	Battery
6566-2	Ø20mm	SØ10mm	5µm	without	23AE, 12Vx1pc
6566-3	Ø20mm	SØ10mm	5µm	with	23AE, 12Vx1pc

## EDGE FINDER



- Hardened shank and contact point

Code	Shank (A)	Contact point (B)	Accuracy
6567-1	Ø10mm	Ø6mm	8µm




## EDGE FINDER




6562-3



6562-4




6562-3




6562-4

Unit: mm



6562-3



6562-4


- Hardened shank and contact point

Code	Shank (A)	Contact point (B)	Contact point (C)	Accuracy
6562-3	Ø10mm	Ø10mm	—	5µm
6562-4	Ø10mm	Ø10mm	Ø4mm	5µm

## CERAMIC EDGE FINDER




6568-1



Unit: mm




- Ceramic contact point, non magnetic

Code	Shank (A)	Contact point (B)	Accuracy
6568-1	Ø10mm	Ø10mm	8µm



## ELECTRONIC ZERO SETTER

LOW TEST FORCE



6553-50


- The base is electrically conducted to the cutting tools through the table and chuck, the LED lights up when the cutting tool touches the anvil
- Magnetic base
- Two batteries LR44

Code	Height (H)	Accuracy	Test force
6553-50	50mm	±10µm	7N (at 49mm)


## ELECTRONIC ZERO SETTER

ATTENTION: HIGH TEST FORCE

- The base is electrically conducted to the cutting tools through the table and chuck, the LED lights up when the cutting tool touches the anvil
- Magnetic base
- Battery LR44



6550-50A





Code	Height (H)	Accuracy	Test force
6550-50A	50mm	±10µm	27N (at 49mm)

## ZERO SETTER



6554-50



Code	Height (H)	Accuracy	Test force
6554-50	50mm	±10µm	9N (at 50mm)



## ZERO SETTER



2397-502A

- Magnetic base

Code	Height (H)	Accuracy	Test force
2397-502A	50mm	±10µm	9N (at 50mm)





## ZERO SETTER



2394-100A

- Magnetic base with on-off switch

Code	Height (H)	Accuracy	Test force
2394-100A	100mm	±10µm	9N (at 100mm)



## 2-PIECE MEASURING TOOL SET

■ Includes:

- 1) Vernier caliper, range 0-150mm/0-6",  
graduation 0.05mm/1/128" (code **1205-150**)
- 2) Outside micrometer, range 0-25mm,  
graduation 0.01mm (code **3202-25A**)



5021

Code

5021

## 2-PIECE MEASURING TOOL SET

■ Includes:

- 1) Digital caliper, range 0-150mm/0-6",  
resolution 0.01mm/0.0005" (code **1108-150W**)
- 2) Digital outside micrometer, range 0-25mm/0-1",  
resolution 0.001mm/0.00005" (code **3109-25B**)



5022-W

Code

5022-W

## 2-PIECE MEASURING TOOL SET

■ Includes:

- 1) Dial test indicator, range 0.8mm, graduation 0.01mm (code **2380-08**)
- 2) Magnetic stand

Code

5023



5023

## 2-PIECE MEASURING TOOL SET

■ Includes:

- 1) Dial indicator, range 10mm, graduation 0.01mm (code **2308-10A**)
- 2) Magnetic stand (code **6201-60**)

Code

5024



5024

## 3-PIECE MEASURING TOOL SET



- Includes:
  - 1) Digital indicator, range 12.7mm/0.5", resolution 0.01mm/0.0005" (code **2112-10**)
  - 2) Flex arm
  - 3) Locking pliers, adjustable jaw opening from 0 to 25mm

Code

5031



5031

## 4-PIECE MEASURING TOOL SET

- Includes:
  - 1) Vernier caliper, range 0-150mm/0-6", graduation 0.05mm/1/128" (code **1205-150**)
  - 2) Outside micrometer, range 0-25mm, graduation 0.01mm (code **3202-25A**)
  - 3) 90° beveled edge square, 100x70mm, grade 0 (code **4790-1000**)
  - 4) Steel rule, 150mm/6" (code **7110-150**)

Code

5041



5041

## 4-PIECE MEASURING TOOL SET

■ Includes:

- 1) Digital caliper, range 0-150mm/0-6", resolution 0.01mm/0.0005" (code **1108-150W**)
- 2) Outside micrometer, range 0-25mm, graduation 0.01mm, (code **3202-25A**)
- 3) 90° beveled edge square, 100x70mm, grade 0 (code **4790-1000**)
- 4) Steel rule, 150mm/6" (code **7110-150**)

Code

5042-W



5042-W

## 5-PIECE MEASURING TOOL SET

■ Includes:

- 1) Digital caliper, range 0-150mm/0-6", resolution 0.01mm/0.0005", (code **1108-150W**)
- 2) Outside micrometer, range 0-25mm, graduation 0.01mm (code **3203-25A**)
- 3) Dial indicator, range 10mm, graduation 0.01mm (code **2308-10A**)
- 4) Magnetic stand (code **6201-60**)
- 5) Micrometer stand (code **6300**)

Code

5051-W



5051-W



## 5-PIECE MEASURING TOOL SET

■ Includes:

- 1) Digital caliper, range 0-150mm/0-6", resolution 0.01mm/0.0005" (code **1108-150W**)
- 2) Digital outside micrometer, range 0-25mm/0-1", resolution 0.001mm/0.00005" (code **3109-25B**)
- 3) Digital indicator, range 12.7mm/0.5", resolution 0.01mm/0.0005" (code **2112-10**)
- 4) Magnetic stand (code **6201-60**)
- 5) Micrometer stand (code **6300**)

Code

5052-W



5052-W

## 6-PIECE MEASURING TOOL SET

■ Includes:

- 1) Digital caliper, range 0-150mm/0-6", resolution 0.01mm/0.0005" (code **1108-150W**)
- 2) Outside micrometer, range 0-25mm, graduation 0.01mm (code **3202-25A**)
- 3) Dial indicator, range 10mm, graduation 0.01mm (code **2308-10FA**)
- 4) 90° beveled edge square, 100x70mm, grade 0 (code **4790-1000**)
- 5) Scriber (code **7230**)
- 6) Steel rule, 150mm/6" (code **7110-150**)

Code

5061-W



5061-W

## 6-PIECE MEASURING TOOL SET

■ Includes:

- 1) Digital caliper, range 0-150mm/0-6"  
resolution 0,01mm/0,0005" (code **1108-150W**)
- 2) Outside micrometer, range 0-25mm  
graduation 0,01mm (code **3202-25A**)
- 3) 90° beveled edge square, 100x70mm  
grade 00 (code **4790-0100**)
- 4) Straight edge, 100mm  
(code **4700-100**)
- 5) Spring divider, 150mm (code **7260-150**)
- 6) Steel rule, 200mm/8" (code **7110-200**)

Code

**5062-W**



**5062-W**

## 6-PIECE MEASURING TOOL SET

■ Includes:

- 1) Vernier caliper, range 0-150mm/0-6"  
graduation 0,05mm/1/128"  
(code **1205-150**)
- 2) Outside micrometer, range 0-25mm  
graduation 0,01mm (code **3202-25A**)
- 3) 90° beveled edge square, 100x70mm  
grade 00 (code **4790-0100**)
- 4) Straight edge, 100mm  
(code **4700-100**)
- 5) Spring divider, 150mm (code **7260-150**)
- 6) Steel rule, 200mm/8" (code **7110-200**)

Code

**5063**



**5063**

## 9-PIECE MEASURING TOOL SET

■ Includes:

- 1) Digital caliper, range 0-150mm/0-6", resolution 0.01mm/0.0005"  
(code **1108-150W**)
- 2) Outside micrometer, range 0-25mm, graduation 0.01mm (code **3202-25A**)
- 3) Protractor, range 0-180°, graduation 1° (code **4799-180**)
- 4) Pitch gauge, range 0.25-7mm, 24pcs, metric 60° thread (code **4820-124**)
- 5) Radius gauge, range 1-7mm (code **4801-17**)
- 6) Feeler gauge, range 0.05-1.00mm, 20pcs (code **4602-20**)
- 7) 90° beveled edge square, 100x70mm, grade 0 (code **4790-1000**)
- 8) Scriber (code **7230**)
- 9) Steel rule, 150mm/6" (code **7110-150**)

Code

5091-W



5091-W

## 13-PIECE MEASURING TOOL SET

■ Includes:

- 1) Digital caliper, range 0-150mm/0-6", resolution 0.01mm/0.0005",  
(code **1108-150W**)
- 2) Outside micrometer, range 0-25mm, graduation 0.01mm (code **3202-25A**)
- 3) Dial indicator, range 10mm, graduation 0.01mm (code **2308-10A**)
- 4) Magnetic stand (code **6201-60**)
- 5) Protractor, range 0-180°, graduation 1° (code **4799-180**)
- 6) Pitch gauge, range 0.25-7mm, 24pcs, metric 60° thread (code **4820-124**)
- 7) Radius gauge, range 1-7mm (code **4801-17**)
- 8) Feeler gauge, range 0.05-1.00mm, 20pcs (code **4602-20**)
- 9) 90° beveled edge square, 100x70mm, grade 0 (code **4790-1000**)
- 10) Scriber (code **7230**)
- 11) Steel rule, 150mm/6" (code **7110-150**)
- 12) Depth base attachment (code **6140**)
- 13) Zero setting bar

Code

5013-W



5013-W

# DIGITAL HORIZONTAL SCALE



DATA  
OUTPUT



7101-300A




7101-400A



Unit: mm **type A**

- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Made of stainless steel
- Supplied with bracket to be mounted on the back
- Optional accessory: data output cable (code **7306-20**, **7302-SPC1A/SPC1B,7305-SPC2**)



Unit: mm **type B**

- Resolution: 0.01mm/0.0005"
- Button function: on/off, zero, mm/inch, ABS, data preset
- Absolute and incremental measurement
- Battery CR2032
- Data output
- Made of stainless steel
- Supplied with bracket to be mounted on the back
- Optional accessory: data output cable (code **7306-20**, **7302-SPC1A/SPC1B,7305-SPC2**)



Code	Range	Type	Accuracy	L (mm)
7101-100A	100mm	A	±0.02mm	215
7101-150A	150mm	A	±0.03mm	265
7101-200A	200mm	A	±0.03mm	315
7101-300A	300mm	A	±0.04mm	445
7101-400A	400mm	B	±0.05mm	590

Code	Range	Type	Accuracy	L (mm)
7101-500A	500mm	B	±0.05mm	690
7101-600A	600mm	B	±0.08mm	790
7101-800A	800mm	B	±0.10mm	990
7101-1000A	1000mm	B	±0.10mm	1190

# DIGITAL VERTICAL SCALE



7102-300



- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero set, mm/in, data set
- Battery LR44
- Made of stainless steel
- Supplied with bracket to be mounted on the back

(mm)


Code	Range	Accuracy	B	C	D	E	F	L
7102-100	100mm	±0.02mm	4	20	6	24	40	245
7102-150	150mm	±0.03mm	4	20	6	24	40	296
7102-200	200mm	±0.03mm	4	20	6	24	40	345
7102-300	300mm	±0.04mm	4	20	6	24	40	445
7102-400	400mm	±0.05mm	4	20	6	24	40	545
7102-500	500mm	±0.05mm	5.5	24	8	32	45	685
7102-600	600mm	±0.08mm	5.5	24	8	32	45	785
7102-800	800mm	±0.10mm	5.5	24	8	32	45	985
7102-1000	1000mm	±0.10mm	5.5	24	8	32	45	1185

# LINEAR SCALE




ISL-A1-300

## Series ISL-A1 and ISL-A5



## Series ISL-B5



To be continued

Continued from previous page

Effective length(L)	Code		
	Series ISL-A1	Series ISL-A5	Series ISL-B5
50mm	ISL-A1-50	ISL-A5-50	ISL-B5-50
100mm	ISL-A1-100	ISL-A5-100	ISL-B5-100
150mm	ISL-A1-150	ISL-A5-150	ISL-B5-150
200mm	ISL-A1-200	ISL-A5-200	ISL-B5-200
250mm	ISL-A1-250	ISL-A5-250	ISL-B5-250
300mm	ISL-A1-300	ISL-A5-300	ISL-B5-300
350mm	ISL-A1-350	ISL-A5-350	ISL-B5-350
400mm	ISL-A1-400	ISL-A5-400	ISL-B5-400
450mm	ISL-A1-450	ISL-A5-450	ISL-B5-450
500mm	ISL-A1-500	ISL-A5-500	ISL-B5-500
550mm	ISL-A1-550	ISL-A5-550	ISL-B5-550
600mm	ISL-A1-600	ISL-A5-600	ISL-B5-600
650mm	ISL-A1-650	ISL-A5-650	ISL-B5-650
700mm	ISL-A1-700	ISL-A5-700	ISL-B5-700
750mm	ISL-A1-750	ISL-A5-750	ISL-B5-750
800mm	ISL-A1-800	ISL-A5-800	ISL-B5-800
850mm	ISL-A1-850	ISL-A5-850	ISL-B5-850
900mm	ISL-A1-900	ISL-A5-900	ISL-B5-900
950mm	ISL-A1-950	ISL-A5-950	ISL-B5-950
1000mm	ISL-A1-1000	ISL-A5-1000	ISL-B5-1000
1100mm		ISL-A5-1100	ISL-B5-1100

Effective length(L)	Code	
	Series ISL-A5	Series ISL-B5
1200mm	ISL-A5-1200	ISL-B5-1200
1300mm	ISL-A5-1300	ISL-B5-1300
1400mm	ISL-A5-1400	ISL-B5-1400
1500mm	ISL-A5-1500	ISL-B5-1500
1600mm	ISL-A5-1600	ISL-B5-1600
1700mm	ISL-A5-1700	ISL-B5-1700
1800mm	ISL-A5-1800	ISL-B5-1800
1900mm	ISL-A5-1900	ISL-B5-1900
2000mm	ISL-A5-2000	ISL-B5-2000
2100mm	ISL-A5-2100	ISL-B5-2100
2200mm	ISL-A5-2200	ISL-B5-2200
2300mm	ISL-A5-2300	ISL-B5-2300
2400mm	ISL-A5-2400	ISL-B5-2400
2500mm	ISL-A5-2500	ISL-B5-2500
2600mm	ISL-A5-2600	ISL-B5-2600
2700mm	ISL-A5-2700	ISL-B5-2700
2800mm	ISL-A5-2800	ISL-B5-2800
2900mm	ISL-A5-2900	ISL-B5-2900
3000mm	ISL-A5-3000	ISL-B5-3000
3100mm	ISL-A5-3100	ISL-B5-3100
3200mm	ISL-A5-3200	ISL-B5-3200


#### SPECIFICATION

	Series ISL-A1		Series ISL-A5		Series ISL-B5	
	<b>L1(mm)</b>	L+30(L<950)	L+50(L≥950)	L+30(L<950)	L+50(L≥950)	L+30(L<950)
<b>L2(mm)</b>	L+132(L<950)	L+152(L≥950)	L+132(L<950)	L+152(L≥950)	L+136(L<950)	L+156(L≥950)
<b>L3(mm)</b>	L+149(L<950)	L+169(L≥950)	L+149(L<950)	L+169(L≥950)	L+154(L<950)	L+174(L≥950)
<b>Resolution</b>	1μm		5μm		5μm	
<b>Max. response speed</b>	50m/min		90m/min		60m/min	
<b>Scale grating pitch</b>	20μm					
<b>Scale reference point pitch</b>	50mm					
<b>Accuracy</b>	±(5+5L/1000)μm L is the effective length in mm					
<b>Cable length</b>	3.5m (L: 50-950mm) 5m (L: 1000-1500mm) 10m (L: 1600-3200mm)					


#### STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>'L' shape support</b>	1pc
<b>Anti-dust cover</b>	1pc
<b>Plain base</b>	1pc (for L ≥ 1500mm)

# COUNTER



ISL-DR2



ISL-DR3

## SPECIFICATION

Code	ISL-DR2	ISL-DR3
Application	two-axis	three-axis
Scale input ports	2	3
Resolution	0.05μm, 0.1μm, 0.2μm, 0.5μm, 1μm, 2μm, 5μm, 10μm, 20μm, 50μm	
Functions	addition of 2-scale data, linearity error compensation, smoothing, RS232C interface unit, BCD code out, zero setting, preset, resolution setting, counting direction setting, inch/mm conversion, ABS/INC conversion, expansion/contraction coefficient setting, "1/2" calculation, detecting RI, bolt-hole circle machining, ramp circle machining	
Power supply	110/220V, 50/60Hz	
Dimension	295×185×45mm	
Weight	1.45kg	

## STANDARD DELIVERY

Main unit	1pc
Mounting bracket	1pc
Ground cable	1pc

RS232C cable	1pc
Software CD for RS232C	1pc





# HIGH PRECISION LINEAR GAGE AND DISPLAY UNIT




7108-10





7108-1



## BACK OF DISPLAY UNIT




Unit: mm



Unit: mm



## APPLICATION



foot switch (optional), code: 7108-2

- Linear gage:
  - Incremental glass scale sensor, with built-in roller bearing, high precision
  - With lifting lever, for quick measurement
- Display unit:
  - Set zero or output data through foot switch (optional)
  - Measuring direction can be changed
  - The reading can be preset
  - Can make accuracy compensation

## LINEAR GAGE SPECIFICATION

Code	7108-10	7108-30
Measuring range	10mm	30mm
Resolution	0.01µm	
Accuracy	(0.5+L/60)µm, L is measuring length in mm	
Dust/waterproof	IP50	
Output signal	1Vss	
Grating pitch	8µm	
Measuring force	0.7~1.6N	
Cable length	1.5m	
Linear gage length (L)	113.5mm	133.5mm




## DISPLAY UNIT SPECIFICATION

Code	7108-1
Display	8 digits
Character height	9mm
Quantity of linear gages to be connected	single channel, to connect one linear gage*
Dust/waterproof	IP20
Display unit	mm, inch, grad
Resolution	1µm, 0.1µm, 0.01µm
Data output	USB, RS232
Power supply	AC 85~264V, 150mA

\* Double channel display is optional

# LINEAR GAGE AND DISPLAY UNIT

LINEAR GAGE  
IP65  
WATERPROOF



- Linear gage: shock-proof, water proof, dust proof, suitable for high speed movement, long working life
- Display unit: set tolerance and make judgment (out of upper limit, within tolerance, out of lower limit), output the judgment to control outside devices, set zero and hold reading from outside


## LINEAR GAGE SPECIFICATION

Code	7106-11	7106-12
Measuring range	12mm	12mm
Resolution	0.01mm	0.001mm
Accuracy	20μm	5μm
Hysteresis	10μm	2μm
Measuring principle	capacity system	
Voltage	5V	
Sampling frequency	100 times/sec.	
Working life	ten million times	
Dust/waterproof	IP65	
Measuring force	1.5N	
Cable length	2m	
Data output	four-core wire	


## DISPLAY UNIT SPECIFICATION

Code	7106-1
Display	6 digits
Quantity of linear gages to be connected	1pc
Tolerance	set tolerance and make judgment with alarm and lights (out of upper limit, within tolerance, out of lower limit)
Output control	output the tolerance judgment (out of upper tolerance, within tolerance, out of lower tolerance) to control outside devices
Outside control	control the display units from outside (set zero, hold reading)
Data output	connect to PC
Power supply	DC 9~24V


LINEAR GAGE  
IP65  
WATERPROOF




linear gage



4-channel interface box  
7107-1




8-channel interface box  
7107-2



INTERFACE BOX SPECIFICATION

Code	7107-1	7107-2
Quantity of linear gages to be connected	4pcs	8pcs
Data port	RS232 and RS485	
Power supply	DC 9~24V	

MULTI LINEAR GAGE SYSTEM




- Software is supplied with interface boxes. In the software, it is possible to set tolerance of each channel and show judgment (red when out of tolerance, green when within tolerance), set zero, collect data manually or automatically (time is adjustable), output data to Excel, print report


LINEAR GAGE SPECIFICATION

Code	7107-11	7107-12
Measuring range	12mm	12mm
Resolution	0.01mm	0.001mm
Accuracy	20μm	5μm
Hysteresis	10μm	2μm
Measuring principle	capacity system	
Voltage	5V	
Sampling frequency	100 times/sec.	
Working life	ten million times	
Dust/waterproof	IP65	
Measuring force	1.5N	
Cable length	2m	
Data output	RS232	

# EXTERNAL THREAD MEASURING DEVICE CODE ISQ-TE100



measure pitch diameter of thread



- Quickly measure major, pitch and minor diameters of external thread
- Suitable for metric, inch, Whitworth, NPT and BSPT

Code	Range	Resolution	Accuracy	Repeatability
ISQ-TE100	0-100mm	0.1µm	2µm	0.5µm

## OPTIONAL ACCESSORY

Measuring pin	ISQ-TE100-A
Measuring prism	ISQ-TE100-B
Female center	ISQ-TE100-C
Clamp	ISQ-TE100-D
Setting disc	ISQ-TE100-E
60° find pointer	ISQ-TE100-F
55° find pointer	ISQ-TE100-G
Display unit	7108-30
Linear gage	7108-1

## Measuring pin (optional)



- To measure pitch diameter of external thread
- Each size is supplied in pair
- Hardness: 60±2HRC

Code	Pins included	Pin diameter(mm)
ISQ-TE100-A	21 pairs	0.170, 0.195, 0.220, 0.250, 0.290, 0.335, 0.390, 0.455, 0.530, 0.620, 0.725, 0.895, 1.100, 1.350, 1.650, 2.050, 2.550, 3.200, 4.000, 5.050, 6.350


## Measuring prism (optional)



- To measure minor diameter of external thread
- Each size is supplied in pair

Code	Prisms included	Size
ISQ-TE100-B	4 pairs	A, B, C, D (for different types and sizes of thread)

## Setting disc (optional)




- To set initial value

Code	Discs included	Disc diameter(mm)
ISQ-TE100-E	22 pcs	3, 5, 8, 12, 16, 20, 24, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100

To be continued

Continued from previous page


### Female center (optional)



- With small holes to support small workpieces without female centers
- Supplied in pair

Code
ISQ-TE100-C

### Find pointer (optional)



- To find measuring point of NPT or BSPT

Code	Angle $\beta$	Applicable thread
ISQ-TE100-F	60°	NPT
ISQ-TE100-G	55°	BSPT



### Display unit (optional)



Code	7108-1*
Display	8 digits
Character height	9mm
Dust/waterproof	IP20
Optional resolution	0.1 $\mu$ m

\* Refer to 7108-1 (page 274) for details


### Clamp (optional)



- To hold large workpieces with inner bore

Code	Clamps included	d	D	L	(mm)
ISQ-TE100-D	3 pcs	13.5	30	0-18	
		23	60	0-18	
		23	75	0-18	

### Linear gage (optional)



Code	7108-30*
Measuring range	30mm
Resolution	0.01 $\mu$ m
Accuracy	(0.5+L/60) $\mu$ m L is measuring length in mm
Dust/waterproof	IP50

\* Refer to 7108-30 (page 274) for details

# PROFILE PROJECTOR

Screen diameter: 300mm

X-Y travel: 150x50mm



ISP-Z3015




ISP-A1000E

digital readout of ISP-A1000E



- touch buttons
- USB data output to Excel and CAD
- show diagram directly




## OPTIONAL ACCESSORY




lens



rotary table  
(glass plate diameter 100mm)



overlay chart (protractor with 1°  
graduation, radius with 1mm increment)



holder with clamp



swivel center support




V-block with clamp



50mm reading scale  
(check magnification accuracy)



300mm calibration scale (check  
magnification accuracy together  
with 50mm reading scale or  
calibrate measuring accuracy)



blue filter



demo sample


















printer (only for ISP-A1000E)

To be continued

Continued from previous page

### SPECIFICATION

Code		ISP-Z3015		ISP-A1000E		
Edge detector		not included		included		
Lens	magnification	10X (included)	20X (optional)	50X (optional)	100X (optional)	
	view field	Ø30mm	Ø15mm	Ø6mm	Ø3mm	
	working distance	77.7mm	44.3mm	38.4mm	25.3mm	
Max. workpiece height		90mm	90mm	90mm	90mm	
Magnification accuracy		±0.08%				
Image		erect image				
Projector screen		diameter: Ø300mm				
		rotation range: 0°~360°, resolution: 1" or 0.01°				
		reference lines: cross-hairs				
Stage	metal stage size	340×152mm				
	glass stage size	196×96mm				
	X-Y stage travel	range: 150×50mm				
		resolution: 0.5µm				
	Z (focus) travel range	accuracy: (4+L/25)µm L is the measuring length in mm				
max. load capacity	90mm					
Illumination		contour illumination: 24V/150W halogen lamp, brightness is adjustable				
		surface illumination: 24V/150W halogen lamp				
Data processing unit	display	X-Y stage travel, screen rotation				
	output	RS232C		RS232C, USB (data output to Excel and CAD)		
	function		measure coordinate of point			measure coordinate of point
			measure coordinate of line			measure coordinate of line
			measure center coordinate, radius of circle with three points			measure center coordinate, radius of circle with three points
		measure distance between two objects			measure distance between two objects	
		measure angle with four points or two lines			measure angle with four points or two lines	
		set origin of coordinate			coordinate transform	
		coordinate transform			choose measurement object automatically according to the selective point and display the result	
	set midpoint of coordinate					
advanced function		—		Programming for batch measurements		
Power supply		110/220V, 50/60Hz				
Dimension (L×W×H)		550×770×110mm				
Weight		135kg				

### STANDARD DELIVERY

Main unit	1pc
10X lens with half-reflection mirror and oblique illuminator mirror	1pc
Overlay chart clip	4pcs
Foot-switch	1pc
Anti-dust cover	1pc
USB cable and software (only for ISP-A1000E)	1pc

### OPTIONAL ACCESSORY

20X lens with half-reflection mirror and oblique illuminator mirror	ISP-Z3015-LENS20X	Swivel center support	ISP-Z3015-SUPPORT
50X lens with half-reflection mirror	ISP-Z3015-LENS50X	V-block with clamp	ISP-Z3015-VBLOCK
100X lens with half-reflection mirror	ISP-Z3015-LENS100X	50mm reading scale	ISP-Z3015-SCALE50
Rotary table	ISP-Z3015-TABLE	300mm calibration scale	ISP-Z3015-RULE
Overlay chart	ISP-Z3015-CHART	Blue filter	ISP-Z3015-FILTER
Holder with clamp	ISP-Z3015-HOLDER	Demo sample	ISP-Z3015-DEMO
		Printer (only for ISP-A1000E)	ISP-A1000-PRINTER

# PROFILE PROJECTOR

Screen diameter: 300mm

X-Y travel: 200x100mm



ISP-AZ3020



edge detector

ISP-A5000E



- Adjust the focus by ascending and descending the projector head, the stage doesn't move up and down
- Maximum workpiece weight 50kg


### digital readout of ISP-A5000E

- touch buttons
- USB data output to Excel and CAD
- show diagram directly

### OPTIONAL ACCESSORY



lens



overlay chart (protractor with 1° graduation, radius with 1mm increment)



50mm reading scale (check magnification accuracy)



300mm calibration scale (check magnification accuracy together with 50mm reading scale or calibrate measuring accuracy)



demo sample



















printer (only for ISP-A5000E)

To be continued



Continued from previous page

**SPECIFICATION**

Code		ISP-AZ3020		ISP-A5000E		
Edge detector		not included		included		
Lens	magnification	10X (included)	20X (optional)	50X (optional)	100X (optional)	
	view field	Ø30mm	Ø15mm	Ø6mm	Ø3mm	
	working distance	77.7mm	44.3mm	38.4mm	25.3mm	
Max. workpiece height		100mm	100mm	100mm	100mm	
Magnification accuracy		±0.08%				
Image		erect image				
Projector screen		diameter: Ø300mm				
		rotation range: 0°~360°, resolution: 1' or 0.01°				
		reference lines: cross-hairs				
Stage	metal stage size	404×228mm				
	glass stage size	260×160mm				
	X-Y stage travel	range: 200×100mm				
		resolution: 0.5µm				
	Z(focus) travel range	accuracy: (3+L/75)µm L is the measuring length in mm				
max. load capacity	100mm					
Illumination		contour illumination: 24V/150W halogen lamp, brightness is adjustable				
		surface illumination: 24V/150W halogen lamp, brightness is adjustable				
Data processing unit	display	X-Y stage travel, screen rotation				
	output	RS232C		RS232C, USB (data output to Excel and CAD)		
	function	 measure coordinate of point	 measure coordinate of line		 measure coordinate of point	
		 measure center coordinate, radius of circle with three points	 measure distance between two objects		 measure coordinate of line	
 measure angle with four points or two lines		 set origin of coordinate		 measure center coordinate, radius of circle with three points		
 coordinate transform		 coordinate transform		 measure distance between two objects		
 set midpoint of coordinate				 measure angle with four points or two lines		
				 coordinate transform		
				 choose measurement object automatically according to the selective point and display the result		
advanced function		—		Programming for batch measurements		
Power supply		110/220V, 50/60Hz				
Dimension (L×W×H)		780×780×1100mm				
Weight		160kg				

**STANDARD DELIVERY**

Main unit	1pc
10X lens with half-reflection mirror and oblique illuminator mirror	1pc
Overlay chart clip	4pcs
Foot-switch	1pc
Anti-dust cover	1pc
USB cable and software (only for ISP-A5000E)	1pc

**OPTIONAL ACCESSORY**

20X lens with half-reflection mirror and oblique illuminator mirror	ISP-A5000-LENS20X
50X lens with half-reflection mirror	ISP-A5000-LENS50X
100X lens with half-reflection mirror	ISP-A5000-LENS100X
Overlay chart	ISP-A5000-CHART

50mm reading scale	ISP-A5000-SCALE50
300mm calibration scale	ISP-A5000-RULE
Demo sample	ISP-A5000-DEMO
Printer (only for ISP-A5000E)	ISP-A5000-PRINTER

# HORIZONTAL PROFILE PROJECTOR

Screen diameter: 300mm

X-Z travel: 200x100mm



ISP-W3020




ISP-A3000E

## OPTIONAL ACCESSORY



lens



overlay chart (protractor with 1° graduation, radius with 1mm increment)




50mm reading scale (check magnification accuracy)



## digital readout of ISP-A3000E

- touch buttons
- USB data output to Excel and CAD
- show diagram directly



demo sample




V-block with clamp



rotary table



300mm calibration scale (check magnification accuracy together with 50mm reading scale or calibrate measuring accuracy)



vise


















printer (only for ISP-A3000E)

To be continued

Continued from previous page

**SPECIFICATION**

Code		ISP-W3020	ISP-A3000E		
Edge detector		not included		included	
Lens	magnification	10X (included)	20X (optional)	50X (optional)	100X (optional)
	view field	Ø30mm	Ø15mm	Ø6mm	Ø3mm
	working distance	77.7mm	44.3mm	38.4mm	25.3mm
Magnification accuracy		±0.08%			
Projector screen		diameter: Ø300mm			
		rotation range: 0°~360°, resolution: 1' or 0.01°			
		reference lines: cross-hairs			
Stage	metal stage size	400×150mm			
	turning range	±15°			
	X-Z stage travel	range: 200×100mm			
		resolution: 0.5µm			
	Y (focus) travel range	accuracy: (4+L/25)µm L is the measuring length in mm			
max. load capacity	50kg				
Illumination		contour illumination: 24V/150W halogen lamp, brightness is adjustable			
		surface illumination: 12V/150W halogen lamp(with 2 fibers), position is adjustable			
Data processing unit	display	X-Z stage travel, screen rotation			
	output	RS232C		RS232C, USB (data output to Excel and CAD)	
	function	 measure coordinate of point	 measure coordinate of point		
		 measure coordinate of line	 measure coordinate of line		
 measure center coordinate, radius of circle with three points		 measure center coordinate, radius of circle with three points			
 measure distance between two objects		 measure distance between two objects			
 measure angle with four points or two lines		 measure angle with four points or two lines			
 set origin of coordinate		 coordinate transform			
 coordinate transform		 choose measurement object automatically according to the selective point and display the result			
 set midpoint of coordinate					
advanced function		—		Programming for batch measurements	
Power supply		110/220V, 50/60Hz			
Dimension (L×W×H)		1090×830×1010mm			
Weight		160kg			

**STANDARD DELIVERY**

Main unit	1pc
10X lens	1pc
Overlay chart clip	4pcs
Foot-switch	1pc
Anti-dust cover	1pc
USB cable and software (only for ISP-A3000E)	1pc

**OPTIONAL ACCESSORY**

20X lens	ISP-A3000-LENS20X
50X lens	ISP-A3000-LENS50X
100X lens	ISP-A3000-LENS100X
Overlay chart	ISP-A3000-CHART
50mm reading scale	ISP-A3000-SCALE50
300mm calibration scale	ISP-A3000-RULE

Demo sample	ISP-A3000-DEMO
V-block with clamp	ISP-A1000-VBLOCK
Rotary table	ISP-A3000-RTABLE
Vice	ISP-A3000-VISE
Printer (only for ISP-A3000E)	ISP-A3000-PRINTER

# HORIZONTAL PROFILE PROJECTOR

Screen diameter: 400mm

X-Z travel: 250x150mm



ISP-W4025



ISP-A7000E

## OPTIONAL ACCESSORY



lens



50mm reading scale  
(check magnification accuracy)



300mm calibration scale (check magnification accuracy together with 50mm reading scale or calibrate measuring accuracy)



Ø300mm overlay chart (protractor with 1° graduation, radius with 1mm increment)




demo sample (need rotary table)



V-block with clamp



rotary table




vise



printer (only for ISP-A7000E)

## digital readout of ISP-A7000E

















- touch buttons
- USB data output to Excel and CAD
- show diagram directly



To be continued

Continued from previous page

### SPECIFICATION

Code		ISP-W4025			ISP-A7000E		
Edge detector		not included			included		
Lens	magnification	5X (optional)	10X (standard)	20X (optional)	50X (optional)	100X (optional)	
	view field	Ø80mm	Ø40mm	Ø20mm	Ø8mm	Ø4mm	
	working distance	93.7mm	103.9mm	95.1mm	65.7mm	35mm	
Magnification accuracy		±0.08%					
Image		erect image					
Projector screen		diameter: Ø400mm					
		rotation range: 0°~360°, resolution: 1' or 0.01°					
		reference lines: cross-hairs					
Stage	metal stage size	450×200mm					
	turning range	±15°					
	X-Z stage travel	range: 250×150mm					
		resolution: 0.5µm					
	Y (focus) travel range	accuracy: (4+L/25)µm L is the measuring length in mm					
max. load capacity	100mm						
Illumination		contour illumination: 24V/150W halogen lamp, brightness is adjustable					
		surface illumination: 12V/150W halogen lamp (with 2 fibers), position is adjustable					
Data processing unit	display	X-Z stage travel, screen rotation					
	output	RS232C			RS232C, USB (data output to Excel and CAD)		
	function	 measure coordinate of point	 measure coordinate of line			 measure coordinate of point	
		 measure center coordinate, radius of circle with three points	 measure distance between two objects			 measure coordinate of line	
		 measure angle with four points or two lines	 set origin of coordinate			 measure center coordinate, radius of circle with three points	
		 coordinate transform	 set midpoint of coordinate			 measure distance between two objects	
		—	—			 measure angle with four points or two lines	
		—	—			 set origin of coordinate	
		—	—			 coordinate transform	
		—	—			 set midpoint of coordinate	
—	—			Programming for batch measurements			
Power supply		110/220V, 50/60Hz					
Dimension (L×W×H)		1215×646×1210mm					
Weight		240kg					

### STANDARD DELIVERY

Main unit	1pc
10X lens	1pc
Overlay chart clip	4pcs
Foot-switch	1pc
Anti-dust cover	1pc
USB cable and software (only for ISP-A7000E)	1pc

### OPTIONAL ACCESSORY

5X lens	ISP-W4025-LENS5X
20X lens	ISP-W4025-LENS20X
50X lens	ISP-W4025-LENS50X
100X lens	ISP-W4025-LENS100X
Ø300mm overlay chart	ISP-A3000-CHART
50mm reading scale	ISP-A3000-SCALE50

300mm calibration scale	ISP-A3000-RULE
Demo sample	ISP-A3000-DEMO
V-block with clamp	ISP-A1000-VBLOCK
Rotary table	ISP-A3000-RTABLE
Vice	ISP-A3000-VICE
Printer (only for ISP-A7000E)	ISP-A3000-PRINTER



# VISION MEASURING SYSTEM



ISD-V250



computer is not included



stylus calibration ball  
probe (optional), includes Ø2mm and Ø3mm styli, Ø25mm calibration ball, measuring accuracy is 10µm



lens with coaxial light (optional, must be mounted in factory)

## SPECIFICATION

Code	ISD-V150	ISD-V250	ISD-V300
Measuring range (X×Y×Z)	150×100×200mm	250×150×200mm	300×200×200mm
Stage size	354×228mm	450×280mm	500×330mm
Stage glass size	210×160mm	306×196mm	350×250mm
Resolution of X/Y/Z axis	0.5µm		
Accuracy of X/Y axis	≤(2.5+L/100)µm (L is the measuring length in mm)		
Repeatability of X/Y axis	2µm		
Objective	0.7X ~ 4.5X (zoom)		
Working distance	92mm		
Magnification	33X ~ 195X (on 19" monitor)		
Camera	1/3" color CCD, 1.5M pixel		
Illumination	surface and contour with adjustable LED		
Max. height of workpiece	160mm		
Max. weight of workpiece	20kg		
Operation system	Windows 7		
Drive method	manual		
Power supply	110/220V, 50/60Hz		
Dimension(L×W×H)	560×540×850mm	760×600×900mm	760×600×900mm
Weight	100kg	120kg	140kg

## STANDARD DELIVERY

Main unit	1pc
Video card with dongle	1pc
Software disc	1pc
Calibration glass chart	1pc
Laser positioner	1pc
Clay	1pc
Foot switch	1pc
Anti-dust cover	1pc

## OPTIONAL ACCESSORY

<b>0.5X auxiliary objective</b>	Code: <b>ISD-V-OB05X</b> Working distance: 175mm Magnification: 16.5 ~ 97.5X (on 19" monitor)
<b>2X auxiliary objective</b>	Code: <b>ISD-V-OB02X</b> Working distance: 36mm Magnification: 66 ~ 390X (on 19" monitor)
<b>Probe</b>	Code: <b>ISD-V-PROBE</b> Includes Ø2mm and Ø3mm styli, Ø25mm calibration ball
<b>Lens with coaxial light</b>	Code: <b>ISD-V-LENS</b> (must be mounted in factory)

To be continued














Continued from previous page

## SOFTWARE


■ **Operation system:** Windows 7

■ **Language:** English

■ **Single measuring tools:**


- |   |  |   |  |
|---|--|---|--|
|  | measure coordinate of point                          |  | measure center coordinate, diameter and area of circle |
|  | measure distance between two points                  |  | measure length and diameter of arc                     |
|  | measure center coordinate and axis length of ellipse |  | measure length, width and area of rectangle            |
|  | measure length, width and diameter of key slot       |  | measure width and diameter of ring                     |
|  | measure length of open curve                         |  | measure length and area of close curve                 |
|  | measure focus distance of surface                    |  | measure distance of two elements                       |
|  | measure angle of two lines                           |   |  |

■ **Combined measuring tools:**



measure distance and angle of two elements


■ **Focus indicator:**




■ **Profile detection:**




■ **Edge-detection:**



■ **Coordinate transfer:**




■ **CAD measuring:**




Input CAD drawing and set reference, then move the stage to make the target box in the center of crosshair, the software will do automatic measurement

■ **Contour scanning:**




■ **Data export to CAD, EXCEL and WORD**



CAD


	Constant	Actual	Nominal	Dev	Up/Down	Unit	State
Start X	0.8172	0.8172	0				
Start Y	0.8007	0.8007	0				
Start Z	0.0000	0.0000	0				
Start R1	0	0	0				
Start M	0.0000	0.0000	0				
Start N	0	0	0				
Length	0.0000	0.0000	0				
Angle A	90	90.0000	0.0000				

EXCEL



WORD

# VISION MEASURING SYSTEM CODE ISD-A100-P



- Measures small workpiece (less than 15mm) easily and accurately



calibration block (included)



X-Y stage (included)

## SPECIFICATION

<b>Objective</b>	0.75X~5X (zoom)	
<b>Auxiliary objective</b>	1X (included)	0.5X (included)
<b>Focus distance</b>	82mm	175mm
<b>View field (diagonal length)</b>	1.15mm~7.5mm	2.3mm~15mm
<b>Magnification (19" widescreen display)</b>	44X~280X	22X~140X
<b>Camera</b>	CMOS (color)	
<b>Resolution (pixel)</b>	1280×1024 (1.3M)	
<b>Output</b>	USB2.0	
<b>Accuracy</b>	4µm	
<b>Repeatability</b>	2µm	
<b>Illumination</b>	surface: adjustable ring LED    contour: adjustable LED	
<b>Power supply *</b>	220V, 50/60Hz	
<b>Dimension (L×W×H)</b>	300×350×450mm	
<b>Weight</b>	2.8kg	

\* Add "-U" on code No. when power supply is 110V, 50/60Hz

## STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>Software disc</b>	1pc
<b>X-Y stage (travel: 74×60mm)</b>	1pc
<b>Calibration block</b>	1pc
<b>0.5X auxiliary objective</b>	1pc


<b>1X auxiliary objective</b>	1pc
<b>Ø95mm glass plate</b>	1pc
<b>Ø95mm white/black plate</b>	1pc
<b>Anti-dust cover</b>	1pc

To be continued



Continued from previous page


## SOFTWARE



- **Operation system:** Windows 7/XP, screen resolution is 1366×768
- **Language:** English, Chinese
- **Output to CAD, EXCEL and WORD**
- **Input CAD, to compare with workpieces**

-  coordinate transform














### Focus indicator:

-  fast and accurately find the focus distance, eliminate the visual error

### Single measuring tools:


-  measure coordinate of point
-  measure length of line
-  measure center coordinate, radius, diameter and area of circle
-  measure length and diameter of arc

### Combined measuring tools:


-  measure distance between two points
-  find midpoint of a line
-  measure distance from point to line
-  find tangent lines between point and circle
-  measure intersection point between two lines
-  measure angle between two lines
-  find angular bisector between two lines
-  measure distance between two lines
-  measure distance from circle to line
-  find intersection points between circle and line
-  find intersection points between two circles
-  measure distance between two circles
-  find tangent lines between two circles

### Edge-detection:


Point tool



Box tool



Circle tool




# WiFi DIGITAL MEASURING MICROSCOPE CODE ISM-WF200



STAND (code: ISM-WSTD, optional)



calibration rule (graduation 1mm)



calibration rule (graduation 0.1mm)

- Maximum working distance is 5m under WiFi mode
- Can be connected to multiple iPads or computers at the same time under WiFi mode
- Can take pictures and videos
- Supplied with software

## SPECIFICATION

<b>Magnification</b>	10X~200X
<b>Pixel</b>	1.3M (resolution: 1280×1024)
<b>Illumination</b>	built-in adjustable LED
<b>Power supply</b>	built-in rechargeable battery

## MAGNIFICATION, FOCUS DISTANCE, VIEW FIELD AND ACCURACY

Magnification	Focus distance	View field	Accuracy
50X	21mm	8.1×6.4mm	30μm
100X	13mm	3.9×3.1mm	15μm
150X	16mm	2.6×2.1mm	10μm
200X	19mm	1.8×1.5mm	8μm



connected to iPad by WiFi



connected to computer by WiFi



connected to computer by USB cable

## STANDARD DELIVERY

<b>Microscope</b>	1pc
<b>Base support</b>	1pc
<b>Focus support ring for 80X/150X</b>	1pc
<b>Focus support ring for 60X/200X</b>	1pc
<b>Calibration rule (graduation 0.1mm)</b>	1pc
<b>Calibration rule (graduation 1mm)</b>	1pc
<b>USB cable and software</b>	1pc
<b>AC/DC adapter</b>	1pc




## OPTIONAL ACCESSORY


<b>Stand</b>	<b>ISM-WSTD</b>
--------------	-----------------

To be continued

### 1 Software ISM-PAD (for iPad by WiFi)












■ Measuring tools:


-  measure length of line or distance between two points
-  measure radius, girth and area of circle with three points
-  measure angle



### 2 Software ISM-WF Partner (for computer by WiFi)













■ Measuring tools:


-  measure length of line or distance between two points
-  measure radius, girth and area of circle with three points
-  measure area of polygon
-  measure angle with two lines
-  measure distance between point and line
-  measure radius, girth and area of circle with two points
-  measure radius, length and angle of arc
-  measure angle with three points
-  measure area of rectangle
-  measure radius, girth and area of circle with center point
-  measure length of continuous line








### 3 Software ISM-PRO (for computer by USB cable)

■ Measuring tools:

-  measure length of line or distance between two points
-  measure distance between point and line
-  measure area of rectangle
-  measure length of continuous line
-  measure radius, length and angle of arc
-  measure angle with three points
-  measure distance between two circles
-  add text
-  measure distance between two parallel lines
-  measure radius, girth and area of circle
-  measure angle with two lines
-  add number with circle




■ Edge detection measurement:

-  detect line automatically, and calculate length
-  detect circle automatically, and calculate radius, girth and area
-  detect two lines automatically, and calculate angle
-  detect arc automatically, and calculate radius, angle and arc length
-  detect two parallel lines automatically and calculate distance

■ Comparison:

Create line, angle or circle with desired size, to compare with workpieces



# DIGITAL MEASURING MICROSCOPE



- Can take pictures and videos
- Supplied with software

## SPECIFICATION


Code	ISM-PM200SB	ISM-PM600SB	ISM-PM160LA
Magnification	10X~200X	450X~600X	35X~160X
Type	short focus distance	short focus distance	long focus distance
Focus support	included	not included	not included
Calibration rule	graduation 0.1 and 1mm	graduation 0.1mm	graduation 0.1 and 1mm
Pixel	2M (resolution: 1600×1200)		
Illumination	built-in adjustable LED		
Power supply	USB 2.0 cable (voltage required: 5±0.1V)		



focus support



calibration rule (graduation 1mm)



calibration rule (graduation 0.1mm)

## MAGNIFICATION, FOCUS DISTANCE, VIEW FIELD AND ACCURACY

ISM-PM200SB			
Magnification	Focus distance	View field	Accuracy
50X	21mm	8.1×6.4mm	30μm
100X	13mm	3.9×3.1mm	15μm
150X	16mm	2.6×2.1mm	10μm
200X	19mm	1.8×1.5mm	8μm

ISM-PM600SB			
Magnification	Focus distance	View field	Accuracy
450X	1.4mm	0.85×0.67mm	6μm
500X	5.5mm	0.76×0.61mm	6μm
550X	8.6mm	0.69×0.55mm	5μm
600X	11.5mm	0.63×0.51mm	5μm

ISM-PM160LA			
Magnification	Focus distance	View field	Accuracy
50X	62mm	8.1×6.4mm	30μm
100X	45mm	3.9×3.1mm	15μm
160X	50mm	2.4×1.9mm	10μm



put the digital microscope directly on the workpiece for inspection and measurement

stand (included)



To be continued

Continued from previous page

## SOFTWARE



- **Language:** English, Japanese, Korean, German, Turkey, Portuguese, Chinese
- **Operation system:** Windows 7/8/XP/ Vista
- **Measuring tools:**

- measure length of line or distance between two points
- measure length of continuous line
- measure radius, length and angle of arc
- measure distance between two circles

- measure distance between point and line
- measure area of rectangle
- measure angle with three points
- add text

- measure distance between two parallel lines
- measure radius, girth and area of circle
- measure angle with two lines
- add number with circle

- **Edge detection measurement:**


- detect line automatically, and calculate length
- detect arc automatically, and calculate radius, angle and arc length
- detect two lines automatically, and calculate angle

- detect circle automatically, and calculate radius, girth and area
- detect two parallel lines automatically and calculate distance


- **Comparison:**

Create line, angle or circle with desired size, to compare with workpieces.


- create line





- create angle



- create circle with tolerance



- **Data export to CAD or Excel:**



# TV DIGITAL MICROSCOPE



**ISM-TV200 (with wire)**




**ISM-TV200W (wireless)**

**STAND (code: ISM-WSTD, optional)**



- Connected to TV directly
- For observation, cannot take pictures and videos




## SPECIFICATION

Code	ISM-TV200	ISM-TV200W
Type	with wire	wireless (maximum transmission distance 5m)
Magnification	10X~200X (on 17" TV)	
Pixel	0.35M	
Illumination	adjustable brightness LED	
Focus	supplied with focus ring, stand (ISM-WSTD) is optional	
Power supply	DC	built-in rechargeable battery

## MAGNIFICATION, FOCUS DISTANCE, VIEW FIELD

ISM-TV200			ISM-TV200W		
Magnification	Focus distance	View field	Magnification	Focus distance	View field
50X	21mm	8.1×6.4mm	60X	19mm	6.9×5.2mm
100X	13mm	3.9×3.1mm	80X	16mm	5.0×3.8mm
150X	16mm	2.6×2.1mm	150X	16mm	2.6×2.1mm
200X	19mm	1.8×1.5mm	200X	19mm	1.8×1.5mm

# ZOOM STEREO MICROSCOPE



ISM-ZS50

## SPECIFICATION

Code	ISM-ZS50	ISM-ZS50T
Optical tube	binocular	trinocular
Eyepiece (wide field)	10X (view field: Ø22mm)	
Objective	0.8X~5X (zoom)	
Zoom ratio	1:6.3	
Pupil distance	55~75mm (adjustable)	
Diopter adjustment	±5 diopter (two eyepieces)	
Working distance of objective	115mm	
Max. workpiece height	215mm	
Illumination	adjustable reflected and transmitted LED light	
Power supply	110/220V, 50/60Hz	
Dimension (L×W×H)	290×260×480mm	
Weight	4.9kg	

## STANDARD DELIVERY

Main unit	1pc
WF 10X eyepiece	2pcs
Ø100mm glass plate	1pc
Ø100mm white/black plate	1pc
Anti-dust cover	1pc

## OPTIONAL ACCESSORY

Auxiliary objective	0.5X	ISM-ZS50-OB05X
	2X	ISM-ZS50-OB2X
Eyepiece	10X dividing eyepiece (0.1mm/div.)	ISM-ZS50-EPD10X
	WF15X (view field: Ø16mm)	ISM-ZS50-EP15X
	WF20X (view field: Ø12mm)	ISM-ZS50-EP20X
Digital camera		ISM-D500

## ZOOM STEREO MICROSCOPE



### SPECIFICATION

<b>Code</b>	<b>ISM-ZS30</b>
<b>Optical tube</b>	binocular
<b>Eyepiece (wide field)</b>	10X (view field: Ø20mm)
<b>Objective</b>	1X~4.5X (zoom)
<b>Zoom ratio</b>	1:4.5
<b>Pupil distance</b>	55~75mm (adjustable)
<b>Diopter adjustment</b>	±5 diopter (two eyepieces)
<b>Working distance of objective</b>	97mm
<b>Max. workpiece height</b>	147mm
<b>Illumination</b>	adjustable reflected and transmitted LED light
<b>Power supply</b>	110/220V, 50/60Hz
<b>Dimension (L×W×H)</b>	260×190×400mm
<b>Weight</b>	4.3kg

### STANDARD DELIVERY




<b>Main unit</b>	1pc
<b>WF 10X eyepiece</b>	2pcs
<b>Ø95mm glass plate</b>	1pc
<b>Ø95mm white/black plate</b>	1pc
<b>Anti-dust cover</b>	1pc

### OPTIONAL ACCESSORY

<b>Auxiliary objective</b>	<b>0.5X</b>	<b>ISM-ZS30-OB05X</b>
	<b>0.63X</b>	<b>ISM-ZS30-OB06X</b>
	<b>0.75X</b>	<b>ISM-ZS30-OB07X</b>
	<b>2X</b>	<b>ISM-ZS30-OB2X</b>
<b>Eyepiece</b>	<b>10X dividing eyepiece (0.1mm/div.)</b>	<b>ISM-ZS30-EPD10X</b>
	<b>WF15X (view field: Ø16mm)</b>	<b>ISM-ZS50-EP15X</b>
	<b>WF20X (view field: Ø12mm)</b>	<b>ISM-ZS50-EP20X</b>
<b>Digital camera</b>		<b>ISM-D500</b>



# HIGH MAGNIFICATION MICROSCOPE CODE ISM-M600-P



- For high magnification observation
- Reflected and transmitted illumination can work at the same time
- Objectives 40X, 60X are spring type

## SPECIFICATION

<b>Eyeiece (wide field)</b>	10X (view field: Ø18mm)				
<b>Objective (plan achromatic)</b>	5X	10X	20X	40X	60X
<b>Numerical aperture</b>	0.12	0.25	0.40	0.60	0.75
<b>Working distance</b>	18.4mm	8.8mm	8.6mm	3.7mm	1.34mm
<b>Stage</b>	double layer with sample clamp				
	size: 160×140mm				
	travel: 75×50mm (graduation: 0.1mm)				
<b>Pupil distance</b>	53~75mm				
<b>Diopter adjustment</b>	±5 diopter (one eyepiece)				
<b>Illumination</b>	reflected and transmitted: 6V/20W halogen lamp, brightness is adjustable				
<b>Power supply *</b>	220V, 50/60Hz				
<b>Dimension (L×W×H)</b>	450×300×350mm				
<b>Weight</b>	11kg				

\* Add "-U" on code No. when power supply is 110V, 50/60Hz

## STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>Anti-dust cover</b>	1pc
<b>Filter (blue/green/frosted glass)</b>	1pc of each

## OPTIONAL ACCESSORY

<b>Objective</b>	<b>PL80X</b>	<b>ISM-MTM-OB80X</b>
	<b>PL100X (dry type)</b>	<b>ISM-MTM-OB100X</b>
<b>10X dividing eyepiece (0.1mm/div.)</b>		<b>ISM-MTM-EPD10X</b>
<b>WF16X eyepiece</b>		<b>ISM-MTM-EP16X</b>

<b>WF20X eyepiece</b>	<b>ISM-MTM-EP20X</b>
<b>Camera adapter (1X)</b>	<b>ISM-M600-ADAPTER</b>
<b>Digital camera</b>	<b>ISM-D500</b>

# HIGH MAGNIFICATION MICROSCOPE CODE ISM-M1000



- For high magnification observation
- Kohler illumination system provides uniform illumination field
- Objectives 20X, 40X, 100X are spring type

## SPECIFICATION

<b>Eyepiece (wide field)</b>	10X (view field: Ø18mm)			
<b>Objective (plan achromatic)</b>	10X	20X	40X	100X (oil type)
<b>Numerical aperture</b>	0.25	0.40	0.60	1.25
<b>Working distance</b>	8.8mm	8.6mm	3.3mm	0.33mm
<b>Stage</b>	double layer			
	size: 180×150mm			
	travel: 15×15mm			
<b>Pupil distance</b>	53~75mm			
<b>Diopter adjustment</b>	±5 diopter (one eyepiece)			
<b>Illumination</b>	6V/20W halogen lamp			
<b>Power supply *</b>	220V, 50/60Hz			
<b>Dimension (L×W×H)</b>	385×300×440mm			
<b>Weight</b>	11kg			

\* Add "-U" on code No. when power supply is 110V, 50/60Hz

## STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>Oil for 100X objective</b>	1 bottle
<b>Anti-dust cover</b>	1pc
<b>Filter (blue/green/yellow)</b>	1pc of each

## OPTIONAL ACCESSORY

<b>Objective</b>	<b>PL50X</b>	<b>ISM-MTM-OB50X</b>
	<b>PL60X</b>	<b>ISM-MTM-OB60X</b>
	<b>PL80X</b>	<b>ISM-MTM-OB80X</b>
	<b>PL100X (dry type)</b>	<b>ISM-MTM-OB100X</b>
<b>10X dividing eyepiece ( 0.1mm/div.)</b>		<b>ISM-MTM-EPD10X</b>

<b>WF16X eyepiece</b>	<b>ISM-MTM-EP16X</b>
<b>WF20X eyepiece</b>	<b>ISM-MTM-EP20X</b>
<b>Camera adapter (1X)</b>	<b>ISM-M1000-ADAPTER</b>
<b>Digital camera</b>	<b>ISM-D500</b>


## DIGITAL CAMERA CODE ISM-D500



adapter 0.45X



connector  $\varnothing 23.2/\varnothing 30\text{mm}$



calibration rule (graduation 0.1mm)

- Inserted into eyepiece tube or camera connector of microscopes
- Supplied with software

### SPECIFICATION

Sensor	1/2.5" CMOS
Pixel	5M
Resolution	2592×1944 or 1296×972
Frame rate	3fps (2592×1944) 12fps (1296×972)
Exposure	manual or auto, exposure time is adjustable
SNR	41dB
Power supply	USB
Weight	400g


### STANDARD DELIVERY

Main unit	1pc
Adapter 0.45X	1pc
Calibration rule (graduation 0.1mm)	1pc
Connector $\varnothing 23.2/\varnothing 30\text{mm}$	1pc
USB cable	1pc
Software disc	1pc

### OPTIONAL ACCESSORY

Connector $\varnothing 23.2/\varnothing 30.5\text{mm}$	ISM-DCA-CON
--	-------------

### SOFTWARE FOR DIGITAL CAMERA (INCLUDED)



### Measuring Tools:

- measure distance between two points
- measure angle with three points
- measure circle
- measure rectangle
- calibration

- Can take pictures and videos
- Exposure/gain/gamma/saturation/colour adjustment
- Image process feature: zoom in/out, image flip and so on

# METALLURGICAL MICROSCOPE


## CODE ISM-M2000



- For high magnification observation and metallurgical image analysis
- Infinite optical system, can add optical accessories like polarizer, analyzer, DIC(code ISM-M2000-DIC) into optical path without image quality influence
- Objective can be used in both bright field and dark field
- Kohler illumination system provides uniform illumination field
- Three working modes: 100% eyepiece observation, 100% camera observation, both eyepiece and camera observation (80% illuminance for camera and 20% illuminance for eyepiece)



adapter 0.5X (included)



calibration rule (graduation 0.01mm)

### SPECIFICATION

<b>Eyepiece (wide field)</b>	10X (view field: Ø22mm)				
<b>Objective (plan achromatic)</b>	5X (included)	10X (included)	20X (included)	50X (included)	100X (included)
<b>Numerical aperture</b>	0.12	0.25	0.40	0.75	0.90
<b>Working distance</b>	10mm	10mm	5mm	1.3mm	0.7mm
<b>Stage</b>	double layer, size: 160×140mm, travel: 75×50mm (graduation: 0.1mm)				
<b>Kohler illumination</b>	12V/50W halogen lamp, brightness is adjustable with polarizer and analyzer, built-in green, yellow, blue, gray and frosted glass				
<b>Pupil distance</b>	48 ~ 75mm				
<b>Diopter adjustment</b>	±5 diopter (two eyepieces)				
<b>Power supply</b>	110/220V, 50/60Hz				
<b>Dimension (L×W×H)</b>	647×268×376mm				
<b>Weight</b>	12kg				

### STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>10X dividing eyepiece (0.1mm/div.)</b>	1pc
<b>Calibration rule (graduation 0.01mm)</b>	1pc
<b>Camera adapter</b>	1pc
<b>Adapter 0.5X</b>	1pc
<b>Anti-dust cover</b>	1pc

### OPTIONAL ACCESSORY

<b>15X eyepiece (view field: Ø16mm)</b>	ISM-M2000-15X
<b>20X eyepiece (view field: Ø12mm)</b>	ISM-M2000-20X
<b>DIC</b>	ISM-M2000-DIC
<b>Metallurgical image analysis software and camera</b>	ISM-MAS100

# METALLURGICAL IMAGE ANALYSIS SOFTWARE AND CAMERA CODE ISM-MAS100


application example



- Inserted into eyepiece tube or camera connector of microscopes
- Supplied with software for metallurgical structure analysis, measurement and evaluation




adapter 0.5X (optional)




calibration rule (optional, graduation 0.01mm)

metallurgical image analysis software (included)

measure the average grain size of metal



measure and evaluate the graphite size of ductile iron



## SPECIFICATION

Sensor	1/2" CMOS
Pixel	300M
Resolution	2048×1536
Frame rate	6fps
Exposure	manual or auto, exposure time is adjustable
SNR	43dB
Power supply	USB
Weight	400g

## STANDARD DELIVERY

Camera	1pc
USB cable and software	1pc

## OPTIONAL ACCESSORY

Calibration rule (graduation 0.01mm)	ISM-MAS-SCALE
Adapter 0.5X	ISM-MAS-ADAPTER

# PORTABLE MEASURING MICROSCOPE



## SPECIFICATION

Code	ISM-PM20	ISM-PM40	ISM-PM50	ISM-PM100
Total magnification	20X	40X	50X	100X
Eyepiece	10X with graduation	10X with graduation	10X with graduation	10X with graduation
Objective (achromatic)	2X (numerical aperture: 0.05)	4X (numerical aperture: 0.1)	5X (numerical aperture: 0.12)	10X (numerical aperture: 0.25)
Working distance	17.2mm	18mm	17.6mm	7mm
Graduation	0.05mm	0.025mm	0.02mm	0.01mm
Viewing field	Ø9mm	Ø4.5mm	Ø3.6mm	Ø1.8mm
Focus range	30mm			
Illumination	LED light			
Diameter of base	Ø63mm			
Height	210mm			
Weight	650g			

## STANDARD DELIVERY

Main unit	1pc
Pen light	1pc
Battery (AAA)	2pcs

TUNGSTEN WIRE WEAVED CABLE  
RESISTANCE TO BREAK AND WEAR

IP65  
WATERPROOF

# MOTORIZED 360° SWIVEL VIDEOSCOPE CODE ISV-4000D


ATTENTION: THE CABLE CAN BE BENT  
BUT CAN'T BE SET AT A FIXED SHAPE



bend in any direction




360° swivel in clockwise  
and counter-clockwise




bend within ±120°


- Motorized joystick to bend the lens in any direction
- Lens bending is automatically locked when joystick is hold for more than 3 seconds



lens with LED  
adjustable illumination



focus distance



angle of view: 110°

## SPECIFICATION

Lens	diameter(D)	6mm
	focus distance(F)	15mm ~ ∞
	illumination	6pcs LED
	pixel	0.41M
	dust/waterproof	IP65
	bend control	motorized joystick
Cable	length	1.5m
	type	tungsten wire weaved cable
Main unit	function	take picture, take video
	file format	picture: JPG, video: AVI
	image process	brightness, image quality zoom (1X, 2X, 3X)
	memory	8G SD card
	output	TV, USB
	power supply	rechargeable battery (for 4 hours working) AC/DC adapter (for continuous working)
Weight		1kg

## STANDARD DELIVERY

Main unit	1pc
Cable with lens	1pc
8G SD card	1pc
AC/DC adapter	1pc
Video output cable	1pc
USB cable	1pc

# MANUAL 360° SWIVEL VIDEOSCOPE


STEEL WIRE WEAVED CABLE  
RESISTANCE TO BREAK AND WEAR

IP65  
WATERPROOF


ATTENTION: THE CABLE CAN BE BENT BUT CAN'T BE SET AT A FIXED SHAPE



bend in any direction



360° swivel in clockwise and counter-clockwise



bend within ±120°

steel wire weaved cable length: 1.5m

lens with adjustable LED illumination



power on/off

3.5" LCD

USB port

charger port

video output

SD card

take video


manual joystick to bend the lens in any direction

zoom


bend lock

LED brightness adjustment


take picture



lens with LED adjustable illumination



focus distance



angle of view: 100°



base (optional)

## SPECIFICATION

Code	ISV-2000D	ISV-2001D	ISV-3000D	ISV-3001D	
Lens	diameter(D)	6.5mm		4.5mm	
	focus distance(F)	15mm ~ ∞		8 ~ 80mm	
	illumination	8pcs LED		6pcs LED	
	pixel	0.35M			
	dust/waterproof	IP65			
Cable	bend control	manual joystick			
	length	1.5m	3m	1.5m	3m
Main unit	type	steel wire weaved cable			
	function	take picture, take video			
	file format	picture: JPG, video: AVI			
	image process	brightness, image quality zoom (1X, 2X, 3X, 4X, 5X)			
	memory	8G SD card			
	output	TV, USB			
Weight	power supply	rechargeable battery (for 2 hours working) AC/DC adapter (for continuous working)			
		650g	800g	600g	700g

## STANDARD DELIVERY

Main unit	1pc
Cable with lens	1pc
8G SD card	1pc
AC/DC adapter	1pc
Video output cable	1pc
USB cable	1pc


## OPTIONAL ACCESSORY

Base	ISV-2000D-BASE
------	----------------




**IP67**  
WATERPROOF


# VIDEOSCOPE CODE ISV-VP60




focus distance: 10~60mm




angle of view: 56°




lens can be bent in two directions ( ±150°)



35° mirror (included)



45° mirror (optional)



55° mirror (optional)



front view



side view (with mirror)

## SPECIFICATION

<b>Lens</b>	diameter	6mm
	dust/waterproof	IP67
	pixel	0.3M
	resolution	640×480
	frame rate	30fps
<b>Cable</b>	length	1m
	type	semi-rigid
<b>Main unit</b>	function	take picture, take video
	file format	picture: JPG , video: ASF
	image process	mirror, rotate, zoom (1.5X, 2X)
	memory	4G SD card
	output	TV, USB
	power supply	4×AA batteries
<b>Weight</b>		550g

## STANDARD DELIVERY







<b>Main unit</b>	1pc
<b>Cable with lens</b>	1pc
<b>35° mirror</b>	1pc
<b>4G SD card</b>	1pc
<b>AA battery</b>	4pcs
<b>Video output cable</b>	1pc
<b>USB cable</b>	1pc

## OPTIONAL ACCESSORY

<b>45° mirror</b>	ISV-VP60-R45
<b>55° mirror</b>	ISV-VP60-R55


# SIDE VIEW VIDEOSCOPE (RIGID) CODE ISV-RV

**IP57**  
WATERPROOF



focus distance: 4.5~5.5mm

side view



angle of view: 54°

## SPECIFICATION

<b>Diameter (D)</b>	5.5mm
<b>Length (L)</b>	350mm
<b>Dust/waterproof probe</b>	IP57
<b>Pixel</b>	0.3M
<b>Resolution</b>	640×480
<b>Frame rate</b>	30fps
<b>Function</b>	take picture, take video
<b>File format</b>	picture: JPG, video: AVI
<b>Memory</b>	2G SD card
<b>Output</b>	TV, USB
<b>Power supply</b>	rechargeable battery (for 3 hours working)
<b>Weight</b>	570g

## STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>2G SD card</b>	1pc
<b>AC/DC adapter</b>	1pc
<b>Video output cable</b>	1pc
<b>USB cable</b>	1pc



STEEL WIRE WEAVED CABLE  
RESISTANCE TO BREAK AND WEAR

ATTENTION: THE CABLE CAN BE BENT  
BUT CAN'T BE SET AT A FIXED SHAPE


IP65  
WATERPROOF

# VIDEOSCOPE CODE ISV-E10


OPTIONAL CABLE  
LENGTH 3M, 5M AND 10M




focus distance: 15~100mm



angle of view: 54°



front view



35° mirror (optional)

45° mirror (included)

60° mirror (optional)



side view (with mirror)

## SPECIFICATION

Lens	diameter	5.5mm
	pixel	0.3M
	resolution	640×480
	frame rate	30fps
Cable	length	1m
	type	steel wire weaved cable
Main unit	function	take picture, take video
	file format	picture: JPG, video: AVI
	image process	brightness, contrast, color saturation
	memory	2G SD card
	output	TV, USB
	power supply	rechargeable battery (for 3 hours working)
Weight		450g

## STANDARD DELIVERY

Main unit	1pc
Cable with lens	1pc
2G SD card	1pc
45° mirror	1pc
AC/DC adapter	1pc
Video output cable	1pc
USB cable	1pc
Lens cleaning kit	1pc


## OPTIONAL ACCESSORY

35° mirror	ISV-E55-M35
60° mirror	ISV-E55-M60



# VIDEOSCOPE CODE ISV-E20

**IP57**  
WATERPROOF

lens with 8pcs LED  
adjustable illumination




the cable has high illumination and can be set at any shape.  
it is suitable to observe large internal space like turbocharger.



focus distance: 20~50mm

memory cable  
length: 1m



angle of view: 54°



45° mirror (optional)



hook (optional)



magnet pick up (optional)

## SPECIFICATION

Lens	diameter (D)	12mm
	pixel	0.4M
	resolution	720×682
	frame rate	30fps
Cable	length	1m
	type	memory (can be set at any shape)
Main unit	function	take picture, take video
	file format	picture: JPG, video: AVI
	image process	brightness, contrast, color saturation
	memory	2G SD card
	output	TV, USB
	power supply	rechargeable battery (for 3 hours working)
Weight		600g

## STANDARD DELIVERY

Main unit	1pc
Cable with lens	1pc
2G SD card	1pc
AC/DC adapter	1pc
Video output cable	1pc
USB cable	1pc
Lens cleaning kit	1pc


## OPTIONAL ACCESSORY

45° mirror	ISV-E20-MIRROR
Hook	ISV-E20-HOOK
Magnet pick up	ISV-E20-MAGNET


ATTENTION: RESISTANCE TO ACID AND ALKALI LIQUID (CONSULT IS NEEDED)

IP68  
WATERPROOF


## PIPE VIDEOSCOPE CODE ISV-VP280





focus distance: 10mm-∞



angle of view: 150°



can turn at least two times  
in the pipe (>Ø40mm)



Ø100mm brush (included)  
fixed on the lens to clean  
the internal wall of pipes



Ø50mm centering ring (optional)  
fixed on the lens to  
center lens in the pipe



vertical

horizontal

### SPECIFICATION

Lens	diameter	28mm
	dust/waterproof	IP68
	pixel	0.3M
	resolution	640×480
	frame	30fps
Cable	length	22m
	dust/waterproof	IP68
	type	semi-rigid
Main unit	function	take picture and video
	file format	picture: JPG, video: ASF
	image process	mirror, rotate, zoom (1.5X, 2X)
	memory	4G SD card
	output	TV, USB
	power supply	4×AA batteries
Weight		5kg

### STANDARD DELIVERY

Main unit	1pc
Cable with lens	1pc
Stand	1pc
4G SD card	1pc
Ø100mm brush	1pc
AA battery	4pcs
Vdieo output cable	1pc
USB cable	1pc

### OPTIONAL ACCESSORY


Ø50mm centering ring	ISV-VP280-R50
Ø150mm brush	ISV-VP280-B150

# RIGID BORESCOPE

**IP67**  
WATERPROOF



ISV-1H4300



- Focus distance: 2mm, depth of view: 5~100mm
- Dust/waterproof level: IP67
- Can be used in the liquid with temperature -10°C~85°C

## SPECIFICATION

Code	Length (L)	View direction (α)	Diameter (D)	Angle of view(θ)
ISV-1H4170	174mm	0°	4mm	≥60°
ISV-1H4173	174mm	30°		
ISV-1H4177	174mm	70°		
ISV-1H4179	166mm	90°		
ISV-1H4300	302mm	0°		
ISV-1H4303	302mm	30°		
ISV-1H4307	302mm	70°		
ISV-1H4309	297mm	90°		

Code	Length (L)	View direction (α)	Diameter (D)	Angle of view(θ)
ISV-1H6200	209mm	0°	6mm	≥70°
ISV-1H6203	209mm	30°		
ISV-1H6207	209mm	70°		
ISV-1H6209	166mm	90°		
ISV-1H6320	328mm	0°		
ISV-1H6323	328mm	30°		
ISV-1H6327	328mm	70°		
ISV-1H6329	330mm	90°		



LED light handle (optional)



adjustable LED light source (optional)



camera (optional)


## OPTIONAL ACCESSORY

LED light handle	ISV-1HLED
Adjustable LED light source	ISV-1LED1
Camera	ISV-1CAM

- For rigid endoscopes

**SPECIFICATION**

<b>Power</b>	3W
<b>Battery</b>	3.7V rechargeable battery (for 2 hours working)
<b>Dimension</b>	120×27×27mm
<b>Weight</b>	300g



battery



charger



**LED LIGHT HANDLE  
CODE ISV-1HLED**

**STANDARD DELIVERY**

<b>Main unit</b>	1pc
<b>Battery</b>	1pc
<b>Charger</b>	1pc

- For rigid endoscopes
- High LED illumination and brightness is adjustable
- For long time work with lower noise

**SPECIFICATION**

<b>Color temperature</b>	5600K
<b>Cooling</b>	fan cooling
<b>Power</b>	AC110~220V, 50/60Hz
<b>Dimension</b>	400×300×112mm
<b>Weight</b>	7kg




**STANDARD DELIVERY**

<b>Main unit</b>	1pc
<b>1.8m optical fiber cable</b>	1pc



**ADJUSTABLE LED LIGHT SOURCE  
CODE ISV-1LED1**




- For rigid endoscopes
- Connected to computer USB port
- Auto-exposure, auto-gain, auto white balance
- Focus is adjustable

**SPECIFICATION**

<b>Sensor</b>	color CMOS
<b>Pixel</b>	1.3M
<b>Resolution</b>	1280×1024
<b>Frame rate</b>	15~50fps
<b>Software</b>	take picture, take video, zoom in, zoom out, image rotate
<b>Power supply</b>	USB



**CAMERA  
CODE ISV-1CAM**





**STANDARD DELIVERY**


<b>Camera</b>	1pc
<b>Connector</b>	1pc
<b>USB cable and software</b>	1pc

# FRONT VIEW BORESCOPE (RIGID) CODE ISV-HF4030

IP67  
WATERPROOF



adjustable focus distance:  
1mm~∞



angle of view: 53°



LED light source (optional)



camera (optional)

- Dust/waterproof level: IP67
- Lens can be used in the liquid with temperature -10°C~100°C
- LED light source is needed

## SPECIFICATION

Diameter (D)	4mm
Length (L)	300mm
Depth of view	>15mm
Dust/waterproof lens	IP67
Dimension	410×105×30mm
Weight	220g

## STANDARD DELIVERY

Main unit	1pc
Handle	1pc

## OPTIONAL ACCESSORY



LED light source	ISV-HL3000
Camera and software	ISV-HCAM






**IP67**  
WATERPROOF


## ROTARY SIDE VIEW BORESCOPE (RIGID) CODE ISV-HR6032



adjustable focus distance:  
3.5mm-∞



angle of view: 53°



observe internal wall  
of small holes



LED light source (optional)



camera (optional)

- Lens can rotate 350°
- Dust/waterproof level: IP67
- Lens can be used in the liquid with temperature -10°C~100°C
- LED light source is needed

### SPECIFICATION

Diameter (D)	6mm
Length (L)	320mm
Depth of view	>15mm
Dust/waterproof lens	IP67
Dimension	430x105x30mm
Weight	300g

### STANDARD DELIVERY


Main unit	1pc
Handle	1pc

### OPTIONAL ACCESSORY

LED light source	ISV-HL3000
Camera and software	ISV-HCAM

# BORESCOPE WITH MIRROR (RIGID)



IP67  
WATERPROOF




ISV-HM6025(with handle)

ISV-HM2817 (without handle)

front view lens



front view



side view (with mirror)

- Front view, side view with mirror
- Dust/waterproof level: IP67
- Lens can be used in the liquid with temperature -10°C~80°C
- LED light source is needed



LED light source (optional)



camera (optional)

## SPECIFICATION

Code	ISV-HM2817	ISV-HM4023	ISV-HM6025	ISV-HM6051
Diameter (D)	2.8mm	4mm	6mm	6mm
Length (L)	175mm	232mm	258mm	490mm
Focus distance (F)	2mm~∞(adjustable)	6mm~∞(adjustable)	4mm~∞(adjustable)	3mm~∞(adjustable)
Angle of view (α)	22°	22°	34°	48°
Depth of view	>15mm			
Dust/waterproof lens	IP67			
Handle	without	included	included	included
Dimension	235×33×30mm	368×105×30mm	368×105×30mm	610×105×30mm
Weight	55g	250g	260g	300g

## STANDARD DELIVERY

Main unit	1pc
Handle (except ISV-HM2817)	1pc
90° mirror	1pc


## OPTIONAL ACCESSORY

LED light source	ISV-HL3000
Camera and software	ISV-HCAM




**IP67**  
WATERPROOF


## OBLIQUE VIEW BORESCOPE (RIGID)




view direction



angle of view



focus distance



observe the bottom of small blind holes



LED light source (optional)



camera (optional)

- Small diameter, used to observe small space
- Dust/waterproof level: IP67
- Lens can be used in the liquid with temperature  $-10^{\circ}\text{C}\sim 100^{\circ}\text{C}$
- Supplied with protection sleeve
- LED light source is needed

### SPECIFICATION

Code	ISV-HP1911	ISV-HP2811	ISV-HP2817
Diameter (D)	1.9mm	2.8mm	2.8mm
Length (L)	110mm	110mm	175mm
Focus distance (F)	0.5mm~∞ (adjustable)	0.5mm~∞ (adjustable)	0.5mm~∞ (adjustable)
View direction	30°		
Angle of view (α)	70°	80°	80°
Depth of view	3 ~ 40mm		
Dust/waterproof lens	IP67		
Dimension	162x33x30mm	228x33x30mm	228x33x30mm
Weight	55g	60g	65g

### STANDARD DELIVERY

Main unit	1pc
Protection sleeve	1pc

### OPTIONAL ACCESSORY

LED light source	ISV-HL3000
Camera and software	ISV-HCAM

## LED LIGHT SOURCE CODE ISV-HL3000



filter (optional)

- For rigid borescopes
- High LED illumination and brightness is adjustable
- For long time work with lower noise



### SPECIFICATION

Brightness	470lm
Color temperature	5800K
Cooling method	fan cooling
Operating temperature	10~40°C
Working life	30000h
Power supply	12V DC, 5420mA
Dimension	170x196x98mm
Weight	3.8kg

### STANDARD DELIVERY

Main unit	1pc
2.3m optical fiber cable	1pc

### OPTIONAL ACCESSORY

Red filter	ISV-HL3000-RED
Green filter	ISV-HL3000-GREEN
Yellow filter	ISV-HL3000-YELLOW
Blue filter	ISV-HL3000-BLUE
3500K color temperature filter	ISV-HL3000-3500K

## CAMERA CODE ISV-HCAM



- For rigid borescopes
- Connected to computer USB port
- High quality CCD
- Auto-exposure, auto-gain, auto white balance
- Focus is adjustable



### SPECIFICATION

Sensor	color CCD
Pixel	0.3M
Resolution	640×480
Frame rate	75fps
Focus distance	18~35mm
Software	take picture, take video, zoom in, zoom out, mirror, image rotate
Power supply	USB
Dimension	95x50x50mm
Weight	150g

### STANDARD DELIVERY

Camera	1pc
Connector	1pc
USB cable and software	1pc

# COATING THICKNESS GAGE CODE ISO-2000FN

connected to probe



**main unit  
ISO-2000FN**

SUITABLE FOR SMALL SURFACES,  
CONCAVE OR CONVEX SURFACES



**magnetic induction probe Fe (optional)  
ISO-2000FN-FE**



**eddy current probe NFe (optional)  
ISO-2000FN-NFE**

- Suitable for small surfaces, concave or convex surfaces
- Magnetic induction probe (Fe) is to measure the thickness of non-magnetic coating on magnetic substrate  
Substrate: iron, steel, magnetic stainless steel (does not include non-magnetic stainless steel)  
Coating: zinc, copper, chrome-tin, plastic powder, paint (does not include nickel)
- Eddy current probe (NFe) is to measure the thickness of non-conductive coating on non-magnetic metal substrate  
Substrate: copper, aluminum, zinc, non-magnetic stainless steel  
Coating: plastic powder, paint, anodizing



standard foil  
(included)

## SPECIFICATION

Measuring range	magnetic induction probe (Fe)	0~2000 $\mu$ m
	eddy current probe (NFe)	0~800 $\mu$ m
Accuracy		$\pm(1.5+2\%L)\mu$ m      L is measuring thickness in $\mu$ m
Resolution		0.1 $\mu$ m (range<100 $\mu$ m)
		1 $\mu$ m (range 100~1000 $\mu$ m)
		10 $\mu$ m (range $\geq$ 1000 $\mu$ m)
Repeatability		1 $\mu$ m (range 0~1000 $\mu$ m)
		10 $\mu$ m (range $\geq$ 1000 $\mu$ m)
Measuring mode		continuous or single
Calibration mode		four points calibration
Minimum substrate thickness		magnetic induction probe (Fe): 0.2mm, eddy current probe (NFe): 0.05mm
Minimum measuring area		5x5mm, calibration should be made on workpiece without coating, test stand (optional) is recommended in order to have same position for calibration and measurement
Power supply		2x1.5V AA batteries
Dimension of main unit		122x65x22mm
Weight of main unit		150g

## STANDARD DELIVERY

Main unit	1pc
Zero calibration block for Fe probe	1pc
Zero calibration block for NFe probe	1pc
Standard foil	7pcs
Battery (AA)	2pcs

## OPTIONAL ACCESSORY

Magnetic induction probe (Fe)	ISO-2000FN-FE
Eddy current probe (NFe)	ISO-2000FN-NFE
Test stand	ISO-2000FN-STAND

# COATING THICKNESS GAGE CODE ISO-1500F

ATTENTION:  
BASIC MODEL

MEASURE NON-MAGNETIC COATING  
ON MAGNETIC SUBSTRATE



zero calibration block (included)



calibration foil (included)



printer (optional)

- To measure the thickness of any non-magnetic coating on magnetic substrate  
substrate: steel, iron, magnetic stainless steel (non-magnetic stainless steel is not included)  
coating: zinc, copper, chrome, tin, plastic, paint (nickel is not included)
- Low and high limits with judgement
- Calculate average value automatically

## SPECIFICATION

Measuring range	0~1500μm	
Accuracy	±(2%L+2)μm L is measuring thickness in μm	
Resolution	0.1μm (range<1000μm)	
	1μm (range≥1000μm)	
Repeatability	±1μm (range<100μm)	
	±(1%L)μm (range≥100μm) L is measuring thickness in μm	
Measuring mode	continuous and single	
Calibration mode	zero calibration, one point calibration, two points calibration	
Minimum substrate thickness	0.5mm	
Minimum measuring area	10×10mm	
Minimum curvature radius of workpiece	concave	30mm
	convex	5mm
Output	USB	
Memory	1200	
Power supply	3×1.5V AAA batteries (power off automatically )	
Dimension	88×67×30mm	
Weight	120g	

## STANDARD DELIVERY

Main unit	1pc
Zero calibration block	1pc
Calibration foil (50μm, 100μm, 500μm, 1000μm, 1500μm)	1set
1.5V AAA battery	3pcs
Software and USB cable	1pc

## OPTIONAL ACCESSORY

Printer	ISH-DS-PRINTER
---------	----------------

DATA  
OUTPUT

# ULTRASONIC THICKNESS GAGE (THROUGH COATING) CODE ISU-300D




CAN PENETRATE NON-METALLIC COATING AND  
MEASURE THE THICKNESS OF METAL SUBSTRATE




- Two measuring modes, Echo-Echo (E-E) and Transmit-Echo (T-E):
  - E-E is applicable for non-metallic coating (such as paint, plastic resin, etc.) on metal substrate, can penetrate coating and measure the thickness of substrate
  - T-E is to measure the thickness of material without coating, such as metal, plastic, glass nylon resin, ceramics, rubber, ice, etc.
- Low and high limits with judgment
- Average calculation of maximum 9 readings
- Memory of maximum 500 readings

Transmit-Echo mode (T-E)




Echo-Echo mode (E-E)



couplant (included)    transducer ISU-T04 (optional)    transducer ISU-T06 (optional)



transducer ISU-T12 (optional)



transducer ISU-T13 (optional)



## SPECIFICATION

Measuring range	E-E mode: coating thickness 0 ~ 1mm, substrate thickness 4 ~ 25mm
	T-E mode: substrate thickness 1.5 ~ 200mm
Resolution	0.01mm (range<100mm) 0.1mm (range≥100mm)
Repeatability	0.03mm (range<100mm) 0.1mm (range≥100mm)
Accuracy	±0.04mm (range<10mm) ±(0.04+H/1000)mm (range 10~100mm) ±H/333mm (range≥100mm) H is the thickness to be measured in mm
Velocity	1000 ~ 9999m/s
Power supply	2×1.5V AAA batteries
Dimension	116×64×27mm
Weight	220g

## STANDARD DELIVERY

Main unit	1pc
Transducer ISU-T07	1pc
Battery (AAA)	2pcs
Couplant (for ISU-T04, ISU-T06, ISU-T07, ISU-T12)	1 bottle
USB cable and software disc	1pc of each

## OPTIONAL ACCESSARY

Transducer	ISU-T04, ISU-T06, ISU-T12, ISU-T13
Couplant ( for ISU-T13)	ISU-HT5-COULPLANT

## SPECIFICATION OF TRANSDUCERS

Code	Mode	Frequency	Diameter (Ød)	Measuring range	Minimum size of pipe for measurement (diameter × wall thickness)	Applicable temperature	Application
ISU-T07	T-E E-E	5.0MHz	10.8mm	T-E mode: 1.5 ~ 200mm E-E mode: 4 ~ 25mm	T-E mode: 20×1.2mm E-E mode: 20×4mm	<60°C	general use
ISU-T04	T-E	10.0MHz	6mm	0.7 ~ 20mm	10×1mm	<60°C	for small tube
ISU-T06	T-E	7.5MHz	8.5mm	0.7 ~ 50mm	15×1.2mm	<60°C	for thin material
ISU-T12	T-E	2.0MHz	16.3mm	2 ~ 400mm	30×4mm	<60°C	for casting iron
ISU-T13	T-E	5.0MHz	13mm	2 ~ 200mm	25×3mm	<350°C	for high temperature

# ULTRASONIC THICKNESS GAGE CODE ISU-250C

DATA  
OUTPUT



- Measure the thickness from one side of object, suitable for pipe, tank, etc.
- Applicable material: metal, plastic, glass, nylon, resin, ceramic, rubber, ice
- Low and high limits with judgement
- Average calculation of maximum 9 readings
- Memory of maximum 5000 readings with location number




couplant (included)



transducer ISU-T04 (optional)



transducer ISU-T06 (optional)



transducer ISU-T12 (optional)



transducer ISU-T13 (optional)

## SPECIFICATION

Resolution	0.01mm (range<100mm)
	0.1mm (range≥100mm)
Repeatability	0.03mm (range<100mm)
	0.1mm (range≥100mm)
Accuracy	±0.04mm (range<10mm)
	±(0.04+H/1000)mm (range10~100mm)
	±H/333mm (range≥100mm)
	H is the thickness to be measured in mm
Velocity	1000 ~ 9999m/s
Power supply	2×1.5V AAA batteries
Dimension	64×116×27mm
Weight	220g

## STANDARD DELIVERY

Main unit	1pc
Transducer ISU-T08	1pc
Battery (AAA)	2pcs
Couplant (for ISU-T04, ISU-T06, ISU-T08, ISU-T12)	1 bottle
USB cable and software disc	1pc of each

## OPTIONAL ACCESSORY

Transducer	ISU-T04, ISU-T06 ISU-T12, ISU-T13
Couplant (for ISU-T13)	ISU-HT5-COUPPLANT

## SPECIFICATION OF TRANSDUCERS

Code	Frequency	Diameter (Ød)	Measuring range	Minimum size of pipe for measurement (diameter × wall thickness)	Applicable temperature	Application
ISU-T08	5.0MHz	10.8mm	0.8 ~ 300mm	20×1.2mm	<60°C	general use
ISU-T04	10.0MHz	6mm	0.7 ~ 20mm	10×1mm	<60°C	for small tube
ISU-T06	7.5MHz	8.5mm	0.7 ~ 50mm	15×1.2mm	<60°C	for thin material
ISU-T12	2.0MHz	16.3mm	2 ~ 400mm	30×4mm	<60°C	for casting steel
ISU-T13	5.0MHz	13mm	2 ~ 200mm	25×3mm	<350°C	for high temperature





DATA  
OUTPUT

ATTENTION:  
BASIC MODEL

## ULTRASONIC THICKNESS GAGE CODE ISU-200D



- Measure the thickness from one side of object, suitable for pipe, tank, etc.
- Applicable material: metal, plastic, glass, nylon, resin, ceramic, rubber, ice
- Low and high limits with judgement
- Memory of maximum 500 readings

### SPECIFICATION

Resolution	0.01mm (range<100mm)
	0.1mm (range≥100mm)
Accuracy	±0.05mm (range<10mm)
	±(0.01+0.5%H)mm (range≥10mm) H is the thickness to be measured in mm
Velocity	1000-9999m/s
Power supply	3×AAA batteries
Dimension	151×70×24mm
Weight	200g

### STANDARD DELIVERY

Main unit	1pc
Transducer ISU-200D-N05	1pc
Couplant	1 bottle
USB cable and software	1pc

### OPTIONAL ACCESSORY

Transducer	ISU-200D-N02
	ISU-200D-N07
	ISU-200D-W05
	ISU-200D-HT5

### SPECIFICATION OF TRANSDUCERS

Code	Frequency	Diameter (Ød)	Measuring range	Minimum size of pipe for measurement (diameter × wall thickness)	Applicable temperature	Application
ISU-200D-N05	5.0MHz	12mm	0.8~300mm	25×3mm	<60°C	general use
ISU-200D-N02	2.0MHz	17mm	2~400mm	30×4mm	<60°C	for casting steel
ISU-200D-N07	7.5MHz	8mm	0.75~40mm	15×1.2mm	<60°C	for thin material
ISU-200D-W05	5.0MHz	10mm	0.8~230mm	20×1.2mm	<60°C	for wall thickness
ISU-200D-HT5	3.0MHz	15mm	3~100mm	25×3mm	<300°C	for high temperature

# DIGITAL LED TACHOMETER/STROBOSCOPE CODE ISQ-TS120K



proximity trigger (included)



- Make cyclical motion (rotation, vibration, etc.) objects to appear slow-moving or stationary
- On-line inspection or observation for moving objects
- Measure the rotation or vibration speed and frequency
- Can be triggered from outside by moving objects, make LED flash frequency same as the rotation or vibration

## SPECIFICATION

<b>Flash frequency range</b>	60 ~ 120000FPM (Flash Per Minute), 1 ~ 2000Hz	
<b>Resolution</b>	<b>FPM</b>	0.1FPM (<100000FPM), 1FPM (≥100000FPM)
	<b>HZ</b>	0.01Hz (<200Hz), 0.1Hz (≥200Hz)
<b>Setting accuracy</b>	±0.01%	
<b>Phase shift increment</b>	3°	
<b>Flash pulse duration time</b>	0.1 ~ 2.5°	
<b>LED light</b>	3pcs American CREE 10W lamp	
<b>LED life</b>	3 ~ 5 years	
<b>Trigger mode</b>	internal and external	
<b>Power supply</b>	built-in rechargeable battery or AC/DC adapter	
<b>Dimension</b>	208×70×60mm	
<b>Weight</b>	380g	

## STANDARD DELIVERY


<b>Main unit</b>	1pc
<b>AC/DC adapter</b>	1pc
<b>Proximity trigger</b>	1pc

**IP52**  
WATERPROOF


## LASER DISTANCE METER CODE ISN-L70




- Large display with backlight
- Unit: m, ft, in
- Distance, area, volume and height measurement
- With continuous measuring mode to track maximum and minimum value
- Automatic power-off: laser 30s, main unit 180s




distance measurement



area measurement



volume measurement



height measurement

### SPECIFICATION

Measuring range	0.05~70m
Accuracy	±1.5mm
Resolution	1mm
Measuring speed	0.5 second
Dust/waterproof	IP52
Laser type	650nm, Class II, <1mW
Beam size	25mm@30m
Memory	20 measuring data
Power supply	2xAA batteries, for 10000 measurements
Dimension (L×W×H)	110×45×30mm
Weight	130g

### STANDARD DELIVERY


Main unit	1pc
Battery (AA)	2pcs
Strap	1pc
Carrying bag	1pc

# SURFACE ROUGHNESS TESTER CODE ISR-S1000B




CAN MEASURE WAVINESS AND  
CURVED SURFACE WITH RADIUS>5MM

DATA  
OUTPUT

CUSTOM-MADE  
PROBES ARE AVAILABLE



- 48 roughness parameters according to ISO-4287, JIS-B0601, ISO-12085, JIS-B0631
- Automatic probe leveling
- Measuring range up to 1000µm, can measure grit and shot blasting
- Traverse length up to 50mm
- The probe can rotate from -90° to +90°
- Color touch screen, display roughness values, profile and curves
- Can print roughness values, profile and curves
- Memory of maximum 1000 results
- Can set tolerance



## ROUGHNESS VALUE, PROFILE AND DATA ANALYSIS



measurement result




total profile graph




R graph




P graph




W graph



Rmr, Pmr, Wmr analysis



R6c, P6c, W6c analysis



Rel. Rmr, Rel. Pmr, Rel. Wmr analysis

To be continued

**SPECIFICATION**

<b>Parameters</b>	Ra, Rq, Rt, Rz, Rp, Rv, Rc, Rsk, Rku, RSm, Rδc RPC, Pa, Pq, Pt, Pp, Pv, Pc, Psm, Pδc, Ppc, Wa Wq, Wt, Wz, Wp, Wv, Wc, Wsm, Wδc, Wpc, Rk Rpk, Rvk, Mr1, Mr2, Rmax, R3z, R3zm, R, AR Rx, Aw, Rke, Rpke, Rvke, Mr1e, Mr2e	
<b>Range</b>	1000µm	
<b>Accuracy</b>	±3%	
<b>Resolution (Ra)</b>	0.001µm	
<b>Probe</b>	type	inductive
	stylus radius/angle	5µm/90°
	stylus material	diamond
<b>Measuring force</b>	0.75mN	
<b>Measuring unit</b>	µm/µin	
<b>Cut off</b>	0.08/0.25/0.8/2.5/8mm	
<b>Number of cut-offs</b>	1-19 (cut off 0.08/0.25/0.8/2.5mm) 1-5 (cut off 8mm)	
<b>Traverse speed</b>	0.5mm/s or 1mm/s	
<b>Memory</b>	1000 measurement results	
<b>Output</b>	USB	
<b>Power</b>	built-in rechargeable battery	
<b>Dimension (LxWxH)</b>	320×210×80mm	
<b>Weight</b>	2.2kg	


**STANDARD DELIVERY**

<b>Main unit</b>	1pc
<b>Probe driver</b>	1pc
<b>Standard probe</b>	1pc
<b>Calibration block</b>	1pc
<b>AC/DC adapter</b>	1pc

**OPTIONAL ACCESSORY**

<b>Probe</b>	see details
<b>USB cable and software</b>	ISR-S-SOFTWARE

measuring software (optional)



measuring software (optional), can control the roughness tester, display roughness values, profile and curve, data statistics


To be continued

**SPECIFICATION OF PROBES**

<p><b>standard probe (included, support is removable), code ISR-SB10B</b></p> <p>with probe support, measure plane surfaces, holes and cylinders with diameter &gt; 10mm</p> <p>remove probe support, measure holes with diameter &gt; 4mm, can measure curved surfaces, narrow spaces and waviness</p>		
<p><b>small hole probe (optional), code ISR-SB60B</b></p> <p>without probe support, measure holes with diameter &gt; 2mm and depth &lt; 30mm, can measure curved surfaces, narrow spaces and waviness</p>	<p><b>internal angle probe (optional), code ISR-SB70B</b></p> <p>without probe support, measure internal angles, can measure curved surfaces, narrow spaces and waviness</p>	<p><b>knife edge probe (optional), code ISR-SB130B</b></p> <p>without probe support, measure knife edges and small rods</p>
<p><b>deep groove probe (optional), code ISR-SB150B</b></p> <p>without probe support, measure curved surfaces and grooves with depth &lt; 13mm, can measure curved surfaces, narrow spaces and waviness</p>		<p><b>deep groove probe (optional), code ISR-SB120B</b></p> <p>measure grooves with depth &lt; 20mm</p>
<p><b>hole probe (optional), code ISR-SB30B</b></p> <p>measure plane surfaces and holes with diameter &gt; 4mm and depth &lt; 20mm</p>	<p><b>small rod probe (optional), code ISR-SB40B</b></p> <p>measure small rods with diameter 1-5mm</p>	<p><b>transverse probe (optional), code ISR-SB50B</b></p> <p>transverse measurement for plane surfaces, cylinders and grooves</p>
<p><b>deep hole probe (optional), code ISR-SB80B</b></p> <p>measure holes with diameter &gt; 4.5mm and depth &lt; 35mm</p>	<p><b>cylinder/hole probe (optional), code ISR-SB110B</b></p> <p>measure cylinders and holes with radius &gt; R5mm</p>	<p><b>groove probe (optional), code ISR-SB20B</b></p> <p>measure plane surfaces and grooves</p>




# SURFACE ROUGHNESS TESTER CODE ISR-S1000A




- 38 roughness parameters according to ISO-4287, JIS-B0601, ISO-12085, JIS-B0631
- Automatic probe leveling
- Measuring range up to 1000 $\mu$ m, can measure grit and shot blasting
- Traverse length up to 25mm
- The probe can be set at 90° or 270°, for transverse measurement
- Color touch screen, display roughness values, profile and curves
- Can print roughness values, profile and curves
- Memory of maximum 1000 results
- Can set tolerance

View	Parameters	M	1
Ra	2.908 $\mu$ m	RSm	391 $\mu$ m
Rq	3.509 $\mu$ m	R&C	20.233 $\mu$ m
Rt	20.233 $\mu$ m	Rmr1	0.0%
Rz	12.548 $\mu$ m	RPC(0.00)	34/cm
Rp	5.039 $\mu$ m	Pa	6.013 $\mu$ m
Rv	7.509 $\mu$ m	Pq	6.810 $\mu$ m
Rc	9.310 $\mu$ m	Pt	26.256 $\mu$ m
Rsk	-0.105	Pp	13.265 $\mu$ m
Rku	2.729	Pv	12.991 $\mu$ m


measurement result




total profile graph




R graph




P graph



Rmr, Pmr analysis



R&C, P&C analysis



Rel. Rmr, Rel. Pmr analysis

To be continued

## SURFACE ROUGHNESS TESTER CODE ISR-S1000A

### SPECIFICATION

<b>Parameters</b>	Ra, Rq, Rt, Rz, Rp, Rv, Rc, Rsk, Rku, Rsm Rδc, RPC, Pa, Pq, Pt, Pp, Pv, Pc, PSm, Pδc PPc, Rk, Rpk, Rvk, Mr1, Mr2, Rmax, R3z, R3zm R, AR, Rx, Aw, Rke, Rpke, Rvke, Mr1e, Mr2e	
<b>Range</b>	1000µm	
<b>Accuracy</b>	±3%	
<b>Resolution (Ra)</b>	0.001µm	
<b>Probe</b>	type	inductive
	stylus radius/angle	5µm/90°
	stylus material	diamond
<b>Measuring force</b>	0.75mN	
<b>Measuring unit</b>	µm/µin	
<b>Cut off</b>	0.08/0.25/0.8/2.5mm	
<b>Number of cut-offs</b>	1-19 (cut off 0.08/0.25/0.8mm)	
	1-9 (cut off 2.5mm)	
<b>Traverse speed</b>	0.5mm/s or 1mm/s	
<b>Memory</b>	1000 measurement results	
<b>Output</b>	USB	
<b>Power</b>	built-in rechargeable battery	
<b>Dimension (L×W×H)</b>	320×210×80mm	
<b>Weight</b>	2.2kg	

### STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>Probe driver</b>	1pc
<b>Standard probe</b>	1pc
<b>Calibration block</b>	1pc
<b>AC/DC adapter</b>	1pc

### OPTIONAL ACCESSORY

<b>Probe</b>	see details
<b>USB cable and software</b>	ISR-S-SOFTWARE
<b>Test stand</b>	ISR-S400-DK



test stand (optional)

### measuring software (optional)













measuring software (optional), can control the roughness tester, display roughness values, profile and curve, data statistics

To be continued



**SPECIFICATION OF PROBES**

Unit: mm

<p><b>standard probe (included), code ISR-SB10A</b></p>  <p>measure plane surfaces, holes and cylinders with diameter &gt; Ø10mm</p>	<p><b>small roughness probe (optional), code ISR-SB10A-R2</b></p>  <p>measure surfaces with small roughness</p>
<p><b>groove probe (optional), code ISR-SB20A</b></p>  <p>measure plane surfaces and grooves</p>	<p><b>deep groove probe (optional), code ISR-SB120A</b></p>  <p>measure grooves with depth &lt; 20mm</p>
<p><b>small hole probe (optional), code ISR-SB30A</b></p>  <p>measure plane surfaces and holes with diameter &gt; Ø4mm and depth &lt; 20mm</p>	<p><b>deep hole probe (optional), code ISR-SB80A</b></p>  <p>measure holes with diameter &gt; Ø4.5mm and depth &lt; 35mm</p>
<p><b>small rod probe (optional), code ISR-SB40A</b></p>  <p>measure small rods with diameter Ø1~5mm</p>	<p><b>cylinder/hole probe (optional), code ISR-SB110A</b></p>  <p>measure cylinders and holes with radius &gt; R5mm</p>
<p><b>transverse probe (optional), code ISR-SB50A</b></p>  <p>transverse measurement for plane surfaces, cylinders and grooves</p>	<p><b>internal angle probe (optional), code ISR-SB140A</b></p>  <p>measure internal angles</p>

# ROUGHNESS TESTER CODE ISR-S500






CUSTOM-MADE  
PROBES ARE AVAILABLE

DATA  
OUTPUT



## ROUGHNESS VALUE, PROFILE AND DATA ANALYSIS

<b>Ra</b>	<b>5.315 <math>\mu\text{m}</math></b>
<b>Rq</b>	<b>6.134 <math>\mu\text{m}</math></b>
<b>Rt</b>	<b>27.050 <math>\mu\text{m}</math></b>
<b>Rp</b>	<b>11.574 <math>\mu\text{m}</math></b>



- Automatic probe leveling
- Language: English, French, German, Italian, Spanish, Portuguese
- 30 roughness parameters
- Can set tolerance
- Measuring range up to 600 $\mu\text{m}$ , can measure grit and shot blasting
- Traverse length up to 16mm
- The probe can be set at 90° or 270°, for transverse measurement
- Color screen, display roughness values, profile and curves
- Memory of maximum 1000 results

Pmr analysis



measuring software (optional), can control the roughness tester, display roughness values, profile and curve, data statistics



transverse measurement



adjustable stand (included)



probe cover (included), can put the small workpieces directly on the probe for measurement



printer (optional), print measuring results and roughness graph

To be continued

**SPECIFICATION**

<b>Parameters</b>	Ra, Rq, Rt, Rp, Rv, Rz, Rc, RSm, R $\delta$ c, R $\rho$ c Pa, Pq, Pt, Pp, Pv, Pc, Psm, P $\delta$ c, P $\rho$ c, Rk, Rpk Rvk, Mr1, Mr2, Rmax, R3z, R3zm, R, AR, Rx	
<b>Range</b>	600 $\mu$ m	
<b>Accuracy</b>	$\pm$ 3%	
<b>Resolution (Ra)</b>	0.001 $\mu$ m	
<b>Probe</b>	<b>type</b>	inductive
	<b>stylus radius/angle</b>	5 $\mu$ m/90°
	<b>stylus material</b>	diamond
<b>Measuring force</b>	0.75mN	
<b>Measuring unit</b>	$\mu$ m/ $\mu$ in	
<b>Cut off</b>	0.25/0.8/2.5mm	
<b>Number of cut-offs</b>	1-10 (cut off 0.25/0.8mm)	
	1-5 (cut off 2.5mm)	
<b>Traverse speed</b>	1mm/s	
<b>Memory</b>	1000 measurement results	
<b>Output</b>	USB	
<b>Power</b>	built-in rechargeable battery	
<b>Dimension (L×W×H)</b>	122×53×75mm	
<b>Weight</b>	590g	

**OPTIONAL ACCESSORY**

<b>Extension rod</b>	ISR-S400-ER100
<b>Probe</b>	see details
<b>Printer</b>	ISR-S500-PRINTER
<b>USB cable and software</b>	ISR-S-SOFTWARE
<b>Test stand</b>	ISR-S400-DK

**STANDARD DELIVERY**

<b>Main unit</b>	1pc
<b>Standard probe</b>	1pc
<b>Calibration block</b>	1pc
<b>Adjustable stand</b>	1pc
<b>AC/DC adapter</b>	1pc
<b>Probe cover</b>	1pc



test stand (optional)

**SPECIFICATION OF PROBES**

Unit: mm


<p><b>standard probe (included)</b></p> <p>measure plane surfaces, holes and cylinders with diameter &gt; <math>\varnothing</math>10mm</p>	<p><b>small roughness probe, code ISR-S400-SB10R2</b></p> <p>measure surfaces with small roughness</p>
<p><b>extension rod, code ISR-S400-ER100</b></p> <p>for long holes</p>	

To be continued

**SPECIFICATION OF PROBES**


Unit: mm

**groove probe, code ISR-S400-SB20**




measure plane surfaces and grooves

**deep groove probe, code ISR-S400-SB120**




measure grooves with depth < 20 mm

**small hole probe, code ISR-S400-SB30**




measure plane surfaces and holes with diameter > 0.4 mm and depth < 20 mm

**deep hole probe, code ISR-S400-SB80**




measure holes with diameter > 0.5 mm and depth < 35 mm

**small rod probe, code ISR-S400-SB40**




measure small rods with diameter  $\varnothing 1 \sim 5$  mm

**cylinder/hole probe, code ISR-S400-SB110**




measure cylinders and holes with radius > 5 mm

**transverse probe, code ISR-S400-SB50**



transverse measurement for plane surfaces, cylinders and grooves

**internal angle probe, code ISR-S400-SB140**



measure internal angles



DATA  
OUTPUT

CUSTOM-MADE  
PROBES ARE AVAILABLE

# ROUGHNESS TESTER



**ISR-S300**  
(probe can't be changed)



**ISR-S400**  
(probe can be changed)

- Automatic probe leveling
- Language: English, French, German, Italian, Spanish, Portuguese
- 12 roughness parameters
- Can set tolerance
- Measuring range up to 400µm, can measure grit and shot blasting
- Traverse length up to 16mm
- The probe can be set at 90° or 270°, for transverse measurement
- Memory of maximum 100 results



transverse measurement



adjustable stand (included)




measuring software (optional), can control the roughness tester, display roughness values, profile and curve, data statistics



probe cover (included), can put the small workpieces directly on the probe for measurement



printer (optional), print measuring results and roughness graphic



test stand (optional)

To be continued

## SPECIFICATION

<b>Code</b>	<b>ISR-S300</b>	<b>ISR-S400</b>
<b>Remark</b>	probe can't be changed	probe can be changed
<b>Parameters</b>	Ra, Rq, Rt, Rz, Rc, Rmax, Rsm, Rpc, Rmr, R, AR, Rx	
<b>Range</b>	Ra: 0~100 $\mu$ m, Rt: 0.05~400 $\mu$ m	
<b>Accuracy</b>	$\pm 3\%$	
<b>Resolution (Ra)</b>	0.001 $\mu$ m	
<b>Probe</b>	<b>type</b>	inductive
	<b>stylus radius/angle</b>	5 $\mu$ m/90°
	<b>stylus material</b>	diamond
<b>Measuring force</b>	0.75mN	
<b>Measuring unit</b>	$\mu$ m/ $\mu$ in	
<b>Cut off</b>	0.25/0.8/2.5mm	
<b>Number of cut-offs</b>	1 to 5	
<b>Traverse speed</b>	1mm/s	
<b>Memory</b>	100 measurement results	
<b>Output</b>	USB	
<b>Power</b>	built-in rechargeable battery	
<b>Dimension(L×W×H)</b>	122×52×68mm	
<b>Weight</b>	650g	

## STANDARD DELIVERY


<b>Main unit</b>	1pc
<b>Standard probe</b>	1pc
<b>Calibration block</b>	1pc
<b>Adjustable stand</b>	1pc
<b>AC/DC adapter</b>	1pc
<b>Probe cover</b>	1pc

## OPTIONAL ACCESSORY

<b>Extension rod (only for ISR-S400)</b>	<b>ISR-S400-ER100</b>
<b>Probe (only for ISR-S400)</b>	see details
<b>Printer</b>	<b>ISR-S400-PRINTER</b>
<b>USB cable and software</b>	<b>ISR-S-SOFTWARE</b>
<b>Test stand</b>	<b>ISR-S400-DK</b>

## SPECIFICATION OF PROBES

Unit: mm



To be continued

**SPECIFICATION OF PROBES**

Unit: mm

<p><b>groove probe (for ISR-S400, optional) code ISR-S400-SB20</b></p> <p>measure plane surfaces and grooves</p>	<p><b>deep groove probe (for ISR-S400, optional) code ISR-S400-SB120</b></p> <p>measure grooves with depth &lt; 20 mm</p>
<p><b>small hole probe (for ISR-S400, optional) code ISR-S400-SB30</b></p> <p>measure plane surfaces and holes with diameter &gt; 0.4 mm and depth &lt; 20 mm</p>	<p><b>deep hole probe (for ISR-S400, optional) code ISR-S400-SB80</b></p> <p>measure holes with diameter &gt; 0.5 mm and depth &lt; 35 mm</p>
<p><b>small rod probe (for ISR-S400, optional) code ISR-S400-SB40</b></p> <p>measure small rods with diameter 1~5 mm</p>	<p><b>cylinder/hole probe (for ISR-S400, optional) code ISR-S400-SB110</b></p> <p>measure cylinders and holes with radius &gt; R5 mm</p>
<p><b>transverse probe (for ISR-S400, optional) code ISR-S400-SB50</b></p> <p>transverse measurement for plane surfaces, cylinders and grooves</p>	<p><b>internal angle probe (for ISR-S400, optional) code ISR-S400-SB140</b></p> <p>measure internal angles</p>

# ROUGHNESS TESTER CODE ISR-C100

DATA  
OUTPUT




remote control (included)

- 16 roughness parameters
- With probe position indicator
- Connected with printer via bluetooth
- Can display roughness values, profile, and curve
- Memory of maximum 100 results
- Automatic power off




Android APP for mobile device (included), the roughness tester can be controlled by mobile phone or tablet via bluetooth, the maximum working distance is 5m

measuring software for PC (included)



control the roughness tester, display roughness values, profile and curve

screen display



measurement result

roughness profile

Rmr analysis

To be continued



Continued from previous page

probe cover (included)



can put the small workpieces directly on the probe for measurement

adjustable stand (included)



wireless printer (optional)



## SPECIFICATION

<b>Parameters</b>	Ra, Rq, Rz, Rv, Rp, Rm, Rt, RS, Rsm R3z, R3y, Rz (JIS), Rku, Rsk, Rmax, Rpc	
<b>Range</b>	160μm	
<b>Accuracy</b>	±10%	
<b>Resolution (Ra)</b>	0.001μm	
<b>Probe</b>	<b>type</b>	inductive
	<b>stylus radius/angle</b>	5μm/90°
	<b>stylus material</b>	diamond
<b>Measuring force</b>	0.4mN	
<b>Measuring unit</b>	μm/μin	
<b>Cut off</b>	0.25/0.8/2.5mm	
<b>Number of cut-offs</b>	1 to 5	
<b>Traverse speed</b>	0.5mm/s, 1mm/s	
<b>Memory</b>	100 measurement results	
<b>Output</b>	USB and bluetooth	
<b>Power</b>	built-in rechargeable battery	
<b>Dimension (L×W×H)</b>	140×52×48mm	
<b>Weight</b>	440g	

## STANDARD DELIVERY


<b>Main unit</b>	1pc
<b>Standard probe</b>	1pc
<b>Calibration block and support</b>	1pc of each
<b>Adjustable stand</b>	1pc
<b>Probe cover</b>	1pc
<b>USB cable and software for PC</b>	1pc
<b>Android APP for mobile device</b>	1pc
<b>AC/DC adapter</b>	1pc

## OPTIONAL ACCESSORY


<b>Extension rod</b>	ISR-C100-ER
<b>Groove probe</b>	ISR-C100-130
<b>Deep groove probe</b>	ISR-C100-131
<b>Test stand</b>	ISR-C100-STAND
<b>Wireless printer</b>	ISR-C100-PRINTER

Unit: mm


extension rod (optional), code ISR-C100-ER



groove probe (optional), code ISR-C100-130



deep groove probe (optional), code ISR-C100-131



test stand (optional)



the maximum workpiece height is 310mm

## SURFACE ROUGHNESS REFERENCE SPECIMEN




MEASURING ACCURACY CAN BE IMPROVED, IF THE CALIBRATION IS MADE ON A REFERENCE SPECIMEN WITH THE ROUGHNESS VALUE CLOSE TO THE WORKPIECE TO BE MEASURED

- To calibrate roughness testers
- Meets ISO 5436-1: 2000
- Rust proof, made of pure Nickel

Code	Roughness (Ra)
ISR-RS525X	6.25µm*
ISR-RS526X	3.15µm*
ISR-RS527X	3.0µm*
ISR-RS528X	0.5µm*
ISR-RS529X	0.1µm* (not suitable for ISR-S300, ISR-S400 and ISR-S500)
ISR-RS530X	1.0µm*
ISR-RS531X	0.3µm* (not suitable for ISR-S300, ISR-S400 and ISR-S500)

\*The actual value may be slightly different



ISR-RS529X

## SURFACE ROUGHNESS SPECIMEN SET CODE ISR-CS130



- For checking, identifying and specifying the roughness by symbol
- Accuracy: +20% ~ -25%, Ra ≤ 0.1µm  
Accuracy: +12% ~ -17%, Ra > 0.1µm
- Meets ISO 2632
- Rust-proof, made of pure Nickel



Machining method	Roughness (Ra)	Roughness (Rz)	Quantity
Flat lapping	0.05, 0.1, 0.2µm	0.55, 1, 1.6µm	3pcs
	2, 4, 8µm		
Reaming	0.4, 0.8, 1.6µm	3, 6, 10µm	3pcs
	16, 32, 63µm		
Plain grinding	0.05, 0.1, 0.2, 0.4, 0.8, 1.6µm	0.55, 1, 1.6, 3, 6, 10µm	6pcs
	2, 4, 8, 16, 32, 63µm		
Horizontal milling	0.4, 0.8, 1.6, 3.2, 6.3, 12.5µm	2.5, 4, 8, 16, 32, 50µm	6pcs
	16, 32, 63, 125, 250, 500µm		
Vertical milling	0.4, 0.8, 1.6, 3.2, 6.3, 12.5µm	2.5, 4, 8, 16, 32, 50µm	6pcs
	16, 32, 63, 125, 250, 500µm		
Turning	0.4, 0.8, 1.6, 3.2, 6.3, 12.5µm	2.5, 4, 8, 16, 32, 50µm	6pcs
	16, 32, 63, 125, 250, 500µm		

## SHOT AND GRIT BLASTING SURFACE ROUGHNESS SPECIMEN

- To check the roughness of steel surfaces which have been blast cleaned before painting
- Meets ISO 8503/1
- Rust-proof, made of pure Nickel
- Each piece contains 4 parts



ISR-CS017

Code	Machining method	Roughness (Ra)	Roughness (Rz)
ISR-CS017	Shot blasting	3.2, 8, 13, 18µm	19.2, 48, 78, 108µm
ISR-CS018	Grit blasting	3.2, 10.5, 18, 25µm	19.2, 63, 108, 150µm

## SURFACE ROUGHNESS SPECIMEN

- For checking, identifying and specifying the roughness by symbol
- Accuracy: +20% ~ -25%, Ra≤0.1µm  
Accuracy: +12% ~ -17%, Ra>0.1µm
- Meets ISO 2632 (ISR-CS329 meets ISO 8503/1)
- Rust-proof, made of pure Nickel



ISR-CS315


Code	Machining method	Roughness (Ra)	Roughness (Rz)	Quantity
ISR-CS315	Surface grinding	0.025, 0.05, 0.1, 0.2, 0.4, 0.8, 1.6, 3.2µm	0.29, 0.55, 0.91, 1.74, 2.6, 4.65, 7.87, 15.6µm	8pcs
ISR-CS316	Cylindrical grinding	0.025, 0.05, 0.1, 0.2, 0.4, 0.8, 1.6, 3.2µm	0.3, 0.53, 0.88, 1.56, 2.64, 4.4, 7.71, 15.3µm	8pcs
ISR-CS317	Flat lapping	Criss-cross	0.025, 0.05, 0.1, 0.2µm	0.4, 0.6, 0.74, 1.26µm
		Parallel	0.025, 0.05, 0.1, 0.2µm	0.34, 0.56, 1.12, 1.5µm
ISR-CS318	Cylindrical lapping	0.025, 0.05, 0.1, 0.2µm	0.46, 0.54, 0.63, 1.23µm	4pcs
	Superfinishing	0.025, 0.05, 0.1, 0.2µm	0.36, 0.7, 1, 1.4µm	4pcs
ISR-CS319	Face turning	0.4, 0.8, 1.6, 3.2, 6.3, 12.5, 25, 50µm	1.92, 3.2, 6.15, 12.5, 23.7, 48.7, 102, 185µm	8pcs
ISR-CS320	Cylindrical turning	0.4, 0.8, 1.6, 3.2, 6.3, 12.5, 25, 50µm	1.7, 3.2, 6.1, 12.2, 23.7, 47.5, 95, 190µm	8pcs
ISR-CS321	End milling	0.4, 0.8, 1.6, 3.2, 6.3, 12.5, 25, 50µm	1.92, 3.82, 6.45, 12.2, 25.2, 49.8, 92.6, 191µm	8pcs
ISR-CS322	Reaming	0.4, 0.8, 1.6, 3.2µm	1.7, 3.2, 6.4, 12.8µm	4pcs
	Drilling	1.6, 3.2, 6.3, 12.5µm	7.5, 15.5, 31, 60µm	4pcs
ISR-CS323	Horizontal milling	0.4, 0.8, 1.6, 3.2, 6.3, 12.5, 25, 50µm	1.8, 3.68, 6.63, 12.8, 25.6, 53, 97.5, 197µm	8pcs
ISR-CS325	Shaping (planing)	0.8, 1.6, 3.2, 6.3, 12.5, 25, 50, 100µm	3.84, 6.7, 12.2, 25.2, 48.7, 99.9, 190, 361µm	8pcs
ISR-CS326	Linishing (belt sanding)	0.1, 0.2, 0.4, 0.8, 1.6, 3.2µm	0.9, 1.55, 3.37, 7.42, 18.5, 31µm	6pcs
ISR-CS328	Vertical grinding	0.2, 0.4, 0.8, 1.6, 3.2, 6.3µm	1.1, 3.5, 6.15, 8.78, 22.19, 40.8µm	6pcs
ISR-CS329	Grit blasting	3.2, 10.5, 18, 25µm	19.2, 63, 108, 150µm	4pcs
	Shot blasting	3.2, 8, 13, 18µm	19.2, 48, 78, 108µm	4pcs
ISR-CS331	Spark erosion (EDM)	0.4, 0.8, 1.6, 3.2, 6.3, 12.5, 25, 50µm	2.5, 4.5, 7.2, 14.2, 24.7, 51.2, 105, 196µm	8pcs
ISR-CS333	Hand filing	0.4, 0.8, 1.6, 3.2, 6.3µm	3, 5.6, 12.4, 22.5, 61µm	5pcs
ISR-CS334	Castings	0.8, 1.6, 3.2, 6.3, 12.5, 25, 50µm	3.2, 8, 16, 32, 56, 112, 225µm	7pcs
ISR-CS335	Honing	0.05, 0.1, 0.2, 0.4, 0.8, 1.6µm	0.31, 0.56, 1, 2, 4.2, 9µm	6pcs
ISR-CS336	Polishing	0.0125, 0.025, 0.05, 0.1, 0.2µm	0.29, 0.35, 0.67, 0.72, 1.52µm	5pcs

# DIGITAL LEVEL

DATA OUTPUT



ISE-2DT



direction of incline


absolute/incremental mode

angle of incline


- Color LCD, touch panel
- X-Y axis measurement
- Set the tolerance and the display is shown in different colors



within the tolerance (green)




slightly out of the tolerance (yellow)




seriously out of the tolerance (red)

- To show the incline with line or bubble



LED light


charging and data output



horizontal use

vertical use

lie-down use



V-slot for cylinder

the bottom has 4 thread mounting holes

## SPECIFICATION

Code	ISE-2DT
Measuring range	±30°
Resolution	0.01°(=0.174mm/m)
Accuracy	±0.03° (range 0~3°) ±0.05° (range >3°)
Power supply	rechargeable battery
Dimension	115×66×23mm
Weight	224g

## STANDARD DELIVERY

Main unit	1pc
USB cable	1pc

## OPTIONAL ACCESSORY


Software	ISE-2DT-SOFTWARE
----------	------------------

## DIGITAL LEVEL AND PROTRACTOR




2173-360

- Aluminum frame
- Magnetic bottom with V-groove for shafts
- Zero setting can be made on any plain surfaces
- Buttons: ON/OFF, ZERO, HOLD (keep the reading)
- CR2032 battery
- Automatic power off



Code	Range	Resolution	Accuracy
2173-360	0-360° (90°x4)	0.1° (= 1.745 mm/m)	0° and 90°: ±0.1°; others: ±0.2°



## DIGITAL LEVEL AND PROTRACTOR

**IP54**  
WATERPROOF

**ABSOLUTE LEVEL**


**BACKLIGHT**

**BUZZER ALARM AT 0° AND 90°**




2179-360

- IP54 dust/waterproof
- Aluminum frame
- Magnetic bottom with V-groove for shafts
- The sea level is permanently set inside the chip, zero setting is not needed when batteries are replaced
- Buttons: ON/OFF, absolute and incremental measurement, keep the reading, buzzer alarm, unit (mm/m, %, in/ft), backlight
- Two AAA batteries
- Automatic power off



Code	Range	Resolution	Accuracy
2179-360	0-360° (90°x4)	0.05°(=0.873mm/m)	0° and 90°: ±0.1°; others: ±0.2°



# DIGITAL LEVEL AND PROTRACTOR


BACKLIGHT

ABSOLUTE LEVEL

MAGNETIC BOTTOM

DISPLAY FLIPS OVER WHEN THE BOTTOM FACES UP


Unit: mm



2170-1

- Aluminum frame
- Magnetic bottom
- The display flips over when the bottom faces up
- The backlight is on automatically when in use, and automatically off in 15 minutes after use
- The sea level is permanently set inside the chip, zero setting is not needed when battery is replaced
- Buttons: ON/OFF, ZERO, absolute and incremental measurement
- One AAA battery
- Automatic power off in 5 minutes

Code	Range	Resolution	Accuracy
2170-1	4x90°	0.1°(=1.745mm/m)	at 0°and 90°: ±0.1°; others: ±0.2°



# FRAME LEVEL




4906-200

NO NEED TO SET ZERO BEFORE USE



Unit: mm



Code	Size (LxL)	Sensitivity
4906-150	150x150mm	0.02mm/m(=0.001°)
4906-200	200x200mm	0.02mm/m(=0.001°)
4906-300	300x300mm	0.02mm/m(=0.001°)

- No need to set zero before use
- Three V-grooves for shafts (shafts dia. 19.3~115.9mm)
- With longitudinal vial



NO NEED TO SET ZERO BEFORE USE


## BLOCK LEVEL

- No need to set zero before use
- V-groove on bottom for shafts (shafts dia. 19.3~115.9mm)
- With longitudinal vial



4905-200

Code	Size (L)	Sensitivity
4905-160	160mm	0.02mm/m(=0.001°)
4905-200	200mm	0.02mm/m(=0.001°)
4905-300	300mm	0.02mm/m(=0.001°)



NO NEED TO SET ZERO BEFORE USE


## SHORT LEVEL

- No need to set zero before use
- Suitable for small spaces like crankshaft
- Longitudinal and transverse V-grooves on bottom for shafts (shafts dia. 19.3~115.9mm)
- With transverse vial



4907-90

Code	Length	Sensitivity
4907-90	90mm	0.1mm/m(=0.0057°)



NO NEED TO SET ZERO BEFORE USE


## MINI LEVEL

- No need to set zero before use
- With mounting holes



4908-100

Code	Length	Sensitivity
4908-100	100mm	0.1mm/m(=0.0057°)



## ALUMINUM ALLOY LEVEL




- Die casting aluminum alloy frame
- With three vials: 180°, 90° and 45°
- Zero position of vial 180° can be set

4911-600

Unit: mm

Code	Length (L)	Accuracy
4911-400	400mm	0.75mm/m
4911-600	600mm	0.75mm/m
4911-800	800mm	0.75mm/m



## DIGITAL LEVEL

ABSOLUTE  
LEVEL


BACKLIGHT

BUZZER ALARM  
AT 0° AND 90°



4910-600

Unit: mm




- With transverse and longitudinal vials
- Used as level and protractor
- Aluminum frame
- Magnetic bottom
- The sea level is permanently set inside the chip, zero setting is not needed when batteries are replaced
- Buttons: ON/OFF, absolute and incremental measurement, keep the reading, buzzer alarm, unit (mm/m, %, in/ft) conversion, backlight
- The display flips over when the bottom faces up
- Two AAA batteries
- Automatic power off

Code	Range	Resolution	Accuracy
4910-600	0-360° (90°x4)	0.1°(=1.745mm/m)	0° and 90°: ±0.1°; others: ±0.2°



# AUTOMATIC DIGITAL ROCKWELL HARDNESS TESTER CODE ISH-MRD200



- Tolerance measurement with alarm
- Set measurement times (2~9) to have average value and the difference of max. and min. value
- Convert to HV or HB automatically
- Memory of 1000 measurement values for browsing and output
- Measurement value can be sent to wireless printer automatically
- Calibration function compensates the measurement value for high accuracy
- The hardness value of soft materials like plastic is not stable. The lock function can obtain the value automatically
- Display unit is automatic power off



Ø60mm flat anvil (included)



Ø150mm flat anvil (included)



V-type anvil (included)



wireless printer (optional)

## SPECIFICATION

<b>Hardness scale</b>	HRA, HRB, HRC, HRD HRF, HRG (with standard indenters) HRE, HRH, HRK (with optional indenter)
<b>Preliminary test force</b>	98N
<b>Test force</b>	588N, 980N, 1471N
<b>Stage elevation</b>	manual
<b>Load control</b>	automatic (load/dwell/unload)
<b>Load dwell time</b>	1~99 second
<b>Resolution</b>	0.1HR
<b>Output</b>	wireless and USB
<b>Memory</b>	1000
<b>Max. workpiece height</b>	170mm
<b>Max. workpiece depth</b>	165mm (from the center of indenter)
<b>Power supply of the display unit</b>	built-in rechargeable battery
<b>Power supply *</b>	220V, 50/60Hz
<b>Dimension</b>	520×160×700mm
<b>Weight</b>	60kg

\* Add "-U" on code No. when power supply is 110V, 50/60Hz

## STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>Ø60mm flat anvil</b>	1pc
<b>Ø150mm flat anvil</b>	1pc
<b>V-type anvil</b>	1pc
<b>Diamond indenter</b>	1pc
<b>Ø1.5875mm carbide ball indenter</b>	1pc
<b>Hardness test block HRB88-95</b>	1pc
<b>Hardness test block HRC60-65</b>	1pc
<b>Hardness test block HRC20-30</b>	1pc
<b>Anti-dust cover</b>	1pc
<b>USB cable and software</b>	1pc
<b>AC/DC adapter</b>	1pc


## OPTIONAL ACCESSORY

<b>Wireless printer</b>	ISH-DS-PRINTER
<b>Ø3.175mm carbide ball indenter</b>	ISH-EHK-INDENTER
<b>Hardness test block HRB88-95</b>	ISH-BHRB
<b>Hardness test block HRC60-65</b>	ISH-BHRC3
<b>Hardness test block HRC20-30</b>	ISH-BHRC1

# MANUAL DIGITAL ROCKWELL HARDNESS TESTER CODE ISH-RD200



DATA  
OUTPUT



- Tolerance measurement with alarm
- Set measurement times (2~9) to have average value and the difference of max. and min. value
- Convert to HV or HB automatically
- Memory of 1000 measurement values for browsing and output
- Measurement value can be sent to wireless printer automatically
- Calibration function compensates the measurement value for high accuracy
- The hardness value of soft materials like plastic is not stable. The lock function can obtain the value automatically
- Automatic power off



Ø60mm flat anvil (included)



Ø150mm flat anvil (included)



V-type anvil (included)



wireless printer (optional)

## SPECIFICATION

Hardness scale	HRA, HRB, HRC, HRD HRF, HRG (with standard indenters)
	HRE, HRH, HRK (with optional indenter)
Preliminary test force	98N
Test force	588N, 980N, 1471N
Stage elevation	manual
Load control	manual
Resolution	0.1HR
Output	wireless and USB
Memory	1000
Max. workpiece height	170mm
Max. workpiece depth	165mm (from the center of indenter)
Power supply	built-in rechargeable battery
Dimension	520×160×700mm
Weight	60kg

## STANDARD DELIVERY

Main unit	1pc
Ø60mm flat anvil	1pc
Ø150mm flat anvil	1pc
V-type anvil	1pc
Diamond indenter	1pc
Ø1.5875mm carbide ball indenter	1pc
Hardness test block HRB88-95	1pc
Hardness test block HRC60-65	1pc
Hardness test block HRC20-30	1pc
Anti-dust cover	1pc
USB cable and software	1pc
AC/DC adapter	1pc

## OPTIONAL ACCESSORY

Wireless printer	ISH-DS-PRINTER
Ø3.175mm carbide ball indenter	ISH-EHK-INDENTER
Hardness test block HRB88-95	ISH-BHRB
Hardness test block HRC60-65	ISH-BHRC3
Hardness test block HRC20-30	ISH-BHRC1

# AUTOMATIC ROCKWELL HARDNESS TESTER CODE ISH-MR150



Ø60mm flat anvil (included)



Ø150mm flat anvil (included)



V-type anvil (included)

## SPECIFICATION

Hardness scale	HRA, HRB, HRC, HRD, HRF, HRG
Preliminary test force	98N
Test force	588N, 980N, 1471N
Display	analogue
Stage elevation	manual
Load control	automatic (load/dwell/unload)
Load dwell time	1~99 second
Min. reading	0.5HR
Max. workpiece height	170mm
Max. workpiece depth	165mm (from the center of indenter)
Power supply *	220V, 50/60Hz
Dimension	520×160×700mm
Weight	60kg

\* Add "-U" on code No. when power supply is 110V, 50/60Hz

## STANDARD DELIVERY

Main unit	1pc
Ø60mm flat anvil	1pc
Ø150mm flat anvil	1pc
V-type anvil	1pc
Diamond indenter	1pc
Ø1.5875mm carbide ball indenter	1pc
Hardness test block HRB88~95	1pc

## STANDARD DELIVERY

Hardness test block HRC60~65	1pc
Hardness test block HRC20~30	1pc
Anti-dust cover	1pc

## OPTIONAL ACCESSORY

Hardness test block HRB88~95	ISH-BHRB
Hardness test block HRC60~65	ISH-BHRC3
Hardness test block HRC20~30	ISH-BHRC1

# MANUAL ROCKWELL HARDNESS TESTER CODE ISH-R150



Ø60mm flat anvil (included)



Ø150mm flat anvil (included)



V-type anvil (included)

## SPECIFICATION

<b>Hardness scale</b>	HRA, HRB, HRC, HRD, HRF, HRG
<b>Preliminary test force</b>	98N
<b>Test force</b>	588N, 980N, 1471N
<b>Display</b>	analogue
<b>Stage elevation</b>	manual
<b>Load control</b>	manual
<b>Min. reading</b>	0.5HR
<b>Max. workpiece height</b>	170mm
<b>Max. workpiece depth</b>	165mm (from the center of indenter)
<b>Dimension</b>	520×160×700mm
<b>Weight</b>	60kg

## STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>Ø60mm flat anvil</b>	1pc
<b>Ø150mm flat anvil</b>	1pc
<b>V-type anvil</b>	1pc
<b>Diamond indenter</b>	1pc
<b>Ø1.5875mm carbide ball indenter</b>	1pc
<b>Hardness test block HRB88~95</b>	1pc

## STANDARD DELIVERY

<b>Hardness test block HRC60~65</b>	1pc
<b>Hardness test block HRC20~30</b>	1pc
<b>Anti-dust cover</b>	1pc

## OPTIONAL ACCESSORY

<b>Hardness test block HRB88~95</b>	ISH-BHRB
<b>Hardness test block HRC60~65</b>	ISH-BHRC3
<b>Hardness test block HRC20~30</b>	ISH-BHRC1

# BRINELL/ROCKWELL/VICKERS HARDNESS TESTER CODE ISH-BRV

projection screen with scale,  
for reading Rockwell hardness



microscope for  
Vickers and Brinell  
15X eyepiece

graduation 0.01mm

objective 2.5X/5X

slider



load/unload handle

stage

test force dial

choose hardness scale



Ø60mm flat anvil for  
Rockwell (included)



Ø150mm flat anvil for  
Rockwell (included)



V-type anvil for  
Rockwell (included)



Ø60mm flat anvil for  
Vickers and Brinell (included)



V-type anvil for Vickers  
and Brinell (included)

## SPECIFICATION

Rockwell test load	98N preload, 588, 980, 1471N total load
Min. Rockwell reading	0.5HR
Brinell test load	306, 613, 1839N
Vickers test load	294N
Stage elevation	manual
Load control	manual
Magnification of microscope	37.5X/75X (selectable)
Max. workpiece height	180mm
Max. workpiece depth	200mm (from the center of indenter)
Power supply *	220V, 50/60Hz
Dimension	546×300×767mm
Weight	90kg

\* Add "-U" on code No. when power supply is 110V, 50/60Hz

## OPTIONAL ACCESSORY




Hardness test block HRB88~95	ISH-BHRB
Hardness test block HRC60~65	ISH-BHRC3
Hardness test block HRC20~30	ISH-BHRC1
Hardness test block 400-500HV30	ISH-BHV30
Hardness test block 180-220HBW2.5/187.5	ISH-BHB25B

## STANDARD DELIVERY

Main unit	1pc
Ø1.5875mm carbide ball indenter	1pc
Diamond Rockwell indenter	1pc
Ø5mm Brinell indenter	1pc
Ø2.5mm Brinell indenter	1pc
Vickers indenter	1pc
Ø60mm flat anvil for Rockwell	1pc
Ø150mm flat anvil for Rockwell	1pc
V-anvil for Rockwell	1pc
Ø60mm flat anvil for Vickers and Brinell	1pc
V-type anvil for Vickers and Brinell	1pc
Hardness test block HRB88~95	1pc
Hardness test block HRC60~65	1pc
Hardness test block HRC20~30	1pc
Hardness test block 400-500HV30	1pc
Hardness test block 180-220HBW2.5/187.5	1pc
Anti-dust cover	1pc

# AUTOMATIC BRINELL HARDNESS TESTER CODE ISHB-M100

AUTOMATIC TESTING AFTER PRELIMINARY  
TEST FORCE IS LOADED BY HAND



- Automatic testing after preliminary test force is loaded by hand
- Measure indentation by measuring microscope then find the hardness value from table
- Electronic close-loop load control system



Ø80mm flat anvil (included)



Ø180mm flat anvil (included)



V-type anvil (included)



measuring microscope (included)

## SPECIFICATION

Range	8 ~ 650HBW	
Reading mode	from table	
Test force	62.5, 100, 125, 187.5, 250, 500, 750, 1000, 1500, 3000kgf	
Max. height of workpiece	230mm	
Max. depth of workpiece	160mm (from the center of indenter)	
Stage elevation	manual	
Load control	automatic (load/dwell/unload)	
Load dwell time	5 ~ 60 second	
Measuring microscope	magnification	20X
	graduation	0.01mm
Power supply *	220V, 50/60Hz	
Dimension	550×210×750mm	
Weight	90kg	

\* Add "-U" on code No. when power supply is 110V, 50/60Hz

## STANDARD DELIVERY

Main unit	1pc
Ø80mm flat anvil	1pc
Ø180mm flat anvil	1pc
V-type anvil	1pc
Ø2.5mm carbide ball indenter	1pc
Ø5mm carbide ball indenter	1pc
Ø10mm carbide ball indenter	1pc
Hardness test block 150 ~ 250HBW2.5/187.5	1pc
Hardness test block 75 ~ 125HBW10/1000	1pc
Hardness test block 175 ~ 250HBW10/3000	1pc
Measuring microscope	1pc
Anti-dust cover	1pc


## OPTIONAL ACCESSORY

Hardness test block 150 ~ 250HBW2.5/187.5	ISH-BHB25B
Hardness test block 75 ~ 125HBW10/1000	ISH-BHB10A
Hardness test block 175 ~ 250HBW10/3000	ISH-BHB10B
Brinell indentation measuring system	ISHB-TSA/TAB


# AUTOMATIC DIGITAL BRINELL HARDNESS TESTER CODE ISHB-D200



AUTOMATIC TESTING AFTER PRELIMINARY  
TEST FORCE IS LOADED BY HAND



hardness value → 97.3 HB1000 → test force  
 HCG NO HRC → conversion  
 ID 3560.000µm → diameter of indenter  
 d2: 3558.750µm → diameter of indentation  
 DWELL 10 S → dwell time  
 START NO 05 001 KGF → finished test times



- Automatic testing after preliminary test force is loaded by hand
- Measure indentation by measuring microscope then read the hardness value from LCD
- Electronic close-loop load control system
- Can take tests up to 40 times and display maximum, minimum and average value
- Converted to HRA, HRB, HRC, HRD, HRF, HV, HK, HR15N, HR30N, HR45N, HR15T, HR30T, HR45T



Ø80mm flat anvil (included)



Ø180mm flat anvil (included)



V-type anvil (included)

## SPECIFICATION

Range	8~650HBW	
Reading mode	directly read from LCD	
Test force	62.5, 100, 125, 187.5, 250, 500, 750, 1000, 1500, 3000kgf	
Max. height of workpiece	200mm	
Max. depth of workpiece	135mm (from the center of indenter)	
Stage elevation	manual	
Load control	automatic (load/dwell/unload)	
Load dwell time	5~60 second	
Measuring microscope	magnification	20X
	resolution	0.625mm
Power supply *	220V, 50/60Hz	
Dimension	550x210x750mm	
Weight	90kg	

\* Add "-U" on code No. when power supply is 110V, 50/60Hz

## STANDARD DELIVERY

Main unit	1pc
Ø80mm flat anvil	1pc
Ø180mm flat anvil	1pc
V-type anvil	1pc
Ø2.5mm carbide ball indenter	1pc
Ø5mm carbide ball indenter	1pc
Ø10mm carbide ball indenter	1pc
Hardness test block 150~250HBW2.5/187.5	1pc
Hardness test block 75~125HBW10/1000	1pc
Hardness test block 175~250HBW10/3000	1pc
Anti-dust cover	1pc

## OPTIONAL ACCESSORY

Hardness test block 150~250HBW2.5/187.5	ISH-BHB25B
Hardness test block 75~125HBW10/1000	ISH-BHB10A
Hardness test block 175~250HBW10/3000	ISH-BHB10B
Brinell indentation measuring system	ISHB-TSA/TAB

# BRINELL INDENTATION MEASURING SYSTEM




- Connected to computer USB port
- Automatically measure the indentation
- Result saved to Excel automatically
- Low and high limits with judgement
- Calibration with indentation on standard hardness block

application



software (included)



## SPECIFICATION

Code	ISHB-TSA	ISHB-TSB
Applicable Brinell indenter	Ø10mm	Ø2.5mm, Ø5mm
Hardness range	8 ~ 650HB	
Range of indentation diameter	Ø2.4 ~ 6mm	Ø0.6 ~ 3mm
Test force	100, 250, 500, 1000, 1500, 3000kgf	62.5, 125, 187.5, 250, 750kgf
Hardness resolution	1HB	
Length resolution	0.01mm	
Length accuracy	±1%(diameter of indentation)	
Camera	Sensor	1/3.2" CMOS
	Pixel	2M (resolution 1024x768)
	View filed	9×6.8mm
Dimension	170×54×54mm	
Weight	420g	


## STANDARD DELIVERY

Main unit	1pc
Software and dongle	1pc of each





# AUTOMATIC DIGITAL MICRO-VICKERS HARDNESS TESTER CODE ISHV-D120



- Based on Vickers(HV), can be converted to HRA, HRB, HRC, HRD, HR15N, HR30N,HR45N, HR15T, HR30T, HR45T, HK, HBW
- Can take tests up to 99 times, display average value and the difference of max. and mini. value
- Low and high limits with judgement
- Also for Knoop hardness test, Knoop indenter is needed (optional)



slice holder (included)



vice (included)



cylinder holder (included)



level (included)

## SPECIFICATION

Range	10 ~ 3000HV	
Test force	0.01, 0.025, 0.05, 0.1, 0.2, 0.3, 0.5, 1kgf	
Vickers scales	HV0.01, HV0.025, HV0.05, HV0.1, HV0.2, HV0.3, HV0.5, HV1	
Load control	automatic (load/dwell/unload)	
Load dwell time	0 ~ 60 second	
Eyepiece	magnification	10X
	resolution	0.01μm (≥10μm), 0.001μm (<10μm)
Objective	10X, 40X	
Total magnification	100X (for observation) 400X (for measurement)	
Max. height of workpiece	210mm	
Max. depth of workpiece	135mm (from the center of indenter)	
X-Y stage	dimension: 100×100mm travel range: 25×25mm graduation: 0.01mm	
Power supply *	220V, 50/60Hz	
Dimension	490×320×530mm	
Weight	45kg	

## STANDARD DELIVERY

Main unit	1pc
Micro Vickers indenter	1pc
Hardness test block (400 ~ 500HV0.2)	1pc
Hardness test block (700 ~ 800HV1)	1pc
Slice holder	1pc
Vice	1pc
Cylinder holder	1pc
Level	1pc
Anti-dust cover	1pc

## OPTIONAL ACCESSORY

Hardness test block (400 ~ 500HV0.2)	ISH-BHV02A
Hardness test block (700 ~ 800HV1)	ISH-BHV1
Knoop indenter	ISHV-D120-KNOOP
Measuring system	ISH-HVC

\* Add "-U" on code No. when power supply is 110V, 50/60Hz

# DIGITAL VICKERS HARDNESS TESTER



Ø60mm flat anvil (included)



Ø150mm flat anvil (included)



V-type anvil (included)

- Based on Vickers(HV), converted to Rockwell(HRA, HRB, HRC, HRD, HRE, HRF, HRG, HRK), Brinell(HB), Superficial Rockwell(HR15N, HR15T, HR30N, HR30T, HR45N, HR45T), Shore(HS) and Strength(MPa)
- Memory of 27 measurement values for print, browsing and output
- LCD display with backlight
- Can measure Knoop hardness, Knoop indenter is needed

## SPECIFICATION

Code	ISH-DV10	ISH-DV50
Measuring range	8HV0.3 ~ 2500HV10	5HV1 ~ 2500HV50
Test force	0.3, 0.5, 1, 3, 5, 10kgf	1, 5, 10, 20, 30, 50kgf
Accuracy	±3%	±3% (test force 1, 5, 10, 20kgf) ±2% (test force 30, 50kgf)
Eyepiece	magnification	10X
	resolution	0.0625µm
Objective	10X, 20X	10X
Total magnification	100X (for observation) 200X (for measuring)	100X (for measuring)
Stage elevation	manual	
Load control	automatic (load/dwell/unload)	
Dwell time	5 ~ 60 second	
Max. workpiece height	160mm	
Max. workpiece depth	135mm	
Data output	RS232C	
Power supply *	220V, 50/60Hz	
Dimension	540×270×650mm	
Weight	35kg	45kg

## STANDARD DELIVERY

Main unit	1 pc
Ø60mm flat anvil	1 pc
Ø150mm flat anvil	1 pc
V-type anvil	1 pc
Vickers indenter	1 pc
10X objective	1 pc
20X objective	1 pc (for ISH-DV10)
Vickers test block	2 pcs
Anti-dust cover	1 pc




## OPTIONAL ACCESSORY

Knoop indenter	ISH-KNOOP
Measuring system	ISH-HVC
Hardness test block 400-500HV5	ISH-BHV5B
Hardness test block 400-500HV10	ISH-BHV10A
Hardness test block 400-500HV30	ISH-BHV30

\* Add "-U" on code No. when power supply is 110V, 50/60Hz

COMPUTER IS NOT NEEDED

# VICKERS HARDNESS MEASURING SYSTEM CODE ISH-HVC



- Computer is not needed. Use mouse to measure on monitor
- Set measuring times (maximum 9) to have average value and the difference of max. and min. value
- Convert to HRA, HRB, HRC, HB, HR45T, HR45N, HR30T, HR30N, HR15T, HR15N
- Memory of 9 last results for browsing
- Result can be printed automatically (wireless printer is optional)
- Hardness block calibration
- Tolerance measurement with alarm
- Image freeze function eliminates error due to vibration

## SPECIFICATION

<b>Sensor</b>	1/2" CMOS
<b>Pixel</b>	2M (resolution 800×600)
<b>Hardness measurement resolution</b>	0.1HV
<b>Length measurement resolution</b>	0.1μm
<b>Length measurement accuracy</b>	±0.5% (diagonal length of indentation)
<b>Test force</b>	0.01, 0.025, 0.05, 0.1, 0.2, 0.3, 0.5, 1, 2, 2.5, 3, 5, 10, 20, 30, 50, 100, 120kgf
<b>Objective</b>	1X, 2X, 4X, 10X, 20X, 40X
<b>Dimension</b>	120×68×55mm
<b>Weight</b>	500g



wireless printer (optional)

## STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>Mouse</b>	1pc
<b>AC/DC adapter</b>	1pc

## OPTIONAL ACCESSORY

<b>Wireless printer</b>	ISH-DS-PRINTER
-------------------------	----------------

# PORTABLE LEEB HARDNESS TESTER CODE ISH-SPHA



DATA  
OUTPUT



included



- Based on Leeb(HL), converted to Vickers(HV), Brinell(HB), Rockwell(HRC and HRB), Shore(HS) and tensile strength(MPa)
- Connected with printer via bluetooth
- Connected with computer via USB port
- Up to 800 test results can be saved
- Low and high limits with judgement
- Touch screen operation, large display with backlight
- Language: English, Chinese, Italian, German, French and Portuguese
- Automatic power off
- According to ASTM A 956

## SPECIFICATION

Min. reading	1HL, 1HV, 1HB, 0.1HRC, 0.1HRB, 1HS, 1MPa
Accuracy	±6HL (when HL=800)
Display	Leeb(HL), converted hardness, material, impact direction, test times, average value, deviation, time
Output	bluetooth and USB
Power supply	built-in rechargeable battery
Dimension	135×83×24mm
Weight	350g

## STANDARD DELIVERY

Main unit	1pc
Impact device D	1pc
Printer	1pc
Hardness test block D	1pc
Small support ring	1pc
Cleaning brush	1pc
AC/DC adapter	1pc
USB cable and software disc	1pc of each
Pen for touch screen	1pc


## OPTIONAL ACCESSORY

Impact device DC	ISH-SPHA-DC
Impact device C	ISH-SPHA-C
Impact device D+15	ISH-SPHA-D15
Impact device DL	ISH-SPHA-DL
Impact device G	ISH-SPHA-G
Hardness test block D**	ISH-BHLD
Hardness test block G**	ISH-BHLG
Couplant	ISH-COUPPLANT
Support rings	page 362

\*\* Hardness test block G (ISH-BHLG) is for impact device G (ISH-SPHA-G).  
Hardness test block D (ISH-BHLD) is for all others impact devices.

To be continued

Continued from previous page



**APPLICABLE WORKPIECE**

Impact device		DC	C	D	D+15	DL	G
Application		inner wall of small space	small or thin workpiece, coating layer	general use	deep groove	narrow slot or small hole	casting or forging workpiece
Maximum roughness of workpiece (Ra)		1.6µm	0.4µm	1.6µm	1.6µm	1.6µm	7µm
Minimum weight of workpiece	direct measurement	5kg	1.5kg	5kg	5kg	5kg	15kg
	on solid support	2kg	0.5kg	2kg	2kg	2kg	5kg
	coupled on plate	0.1kg	0.02kg	0.1kg	0.1kg	0.1kg	0.5kg
Minimum thickness of workpiece		5mm	1mm	5mm	5mm	5mm	10mm

**APPLICABLE MATERIAL AND HARDNESS RANGE**

Material	Scale	DC	C	D	D+15	DL	G
Steel & cast steel	HRC	20-68	20-69.5	20-68	19.3-67.9	20.6-68.2	
	HRB	38-100	38.4-99.5	38-100		37.0-99.9	47.7-99.9
	HB	81-654	80-683	81-654	80-638	81-646	90-646
	HV	81-955	80-996	81-955	180-818	80-950	
	HS	32-100	32-102	32-100	33-99	31-97	
	Tensile strength (MPa)			375-2639			
Cast iron	HB	93-334		93-334			92-326
	HV						
	HRC						
Tool steel	HRC	20-67		20-67			
	HV	80-898		80-898			
Stainless steel	HRB	46-101		46-101			
	HV	85-802		85-802			
	HB	85-655		85-655			
Cast aluminum alloy	HB	19-164		19-164			
	HRB	23-84		23-84			
Brass	HB	40-173		40-173			
	HRB	13-95		13-95			
Bronze	HB	60-290		60-290			
Copper	HB	45-315		45-315			

# PORTABLE LEEB HARDNESS TESTER CODE ISH-PHA



included



printer



hardness test block D



small support ring

- Supplied with impact device D
- Based on Leeb(HLD), converted to Vickers(HV), Brinell(HB), Rockwell(HRC and HRB), Shore(HS) and tensile strength(MPa)
- Connected with printer via bluetooth
- LCD display with backlight
- Automatic power off
- According to ASTM A 956

## SPECIFICATION

<b>Min. reading</b>	1HLD, 1HV, 1HB, 0.1HRC, 0.1HRB, 1HS, 1MPa	
<b>Accuracy</b>	±6HLD(when HLD=800)	
<b>Display</b>	Leeb(HLD), converted hardness, material, impact direction, test times, average value, date	
<b>Output</b>	bluetooth	
<b>Applicable workpiece</b>	minimum weight	5kg (direct measurement)
		2kg (on solid support)
		0.1kg (coupled on plate)
	minimum thickness: 5mm	
minimum radius of curved surface: 11mm		
maximum roughness (Ra): 1.6µm		
<b>Power supply</b>	3×AAA batteries	
<b>Dimension</b>	150×80×24mm	
<b>Weight</b>	200g	

## STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>Impact device D</b>	1pc
<b>Printer</b>	1pc
<b>Hardness test block D</b>	1pc
<b>Small support ring</b>	1pc
<b>Cleaning brush</b>	1pc
<b>AC/DC adapter</b>	1pc

## OPTIONAL ACCESSORY

<b>Couplant</b>	<b>ISH-COULPLANT</b>
<b>Support rings</b>	page 362
<b>Hardness test block D</b>	<b>ISH-BHLD</b>

## APPLICABLE MATERIAL AND HARDNESS RANGE FOR IMPACT DEVICE D

Material	HLD	HV	HB	HRC	HRB	HS	Tensile strength (MPa)
Steel & cast steel	300-900	81-955	81-654	20-68	38-100	32-100	375-2639
Tool steel	300-840	80-898		20-67			
Stainless steel	300-800	85-802	85-655		46-101		
Cast iron	360-650		93-334				
Cast aluminum alloy	170-570		19-164		23-84		
Brass	200-550		40-173		13-95		
Bronze	300-700		60-290				
Copper	200-690		45-315				

# PORTABLE LEEB HARDNESS TESTER CODE ISH-PHB



hardness test block D (included)



small support ring (included)



wireless printer (optional)

- Supplied with impact device D
- Set measurement times (1~9) to have average value
- Based on Leeb(HLD), converted to Vickers(HV), Brinell(HB), Rockwell(HRC and HRB), Shore(HS) and tensile strength(MPa)
- Memory of 99 measurement values for browsing
- Connected with printer via bluetooth
- Automatic power off
- According to ASTM A 956



## SPECIFICATION

<b>Min. reading</b>	1HLD, 1HV, 1HB, 0.1HRC, 0.1HRB, 1HS, 1MPa	
<b>Accuracy</b>	±6HLD (when HLD=800)	
<b>Display</b>	Leeb(HLD), converted hardness, material, impact direction, test times, average value, date	
<b>Output</b>	bluetooth	
<b>Applicable workpiece</b>	minimum weight	5kg
		2kg (on solid support)
		0.1kg (coupled on plate)
	minimum thickness: 5mm	
minimum radius of curved surface: 11mm		
maximum roughness(Ra): 1.6µm		
<b>Power supply</b>	3×AAA batteries	
<b>Dimension</b>	150×84×28mm	
<b>Weight</b>	200g	

## STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>Impact device D</b>	1pc
<b>Hardness test block D</b>	1pc
<b>Small support ring</b>	1pc
<b>Cleaning brush</b>	1pc

## OPTIONAL ACCESSORY

<b>Wireless printer</b>	ISH-DS-PRINTER
<b>Couplant</b>	ISH-COULPANT
<b>Support rings</b>	page 362
<b>Hardness test block D</b>	ISH-BHLD


## APPLICABLE MATERIAL AND HARDNESS RANGE FOR IMPACT DEVICE D

Material	HLD	HV	HB	HRC	HRB	HS	Tensile strength(MPa)
Steel & cast steel	300-900	81-955	81-654	20-68	38-100	32-100	375-2639
Tool steel	300-840	80-898		20-67			
Stainless steel	300-800	85-802	85-655		46-101		
Cast iron	360-650		93-334				
Cast aluminum alloy	170-570		19-164		23-84		
Brass	200-550		40-173		13-95		
Bronze	300-700		60-290				
Copper	200-690		45-315				


# PORTABLE LEEB HARDNESS TESTER CODE ISH-SPHD



DATA  
OUTPUT



included



- Impact device D
- Based on Leeb(HLD), converted to Vickers(HV), Brinell(HB), Rockwell(HRC and HRB), Shore(HS) and tensile strength(MPa)
- Automatic direction correction
- Connected with printer via bluetooth
- Connected with computer via USB port
- Up to 500 test results can be saved
- According to ASTM A 956

## SPECIFICATION

<b>Min. reading</b>	1HLD, 1HV, 1HB, 0.1HRC, 0.1HRB, 1HS	
<b>Accuracy</b>	±6HLD (when HLD=800)	
<b>Output</b>	USB and bluetooth	
<b>Applicable workpiece</b>	minimum weight	5kg (direct measurement)
		2kg (on solid support)
		0.1kg (coupled on plate)
	minimum thickness: 5mm	
minimum radius of curved surface: 11mm		
maximum roughness(Ra): 1.6µm		
<b>Power supply</b>	built-in rechargeable battery	
<b>Dimension</b>	147×35×22mm	
<b>Weight</b>	65g	

## STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>Printer</b>	1pc
<b>Hardness test block D</b>	1pc
<b>Small support ring</b>	1pc
<b>Cleaning brush</b>	1pc
<b>AC/DC adapter</b>	1pc
<b>USB cable and software disc</b>	1pc of each

## OPTIONAL ACCESSORY

<b>Couplant</b>	<b>ISH-COUPPLANT</b>
<b>Support rings</b>	page 362
<b>Hardness test block D</b>	<b>ISH-BHLD</b>

## APPLICABLE MATERIAL AND HARDNESS RANGE FOR IMPACT DEVICE D

Material	HLD	HV	HB	HRC	HRB	HS
Steel & cast steel	300-900	81-955	81-654	20-68	38-100	32-100
Tool steel	300-840	80-898		20-67		
Stainless steel	300-800	85-802	85-655		46-101	
Cast iron	360-650		93-334			
Cast aluminum alloy	170-570		19-164		23-84	
Brass	200-550		40-173		13-95	
Bronze	300-700		60-290			
Copper	200-690		45-315			




## SUPPORT RINGS FOR PORTABLE LEEB HARDNESS TESTER

type A




ISH-R1015



type B




ISH-R1113



type C




ISH-SR1113



type D




ISH-SR1015



type E



ISH-RUN



### SPECIFICATION

Code	Type	Applicable workpiece	Range (mm)
ISH-R1015	A	cylindrical outside surface	R10 - 15
ISH-R14530			R14.5 - 30
ISH-R2550			R25 - 50
ISH-R1113	B	cylindrical inside surface	R11 - 13
ISH-R12517			R12.5 - 17
ISH-R16530			R16.5 - 30
ISH-SR1113	C	spherical inside surface	SR11 - 13
ISH-SR12517			SR12.5 - 17
ISH-SR16530			SR16.5 - 30
ISH-SR1015	D	spherical outside surface	SR10 - 15
ISH-SR14530			SR14.5 - 30
ISH-RUN	E	cylindrical outside surface	R > 10

# ULTRASONIC HARDNESS TESTER CODE ISHU-460

DATA  
OUTPUT



### Application:

1. For steel, non-ferrous metal and alloy
2. Can test surface hardening layers(carburized, nitriding, high frequency hardened, etc.) and plating (like chrome plating)
3. Suitable for thin wall or edge of workpieces
4. Suitable for small areas like arc, conical surface and other complex shapes
5. Suitable for small or light workpieces
6. Suitable for narrow spaces, like grooves and blind holes
7. Can test large workpieces at any direction
8. Suitable for rough surfaces

- Small test indentation
- Test force and time are not affected by the operator
- Quick test, only 2 seconds
- Memory of 1000 test results
- Automatic power off
- Anti-dust and waterproof



test flat surfaces  
(with the cover)



test cylinder surfaces  
(use V-groove on the cover)



test narrow areas  
(remove the cover)

user scales

	HRC	HB	HV	HRB	HS	U1	U2	U3
steel -ST	■	■	■					
alloy ateel -AST								
stainless steel -SST								
cast iron -CI								
ductile iron -NI								
aluminum -AL								
brass -BRS								
bronze -BRZ								
copper -CU								
user material 1 -U1								
user material 2 -U2								

Empty cell  
 Calibrated  
 User calibration

select the material and scale, use the corresponding standard hardness blocks or workpieces for calibration (calibration of HRC, HB and HV for steel are already made, calibration is needed before use other materials and scales)



can take a picture on the workpiece and get a report with testing result and picture, the report can be sent to computer




back

To be continued

Continued from previous page



Graph display mode, show average value, relative range and test times




Histogram display mode, show average value, relative range and relative standard deviation



Statistics display mode, show maximum, minimum, deviation, average, relative range and test times



Smart display mode, can set tolerance, automatically reject the result when out of tolerance



software(included), can output data, get and print reports, screen capture, set screen colors of hardness tester

### SPECIFICATION

<b>Hardness scale</b>		HV, HB, HRB, HRC, HS
<b>Resolution</b>		1HV, 1HB, 1HRB, 0.1HRC, 1HS
<b>Accuracy</b>	<b>HB</b>	±10HB
	<b>HV</b>	±15HV
	<b>HRC</b>	±2HRC
<b>Minimum measuring area</b>		Ø1mm
<b>Data output</b>		USB
<b>Operating temperature</b>		-20°C ~ +40°C
<b>Power supply</b>		built-in rechargeable battery
<b>Dimension and weight of main unit</b>		160×80×40mm, 315g

### STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>Probe A</b>	1pc
<b>AC/DC adapter</b>	1pc
<b>USB cable and software</b>	1pc

### OPTIONAL ACCESSORY

<b>Probe B</b>	ISHU-460-B
<b>Couplant</b>	ISH-COUPPLANT

### SPECIFICATION OF PROBE

Type	A(standard)	B(optional)
<b>Measuring force</b>	50N	10N(small force)
<b>Application</b>	general use	plating
<b>Maximum roughness of workpiece (Ra)</b>	2.5µm	1.5µm
<b>Minimum weight of workpiece(direct measurement)</b>	0.1kg*	0.1kg*
<b>Minimum thickness of workpiece(direct measurement)</b>	1mm*	1mm*
<b>Minimum thickness of surface hardening layer or plating</b>	0.1mm	0.03mm
<b>Dimension and weight of probe</b>	140×Ø37mm, 271g	145×Ø37mm, 271g

\* If the weight or thickness of workpiece is less than required, the workpiece should be fixed or coupled on solid support.

# PORTABLE ROCKWELL HARDNESS TESTER CODE ISHR-P151



■ According to ISO 6508, ASTM E18



flat anvil (included)



V-type anvil (included)



anvil extension for thin workpieces (included)

## SPECIFICATION

<b>Hardness scale</b>	HRA, HRB, HRC, HRD, HRF, HRG
<b>Preliminary test force</b>	10kg
<b>Test force</b>	60kg, 100kg, 150kg
<b>Load control</b>	manual
<b>Min. reading</b>	1HR
<b>Max. workpiece thickness</b>	25mm
<b>Max. workpiece depth</b>	25mm
<b>Dimension</b>	240×70×160mm
<b>Weight (with base)</b>	2.5kg

## STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>Diamond indenter</b>	1pc
<b>Ø1.5875mm carbide ball indenter</b>	2pcs
<b>Hardness test block HRC20 ~ 30</b>	1pc
<b>Hardness test block HRC60 ~ 65</b>	1pc
<b>Hardness test block HRB88 ~ 95</b>	1pc

<b>Flat anvil</b>	1pc
<b>V-type anvil</b>	1pc
<b>Base</b>	1pc
<b>Anvil extension</b>	1pc
<b>Magnifier</b>	2pcs

# DIGITAL MAGNETIC ROCKWELL HARDNESS TESTER CODE ISHR-D121



- Apply to large and heavy steel or iron workpieces
- With statistic function, display average, maximum and minimum values
- Convert to HV, HB and tensile strength
- According to ISO 6508, ASTM E18



flat anvil for test block (included)

## SPECIFICATION


Hardness scale	HRA, HRB, HRC
Preliminary test force	10kg
Test force	60kg, 100kg, 150kg
Load control	manual
Min. reading	0.1HR
Flat workpiece requirement	length>190mm, width>60mm, thickness>5mm
Cylinder or tube workpiece requirement	length>200mm, diameter>Ø50mm, wall thickness>8mm
Power supply	3×AAA batteries
Dimension	245×105×230mm
Weight	5.3kg

## STANDARD DELIVERY


Main unit	1pc
Flat anvil	1pc
Diamond indenter	1pc
Ø1.5875mm carbide ball indenter	1pc

Hardness test block HRB85-95	1pc
Hardness test block HRC60-70	1pc
Hardness test block HRC20-30	1pc

# MAGNETIC ROCKWELL HARDNESS TESTER CODE ISHR-M111



- Apply to large and heavy steel or iron workpieces
- According to ISO 6508, ASTM E18



flat anvil for test block (included)



supports for cylinder or tube workpieces (included)



magnifier with LED (included)

## SPECIFICATION


<b>Hardness scale</b>	HRA, HRB, HRC, HRD, HRF, HRG
<b>Preliminary test force</b>	10kg
<b>Test force</b>	60kg, 100kg, 150kg
<b>Load control</b>	manual
<b>Min. reading</b>	1HR
<b>Flat workpiece requirement</b>	length>180mm, width>60mm, thickness>5mm
<b>Cylinder or tube workpiece requirement</b>	length>180mm, diameter>Ø50mm, wall thickness>8mm
<b>Dimension</b>	220×70×220mm
<b>Weight</b>	4.7kg

## STANDARD DELIVERY


<b>Main unit</b>	1pc
<b>Diamond indenter</b>	1pc
<b>Ø1.5875mm carbide ball indenter</b>	2pcs
<b>Hardness test block HRC60-70</b>	1pc
<b>Hardness test block HRC20-30</b>	1pc

<b>Hardness test block HRB85-95</b>	1pc
<b>Flat anvil</b>	1pc
<b>Support</b>	4pcs
<b>Magnifier with LED</b>	1pc

# MAGNETIC BRINELL/ROCKWELL HARDNESS TESTER CODE ISHR-B141



- Apply to large steel or iron workpieces
- According to ISO 6508, ASTM E18



flat anvil for test block (included)



supports for cylinder or tube workpieces (included)



magnifier with LED (included)



measuring microscope (included)

## SPECIFICATION


<b>Rockwell scale</b>	HRA, HRB, HRC, HRD, HRF, HRG
<b>Brinell measuring range</b>	20~650HBW
<b>Rockwell test force</b>	10kg preload, 60kg, 100kg, 150kg total load
<b>Brinell test force</b>	62.5kg, 125kg, 187.5kg
<b>Load control</b>	manual
<b>Min. Rockwell reading</b>	1HR
<b>Measuring microscope</b>	40X, graduation 0.01mm
<b>Flat workpiece requirement</b>	length>180mm, width>60mm, thickness>5mm
<b>Cylinder and tube workpiece requirement</b>	length>180mm, diameter>Ø50mm, thickness>8mm
<b>Dimension</b>	220×70×220mm
<b>Weight</b>	4.7kg

## STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>Flat anvil</b>	1pc
<b>Support</b>	4pcs
<b>Diamond Rockwell indenter</b>	1pc
<b>Ø1.5875mm carbide ball indenter</b>	1pc
<b>Ø2.5mm Brinell indenter</b>	1pc

<b>Hardness test block HRB85-95</b>	1pc
<b>Hardness test block HRC60-70</b>	1pc
<b>Hardness test block HRC20-30</b>	1pc
<b>Brinell test block</b>	1pc
<b>Measuring microscope</b>	1pc
<b>Magnifier with LED</b>	1pc

# HYDRAULIC BRINELL HARDNESS TESTER CODE ISHB-H131



V-type anvil (included)



spherical anvil (included)



measuring microscope (included)

- According to ISO 6505, ASTM E10

## SPECIFICATION

Measuring range	16~650HBW
Test force	3000kg
Indenter	Ø10mm carbide ball
Measuring microscope	20X, graduation 0.01mm
Max. workpiece height	350mm
Max. workpiece depth	90mm (from the center of indenter)
Dimension	270×225×570mm
Weight	13.8kg



## STANDARD DELIVERY

Main unit	1pc
Flat anvil	1pc
V-type anvil	1pc
Spherical anvil	1pc


Ø10mm carbide ball	2pcs
Brinell test block	2pcs
Measuring microscope	1pc



# PIN BRINELL HARDNESS TESTER CODE ISHB-P101




static test clamp



impact test clamp



static test



impact test

- Measure Brinell hardness of large and heavy workpieces
- 1580kg test force and  $\varnothing 7.26\text{mm}$  ball indenter, equal to 3000kg test force and  $\varnothing 10\text{mm}$  ball indenter
- Static and impact test modes
- According to ISO and ASTM standard



V-type anvil (included)



pins (included)



measuring microscope (included)

## SPECIFICATION

Measuring range	100~350HBW (with $\varnothing 7.26\text{mm}$ indenter, included) 350~650HBW (with $\varnothing 4\text{mm}$ indenter, optional)
Test force	1580kg
Accuracy	static test: $\pm 3\%$ impact test: $\pm 5\%$
Measuring microscope	20X, graduation 0.01mm
Max. workpiece height in static test	150mm
Max. workpiece depth in static test	80mm (from the center of indenter)
Dimension	195×60×350mm
Weight	4.2kg

## STANDARD DELIVERY

Static test clamp	1pc
Impact test clamp	1pc
Flat anvil	1pc
V-type anvil	1pc
$\varnothing 7.26\text{mm}$ indenter	1pc
Hardness test block	1pc
Pin	250pcs
Measuring microscope	1pc

## OPTIONAL ACCESSORY

$\varnothing 4\text{mm}$ indenter	ISHB-P101-INDENTER
Pin (250pcs)	ISHB-P101-PIN

# WEBSTER HARDNESS TESTER



ISHW-L20

- To measure the hardness of soft metal such as aluminum alloy, copper, brass, soft steel, etc.
- According to ASTM B647-84 (2000)

## SPECIFICATION

Code	ISHW-L20	ISHW-L20A	ISHW-L20B	ISHW-B70	ISHW-B75	ISHW-B92
Application	for aluminum alloy general use	for aluminum alloy thick workpiece	for aluminum alloy small tube	for hard aluminum alloy and hard brass	for soft brass and copper	for soft steel and cold-rolled steel
Thickness requirement of flat workpiece	0.6 ~ 6mm	0.6 ~ 13mm	0.6 ~ 8mm	0.6 ~ 6mm	0.6 ~ 6mm	0.6 ~ 6mm
Internal diameter requirement of tube workpiece	>Ø10mm	>Ø10mm	>Ø6mm	>Ø10mm	>Ø10mm	>Ø10mm
Wall thickness requirement of tube workpiece	0.6 ~ 6mm	6 ~ 13mm (internal diameter Ø10 ~ 23.3mm) 0.6 ~ 6mm (internal diameter >Ø23.3mm)	0.6 ~ 8mm	0.6 ~ 6mm	0.6 ~ 6mm	0.6 ~ 6mm
Hardness range	0 ~ 20HW					
Min. reading	1HW					
Accuracy	±0.5HW (at 5 ~ 17HW)					
Dimension	205×30×85mm					
Weight	500g					

## STANDARD DELIVERY

Main unit	1pc
Spare indenter	1pc
Hardness test block	1pc
Wrench	1pc

## BARCOL HARDNESS TESTER CODE ISHB-B300



- To measure the hardness of thick workpieces made of pure aluminum aluminum alloy, fiber reinforced plastic, hard plastic, etc.
- According to ASTM B648-00, ASTM D2853-07

### SPECIFICATION

<b>Hardness range</b>	0~100HBa (equal to 25~150HBW)
<b>Min. reading</b>	1HBa
<b>Accuracy</b>	±2HBa (at 42~52HBa) ±1HBa (at 84~88HBa)
<b>Min. workpiece thickness</b>	0.8mm
<b>Dimension</b>	142×65×90mm
<b>Weight</b>	500g

### STANDARD DELIVERY

<b>Main unit</b>	1pc
<b>Spare indenter</b>	2pcs
<b>Hardness test block</b>	2pcs
<b>Wrench</b>	1pc

# DIGITAL SHORE DUROMETER

DATA  
OUTPUT



- According to ISO868, ISO7619, ASTM D 2240
- Average and peak (max.) mode
- Dwell time is adjustable
- Low and high limits with judgement
- 500 memories
- Wireless connection to printer
- Handhold use or work with test stand (code **ISH-DS-STAND**)
- Automatic power off



## SPECIFICATION

Code	ISH-DSA	ISH-DSD
Unit	Shore A	Shore D
Test material	soft plastic, soft rubber, etc.	hard plastic, hard rubber, etc.
Measuring range*	0~100HA	0~100HD
Resolution	0.1HA	0.1HD
Accuracy	±1HA	±1HD
Indenter protrusion	2.5mm	
Output	wireless and USB	
Power supply	built-in rechargeable battery	
Dimension	153×50×29mm	
Weight	170g	

## STANDARD DELIVERY

Main unit	1 pc
Calibration block	1 pc
USB cable and software	1 pc
AC/DC adapter	1 pc

## OPTIONAL ACCESSORY

Printer	ISH-DS-PRINTER
Test stand	ISH-DS-STAND
1kg weight block (for ISH-DSA)	ISH-DSA-W1
5kg weight block (for ISH-DSD)	ISH-DSD-W5

- \* Use **ISH-DSD** when measuring result is higher than 90HA  
Use **ISH-DSA** when measuring result is lower than 20HD

## TEST STAND FOR DIGITAL SHORE DUROMETER CODE ISH-DS-STAND



5kg weight block (optional)  
for ISH-DSD

- Can perform repeatable hardness measurement due to fewer possibilities of human error or measurement variations
- 1kg weight block is for **ISH-DSA**, 5kg weight block is for **ISH-DSD**

### SPECIFICATION

Stage diameter	Ø88mm
Maximum workpiece height	75mm
Dimension	125×163×350mm
Weight	4kg


### STANDARD DELIVERY

Test stand	1pc
Durometer supporter	1pc

### OPTIONAL ACCESSORY

1kg weight block (for ISH-DSA)	ISH-DSA-W1
5kg weight block (for ISH-DSD)	ISH-DSD-W5

# SHORE DUROMETER



- According to ISO868, ISO7619, ASTM D 2240
- With peak value indicator
- Handhold use or work with test stand (code ISH-OS2)

## SPECIFICATION

Code	ISH-S30A	ISH-S30D
Unit	Shore A	Shore D
Test material	soft plastic, soft rubber, etc.	hard plastic, hard rubber, etc.
Measuring range*	0~100HA	0~100HD
Resolution	1HA	1HD
Accuracy	±0.5HA	±0.5HD
Indenter protrusion	2.5mm	
Bezel diameter	57mm	
Overall height	121mm	
Weight	184g	

\* Use ISH-S30D when measuring result is higher than 90HA  
 Use ISH-S30A when measuring result is lower than 20HD

# HARDNESS TEST BLOCK FOR SHORE DUROMETER



ISH-S30A-BLOCK




ISH-S30D-BLOCK

## SPECIFICATION

Code	ISH-S30A-BLOCK	ISH-S30D-BLOCK
Type	Shore A	Shore D
Hardness value	7pcs/set: 30, 40, 50, 60, 70, 80, 90HA	3pcs/set: 60, 75, 85HD



## TEST STAND FOR SHORE DUROMETER CODE ISH-OS2



calibration block (included)



4kg weight block (optional)  
for ISH-S30D

- Can perform repeatable hardness measurement due to fewer possibilities of human error or measurement variations
- Special structure for stable loading
- 1kg weight block is for ISH-S30A, 4kg weight block is for ISH-S30D

### SPECIFICATION

Stage diameter	Ø98mm
Maximum workpiece height	180mm
Maximum workpiece depth	115mm (from test point to column)
Weight block	1kg (for ISH-S30A)
Dimension	Ø200×500mm
Weight	18kg


### STANDARD DELIVERY

Test stand	1pc
Calibration block	1pc

### OPTIONAL ACCESSORY

4kg weight block (for ISH-S30D)	ISH-OS2-W4
---------------------------------	------------

# SHORE DUROMETER



- According to ISO868, ISO7619, ASTM D 2240
- With peak value indicator
- Optional accessory: test stand ISH-STAC and ISH-STD


## SPECIFICATION

Code	ISH-SAM	ISH-SDM
Scale	Shore A	Shore D
Application	nature rubber, soft elastomer, etc.	hard rubber, plastic, hard elastomer, etc.
Measuring range *	10~90HA	20~90HD
Graduation	1HA	1HD
Indenter protrusion	2.5mm	
Dimension	115×60×25mm	
Weight	160g	

\* Use ISH-SDM when measuring result is higher than 90HA  
Use ISH-SAM when measuring result is lower than 20HD

# TEST STAND FOR SHORE DUROMETER

- Can perform repeatable hardness measurement due to fewer possibilities of human error or measurement variations



## SPECIFICATION

Code	ISH-STAC	ISH-STD
Applicable durometer	ISH-SAM	ISH-SDM
Stage diameter	Ø100mm	Ø100mm
Maximum workpiece height	75mm	75mm
Weight block	1kg	5kg





DATA  
OUTPUT


## DIGITAL FORCE GAGE



ISF-1DF100

- Push and pull test
- Units: N, gf, kgf, ozf, lbf
- 500 memories
- Automatic power off
- Metal case
- LCD display with backlight, can turn 180°
- Overload alarm

push/pull accessory (included)



printer (optional)



### SPECIFICATION

Code	ISF-1DF10	ISF-1DF50	ISF-1DF100	ISF-1DF500	ISF-1DF1000
Load capacity (N)	10	50	100	500	1000
Resolution (N)	0.01	0.01	0.1	0.1	1
Accuracy	±0.3% (of load capacity)				
Measuring mode	tracking, peak (max.), low and high limits with judgement				
Power supply	built-in rechargeable battery				
Dimension	150×73×33mm				
Weight	450g				

### STANDARD DELIVERY

Main unit	1pc
AC/DC adapter	1pc
USB cable and software	1pc
Push/pull accessory	6pcs (flat push tip, V push tip, knife-edge push tip, point push tip, pull clamp, extension rod)

### OPTIONAL ACCESSORY

Printer	ISF-DF-PRINTER
Test stand	ISF-MT1K

# DIGITAL FORCE GAGE (HIGH RESOLUTION)

DATA  
OUTPUT



ISF-DF100A  
type A




ISF-DF5KA  
type B

- Push and pull test
- Peak (max.) and tracking mode
- Units: mN, N, gf, kgf, ozf, lbf
- Low and high limits with judgement
- 1000 memories
- Automatic power off
- Metal case, touch buttons
- LCD display with backlight, can automatically turn 180°
- Overload alarm



printer (optional)

accessory for type A (included)



accessory for type B (included)



## SPECIFICATION

Code	ISF-DF 5A	ISF-DF 10A	ISF-DF 20A	ISF-DF 50A	ISF-DF 100A	ISF-DF 200A	ISF-DF 500A	ISF-DF 1KA	ISF-DF 2KA	ISF-DF 5KA	ISF-DF 10KA	ISF-DF 20KA
Type	A (internal sensor)								B (external sensor)			
Load capacity (N)	5	10	20	50	100	200	500	1000	2000	5000	10000	20000
Resolution (N)	0.0005	0.001	0.005	0.005	0.01	0.05	0.05	0.1	1	1	10	10
Accuracy	±0.3% (of load capacity)											
Power supply	built-in rechargeable battery											

## STANDARD DELIVERY

Code	ISF-DF 5A	ISF-DF 10A	ISF-DF 20A	ISF-DF 50A	ISF-DF 100A	ISF-DF 200A	ISF-DF 500A	ISF-DF 1KA	ISF-DF 2KA	ISF-DF 5KA	ISF-DF 10KA	ISF-DF 20KA
Main unit	1pc								1pc			
AC/DC adapter	1pc								1pc			
USB cable and software	1pc								1pc			
Push/pull accessory	6pcs (flat push tip, V push tip, knife-edge push tip, point push tip, pull clamp, extension rod)								4pcs (flat push tip, adapter, pull clamps)			

## OPTIONAL ACCESSORY

Printer	ISF-DF-PRINTER
Test stand	ISF-MT1K

## TEST STAND CODE ISF-MT1K

force gages are not included



digital scale (optional)

horizontal orientation test



- For tensile and compress test with force gages (code **ISF-1DFxx** and **ISF-DFxx**)
- Can be used in vertical and horizontal orientation

### SPECIFICATION

<b>Load capacity</b>	1000N
<b>Travel</b>	200mm (3mm vertical movement per revolution of handwheel)
<b>Dimension</b>	196 x 250 x 446mm
<b>Weight</b>	13kg


### OPTIONAL ACCESSORY

<b>Digital scale (range: 200mm, resolution: 0.01mm/0.0005")</b>	<b>ISF-MT1K-SCALE</b>
---	-----------------------

# DIGITAL TORQUE TESTER

ATTENTION: NOT SUITABLE FOR ELECTRIC WRENCHES, IMPACTWRENCHES OR PNEUMATIC WRENCHES

DATA OUTPUT



- With external sensor, to test torque wrenches, torque screwdrivers and other torque tools
- Clockwise and counter-clockwise operation
- Peak and track working modes
- Unit: N.m, in.lb, kg.cm
- Target torque value can be set (9 target torque values can be saved and selected quickly), with audible and visible alarm:
  - Green LED light on and buzzer sounds when the value is 90%~100% of target torque
  - Both green and red LED light on and buzzer sounds when the target torque value is reached
- Memory of 250 measurement values for browsing and output
- Power off in 5 minutes automatically



with 3 mounting holes on the bottom



adaptor (included)



## SPECIFICATION

Code	IST-TT5	IST-TT50	IST-TT220	IST-TT550	IST-TT2200
Range	0.5~5N.m	5~50N.m	22~220N.m	55~550N.m	220~2200N.m
Accuracy	±1% (clockwise and counter-clockwise)				
Resolution	0.001N.m	0.01N.m	0.1N.m	0.1N.m	1N.m
Square socket (L)	1/4"	3/8"	1/2"	3/4"	1"
Power supply	built-in rechargeable battery				
Adaptor	no	3/8" to 1/4"	1/2" to 3/8" 3/8" to 1/4"	3/4" to 1/2" 1/2" to 3/8"	1" to 3/4" 3/4" to 1/2"
Transducer dimension	60×60×47mm	89×89×65mm	109×109×73mm	140×140×97mm	160×160×116mm
Weight	0.7kg	1.1kg	1.4kg	2.8kg	4.7kg

## STANDARD DELIVERY

Main unit	1pc
Transducer with 1m cable	1pc
AC/DC adapter	1pc
USB cable and software	1pc
Adaptor	refer to the above

# TORQUE WRENCH TEST STAND CODE IST-TS500



Unit: mm

application example



digital torque tester (optional)



adaptor (optional, for digital torque tester IST-TT5, IST-TT50, IST-TT220)

- Work with digital torque testers (IST-TT5, IST-TT50, IST-TT220, IST-TT550)

## SPECIFICATION

Digital torque tester	IST-TT5 (optional)	IST-TT50 (optional)	IST-TT220 (optional)	IST-TT550 (optional)
Applicable torque wrenches	0.5 ~ 5N.m	5 ~ 50N.m	22 ~ 220N.m	220 ~ 340N.m
Arm length (L1)	150 ~ 550mm, adjustable			
Maximum travel (L2)	200mm			
Weight	12kg			

## OPTIONAL ACCESSORY

Digital torque tester	IST-TT5, IST-TT50, IST-TT220, IST-TT550
Adaptor	IST-TS500-BLOCK (necessary for IST-TT5, IST-TT50 and IST-TT220, not needed for IST-TT550)

# DIGITAL BOTTLE CAP TORQUE TESTER


DATA  
OUTPUT

- Measure the open and tighten torque of bottle cap
- Units: N.m, N.cm, kgf.cm, lbf.in, lbf.ft
- 1500 memories
- Wireless connection to printer
- Automatic power off
- LCD display with backlight
- Overload alarm
- With calibration function



IST-DCT20

two display modes



printer (optional)



## SPECIFICATION

Code	IST-DCT2	IST-DCT5	IST-DCT10	IST-DCT20
Load capacity	2N.m	5N.m	10N.m	20N.m
Resolution	0.001N.m	0.001N.m	0.01N.m	0.01N.m
Clamping range	Ø19.5~190mm			
Accuracy	±0.5% (of load capacity)			
Measuring mode	tracking, peak (max.), first peak, double peak, low and high limits with judgement			
Output	wireless and USB			
Power supply	built-in rechargeable battery			
Dimension	200×197×142mm			
Weight	2.5kg			


## STANDARD DELIVERY

Main unit	1pc
AC/DC adapter	1pc
USB cable and software	1pc

## OPTIONAL ACCESSORY

Printer	ISH-DS-PRINTER
---------	----------------

## DIGITAL TORQUE SCREWDRIVER



IST-SD200

### SPECIFICATION

Code	IST-SD50	IST-SD200	IST-SD400
Range	10~50cN.m	40~200cN.m	80~400cN.m
Accuracy	clockwise	±3%	±2.5%
	counter-clockwise	±4%	±3.5%
Resolution	0.1cN.m	0.1cN.m	0.1cN.m
Size of shank (L)	1/4"	1/4"	1/4"
Power supply	1×AAA battery		
Length	193mm	203mm	203mm
Weight	190g	200g	200g

- Clockwise and counter-clockwise operation
- Unit: cN.m, in.lb, kg.cm
- Peak and track working mode
- Target torque value can be set, with audible and visible alarm:
  - Green LED light on and buzzer sounds when target torque value is 90%~100% of target torque
  - Red LED light on and buzzer sounds when target torque value is reached
- Power off automatically in 5 minutes without any operations

### OPTIONAL ACCESSORY

Calibration cable    IST-SD-CABLE

## SMALL RANGE DIGITAL TORQUE WRENCH



IST-WP20

### SPECIFICATION

Code	IST-WP12	IST-WP20
Range	2.4~12N.m	4~20N.m
Accuracy	clockwise	±3%
	counter-clockwise	±4%
Resolution	0.01N.m	0.01N.m
Square driver (L)	1/4"	1/4"
Power supply	1×AAA battery	
Length	260mm	260mm
Weight	430g	430g

- Clockwise and counter-clockwise operation
- Unit: N.m, in.lb, ft.lb, kg.cm
- Peak and track working mode
- Target torque value can be set, with audible and visible alarm:
  - Green LED light on and buzzer sounds when target torque value is 90%~100% of target torque
  - Red LED light on and buzzer sounds when target torque value is reached
- Power off automatically in 5 minutes without any operations
- Non-slip grip handle
- With overload record (once the torque reaches 110% of the maximum range)

### OPTIONAL ACCESSORY

Calibration cable    IST-W-CABLE

# SHORT HANDLE DIGITAL TORQUE WRENCH



IST-WS60

- Clockwise and counter-clockwise operation
- Unit: N.m, in.lb, ft.lb, kg.cm
- Peak and track working mode
- Target torque value can be set, with audible and visible alarm:
  - Green LED light on and buzzer sounds when torque value is 90%~100% of target torque
  - Both green and red LED light on and buzzer sounds when target torque value is reached
- Power off in 5 minutes automatically
- Non-slip grip handle
- With damp record
- With overload record (once the torque reaches 110% of the maximum range)

## SPECIFICATION

Code	IST-WS30	IST-WS30A	IST-WS60	IST-WS85
Range	6~30N.m	6~30N.m	12~60N.m	17~85N.m
Accuracy	clockwise	±3%		
	counter-clock wise	±4%		
Resolution	0.01N.m	0.01N.m	0.01N.m	0.1N.m
Square driver (L)	1/4"	3/8"	3/8"	3/8"
Power supply	2×AAA batteries			
Length	215mm	215mm	225mm	271mm
Weight	750g	830g	917g	1000g

## OPTIONAL ACCESSORY

Calibration cable	IST-WS-CABLE
-------------------	--------------



# DIGITAL TORQUE WRENCH



IST-W135A

- Clockwise and counter-clockwise operation
- Unit: N.m, in.lb, ft.lb, kg.cm
- Peak and track working mode
- Target torque value can be set, with audible and visible alarm:
  - Green LED light on and buzzer sounds when torque value is 90%~100% of target torque
  - Both green and red LED light on and buzzer sounds when target torque value is reached
- Power off automatically in 5 minutes without any operations
- Non-slip grip handle
- With overload record (once the torque reaches 110% of the maximum range)

## SPECIFICATION

Code	Range	Accuracy	Resolution	Square driver (L)	Power supply	Length	Weight
IST-W30A	6~30N.m	clockwise: $\pm 2\%$ counter-clockwise: $\pm 3\%$	0.01N.m	1/4"	2×AA batteries	390mm	830g
IST-W135A	27~135N.m		0.1N.m	3/8"		415mm	950g
IST-W200A	40~200N.m		0.1N.m	1/2"		530mm	1.4kg
IST-W340A	68~340N.m		0.1N.m	1/2"		650mm	1.6kg
IST-W500A	100~500N.m	clockwise: $\pm 2.5\%$ counter-clockwise: $\pm 3.5\%$	0.1N.m	3/4"		950mm	2.1kg
IST-W850A	170~850N.m		0.1N.m	3/4"		1220mm	2.55kg
IST-W1200A	240~1200N.m		1N.m	1"		1800mm	13kg
IST-W1500A	300~1500N.m		1N.m	1"		1800mm	13kg
IST-W2000A	400~2000N.m		1N.m	1"	1800mm	14kg	

## OPTIONAL ACCESSORY

Calibration cable	IST-W-CABLE
-------------------	-------------

# DIGITAL ANGLE TORQUE WRENCH



IST-1W135A

- Clockwise and counter-clockwise operation
- Set the desired torque first. After reaching the desired torque, set the angle and turn the wrench at this angle to apply extra torque
- Unit: N.m, in.lb, ft.lb, kg.cm, degree
- Peak and track working mode
- Target torque or angle value can be set, with audible and visible alarm:
  - Green LED light on and buzzer sounds when torque or angle value is 90%~100% of target torque or angle
  - Both green and red LED light on and buzzer sounds when target torque or angle value is reached
- Power off in 5 minutes automatically
- Non-slip grip handle
- With damp record
- With overload record (once the torque reaches 110% of the maximum range)



Set the desired torque first. After reaching the desired torque, set the angle and turn the wrench at this angle to apply extra torque


## SPECIFICATION

Code		IST-1W30A	IST-1W135A	IST-1W200A	IST-1W340A
Range	torque	6~30N.m	27~135N.m	40~200N.m	68~340N.m
	angle	0~999°			
Accuracy	clockwise	±2%			
	counter-clock wise	±3%			
	angle	±2° (rotate 90°)			
Resolution	torque	0.01N.m	0.1N.m	0.1N.m	0.1N.m
	angle	1°			
Square driver (L)		1/4"	3/8"	1/2"	1/2"
Power supply		2xAA batteries, for 110 hours working			
Length		390mm	415mm	530mm	650mm
Weight		830g	950g	1400g	1600g

## OPTIONAL ACCESSORY

Calibration cable	IST-1W-CABLE
-------------------	--------------

# WIRELESS DATA TRANSFER DIGITAL TORQUE WRENCH




**DIGITAL TORQUE WRENCH  
IST-3W135A**



**RECEIVER  
IST-3WREC**



- Wireless data transfer to computer
- Unit: N.m, in.lb, ft.lb, kg.cm
- Clockwise and counter-clockwise operation
- Peak and track working mode
- Can set tolerance with judgement in peak working mode
- 9 target torque values can be set, with audible and visible alarm:
  - Green LED light on and buzzer sounds when torque value is 80% ~ 99.5% of target torque
  - Both green and red LED light on and buzzer sounds when torque value is over 99.5% of target torque
- Power off in 2 minutes automatically
- Non-slip grip handle
- With damp record
- With overload record (once the torque reaches 110% of the maximum range)



## DIGITAL TORQUE WRENCH SPECIFICATION

Code	IST-3W30A	IST-3W135A	IST-3W200A	IST-3W340A
Range	6~30N.m	27~135N.m	40~200N.m	68~340N.m
Accuracy	clockwise	±2%		
	counter-clock wise	±3%		
Tolerance setting range	-25% ~ +25% (target torque value)			
Resolution	0.01N.m	0.1N.m	0.1N.m	0.1N.m
Square driver (L)	1/4"	3/8"	1/2"	1/2"
Working frequency	ISM433MHz (432.0~433.8MHz, adjustable)			
Power supply	2xAA batteries, for 110 hours working			
Length	390mm	415mm	530mm	650mm
Weight	760g	940g	1340g	1540g

## RECEIVER SPECIFICATION

Code	IST-3WREC
Working frequency	ISM433MHz (432.0 ~ 433.8MHz adjustable)
Power supply	DC 24V, 0.5A
Dimension	200×108×31mm
Weight	500g

## OPTIONAL ACCESSORY


Calibration cable	IST-3W-CABLE
-------------------	--------------

# INTERCHANGEABLE HEAD DIGITAL TORQUE WRENCH




IST-2W135A

- Clockwise and counter-clockwise operation
- Unit: N.m, in.lb, ft.lb, kg.cm, degree
- Peak and track working mode
- Target torque value can be set, with audible and visible alarm:
  - Green LED light on and buzzer sounds when torque value is 90%~100% of target torque
  - Both green and red LED light on and buzzer sounds when target torque value is reached
- Power off in 5 minutes automatically without any operations
- Non-slip grip handle
- With damp record
- With overload record  
(once the torque reaches 110% of the maximum range)



Ratchet head (included)

square driver



torque correction

torque value needs to be corrected if L2 is different when head is changed

## SPECIFICATION

Code	IST-2W30A	IST-2W135A	IST-2W200A	IST-2W340A
Range	6 ~ 30N.m	27 ~ 135N.m	40 ~ 200N.m	68 ~ 340N.m
Accuracy	clockwise	±2%		
	counter-clock wise	±3%		
Resolution	0.01N.m	0.1N.m	0.1N.m	0.1N.m
Socket size (A×B)	12×9mm	12×9mm	18×14mm	18×14mm
Arm length (L1)	272.7mm	287.7mm	381.2mm	501.2mm
Power supply	2xAA batteries, for 110 hours working			
Weight	1400g	1570g	2170g	2320g

## RATCHET HEAD (included) SPECIFICATION

Code of torque wrench	IST-2W30A	IST-2W135A	IST-2W200A	IST-2W340A
Square driver (D)	1/4"	3/8"	1/2"	1/2"
Length (L2)	29mm	29mm	40mm	40mm

## STANDARD DELIVERY

Torque wrench	1 pc
Ratchet head	1 pc

## OPTIONAL ACCESSORY

Calibration cable	IST-1W-CABLE
Interchangeable head	refer to next page

To be continued

Continued from previous page

## INTERCHANGEABLE HEAD DIGITAL TORQUE WRENCH



Ratchet head (optional)

Code	Square driver (D)	Applicable wrenches
IST-2W-R1	1/4"	IST-2W30A
IST-2W-R2	3/8"	IST-2W135A
IST-2W-R3	1/2"	IST-2W135A
IST-2W-R4	1/2"	IST-2W200A IST-2W340A



ADJUSTABLE SPANNER HEAD (optional)

Code	Open size	Applicable wrenches
IST-2W-A1	5 ~ 27mm	IST-2W135A
IST-2W-A2	5 ~ 30mm	IST-2W200A
IST-2W-A3	10 ~ 41mm	IST-2W340A



OPEN END HEAD (optional)

Code	Open size	Applicable wrenches
IST-2W-K7	7mm	IST-2W30A IST-2W135A
IST-2W-K8	8mm	
IST-2W-K9	9mm	
IST-2W-K10	10mm	
IST-2W-K11	11mm	
IST-2W-K12	12mm	
IST-2W-K13	13mm	
IST-2W-K14	14mm	
IST-2W-K15	15mm	
IST-2W-K16	16mm	
IST-2W-K17	17mm	
IST-2W-K18	18mm	
IST-2W-K19	19mm	
IST-2W-K13A	13mm	
IST-2W-K14A	14mm	
IST-2W-K15A	15mm	
IST-2W-K16A	16mm	
IST-2W-K17A	17mm	
IST-2W-K18A	18mm	
IST-2W-K19A	19mm	
IST-2W-K21A	21mm	
IST-2W-K22A	22mm	
IST-2W-K24A	24mm	



BOX END HEAD (optional)

Code	Open size	Applicable wrenches	
IST-2W-M7	7mm	IST-2W30A IST-2W135A	
IST-2W-M8	8mm		
IST-2W-M10	10mm		
IST-2W-M11	11mm		
IST-2W-M12	12mm		
IST-2W-M13	13mm		
IST-2W-M14	14mm		
IST-2W-M15	15mm		
IST-2W-M16	16mm		
IST-2W-M17	17mm		
IST-2W-M18	18mm		
IST-2W-M19	19mm		
IST-2W-M21	21mm		
IST-2W-M22	22mm		
IST-2W-M13A	13mm		IST-2W200A IST-2W340A
IST-2W-M14A	14mm		
IST-2W-M15A	15mm		
IST-2W-M16A	16mm		
IST-2W-M17A	17mm		
IST-2W-M18A	18mm		
IST-2W-M19A	19mm		
IST-2W-M21A	21mm		

# TORQUE WRENCH

ACCURACY  $\pm 3\%$

ATTENTION: CLOCKWISE  
OPERATION ONLY




IST-2WM100

■ According to DIN ISO 6789, ASME B107.300-2010

Set torque:



step 1: unlock



step 2: set



step 3: lock

## SPECIFICATION

Code	IST-2WM25	IST-2WM60	IST-2WM100	IST-2WM200	IST-2WM340	IST-2WM600	IST-2WM800
Range (clockwise)	5 ~ 25N.m	10 ~ 60N.m	20 ~ 100N.m	40 ~ 200N.m	60 ~ 340N.m	100 ~ 600N.m	150 ~ 800N.m
Accuracy	$\pm 3\%$	$\pm 3\%$	$\pm 3\%$	$\pm 3\%$	$\pm 3\%$	$\pm 3\%$	$\pm 3\%$
Graduation	0.2N.m	0.5N.m	0.5N.m	1N.m	2N.m	5N.m	5N.m
Square driver (D)	1/4"	3/8"	3/8"	1/2"	1/2"	3/4"	3/4"
Length	281mm	337mm	436mm	512mm	614mm	1050mm	1240mm
Weight	590g	760g	1320g	1580g	1800g	5030g	6110g

# PRECISION CUTTING MACHINE CODE ISJ-CMA35



- Low noise
- Manual and automatic mode switch
- Built-in recycling water cooling system
- Ball bearing for long working life
- With currency overload protection



cutting blade



coolant



wrench

## SPECIFICATION

Maximum cutting diameter	Ø35mm
Maximum cutting depth	200mm
Diameter of cutting blade	Ø255mm
Hole diameter of cutting blade	Ø31.75mm
Feeding method	manual or automatic
Rotating speed	2500rpm
Power supply	AC 380V, 50Hz, 900W
Dimension	830×900×1300mm
Weight	226kg

## STANDARD DELIVERY

Main unit	1pc
Cutting blade	2pcs
Coolant	3 bottles
Wrench	2pcs

## OPTIONAL ACCESSORY

Cutting blade	ISJ-CMA35-CUT
Coolant	ISJ-CMA35-COLT


# GRINDER AND POLISHER CODE ISJ-PMA200



- Low noise
- With motor overload protection



aluminum oxide powder



silicon carbide paper



polishing cloth

## SPECIFICATION

Quantity of platen	2
Grinding method	manual
Platen diameter	Ø200mm
Rotation speed	50~600rpm (adjustable)
Power supply	AC 220V, 50Hz, 250W
Dimension	750×690×460mm
Weight	55kg

## STANDARD DELIVERY


Main unit	1pc
Aluminum oxide powder (100g)	1 bag
Silicon carbide paper	4pcs
Polishing cloth	2pcs

## OPTIONAL ACCESSORY

Aluminum oxide powder (100g)	ISJ-PMA200-ALU
Silicon carbide paper	ISJ-PMA200-SAN
Polishing cloth	ISJ-PMA200-CLT



# MOUNTING PRESS CODE ISJ-MMA32



- Low noise
- Water cooling system
- Can set temperature, heating time and cooling time
- Maximum 40 settings can be saved



spray



hot mounting resin

## SPECIFICATION

Maximum diameter of workpiece	Ø32mm
Mounting quantity	1pc
Power supply	AC 220V, 50Hz, 1600W
Dimension	580×550×590mm
Weight	80kg

## STANDARD DELIVERY

Main unit	1pc
Spray	1 bottle
Hot mounting resin (1kg)	1 bag

## OPTIONAL ACCESSORY

Spray	ISJ-MMA32-LQD
Hot mounting resin (1kg)	ISJ-MMA32-PDR

# CODE NO. INDEX

CODE	DESCRIPTION	PAGE
<b>11</b>		
1103	Digital Caliper	7
1106	Digital Caliper	17
1108	Digital Caliper	8
1109	Metric Digital Caliper	8
1110	Digital Caliper With Carbide Tipped Jaws	9
1111	Mini Digital Caliper	11
1114	Digital Caliper	7
1117	Digital Caliper	17
1118	Waterproof Digital Caliper	6
1119	Digital Caliper With Round Depth Bar	9
1120	Digital Inside Groove Caliper	28
1121	Digital Inside Point Caliper	28
1122	Digital Hook Caliper	35
1123	Digital Inside Knife-Edge Caliper	35
1124	Digital Caliper With Interchangeable Points	27
1125	Universal Caliper	23~24
1130	Left Hand Digital Caliper	10
1135	Digital Caliper	18
1136	Digital Caliper	18
1139	Plastic Digital Caliper	12
1141	Digital Depth Gage	41
1142	Digital Hook Depth Gage	43
1143	Digital Point Depth Gage	42
1144	Digital Double Hook Depth Gage	43
1145	Digital Depth Gage	48
1147	Digital Depth Gage	42
1148	Digital Depth Gage With Round Depth Bar	44
1149	Waterproof Digital Depth Gage	41
1150	Digital Height Gage	53
1154	Digital Height Gage	54
1156	Digital Height Gage With Driving Wheel	54
1161	Digital Tube Thickness Caliper	37
1162	Digital Disk Brake Caliper	39
1163	Digital Snap Gage	166
1165	Digital Crimp Height Caliper	38
1166	Digital Scribing Caliper	236
1167	Digital Disk Brake And Pad Caliper	40
1168	Digital Drum Brake Caliper	40
1169	Digital Small Point Caliper	32
1170	Digital Caliper	12
1171	Digital Caliper	11
1172	Digital Caliper With Large Measuring Faces	38
1176	Digital Inside Groove Caliper	29
1177	Digital Back-Jaw Centerline Caliper	33
1178	Digital Inside Groove Caliper	29
1179	Digital RTJ Ring Groove Caliper	37
1181	Digital Gear Tooth Caliper	39
1183	Digital Point Caliper	32
1185	Digital Outside Point Caliper	31
1186	Digital Offset Caliper	36
1187	Digital Outside Neck Caliper	31
1188	Digital Blade Caliper	30
1189	Digital Arc Radius Caliper	36

CODE	DESCRIPTION	PAGE
1192	Digital Offset Centerline Caliper	33
1193	Digital Caliper With Ceramic Tipped Jaws	10
<b>12</b>		
1201	Mini Vernier Caliper	14
1202	Vernier Caliper With Round Depth Bar	16
1203	Mini Vernier Caliper	13
1204	Mini Vernier Caliper	13
1205	Vernier Caliper	14
1207	Vernier Caliper	19
1208	Vernier Caliper	20
1210	Vernier Caliper	20
1214	Vernier Caliper	21
1215	Long Jaw Vernier Caliper	21
1223	Vernier Caliper With Thumb Clamp	15
1233	Vernier Caliper With Fine Adjustment	15
1236	Vernier Caliper	19
1238	Vernier Caliper With Carbide Tipped Jaws	16
1240	Vernier Depth Gage	45
1244	Vernier Depth Gage	48
1247	Vernier Depth Gage	45
1248	Vernier Hook Depth Gage	46
1249	Vernier Depth Gage	46
1250	Vernier Height Gage	55
1253	Vernier Height Gage	56
1267	Chamfer Gage	220
1275	T-Shape Marking Gage	234
<b>13</b>		
1311	Dial Caliper	13
1312	Dial Caliper	13
1351	Dial Height Gage	55
<b>15</b>		
1520	Digital Inside Groove Caliper	30
1524	Digital Back-Jaw Edge To Center Caliper	34
1525	Digital Centerline/Edge To Center Caliper	34
1526	Digital Caliper With Interchangeable Points	25~26
<b>21</b>		
2103	Digital Indicator	120
2104	Digital Indicator	120
2108	Digital Indicator For Bore Gages	123
2112	Digital Indicator	119
2113	No Auto Power Off Digital Indicator	123
2114	Compact Digital Indicator	124
2115	Waterproof Digital Indicator	122
2116	Metric Digital Indicator	121
2117	Large Stroke Digital Indicator	124
2122	Bore Gage	112
2132	Digital External Caliper Gage	154
2141	Digital Depth Gage	51
2142	Digital Depth Gage	49
2151	Digital Internal Caliper Gage	154
2152	Bore Gage For Small Holes	111

# CODE NO. INDEX

CODE	DESCRIPTION	PAGE
2163	Digital Snap Gage	165
2164	Digital 3-Purpose Snap Gage	166
2166	Digital Snap Gage	165
2167	Digital Snap Gage	165
2168	Step And Gap Gage	167
2170	Digital Level And Protractor	343
2171	Digital Protractor	195
2172	Digital Protractor	199
2173	Digital Level And Protractor	342
2176	Digital Protractor	195
2179	Digital Level And Protractor	342
2183	Digital Radius Gage	118
2184	Dial Snap Gage	162
2186	Dial Snap Gage	163
2187	Adjustable Snap Gage	164
<b>22</b>		
2222	Internal Dial Caliper Gage	152
2278	Combination Square Set	200
<b>23</b>		
2301	Dial Indicator	126
2308	Dial Indicator	126
2309	Dial Indicator	130
2310	Dial Indicator	129
2311	Compact Dial Indicator	125
2313	Precision Dial Indicator	125
2314	Shockproof Dial Indicator	127
2316	One Revolution Dial Indicator	129
2318	Dial Indicator	128
2321	Internal Dial Caliper Gage	153
2322	Bore Gage	112
2324	Waterproof Dial Indicator	127
2328	Double Face Dial Indicator	128
2332	External Dial Caliper Gage	153
2333	External Dial Caliper Gage	152
2341	Dial Depth Gage	50
2342	Dial Depth Gage	50
2343	Dial Depth Gage	49
2361	Thickness Gage	157
2363	Thickness Gage	159
2364	Thickness Gage	155
2365	Thickness Gage	156
2366	Thickness Gage	157
2367	Tube Thickness Gage	158
2372	Universal Protractor	198
2373	Dial Protractor	199
2374	Protractor	198
2380	Dial Test Indicator	136
2381	Dial Test Indicator	136
2385	Centering Indicator	255
2386	Large Range Dial Test Indicator	137
2391	Round Body Dial Test Indicator	138
2394	Zero Setter	261
2395	Bore Gage Setter	115

CODE	DESCRIPTION	PAGE
2397	Zero Setter	261
2398	Back Plunger Type Dial Test Indicator	136
2399	Dial Test Indicator	137
<b>28</b>		
2824	Bore Gage Set	113
2827	Bore Gage	113
2828	Bore Gage	114
2841	Crankshaft Tester	167
2842	3D Tester	256
2852	Bore Gage For Small Holes	111
2862	Thickness Gage	159
2863	Thickness Gage	159
2866	Thickness Gage With Pointed Tips	160
2871	Digital Thickness Gage	155
2872	Digital Thickness Gage	156
2873	Digital Tube Thickness Gage	158
<b>31</b>		
3101	Digital Outside Micrometer	58
3108	Metric Digital Outside Micrometer	59
3109	Digital Outside Micrometer	59
3127	Digital Three Points Internal Micrometer	101~102
3128	Digital Wide Range Three Points Internal Micrometer	103
<b>32</b>		
3202	Outside Micrometer	61
3203	Outside Micrometer	60
3205	Outside Micrometer With Extension Anvil Collar	65
3206	Outside Micrometer With Interchangeable Anvils	63
3208	Quick Feeding Outside Micrometer	60
3209	Long Spindle Outside Micrometer	62
3210	1 $\mu$ m Graduation Outside Micrometer	61
3220	Inside Micrometer	97
3221	Tubular Inside Micrometer	105
3222	Tubular Inside Micrometer	105
3224	Tubular Inside Micrometer	106
3225	Tubular Inside Micrometer	106
3226	Internal Screw Thread Micrometer	110
3227	Three Points Internal Micrometer	99~100
3228	Wide Range Three Points Internal Micrometer	103
3229	Tubular Inside Micrometer	104
3230	Point Micrometer	75
3232	Blade Micrometer	76
3233	Spline Micrometer	78
3235	Limit Micrometer	67
3236	Outside Micrometer For Left And Right Hand	62
3238	Caliper Type Micrometer	88
3239	Sheet Metal Micrometer	82
3240	Depth Micrometer	52
3241	Depth Micrometer	52
3260	Spherical Anvil Tube Micrometer	80
3261	Cylindrical Anvil Tube Micrometer	79
3262	Interchangeable Anvil Micrometer	83

# CODE NO. INDEX

CODE	DESCRIPTION	PAGE
3263	Sheet Metal Micrometer	87
3266	Crimp Height Micrometer	77
3280	Non Rotating Spindle Universal Micrometer	85
3281	Screw Thread Micrometer	71
3282	Disk Micrometer	86
3285	Wire Micrometer	88
3287	Groove Micrometer	85
3288	Disk Brake Micrometer	81
3290	V-Anvil Micrometer	84
3291	Gear Tooth Micrometer	74
3292	Hub Micrometer	88
3293	Can Seam Micrometer	89
3294	Non Rotating Spindle Disk Micrometer	86
3296	Micrometer With Dial Indicator	67
<b>33</b>		
3331	Micrometer With Dial Indicator	68
3332	Indicating Micrometer	66
3333	Indicating Micrometer	66
3334	Dial Snap Gage	162
3335	Dial Snap Gage	161
3336	Dial Snap Gage	161
3337	Dial Snap Gage	160
<b>35</b>		
3506	Digital Outside Micrometer With Interchangeable Anvils	64
3520	Digital Inside Micrometer	97
3530	Digital Point Micrometer	75
3532	Digital Blade Micrometer	76
3533	Digital Spline Micrometer	78
3539	Digital Sheet Metal Micrometer	82
3540	Digital Depth Micrometer	51
3560	Digital Spherical Anvil Tube Micrometer	80
3561	Digital Cylindrical Anvil Tube Micrometer	79
3562	Digital Interchangeable Anvil Micrometer	83
3566	Digital Crimp Height Micrometer	77
3580	Digital Universal Micrometer	86
3581	Digital Screw Thread Micrometer	72
3588	Digital Disk Brake Micrometer	81
3590	Digital V-Anvil Micrometer	84
3591	Digital Gear Tooth Micrometer	74
3594	Digital Non Rotating Spindle Disk Micrometer	87
<b>36</b>		
3631	Non-Rotating Spindle Digital Micrometer	57
3632	Non-Rotating Spindle Digital Micrometer	57
3633	Micrometer With Dial Indicator	68
3634	Tubular Inside Micrometer	108
3635	Digital Non-Rotating Spindle Tubular Inside Micrometer	107
3636	External Gear Tooth Micrometer	73
3637	Internal Gear Tooth Micrometer	98
3638	Internal Gear Tooth Micrometer	109
3639	External Screw Thread Micrometer	69

CODE	DESCRIPTION	PAGE
3640	Internal Screw Thread Micrometer	98
3641	Internal Screw Thread Micrometer	109
<b>40</b>		
4001	Cylinder Gage Block	179
4002	Angle Gage Block	182
4003	Angle Plate Set	249
4004	Universal Angle Plate Set	250
<b>41</b>		
4100	Steel Gage Block Set	171-172
4101	Individual Steel Gage Block	174
4105	Ceramic Gage Block Set	169
4106	Individual Ceramic Gage Block	173
4107	Micrometer Inspection Gage Block Set	175
4108	Caliper Inspection Gage Block Set	176
4109	Angle Gage Block Set	181
4110	Individual Pin Gage	184
4111	Wear Block Set	175
4118	Custom-Made Pin Gage	184
4120	Thread Ring Gage	188
4121	American Standard Thread Ring Gage	190
4124	Plain Plug Gage	186
4129	Fine Thread Ring Gage	189
4130	Thread Plug Gage	186
4131	American Standard Thread Plug Gage	190
4139	Fine Thread Plug Gage	187
4141	Granite Square	201
4143	Granite Parallel Set	249
4144	Granite Square	201
4147	Granite Straight Edge	211
4155	Sine Bar	251
4157	Sine Bench Center	151
4164	Carbide Gage Block Set	170
4166	Pin Gage Set	183
4180	Magnalium Straight Edge	211
4184	Optical Parallel	90
<b>42</b>		
4206	Telescoping Gage Set	117
4208	Small Hole Gage Set	116
4209	Long Handle Telescoping Gage	117
<b>46</b>		
4601	Feeler Gage	213
4602	Feeler Gage	213
4605	Long Feeler Gage	214
4621	Feeler Gage Tape	215
4622	Feeler Gage Stock	214
4630	Taper Gage	221
4631	Metric Thread Ring Gage	192
4632	Metric Fine Thread Ring Gage	192
4633	American Standard Thread Ring Gage	193
4634	NPT Thread Ring Gage	194
4641	Metric Thread Plug Gage	191

# CODE NO. INDEX

CODE	DESCRIPTION	PAGE
4642	Metric Fine Thread Plug Gage	191
4643	American Standard Thread Plug Gage	193
4644	NPT Thread Plug Gage	194
<b>47</b>		
4700	Straight Edge	210
4701	Adjustable Square	206
4702	Square Set	210
4706	120° Square	209
4707	Machinist Square With Wide Base	206
4710	Cylinder Square	202
4720	Bench Center With Roller Tailstocks	150
4721	Mini Bench Center	148
4722	Vertical And Horizontal Bench Center	149
4723	Bench Center With Straightness Measurement	149
4724	Concentricity Gage	147
4725	Concentricity Gage	147
4745	45° Square	207
4747	45° Square With Wide Base	207
4754	135° Square With Wide Base	209
4760	60° Square	208
4762	60° Square With Wide Base	208
4770	Perpendicularity Tester	202
4780	Protractor	196
4781	Protractor	196
4782	Bench Center	150
4783	Vertical And Horizontal Bench Center	148
4788	Bench Center	151
4789	Concentricity Gage	146
4790	90° Beveled Edge Square	203
4791	90° Flat Edge Square	204
4792	90° Flat Edge Square With Wide Base	205
4793	90° Flat Edge Square With Wide Base	204
4794	90° Tool Maker Square	203
4795	90° Beveled Edge Square With Wide Base	205
4797	Protractor	197
4799	Protractor	197
<b>48</b>		
4801	Radius Gage	219
4804	Radius Gage Set	219
4806	Angle Gage	218
4807	Angle Gage Set	218
4810	Center Gage	217
4812	Thread Gage	217
4820	Pitch Gage	216
4824	Pitch Gage	215
4830	Welding Gage	222
4831	Digital Welding Gage	223
4832	Fillet Welding Gage	223
4833	Taper Gage	221
4834	Welding Gage	224
4835	Welding Gage	226
4836	Fillet Welding Gage	224
4837	Taper Gage Set	222

CODE	DESCRIPTION	PAGE
4838	Welding Gage	225
4839	Pipe Welding Gage	228
4840	Welding Gage	227
4841	Pipe Welding Gage	227
4842	Drill Angle Gage	229
4843	Drill Point Gage	229
4844	Chamfer Gage	220
<b>49</b>		
4905	Block Level	344
4906	Frame Level	343
4907	Short Level	344
4908	Mini Level	344
4910	Digital Level	345
4911	Aluminum Alloy Level	345
<b>50</b>		
5013	13-Piece Measuring Tool Set	268
5021	2-Piece Measuring Tool Set	262
5022	2-Piece Measuring Tool Set	262
5023	2-Piece Measuring Tool Set	263
5024	2-Piece Measuring Tool Set	263
5031	3-Piece Measuring Tool Set	264
5041	4-Piece Measuring Tool Set	264
5042	4-Piece Measuring Tool Set	265
5051	5-Piece Measuring Tool Set	265
5052	5-Piece Measuring Tool Set	266
5061	6-Piece Measuring Tool Set	266
5062	6-Piece Measuring Tool Set	267
5063	6-Piece Measuring Tool Set	267
5091	9-Piece Measuring Tool Set	268
<b>61</b>		
6140	Depth Base Attachment	47
6141	Extension Base	47
6143	Depth Stop For Calipers	31
<b>62</b>		
6200	Magnetic Stand	142
6201	Magnetic Stand	142
6202	Magnetic Stand	142
6207	Flex Arm Magnetic Stand	143
6208	Universal Magnetic Stand	141
6210	Universal Magnetic Stand	141
6211	Mini Magnetic Stand	144
6214	Universal Stand	143
6215	Magnetic Stand For Uneven Surface	142
6224	Mini Magnetic Stand	143
6282	Point	131~134
6282	Extension Rod	134
6282	Point Set	134
6284	Styli For Dial Test Indicators	138
6291	Dial Test Indicator Centering Holder	140
6293	Dial Test Indicator Holder	139
6294	Indicator Centering Holder	140

# CODE NO. INDEX

CODE	DESCRIPTION	PAGE
6295	Dial Test Indicator Centering Holder	140
6296	Dial Test Indicator Holder	139
6297	Dial Test Indicator Universal Holder	139
<b>63</b>		
6300	Micrometer Stand	90
6301	Micrometer Stand	90
6310	Micrometer Setting Standard	91
6312	Setting Ring	116
6315	Micrometer Measuring Force Detector	89
6353	Digital Micrometer Head	92
6354	Digital Micrometer Head	92
6372	Small Micrometer Head	92
6373	Large Thimble Micrometer Head	93
6375	Quick Spindle Feeding Micrometer Head	96
6377	Non Rotating Spindle Micrometer Head	95
6381	Micrometer Head	95
6384	Micrometer Head With Zero Adjustable Thimble	93
6385	Small Micrometer Head	93
6386	Micrometer Head	94
6387	Micrometer Head	94
6388	Large Micrometer Head	96
<b>65</b>		
6521	Precision Universal Vise	254
6522	Precision Sine Vise	252
6523	Precision Sine Vise	253
6524	Precision Compound Sine Vise	253
6525	Precision Vise	254
6526	Precision Vise	255
6527	Sine Table	252
6533	Parallel Set	247
6534	Parallel Set	248
6535	Adjustable Angle Block	250
6547	Right Angle Plate	251
6550	Electronic Zero Setter	260
6553	Electronic Zero Setter	260
6554	Zero Setter	260
6562	Edge Finder	259
6566	Electronic Edge Finder	258
6567	Edge Finder	258
6568	Ceramic Edge Finder	259
6570	2D Electronic Edge Finder	257
6571	3D Electronic Edge Finder	257
<b>68</b>		
6801	Magnetic V-Block	245
6802	V-Block Set	241
6803	V-Block Set	242
6804	V-Block	241
6862	Dial Indicator Stand	145
6863	Dial Indicator Stand	145
6864	Dial Indicator Stand	145
6865	Transfer Stand	146

CODE	DESCRIPTION	PAGE
6866	Granite Dial Indicator Stand	144
6867	Granite Dial Indicator Stand	144
6881	Gage Block Accessory	177~178
6882	Check Master	181
6883	Gage Block Holder	176
6884	Caliper/Height Gage Checker	180
6887	V-Block Set	242
6888	Roller Bearing V-Block Set	243
6889	Magnetic V-Block	244
6890	Magnetic V-Block	245
6891	Magnetic V-Block Set	246
6892	Magnetic Induction V-Block	246
6894	Magnetic Induction Parallel Set	248
6896	V-Block Set	240
6897	Granite V-Block Set	243
6898	Magnetic Rectangular Blocks	240
6899	Magnetic Induction V-Block Set	247
<b>69</b>		
6900	Granite Surface Plate	238
6902	Stand For Granite Surface Plate	239
6903	Jack Set For Granite Surface Plate	239
6990	Height Scriber	237
<b>71</b>		
7101	Digital Horizontal Scale	269
7102	Digital Vertical Scale	270
7106	Linear Gage And Display Unit	275
7107	Multi Linear Gage System	276
7108	High Precision Linear Gage And Display Unit	274
7110	Steel Rule	233
7111	Straight Edge	234
7113	Rigid Rule	233
7114	Circumference Tape	118
7117	Precision Straight Edge	212
7118	Precision Straight Edge With Beveled Edge	212
7120	Marking Gage	234
7121	Flexible Rule	232
7122	Rigid Rule	232
7150	Scriber For Height Gages	56
<b>72</b>		
7202	Scribing Caliper	235
7203	Scribing Caliper	236
7205	Center Marking Gage	235
7230	Scriber	237
7231	Scriber	237
7232	Scriber	237
7247	Divider	231
7260	Spring Divider	231
7261	Inside Spring Caliper	230
7262	Outside Spring Caliper	230
<b>73</b>		
7302	Data Output Cable	4

# CODE NO. INDEX

CODE	DESCRIPTION	PAGE
7304	Foot Switch With Cable	5
7305	RS232 Data Output Cable	5
7306	Wireless Data Transfer System	3
7311	Measuring Data Management Software	1~2
7321	Measuring Tips For Internal Screw Thread Micrometer	110
7330	Back	135
7332	Spindle Lift Knob	134
7340	Box For Pin Gages	184
7341	Pin Gage Handle	185
7350	Anvil For Bore Gages	115
7351	Long Handle	114
7381	Measuring Tips For Screw Thread Micrometer	72
7382	3-Wires	69
7383	Ball Tips For Gear Tooth Micrometer	73
7384	Measuring Tips For External Screw Thread Micrometer	70
7385	Measuring Tips For Internal Screw Thread Micrometer	71
7391	Ball Tips For Gear Tooth Micrometer	74
<b>ISD</b>		
ISD-A100-P	Vision Measuring System	289~290
ISD-V150	Vision Measuring System	287~288
ISD-V250	Vision Measuring System	287~288
ISD-V300	Vision Measuring System	287~288
<b>ISE</b>		
ISE-2DT	Digital Level	341
<b>ISF</b>		
ISF-1DFxxx	Digital Force Gage	378
ISF-DFxxx	Digital Force Gage (High Resolution)	379
ISF-MT1K	Test Stand	380
<b>ISH</b>		
ISH-BRV	Brinell/Rockwell/Vickers Hardness Tester	350
ISH-DSA	Digital Shore Durometer	373
ISH-DSD	Digital Shore Durometer	373
ISH-DS-STAND	Test Stand For Digital Shore Durometer	374
ISH-DV10	Digital Vickers Hardness Tester	355
ISH-DV50	Digital Vickers Hardness Tester	355
ISH-HVC	Vickers Hardness Measuring System	356
ISH-MR150	Automatic Rockwell Hardness Tester	348
ISH-MRD200	Automatic Digital Rockwell Hardness Tester	346
ISH-OS2	Test Stand For Shore Durometer	376
ISH-PHA	Portable Leeb Hardness Tester	359
ISH-PHB	Portable Leeb Hardness Tester	360
ISH-R150	Manual Rockwell Hardness Tester	349
ISH-RD200	Manual Digital Rockwell Hardness Tester	347
ISH-RUN	Support Rings For Portable Leeb Hardness Tester	362

CODE	DESCRIPTION	PAGE
ISH-Rxxx	Support Rings For Portable Leeb Hardness Tester	362
ISH-S30A	Shore Durometer	375
ISH-S30A-BLOCK	Hardness Test Block For Shore Durometer	375
ISH-S30D	Shore Durometer	375
ISH-S30D-BLOCK	Hardness Test Block For Shore Durometer	375
ISH-SAM	Shore Durometer	377
ISH-SDM	Shore Durometer	377
ISH-SPHA	Portable Leeb Hardness Tester	357~358
ISH-SPHD	Portable Leeb Hardness Tester	361
ISH-SRxxx	Support Rings For Portable Leeb Hardness Tester	362
ISH-STAC	Test Stand For Shore Durometer	377
ISH-STD	Test Stand For Shore Durometer	377
<b>ISHB</b>		
ISHB-B300	Barcol Hardness Tester	372
ISHB-D200	Automatic Digital Brinell Hardness Tester	352
ISHB-H131	Hydraulic Brinell Hardness Tester	369
ISHB-M100	Automatic Brinell Hardness Tester	351
ISHB-P101	Pin Brinell Hardness Tester	370
ISHB-TSA	Brinell Indentation Measuring System	353
ISHB-TSB	Brinell Indentation Measuring System	353
<b>ISHR</b>		
ISHR-B141	Magnetic Brinell/Rockwell Hardness Tester	368
ISHR-D121	Digital Magnetic Rockwell Hardness Tester	366
ISHR-M111	Magnetic Rockwell Hardness Tester	367
ISHR-P151	Portable Rockwell Hardness Tester	365
<b>ISHU</b>		
ISHU-460	Ultrasonic Hardness Tester	363~364
<b>ISHV</b>		
ISHV-D120	Automatic Digital Micro-Vickers Hardness Tester	354
<b>ISHW</b>		
ISHW-Bxxx	Webster Hardness Tester	371
ISHW-Lxxx	Webster Hardness Tester	371
<b>ISJ</b>		
ISJ-CMA35	Precision Cutting Machine	392
ISJ-MMA32	Mounting Press	394
ISJ-PMA200	Grinder And Polisher	393
<b>ISL</b>		
ISL-A1xxx	Linear Scale	271~272
ISL-A5xxx	Linear Scale	271~272
ISL-B5xxx	Linear Scale	271~272
ISL-DR2	Counter	273
ISL-DR3	Counter	273


# CODE NO. INDEX

CODE	DESCRIPTION	PAGE
<b>ISM</b>		
ISM-D500	Digital Camera	300
ISM-M1000	High Magnification Microscope	299
ISM-M2000	Metallurgical Microscope	301
ISM-M600-P	High Magnification Microscope	298
ISM-MAS100	Metallurgical Image Analysis Software And Camera	302
ISM-PM160LA	Digital Measuring Microscope	293~294
ISM-PM200SB	Digital Measuring Microscope	293~294
ISM-PM600SB	Digital Measuring Microscope	293~294
ISM-PMxxx	Portable Measuring Microscope	303
ISM-TV200	TV Digital Microscope	295
ISM-TV200W	TV Digital Microscope	295
ISM-WF200	WiFi Digital Measuring Microscope	291~292
ISM-ZS30	Zoom Stereo Microscope	297
ISM-ZS50	Zoom Stereo Microscope	296
ISM-ZS50T	Zoom Stereo Microscope	296
<b>ISN</b>		
ISN-L70	Laser Distance Meter	324
<b>ISO</b>		
ISO-1500F	Coating Thickness Gage	319
ISO-2000FN	Coating Thickness Gage	318
<b>ISP</b>		
ISP-A1000E	Profile Projector	279~280
ISP-A3000E	Horizontal Profile Projector	283~284
ISP-A5000E	Profile Projector	281~282
ISP-A7000E	Horizontal Profile Projector	285~286
ISP-AZ3020	Profile Projector	281~282
ISP-W3020	Horizontal Profile Projector	283~284
ISP-W4025	Horizontal Profile Projector	285~286
ISP-Z3015	Profile Projector	279~280
<b>ISQ</b>		
ISQ-TE100	External Thread Measuring Device	277~278
ISQ-TS120K	Digital LED Tachometer/Stroboscope	323
<b>ISR</b>		
ISR-C100	Roughness Tester	337~338
ISR-CS017	Shot And Grit Blasting Surface Roughness Specimen	340
ISR-CS018	Shot And Grit Blasting Surface Roughness Specimen	340
ISR-CS130	Surface Roughness Specimen Set	339
ISR-CSxxx	Surface Roughness Specimen	340
ISR-RSxxx	Surface Roughness Reference Specimen	339
ISR-S1000A	Surface Roughness Tester	328~330
ISR-S1000B	Surface Roughness Tester	325~327
ISR-S300	Roughness Tester	334~336
ISR-S400	Roughness Tester	334~336
ISR-S500	Roughness Tester	331~333

CODE	DESCRIPTION	PAGE
<b>IST</b>		
IST-1Wxxx	Digital Angle Torque Wrench	387
IST-2WMxxx	Torque Wrench	391
IST-2Wxxx	Interchangeable Head Digital Torque Wrench	389~390
IST-3Wxxx	Wireless Data Transfer Digital Torque Wrench	388
IST-DCTxxx	Digital Bottle Cap Torque Tester	383
IST-SD200	Digital Torque Screwdriver	384
IST-SD400	Digital Torque Screwdriver	384
IST-SD50	Digital Torque Screwdriver	384
IST-TS500	Torque Wrench Test Stand	382
IST-TTxxx	Digital Torque Tester	381
IST-WP12	Small Range Digital Torque Wrench	384
IST-WP20	Small Range Digital Torque Wrench	384
IST-WSxxx	Short Handle Digital Torque Wrench	385
IST-Wxxx	Digital Torque Wrench	386
<b>ISU</b>		
ISU-200D	Ultrasonic Thickness Gage	322
ISU-250C	Ultrasonic Thickness Gage	321
ISU-300D	Ultrasonic Thickness Gage (Through Coating)	320
<b>ISV</b>		
ISV-1CAM	Camera	312
ISV-1HLED	LED Light Handle	312
ISV-1Hxxx	Rigid Borescope	311
ISV-1LED1	Adjustable LED Light Source	312
ISV-2000D	Manual 360° Swivel Videoscope	305
ISV-2001D	Manual 360° Swivel Videoscope	305
ISV-3000D	Manual 360° Swivel Videoscope	305
ISV-3001D	Manual 360° Swivel Videoscope	305
ISV-4000D	Motorized 360° Swivel Videoscope	304
ISV-E10	Videoscope	308
ISV-E20	Videoscope	309
ISV-HCAM	Camera	317
ISV-HF4030	Front View Borescope (Rigid)	313
ISV-HL3000	LED Light Source	317
ISV-HMxxx	Borescope With Mirror (Rigid)	315
ISV-HP1911	Oblique View Borescope (Rigid)	316
ISV-HP2811	Oblique View Borescope (Rigid)	316
ISV-HP2817	Oblique View Borescope (Rigid)	316
ISV-HR6032	Rotary Side View Borescope (Rigid)	314
ISV-RV	Side View Videoscope (Rigid)	307
ISV-VP280	Pipe Videoscope	310
ISV-VP60	Videoscope	306



## DATA OUTPUT AND SOFTWARE



Measuring data management software  
7311- (PAGE 1)


Wireless data transfer system  
7306- (PAGE 3)



Data output cable  
7302-, 7305- (PAGE 4-5)



## HEIGHT



Height gage  
1150-, 1156-, 1154-, 1351-, 1250-, 1253-  
(PAGE 53-56)




Dial indicator stand  
6866-, 6867-, 6863-, 6864-, 6862-  
(PAGE 144-145)



Transfer stand  
6865-  
(PAGE 146)




## DEPTH




Depth gage  
1149-, 1141-, 1147- (PAGE 41-42)  
1240-, 1247-, 1249- (PAGE 45-46)




Depth gage with point  
1143-  
(PAGE 42)



Depth gage with hook  
1142-, 1144- (PAGE 43)  
1248- (PAGE 46)



Depth gage for small hole  
1148- (PAGE 44)



Mini depth gage  
1244-, 1145-  
(PAGE 48)




Dial/digital depth gage  
2343-, 2142-, 2341-, 2342-, 2141-  
(PAGE 49-51)



Depth micrometer  
3540-, 3240-, 3241-  
(PAGE 51-52)



Extension base  
6141-  
(PAGE 47)




Depth base attachment  
6140-  
(PAGE 47)



Digital/dial/vernier caliper with depth bar  
(PAGE 6-16)



## INTERNAL DIAMETER



Digital/dial/vernier caliper with internal measuring jaws  
(PAGE 6-21)



Inside micrometer  
3220-, 3520-  
(PAGE 97)



Three points internal micrometer  
3227-, 3127-, 3228-, 3128-  
(PAGE 99-103)



Tubular inside micrometer  
3229-, 3221-, 3222-, 3225-, 3224-,  
3635-, 3634- (PAGE 104-108)




Bore gage  
2852-, 2152-, 2322-, 2122-, 2824-,  
2827-, 2828- (PAGE 111-114)




Telescoping gage  
4208-, 4206-, 4209-  
(PAGE 116-117)



Digital inside knife-edge caliper  
1123-  
(PAGE 35)



Universal caliper  
1125-  
(PAGE 23-24)



Inside spring caliper  
7261-  
(PAGE 230)




Pin gage  
4166-, 4110-, 4118- (PAGE 183-184)




Plain plug gage  
4124-  
(PAGE 186)




## ARC RADIUS



Digital radius gage  
2183  
(PAGE 118)



Digital arc radius caliper  
1189-  
(PAGE 36)



Radius gage  
4801-, 4804-  
(PAGE 219)



## SHAFT DIAMETER QUICK MEASUREMENT



Dial snap gage  
2186-  
(PAGE 163)




Adjustable snap gage  
2187-  
(PAGE 164)



# APPLICATION INDEX

## EXTERNAL DIAMETER



Universal caliper  
1125-  
(PAGE 23-24)



Circumference tape  
7114-  
(PAGE 118)



Digital/dial/vernier caliper  
(PAGE 6-21)



Outside micrometer  
(PAGE 57-65)



Indicating micrometer  
3333-, 3332-  
(PAGE 66)



Micrometer with dial indicator  
3296-, 3331-, 3633-  
(PAGE 67-68)




Dial snap gage  
3337-, 3336-, 2184-  
(PAGE 160-162)



Dial Snap gage  
3335-, 3334-  
(PAGE 161-162)



## DIAMETER OF GROOVE INSIDE HOLE



Universal caliper  
1125-  
(PAGE 23-24)




Digital caliper with interchangeable points  
1526-, 1124-  
(PAGE 25-27)



Digital inside groove caliper  
1120-, 1121-, 1176-, 1178-, 1520-  
(PAGE 28-30)



Internal caliper gage  
2222-, 2321-, 2151-  
(PAGE 152-154)




## WIDTH AND POSITION OF GROOVE INSIDE HOLE




Digital hook caliper  
1122-  
(PAGE 35)




Depth gage with hook  
1142-, 1144- (PAGE 43)  
1248- (PAGE 46)



Digital depth gage with round depth bar  
1148- (PAGE 44)



Groove micrometer  
3287-  
(PAGE 85)



## EXTERNAL GROOVE DIAMETER




Digital blade caliper  
1188-  
(PAGE 30)



Blade micrometer  
3232-, 3532-  
(PAGE 76)



Digital outside neck caliper  
1187-  
(PAGE 31)



Universal caliper  
1125-  
(PAGE 23-24)



Digital caliper with interchangeable points  
1526-, 1124-  
(PAGE 25-27)



## THICKNESS



Thickness gage  
2871-, 2872-, 2364-, 2365-, 2366-, 2361-  
2363-, 2862-, 2863-, 2866-  
(PAGE 155-160)




Digital snap gage  
2166-, 2167-, 2163-, 1163-  
(PAGE 165-166)



External caliper gage  
2333-, 2332-, 2132-  
(PAGE 152-154)



## TUBE WALL THICKNESS



Digital tube thickness caliper  
1161-  
(PAGE 37)



Cylindrical anvil tube micrometer  
3261-, 3561-  
(PAGE 79)




Spherical anvil tube micrometer  
3260-, 3560-  
(PAGE 80)




Tube thickness gage  
2367-  
(PAGE 158)



Digital tube thickness gage  
2873-  
(PAGE 158)




## CHAMFER



Chamfer gage  
4844-, 1267-  
(PAGE 220)



## GAP WIDTH



**Taper gage**  
4630-, 4833-, 4837-  
(PAGE 221-222)




**Internal caliper gage**  
2222-, 2321-, 2151-  
(PAGE 152-154)




**Feeler gage**  
4601-, 4602-, 4605-  
(PAGE 213-214)



**Step and gap gage**  
2168-  
(PAGE 167)



## HOLE CENTER DISTANCE AND HOLE CENTER TO EDGE DISTANCE




**Digital centering caliper**  
1192-, 1177-, 1525-,  
1524- (PAGE 33-34)



**Universal caliper**  
1125-  
(PAGE 23-24)



## ANGLE



**Protractor**  
2171-, 2176-, 4780-, 4781-, 4799-, 4797-  
(PAGE 195-197)



**Protractor**  
2374-, 2372-, 2373-, 2172-  
(PAGE 198-199)



**Combination square set**  
2278-  
(PAGE 200)



**Square**  
4745-, 4747-, 4760-, 4762-, 4706-, 4754-  
(PAGE 207-209)




**Angle gage**  
4806-, 4807  
(PAGE 218)




**Angle gage block**  
4109-, 4002-  
(PAGE 181-182)



**Digital level and protractor**  
2173-, 2179-, 2170-  
(PAGE 342-343)




## STRAIGHTNESS



**Straight edge**  
4700-, 4147-, 4180-, 7117-, 7118-  
(PAGE 210-212)



## SQUARENESS



**Square**  
4141-, 4144-, 4710-  
(PAGE 201-202)



**Perpendicularity tester**  
4770-  
(PAGE 202)




**Combination square set**  
2278-  
(PAGE 200)



**Square**  
4794-, 4790-, 4791-, 4793-, 4792-,  
4795-, 4707-, 4701- (PAGE 203-206)



## COAXIALITY AND RUNOUT




**Concentricity gage**  
4789-, 4725-, 4724-  
(PAGE 146-147)



**Bench center**  
4721-, 4783-, 4722-, 4723-,  
4720-, 4782-, 4788-  
(PAGE 148-151)



**Sine bench center**  
4157-  
(PAGE 151)



**V-block**  
6896-, 6802-, 6804-, 6803-, 6887-, 6888-, 6897-  
(PAGE 240-243)




**Magnetic V-block**  
6889-, 6890-, 6801-, 6891-, 6892-, 6899-  
(PAGE 244-247)




## GEAR




**Digital gear tooth caliper**  
1181-  
(PAGE 39)




**Disk micrometer**  
3282-, 3294-, 3594-  
(PAGE 86-87)




**External gear tooth micrometer**  
3636-, 3291-, 3591-  
(PAGE 73-74)




**Internal gear tooth micrometer**  
3637-  
(PAGE 98)



**Internal gear tooth micrometer**  
3638-  
(PAGE 109)



**Universal caliper**  
1125-  
(PAGE 23-24)




**Digital caliper with interchangeable points**  
1526-, 1124-  
(PAGE 25-27)




# APPLICATION INDEX


## THREAD




**3-wires**  
7382-  
(PAGE 69)




**External screw thread micrometer**  
3639-, 3281-, 3581-  
(PAGE 69-72)



**Internal screw thread micrometer**  
3640- (PAGE 98)



**Internal screw thread micrometer**  
3641-, 3226- (PAGE 109-110)



**Thread plug gage**  
4130-, 4139-, 4131-, 4641-, 4642-  
4643-, 4644- (PAGE 186-194)



**Thread ring gage**  
4120-, 4129-, 4121-, 4631-, 4632-, 4633-  
4634- (PAGE 188-194)




**Pitch gage**  
4824-, 4820-  
(PAGE 215-216)




**External thread measuring device**  
ISQ-TE100  
(PAGE 277-278)




**Universal caliper**  
1125-  
(PAGE 23-24)



**Digital caliper with interchangeable points**  
1526-, 1124-  
(PAGE 25-27)



## MICROMETER CALIBRATION



**Micrometer measuring force detector**  
6315  
(PAGE 89)



**Optical parallel**  
4184-  
(PAGE 90)



**Micrometer inspection gage block set**  
4107-  
(PAGE 175)



## WELDING




**Welding gage**  
4830, 4831-,  
4832-, 4836-,  
4834-, 4838-,  
4835-, 4840-  
(PAGE 222-227)



**Pipe welding gage**  
4841-, 4839-  
(PAGE 227-228)




## CALIPER CALIBRATION




**Caliper inspection gage block set**  
4108-  
(PAGE 176)




**Caliper/height gage checker**  
6884-  
(PAGE 180)




**Check master**  
6882-  
(PAGE 181)




## DRILL BITS




**Drill point gage**  
4843-  
(PAGE 229)



**Drill angle gage**  
4842-  
(PAGE 229)



## TAPS, REAMERS AND END MILLS




**V-anvil micrometer**  
3290-, 3590-  
(PAGE 84)



## JEWELLERY



**Thickness gage**  
2361-  
(PAGE 157)



Lie-down use for small articles on the table


**Digital snap gage**  
2167-  
(PAGE 165)




**Digital 3-purpose snap gage**  
2164-  
(PAGE 166)




## CRANKSHAFT DEFLECTION



**Crankshaft tester**  
2841-  
(PAGE 167)



## CAR BRAKE



**Digital disk brake caliper**  
1162-, 1167-  
(PAGE 39-40)




**Digital drum brake caliper**  
1168-  
(PAGE 40)



**Disc brake micrometer**  
3288-, 3588-  
(PAGE 81)




## CABLE CRIMP HEIGHT




**Digital crimp height caliper**  
1165-  
(PAGE 38)




**Crimp height micrometer**  
3266-, 3566-  
(PAGE 77)




## WIRE DIAMETER





**Wire micrometer**  
3285-  
(PAGE 88)




## RTJ RING GROOVE DIAMETER




**Digital RTJ ring groove caliper**  
1179-  
(PAGE 37)




## WIRE ROPE DIAMETER, RUBBER AND SPONGE THICKNESS



**Digital caliper with large measuring faces**  
1172-  
(PAGE 38)




measure diameter of wire ropes




measure thickness of rubber, sponge, etc.




## CAN SEAM



**Can seam micrometer**  
3293-  
(PAGE 89)




## COATING THICKNESS





**Coating thickness gage**  
ISO-2000FN,  
ISO-1500F (PAGE 318-319)



## MEASURING THICKNESS FROM ONE SIDE




**Ultrasonic thickness gage (through coating)**  
ISU-300D (PAGE 320)



**Ultrasonic thickness gage**  
ISU-250C, ISU-200D  
(PAGE 321-322)



## VISION MEASUREMENT



**Profile projector**  
ISP-Z3015/A1000E  
ISP-AZ3020/A5000E  
ISP-W3020/A3000E  
ISP-W4025/A7000E  
(PAGE 279-286)



**Vision measuring system**  
ISD-V150/V250/V300, ISD-A100-P  
(PAGE 287-290)




**Digital measuring microscope**  
ISM-WF200, ISM-PM200SB/600SB/PM160LA  
(PAGE 291-294)



**Portable measuring microscope**  
ISM-PM20/40/50/100  
(PAGE 303)



## VISION INSPECTION



**Digital microscope**  
ISM-WF200/PM200SB/PM600SB  
/PM160LA/TV200/TV200W  
(PAGE 291-295)



**Stereo microscope**  
ISM-ZS50/ZS50T/ZS30  
(PAGE 296-297)




**High magnification microscope**  
ISM-M600-P/M1000/M2000  
(PAGE 298-301)



**Portable measuring microscope**  
ISM-PM20/40/50/100  
(PAGE 303)



## ROTARY SPEED



**Digital LED tachometer/stroboscope**  
ISQ-TS120K  
(PAGE 323)



# APPLICATION INDEX

## VIDEOSCOPE AND BORESCOPE



**Videoscope**  
ISV-4000D/2000D/2001D/3000D/3001D/  
VP60/RV/E10/E20 (PAGE 304-309)




**Pipe videoscope**  
ISV-VP280  
(PAGE 310)



**Borescope**  
ISV-1Hxxx/HF4030/HR6032/HMxxx/HPxxx  
(PAGE 311-317)



## DISTANCE



**Laser distance meter**  
ISN-L70  
(PAGE 324)



## SCALE



**Digital horizontal scale**  
7101-  
(PAGE 269)




**Digital vertical scale**  
7102-  
(PAGE 270)



**Linear scale**  
ISL-A1-xxx/A5-xxx/B5-xxx  
(PAGE 271-272)



## LEVEL



**Digital level**  
ISE-2DT  
(PAGE 341)



**Digital level and protractor**  
2173-, 2179-, 2170-  
(PAGE 342-343)



**Level**  
4906-, 4905-, 4907-, 4908-  
(PAGE 343-344)




**Aluminum alloy level**  
4911-  
(PAGE 345)



**Digital level**  
4910-  
(PAGE 345)



## ROUGHNESS




**Roughness tester**  
ISR-S1000B/S1000A/S500/S300/S400/C100  
(PAGE 325-338)



**Roughness specimen**  
ISR-RSxxx, ISR-CS130, ISR-CSxxx  
(PAGE 339-340)



## HARDNESS



**Rockwell (desk model)**  
ISH-MRD200/RD200/MR150/R150/BRV  
(PAGE 346-350)



**Rockwell (portable)**  
ISHR-P151/D121/M111/B141  
(PAGE 365-368)



**Brinell (desk model)**  
ISH-BRV, ISHB-M100/D200  
(PAGE 350-352)



**Brinell (portable)**  
ISHR-B141/H131/P101  
(PAGE 368-370)



**Vickers (desk model)**  
ISH-BRV (PAGE 350)  
ISHV-D120, ISH-DV10/DV50 (PAGE 354-355)



**Leeb (portable)**  
ISH-SPHA/PHA/PHB/SPHD  
(PAGE 357-362)



**Ultrasonic (portable)**  
ISHU-460  
(PAGE 363-364)



**Webster (portable)**  
ISHW-L20/L20A/L20B/B70/B75/B92  
(PAGE 371)




**Barcol (portable)**  
ISHB-B300  
(PAGE 372)



**Shore (portable)**  
ISH-DSA/DSD, ISH-S30A/S30D, ISH-SAM/SDM  
(PAGE 373-377)



## TORQUE



**Digital torque tester**  
IST-TTxxx  
(PAGE 381)



**Digital bottle cap torque tester**  
IST-DCTxxx  
(PAGE 383)



**Digital torque wrench screwdriver**  
IST-SDxxx (PAGE 384)



**Torque wrench**  
IST-WPxxx/WSxxx/Wxxx/1Wxxx/3Wxxx  
/2Wxxx/2WMxxx (PAGE 384-391)



## METALLURGICAL ANALYZE



**Metallurgical microscope**  
ISM-M2000  
(PAGE 301)



**Precision cutting machine**  
ISJ-CMA35  
(PAGE 392)




**Grinder and polisher**  
ISJ-PMA200  
(PAGE 393)




**Mounting press**  
ISJ-MMA32  
(PAGE 394)




## MARK AND SCRIBE




**Marking gage**  
7120-, 1275-  
(PAGE 234)



**Center marking gage**  
7205-  
(PAGE 235)



**Scribing caliper**  
7202-, 1166-, 7203-  
(PAGE 235-236)




**Height scriber**  
6990-  
(PAGE 237)



**Scriber**  
7230, 7231, 7232 (PAGE 237)



**Divider**  
7260-, 7247-  
(PAGE 231)



## PULL AND PUSH FORCE



**Digital force gage**  
ISF-1DFxxx, ISF-DFxxx  
(PAGE 378-379)



## WORKPIECE CLAMPING AND SET UP

**Magnetic rectangular blocks**  
6898-  
(PAGE 240)



**V-block**  
6896-, 6802-, 6804-, 6803-, 6887-, 6888-, 6897-  
(PAGE 240-243)



**Magnetic V-block**  
6889-, 6890-, 6801-, 6891-, 6892-, 6899-  
(PAGE 244-247)



**Parallel**  
6533-, 6534-, 6894-, 4143-  
(PAGE 247-249)



**Angle plate**  
4003-, 4004-, 6535-  
(PAGE 249-250)



**Right angle plate**  
6547-  
(PAGE 251)




**Sine bar and vise**  
4155-, 6527-, 6522-, 6523-, 6524-  
(PAGE 251-253)



**Precision vise**  
6521-, 6525-, 6526-  
(PAGE 254-255)



## TOOLING SET UP



**Centering indicator**  
2385-  
(PAGE 255)



**Indicator centering holder**  
6291-, 6295-, 6294-  
(PAGE 140)



**3D tester**  
2842-  
(PAGE 256)



**Edge finder**  
6570-, 6571-, 6566-, 6567-,  
6562-, 6568-  
(PAGE 257-259)



**Zero setter**  
6553-, 6550-, 6554-,  
2397-, 2394-  
(PAGE 260-261)





[www.insize-eu.com](http://www.insize-eu.com)



Distributed by:



**INSIZE EUROPE**

Add: Plg. Ugaldeguren I P3 - Hall 2  
48170 - Zamudio (Bizkaia) Spain  
Tel: +34-94-4544308  
Fax: +34-94-4542452  
E-mail: [europa@insize.com](mailto:europa@insize.com)